

**FCC ID: 2APU8-CQL1524-B**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	2.886	1.94	3±1	4.00	2.51	<5	0.77860	3.00	YES
	2.441	2.828	1.92	3±1	4.00	2.51	<5	0.78490	3.00	YES
	2.480	1.886	1.54	2±1	3.00	2.00	<5	0.62843	3.00	YES
π/4 DQPSK	2.402	4.732	2.97	5±1	6.00	3.98	<5	1.23400	3.00	YES
	2.441	4.66	2.92	5±1	6.00	3.98	<5	1.24398	3.00	YES
	2.480	3.973	2.50	4±1	5.00	3.16	<5	0.99599	3.00	YES

**Conclusion:**

For the max result :  $1.24398\text{W/Kg} \leq \text{FCC Limit } 3.0$  for 1g SAR.