



Test report No. : 11359370S-A
 Page : 1 of 44
 Issued date : December 2, 2016
 Revised date : December 15, 2016 (-r01)
 FCC ID : AZD230

SAR TEST REPORT

Test Report No.: 11359370S-A


Applicant : Canon Inc.
 Type of Equipment : Wireless Module
 Model No. : ES200 (*. It was installed into ES200's platform (7).)
 FCC ID : AZD230
 Test Standard : FCC 47CFR §2.1093
 Test Result : Complied


Highest Reported SAR(1g)		SAR type	Platform No.	Platform type	Platform model	Band	Frequency [MHz]	Mode	Power [dBm]		ES200 Type	Report No.
Tune-up value	(Measured)								Actual	Max.		
0.66 W/kg	0.506 W/kg	Body-worn	#7	Digital camera	PC2329	DTS	2462	b(1Mbps,DSSS)	10.36	11.5	Low	*. This report.
*. This Wireless Module had installed into the following platforms under 0.8W/kg of reported SAR(1g) (KDB447498 D01 (v06): multi-platform operation requirement).												
0.15 W/kg	0.123 W/kg	Body-worn	#1	Digital camera	DS126621	DTS	2437	b(1Mbps,DSSS)	12.79	13.5	Normal	10840761S-A
< 0.10 W/kg	0.056 W/kg	Body-worn	#2	Digital camera	DS126591	DTS	2462	b(1Mbps,DSSS)	12.62	13.5	Normal	10840759S-A
0.60 W/kg	0.508 W/kg	Body-worn	#3	Digital camera	DS126601	DTS	2437	b(1Mbps,DSSS)	12.79	13.5	Normal	10840760S-A-r03
< 0.10 W/kg	0.037 W/kg	Body-worn	#4	Digital camera	DS126651	DTS	2462	b(1Mbps,DSSS)	12.62	13.5	Normal	11353340S-A
< 0.10 W/kg	0.045 W/kg	Body-worn	#5	Digital camera	DS126661	DTS	2462	b(1Mbps,DSSS)	12.62	13.5	Normal	11353341S-A
0.25 W/kg	0.205 W/kg	Body-worn	#6	Digital camera	DS126671	DTS	2462	b(1Mbps,DSSS)	12.62	13.5	Normal	11355392S-A

- *. **Highest reported SAR (1g) across all exposure conditions and on the platforms = "0.66 W/kg (body-worn)" = grant listed.**
 *. Since highest reported SAR (1g) on a platform of ES200 (EUT) which obtained in accordance with KDB447498 (v06) was kept under 0.8 W/kg, this EUT was approved to operate multi-platform (which were tested in above.).

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.
7. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)

Date of test: October 28, 2016

Test engineer: 
 Hiroshi Naka
 Engineer, Consumer Technology Division

Approved by: 
 Toyokazu Imamura
 Leader, Consumer Technology Division

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
☒ There is no testing item of "Non-accreditation".



UL Japan, Inc.
 Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN
 Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

13-EM-F0429

REVISION HISTORY

Revision	Test report No.	Date	Page revised	Contents
Original	11359370S-A	December 2, 2016	-	-
-r01	11359370S-A	December 15, 2016	P1,2,7	(p7) Added comment.

*. By issue of new revision report, the report of an old revision becomes invalid.

CONTENTS

PAGE

REVISION HISTORY	2
CONTENTS	2
SECTION 1: Customer information	3
SECTION 2: Equipment under test (EUT).....	3
2.1 Identification of EUT	3
2.2 Product Description	3
SECTION 3: Test specification, procedures and results	4
3.1 Test specification	4
3.2 Exposure limit	4
3.3 Procedure and result	4
3.4 Test location	5
3.5 Confirmation before SAR testing	5
3.6 Confirmation after SAR testing	5
3.7 Test setup of EUT and SAR measurement procedure	6
SECTION 4: Operation of EUT during testing	7
SECTION 5: Uncertainty assessment (SAR measurement)	7
SECTION 6: Confirmation before testing	8
6.1 SAR reference power measurement (antenna terminal conducted average power of EUT)	8
SECTION 7: SAR Measurement results	9

Contents of appendixes

APPENDIX 1: Photographs of test setup	10
Appendix 1-1 Photograph of Platform and antenna position	10
Appendix 1-2 EUT and support equipment	11
Appendix 1-3 Photograph of test setup	12
APPENDIX 2: SAR Measurement data	14
Appendix 2-1 Evaluation procedure	14
Appendix 2-2 SAR measurement data	15
APPENDIX 3: Test instruments	21
Appendix 3-1 Equipment used	21
Appendix 3-2 Configuration and peripherals	22
Appendix 3-3 Test system specification	23
Appendix 3-4 Simulated tissues composition and parameter confirmation	24
Appendix 3-5 Daily check results	24
Appendix 3-6 Daily check measurement data	25
Appendix 3-7 Daily check uncertainty	25
Appendix 3-8 Calibration certificate: E-Field Probe (EX3DV4)	26
Appendix 3-9 Calibration certificate: Dipole (D2450V2)	37

SECTION 1: Customer information

Company Name	Canon Inc.
Brand Name	Canon
Address	30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501 Japan
Telephone Number	+81-3-5482-8070
Facsimile Number	+81-3-3757-8431
Contact Person	Chihiro Saito

SECTION 2: Equipment under test (EUT)

2.1 Identification of EUT

	EUT	Platform
Type of Equipment	Wireless Module	Platform (7): Digital camera
Model Number	ES200	PC2329
Serial Number	A408EA544874	42
Condition of EUT	Engineering prototype (*: Not for sale: These samples are equivalent to mass-produced items.)	Engineering prototype
Receipt Date of Sample	July 1, 2016 (*: EUT for power measurement.) *: No modification by the Lab. October 27, 2016 (*: EUT for SAR test.) *: No modification by the Lab. (*: The EUT that had been measured the power of SAR test reference, was installed into the platform-digital camera (model: PC2329) from the beginning. After power measurement, the EUT was returned to the customer, and the RF wiring was changed to the original antenna line from the antenna conducted power measurement line for SAR test. The EUT was installed into a platform which SAR tested, by the customer.)	
Country of Mass-production	China, Japan	Japan
Category Identified	Portable device *: Since EUT may contact and/or very close to a human body during Wi-Fi operation, the partial-body SAR (1g) shall be observed.	
Rating	DC3.3V and DC1.8V supplied from the platform *: The EUT is installed into the specified the platform that was operated by the re-chargeable Li-ion battery.	
Feature of EUT	The EUT is a Wireless Module which installs into the specified platform: digital camera.	
SAR Accessory	None	

2.2 Product Description (Model: ES200)

Equipment type	Transceiver					
Frequency of operation	2412-2462MHz (11b, 11g, 11n(20HT))					
Channel spacing	5MHz					
Bandwidth	20MHz					
Type of modulation	DSSS(11b): CCK, DQPSK, DBPSK OFDM(11g, 11n(20HT): 64QAM, 16QAM, QPSK, BPSK					
Q'ty of Antenna	1 pc.					
Antenna / Connector type	Pattern antenna / No connector (Printed on the PCB).					
Antenna gain (peak)	2.14 dBi					
Power level	Normal power mode (*1,*2)			Low power mode (*1,*2)		
Transmit power and tolerance	11b: 12 dBm	11g: 12 dBm	11n(20HT): 11 dBm	11b: 10 dBm	11g: 8 dBm	11n(20HT): 7 dBm
Manufacture variation	+1.5/-1.5 dB	+1.5/-1.5 dB	+1.5/-1.5 dB	+1.5/-1.5 dB	+1.5/-1.5 dB	+1.5/-1.5 dB
Maximum output power	13.5 dBm	13.5 dBm	12.5 dBm	11.5 dBm	9.5 dBm	8.5 dBm
-	*: The measured Tx output power (conducted) refers to section 6 in this report.					
Power supply	DC 3.3V, DC1.8V (*: These powers are supplied from the platform via constant voltage circuit.)					

*. The EUT do not use the special transmitting technique such as "beam-forming" and "time-space code diversity."

*1. ES200 has two kinds of power level which specified as "Normal power" mode and "Low power" mode. The power of "Low power" mode is lower than "Normal power" mode for all Tx conditions.

*2. Since "Low power mode" is selected by firmware in this platform (PC2329), the EUT can not output power level of "Normal power" mode.

SECTION 3: Test specification, procedures and results

3.1 Test specification

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. The device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling in accordance with the following measurement procedures.

KDB 447498 D01 (v06):	General RF exposure guidance
KDB 248227 D01 (v02r02):	SAR Guidance for IEEE 802.11 (Wi-Fi) transmitters
KDB 865664 D01 (v01r04):	SAR measurement 100MHz to 6GHz
IEEE Std. 1528-2013:	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

3.2 Exposure limit

Environments of exposure limit	Whole-Body (averaged over the entire body)	Partial-Body (averaged over any 1g of tissue)	Hands, Wrists, Feet and Ankles (averaged over any 10g of tissue)
(A) Limits for Occupational /Controlled Exposure (W/kg)	0.4	8.0	20.0
(B) Limits for General population /Uncontrolled Exposure (W/kg)	0.08	1.6	4.0

- *. **Occupational/Controlled Environments:** are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).
- *. **General Population/Uncontrolled Environments:** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

The limit applied in this test report is;

General population / uncontrolled exposure, Partial-Body (averaged over any 1g of tissue) limit: 1.6 W/kg

3.3 Procedures and Results

	Wi-Fi (DTS) / in Platform (7)
Test Procedure	SAR measurement; KDB 447498, KDB 248227, KDB 865664, IEEE Std.1528
Category	FCC 47CFR §2.1093 (Portable device)
Results (SAR(1g))	Complied
Reported SAR value (*, Scaled)	0.66 w/kg
Measured SAR value	0.506 W/kg
Operation mode, channel	802.11b, 1 Mbps (DBPSK/DSSS), 2462 MHz (11ch)
Power measured/max. (scaled factor)	10.36 dBm/11.5 dBm (×1.30) (*. Low power mode)
Duty cycle [%] (scaled factor)	99.9 (×1.00)

Note: UL Japan's SAR Work Procedures No.13-EM-W0429 and 13-EM-W0430. No addition, deviation nor exclusion has been made from standards

Test outline: Where this product is built into a new platform (7), it was verified whether multiplatform conditions can be suited in according with section 2) of 5.2.2 in KDB447498 D01 (v06).

Consideration of the test results: **The highest reported SAR (1g) of this platform (7) was kept; ≤ 0.8 W/kg.**
Since highest reported SAR (1g) on this EUT's platform obtained in accordance with KDB447498 D01 (v06) was kept under 0.8 W/kg, this EUT was approved to operate multi-platform.

3.4 Test Location

No.7 shielded room (2.76 m (Width) × 3.76 m (Depth) × 2.4 m (Height)) for SAR testing.

UL Japan, Inc., Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number: +81 463 50 6400 / Facsimile number: +81 463 50 6401

3.5 Confirmation before SAR testing

3.5.1 Average power for SAR tests

Before SAR test, the RF wiring for the sample had been switched to the antenna conducted power measurement line from the antenna line and the average power was measured. The result is shown in Section 6.

*. The EUT transmission power was verified that it was within 2dB lower than the maximum tune-up tolerance limit when it was set the rated power. (Clause 4.1, KDB447498 D01(v06))

Check the power by data rate and operation channel

The data rate check was measured for all modes in one of default channel. For the SAR test reference, the average output power was measured on the lower, middle and upper channels with the worst data rate condition in.

11b		11g				11n(20HT)					
Modulation	Data rate [Mbps]	Modulation	Data rate [Mbps]	Modulation	Data rate [Mbps]	MCS Index	Spatial Stream	Modulation	MCS Index	Spatial Stream	Modulation
DBPSK/DSSS	1	BPSK/OFDM	6	16QAM/OFDM	24	MCS0	1	BPSK/OFDM	MCS4	1	16QAM/OFDM
DQPSK/DSSS	2	BPSK/OFDM	9	16QAM/OFDM	36	MCS1	1	QPSK/OFDM	MCS5	1	64QAM/OFDM
CCK/DSSS	5.5	QPSK/OFDM	12	64QAM/OFDM	48	MCS2	1	QPSK/OFDM	MCS6	1	64QAM/OFDM
CCK/DSSS	11	QPSK/OFDM	18	64QAM/OFDM	54	MCS3	1	16QAM/OFDM	MCS7	1	64QAM/OFDM

3.6 Confirmation after SAR testing

It was checked that the power drift [W] is within ±5% in the evaluation procedure of SAR testing. The verification of power drift during the SAR test is that DASY5 system calculates the power drift by measuring the e-filed at the same location at beginning and the end of the scan measurement for each test position.

The result is shown in APPENDIX 2.

- *. DASY5 system calculation Power drift value[dB] = 20log(Ea)/(Eb) (where, Before SAR testing: Eb[V/m] / After SAR testing: Ea[V/m])
Limit of power drift[W] = ±5%; Power drift limit (X) [dB] = 10log(P_drift)=10log(1.05/1)=10log(1.05)-10log(1)=0.21dB
from E-filed relations with power; $S=E \times H = E^2 / \eta = P / (4 \times \pi \times r^2)$ (η : Space impedance) → $P = (E^2 \times 4 \times \pi \times r^2) / \eta$
Therefore, The correlation of power and the E-filed
Power drift limit (X) dB=10log(P_drift)=10log(E_drift)^2=20log(E_drift)
From the above mentioned, **the calculated power drift of DASY5 system must be the less than ±0.21dB.**

3.7 Test setup of EUT and SAR measurement procedure

Antenna separation distances in each test setup plan are shown as follows.

Setup plan	Explanation of SAR test setup plan (* Refer to Appendix 1 for test setup photographs which had been tested.)	D [mm]	SAR Tested /Reduced (*1)	SAR type
Top	When test is required, the top surface of camera is touched to the Flat phantom.	4.15	Tested	Body-touch
Top-front	When test is required, the front portion of top surface on camera is touched to the Flat phantom with tilt.	13.63	Tested	
Rear (LCD)	When test is required, the rear surface of camera is touched to the Flat phantom.	14.4	Tested	
Front (Lens)	When test is required, the front portion (Lens) of camera is touched to the Flat phantom.	14.7	Tested	
Left	When test is required, the left surface of camera is touched to the Flat phantom.	36.89	Reduced	
Bottom	When test is required, the bottom surface on a camera is touched to the Flat phantom.	59.65	Reduced	
Right	When test is required, the right surface on a camera is touched to the Flat phantom.	73.27	Reduced	

- *. D: Antenna separation distance. It is the distance from the EUT antenna inside a platform to the outer surface of platform which an operator may touch.
*. Size of EUT (ES200): 11.5 mm (width) × 22.5 mm (depth) × 2.0 mm max (thickness)
. Size of platform: 110.1 mm (width) × 63.8 mm (height) × 39.9 mm (depth) (The convex portion is not contained in size.)

*1. Consideration for SAR evaluation exemption

KDB 447498 D01 (v06) was taken into consideration to reduce SAR test.

Consideration of SAR test reduction by the antenna separation distance (100MHz~6GHz, ≤50mm)												
Band, Mode	Setup Position	Minimum distance		Upper frequency [GHz]	Maximum power			Calculation of exclusion (*2)	SAR type	SAR test exclusion		Remarks
		[mm]	[mm] (rounded)		[dBm]	[mW]	[mW] (rounded)			Judge for Exclusion	Standalone SAR test required?	
WLAN 2.4GHz 11b	Top	4.15	≤ 5	2.462	11.5	14.13	14	4.4	1g	≤3.0	Required	-
	Top-front	13.63	14					1.6	1g	≤3.0	Not required	*.SAR test was applied.
	Rear	14.4	14					1.6	1g	≤3.0	Not required	*.SAR test was applied.
	Front	14.7	15					1.5	1g	≤3.0	Not required	*.SAR test was applied.

- *2. Parenthesis 1), Clause 4.3.1, KDB 447498 D01 (v06) gives the following formula to calculate the SAR(1g) test exclusion thresholds for 100MHz-6GHz at test separation distance ≤50mm.

$$[(\text{max.power of channel, including tune-up tolerance, mW}) / (\text{min.test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ (for SAR(1g))}, 7.5 \text{ (for SAR(10g))} \quad \text{formula (1)}$$
If power is calculated from the upper formula (1);

$$[\text{SAR(1g) test exclusion thresholds, mW}] = 3 \times [\text{test separation distance, mm}] / [\sqrt{f(\text{GHz})}] \quad \text{formula (2)}$$

<Conclusion for consideration for SAR test reduction>

- 1) The SAR setups of the near antenna which includes "Top", "Top-front", "Rear" and "Front" are considered body-touch SAR and are applied the SAR test in body-liquid.
- 2) The SAR tests of "Left", "Bottom" and "Right" setup are reduced because there is enough antenna separation distance.
- 3) A platform of digital camera didn't have view finder, so a SAR test of front-of-face wasn't considered.

By the determined test setup shown above, the SAR test was applied in the following procedures.

Step 1	Worst SAR search by DSSS mode; Determine the highest reported SAR(1g) of DSSS mode. (* Change the channel, if it is necessary.)
--------	--

- *. During SAR test, the radiated power is always monitored by Spectrum Analyzer.

SECTION 4: Operation of EUT during testing

4.1 Operating modes for SAR testing

This EUT has IEEE.802.11b, 11g and 11n(20HT) continuous transmitting modes.
The frequency and the modulation used in the SAR testing are shown as a following.

Operation mode		11b	11g	11n(20HT)
Tx frequency band		2412-2462MHz		
Maximum power [dBm]		11.5	9.5	8.5
SAR tested/reduced?		Tested	Tested (*lower power than 11b)	Tested (*lower power than 11b)
Tested condition	Frequency	2412, 2437, 2462 MHz (*1, *2)	2462 MHz (*3)	2462 MHz (*3)
	Modulation	DBPSK/DSSS	BPSK/OFDM	BPSK/OFDM
	Data rate	1 Mbps	6 Mbps	MCS0
Controlled software		"RF TEST" mode. (*. Low power mode) This software was used for both antenna terminal conducted power measurement and SAR measurement. Set Tx parameters which includes: "channel", "BW(20MHz or 40MHz)", "Power(dBm)" and "data rate" via LCD of platform.		
Power setting (power measurement)		default=10	default=8	default=7
Power setting (SAR)		default=10	default=8	default=7

- *1. Any output power reducing for channel 1 and 11 to meet restricted band requirements was not observed. Therefore channel 1 and 11 was tested.
*2. (KDB248227 D01 (v02r02)) Since the reported SAR of the highest measured maximum output power channel is ≤ 0.8 W/kg, the SAR testing for other channels were omitted. However, the SAR testing was applied to lower, middle and upper channels for the worst SAR condition.
*3. This channel is a worst SAR of 11b mode.

SECTION 5: Uncertainty Assessment (SAR measurement)

Uncertainty of SAR measurement (2.4-6GHz) (*.ε&σ: ≤±5%, DAK3.5, Tx: ≈100% duty cycle) (v08)							1g SAR	10g SAR	
Combined measurement uncertainty of the measurement system (k=1)							± 13.7%	± 13.6%	
Expanded uncertainty (k=2)							± 27.4%	± 27.2%	
	Error Description (2.4-6GHz) (v08)	Uncertainty Value	Probability distribution	Divisor	ci (1g)	ci (10g)	ui (1g)	ui (10g)	Vi, veff
A	Measurement System (DASY5)						(std. uncertainty)	(std. uncertainty)	
1	Probe Calibration Error	±6.55 %	Normal	1	1	1	±6.55 %	±6.55 %	∞
2	Axial isotropy Error	±4.7 %	Rectangular	√3	√0.5	√0.5	±1.9 %	±1.9 %	∞
3	Hemispherical isotropy Error	±9.6 %	Rectangular	√3	√0.5	√0.5	±3.9 %	±3.9 %	∞
4	Linearity Error	±4.7 %	Rectangular	√3	1	1	±2.7 %	±2.7 %	∞
5	Probe modulation response	±2.4 %	Rectangular	√3	1	1	±1.4 %	±1.4 %	∞
6	Sensitivity Error (detection limit)	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
7	Boundary effects Error	±4.3 %	Rectangular	√3	1	1	±2.5 %	±2.5 %	∞
8	Readout Electronics Error(DAE)	±0.3 %	Rectangular	√3	1	1	±0.3 %	±0.3 %	∞
9	Response Time Error	±0.8 %	Normal	1	1	1	±0.8 %	±0.8 %	∞
10	Integration Time Error (≈100% duty cycle)	±0 %	Rectangular	√3	1	1	0 %	0 %	∞
11	RF ambient conditions-noise	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
12	RF ambient conditions-reflections	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
13	Probe positioner mechanical tolerance	±3.3 %	Rectangular	√3	1	1	±1.9 %	±1.9 %	∞
14	Probe Positioning with respect to phantom shell	±6.7 %	Rectangular	√3	1	1	±3.9 %	±3.9 %	∞
15	Max. SAR evaluation (Post-processing)	±4.0 %	Rectangular	√3	1	1	±2.3 %	±2.3 %	∞
B	Test Sample Related								
16	Device Holder or Positioner Tolerance	±3.6 %	Normal	1	1	1	±3.6 %	±3.6 %	5
17	Test Sample Positioning Error	±5.0 %	Normal	1	1	1	±5.0 %	±5.0 %	145
18	Power scaling	±0 %	Rectangular	√3	1	1	±0 %	±0 %	∞
19	Drift of output power (measured, <0.2dB)	±2.3 %	Rectangular	√3	1	1	±2.9 %	±2.9 %	∞
C	Phantom and Setup								
20	Phantom uncertainty (shape, thickness tolerances)	±7.5 %	Rectangular	√3	1	1	±4.3 %	±4.3 %	∞
21	Algorithm for correcting SAR (ε',σ: ≤5%)	±1.2 %	Normal	1	1	0.84	±1.2 %	±0.97 %	∞
22	Measurement Liquid Conductivity Error (DAK3.5)	±3.0 %	Normal	1	0.78	0.71	±2.3 %	±2.1 %	7
23	Measurement Liquid Permittivity Error (DAK3.5)	±3.1 %	Normal	1	0.23	0.26	±0.7 %	±0.8 %	7
24	Liquid Conductivity-temp.uncertainty (≤2deg.C.)	±5.3 %	Rectangular	√3	0.78	0.71	±2.4 %	±2.2 %	∞
25	Liquid Permittivity-temp.uncertainty (≤2deg.C.)	±0.9 %	Rectangular	√3	0.23	0.26	±0.1 %	±0.1 %	∞
	Combined Standard Uncertainty						±13.7 %	±13.6 %	733
	Expanded Uncertainty (k=2)						±27.4 %	±27.2 %	

- *. Table of uncertainties are listed for ISO/IEC 17025.
*. This measurement uncertainty budget is suggested by IEEE Std.1528(2013) and determined by Schmid & Partner Engineering AG (DASY5 Uncertainty Budget).
*. Per KDB 865664 D01 (v01r04) SAR Measurement 100 MHz to 6 GHz, Section 2.8.1., when the highest measured SAR(1g) within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std.1528 (2013) is not required in SAR reports submitted for equipment approval.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN
Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

SECTION 6: Confirmation before testing

6.1 SAR reference power measurement (antenna terminal conducted average power of EUT) - Worst data rate/channel determination

*. Antenna gain (peak): 2.14 dBi (2.4 GHz band)

Mode	Freq.	Data rate	Power Setting	Duty cycle	Duty factor	Duty scaled factor	Time average power		PAR	Power tolerance & correction			SAR Tested/Reduced	ES200 Power Level Type	Remarks (*, Low power mode)	Power Tune-up?
							Result			Target & (+)tolerance	Deviation from max	Tune-up factor				
							[dBm]	[mW]								
11b	2412	1	10	99.9	0.00	×1.00	10.71	11.78	2.6	10.0+1.5	-0.79	×1.20	Tested	Low		n/a
	2437	1	10	99.9	0.00	×1.00	10.38	10.91	3.0	10.0+1.5	-1.12	×1.29	Tested	Low		n/a
	2462	1	10	99.9	0.00	×1.00	10.36	10.86	3.0	10.0+1.5	-1.14	×1.30	Tested	Low		n/a
11g	2412	6	8	99.6	0.02	×1.00	8.64	7.31	10.5	8.0+1.5	-0.86	×1.22	Reduced	Low	* lower power than 11b.	n/a
	2437	6	8	99.6	0.02	×1.00	8.51	7.10	10.4	8.0+1.5	-0.99	×1.26	Reduced	Low	* lower power than 11b.	n/a
	2462	6	8	99.6	0.02	×1.00	8.47	7.03	10.5	8.0+1.5	-1.03	×1.27	Tested	Low	* Worst SAR Ch. of 11b.	n/a
11n (20HT)	2412	MCS0	7	99.4	0.03	×1.01	7.66	5.83	9.7	7.0+1.5	-0.84	×1.21	Reduced	Low	* lower power than 11b.	n/a
	2437	MCS0	7	99.4	0.03	×1.01	7.50	5.62	9.7	7.0+1.5	-1.00	×1.26	Reduced	Low	* lower power than 11b.	n/a
	2462	MCS0	7	99.4	0.03	×1.01	7.42	5.52	9.7	7.0+1.5	-1.08	×1.28	Tested	Low	* Worst SAR Ch. of 11b.	n/a

*. : SAR test was applied. *: xx.xx highlight is shown the maximum measured output power. n/a: not applied

*. Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test in following tables.

Data rate (D/R) vs Time average power (add duty factor) (dBm)															
11b (2412MHz)				11g (2412MHz)				11n(20HT) (2412MHz)							
D/R	Duty cycle (%)	Duty factor (dB)	Power	D/R	Duty cycle (%)	Duty factor (dB)	Power	D/R	Duty cycle (%)	Duty factor (dB)	Power	D/R	Duty cycle (%)	Duty factor (dB)	Power
1	99.9	0.00	10.71	6	99.6	0.02	8.64	24	97.8	0.10	8.61	MCS0	99.4	0.00	7.66
2	99.8	0.01	10.55	9	99.2	0.04	8.52	36	96.7	0.15	8.59	MCS1	98.9	0.00	7.64
5.5	99.6	0.02	10.36	12	98.9	0.05	8.55	48	95.6	0.19	8.42	MCS2	98.3	0.00	7.41
11	99.1	0.04	10.49	18	98.3	0.07	8.56	56	95.7	0.19	8.58	MCS3	97.6	0.00	7.44
												MCS4	96.7	0.00	7.53
												MCS5	95.6	0.00	7.52
												MCS6	95.3	0.00	7.52
												MCS7	95.0	0.00	7.45

*. Freq.: Frequency, PAR: Peak average ratio ("Peak power" - "Average power", in dBm), Ch: channel, D/R: Data Rate, pwr: power, Ref: Reference.

*. Calculating formula: Time average power-result: Results (dBm) = (P/M Reading, dBm) + (Cable loss, dB) + (Attenuator, dB) + (duty factor, dB)
Duty factor: (duty factor, dBm) = $10 \times \log(100/(\text{duty cycle, \%}))$
Deviation form max.: (Power deviation, dB) = (results power (average, dBm)) - (Max.-specification output power (average, dBm))
Duty scaled factor: Duty cycle correction factor for obtained SAR value, Duty scaled factor [-] = $100\% / (\text{duty cycle, \%})$
Tune-up factor: Power tune-up factor for obtained SAR value, Tune-up factor [-] = $1 / (10^{(Deviation from max., dB / 10)})$

*. Date measured: July 7, 2016 / Measured by: Hiroshi Naka / Place: preparation room of No. 7 shielded room, (25 deg.C. / 50 %RH)

*. Uncertainty of antenna port conducted test; Power measurement uncertainty above 1GHz for this test was: (±) 0.76 dB(Average)/(±) 0.79 dB(Peak)

*. Uncertainty of antenna port conducted test; Duty cycle and time measurement: (±) 0.012 %.

*. EUT (ES200) has two kinds of power level which specified as "Normal power" mode and "Low power" mode. The power of "Low power" mode is lower than "Normal power" mode for all Tx conditions.

*. Since "Low power mode" is selected by firmware in this platform (PC2329), the EUT can not output power level of "Normal power" mode.

SECTION 7: SAR Measurement results

Measurement date: October 28, 2016

Measurement by: Hiroshi Naka

[Liquid measurement]

Target Frequency [MHz]	Liquid type	Liquid parameters (*a)								ASAR Coefficients(*c)		Date measured		
		Permittivity (εr) [-]				Conductivity [S/m]				Temp. [deg.C.]	Depth [mm]		ΔSAR (1g) [%]	Correction required?
		Target	Measured		Limit (※b)	Target	Measured		Limit (※b)					
			Meas.	Δεr [%]			Meas.	Δσ [%]						
2412	Body	52.75	50.68	-3.9	-5% ≤	1.914	1.937	+1.2	0% ≤	22.3	151	+1.47	not required.	October 28, 2016, before SAR test
2437		52.72	50.57	-4.1	εr-meas.	1.938	1.970	+1.7	σ-meas.			+1.66	not required.	
2462		52.68	50.47	-4.2	≤ 0%	1.967	1.998	+1.6	≤ +5%			+1.58	not required.	

[SAR measurement results]

SAR measurement results											Reported SAR (1g) [W/kg]						Remarks	
Mode	Frequency [MHz] (Channel)	Data rate [Mbps]	EUT setup				Power drift [dB]	SAR (1g) [W/kg]			SAR plot # in Appendix 2-2	Duty cycle correction		Output average power correction				SAR Corrected (*d)
			Position	Gap [mm]	Bty. ID	LCD position		Max.value of multi-peak				Duty [%]	Duty scaled	Meas. [dBm]	Max. [dBm]	Tune-up factor		
								Meas.	ASAR [%]	ASAR corrected								
Step 1: Worst SAR search by DSSS mode.																		
11b	2412(1)	1	Top	0	#1	Close	-0.05	0.406	+1.47	n/a (*c)	Plot 1-2	99.9	×1.00	10.71	11.5	×1.20	0.487	-
	2437(6)			0	#1	Close	0.13	0.411	+1.66	n/a (*c)	Plot 1-3	99.9	×1.00	10.38	11.5	×1.29	0.530	-
	2462(11)			0	#1	Close	-0.03	0.506	+1.58	n/a (*c)	Plot 1-1	99.9	×1.00	10.36	11.5	×1.30	0.658	Higher.
				0	#2	OP90	-0.01	0.470	+1.58	n/a (*c)	Plot 143	99.9	×1.00	10.36	11.5	×1.30	0.611	-
			Top-front	0	#2	Close	0.08	0.185	+1.58	n/a (*c)	Plot 1-5	99.9	×1.00	10.36	11.5	×1.30	0.241	-
			Rear	0	#2	Close	-0.20	0.014	+1.58	n/a (*c)	Plot 1-6	99.9	×1.00	10.36	11.5	×1.30	0.018	-
	0			#2	OP180	-0.20	0.011	+1.58	n/a (*c)	Plot 1-7	99.9	×1.00	10.36	11.5	×1.30	0.015	-	
	Front		0	#3	Close	0.09	0.029	+1.58	n/a (*c)	Plot 1-8	99.9	×1.00	10.36	11.5	×1.30	0.037	-	
11g	2462(11)	6	Top	0	#1	Close	-0.08	0.343	+1.58	n/a (*c)	Plot 1-9	99.6	×1.00	8.47	9.5	×1.27	0.434	-
n(20HT)				0	#1	Close	-0.02	0.272	+1.58	n/a (*c)	Plot 1-10	99.4	×1.01	7.42	8.5	×1.28	0.348	-

Notes:

- *. Gap: It is the separation distance between the nearest position of platform outer surface and the bottom outer surface of phantom;
- *. Bty.ID: Battery ID (*. Battery ID No."1, #2 and #3 are same. Refer to Appendix 1 for more detail.); Max.: maximum, Meas.: Measured; n/a: not applied.
- *. LCD position; OP90: Open with 90 degrees, OP180: Open with 180 degrees. Refer to Appendix 1 for more detail.
- *. During test, the EUT was operated with full charged battery and without all interface cables.
- *. Calibration frequency of the SAR measurement probe (and used conversion factors)

SAR test frequency	Probe calibration frequency	Validity	Conversion factor	Uncertainty
2412, 2437, 2462 MHz	2450MHz	within ±50MHz of calibration frequency	7.30	±12.0%

*. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

- *a. The target value is a parameter defined in Appendix A of KDB865664 D01 (v01r04), the dielectric parameters suggested for head and body tissue simulating liquid are given at 2000 and 2450MHz. Parameters for the frequencies 2000-2450MHz were obtained using linear interpolation. (Refer to appendix 3-4.)
- *b. Refer to KDB865664 D01 (v01r04), item 2), Clause 2.6; "When nominal tissue dielectric parameters are recorded in the probe calibration data; for example, only target values and tolerance are reported, the measured εr and σ of the liquid used in routine measurements must be: ≤ the target εr and ≥ the target σ values and also within 5% of the required target dielectric parameters."
- *c. Calculating formula: $\Delta SAR(1g) = C_{\epsilon r} \times \Delta \epsilon r + C_{\sigma} \times \Delta \sigma$, $C_{\epsilon r} = 7.854E-4 \times f^3 + 9.402E-3 \times f^2 - 2.742E-2 \times f + 0.2026$, $C_{\sigma} = 9.804E-3 \times f^3 - 8.661E-2 \times f^2 + 2.981E-2 \times f + 0.7829$
 $\Delta SAR \text{ corrected SAR (1g) (W/kg)} = (\text{Meas. SAR (1g) (W/kg)}) \times (100 - (\Delta SAR(\%))) / 100$
- *d. Calculating formula: $\text{Reported SAR (1g) (W/kg)} = (\text{Measured SAR (1g) (W/kg)}) \times (\text{Duty scaled}) \times (\text{Tune-up factor})$
Duty scaled = Duty scaled factor: Duty cycle correction factor for obtained SAR value, Duty scaled factor [-] = 100(%) / (duty cycle, %)
Tune-up factor: Power tune-up factor for obtained SAR value, Tune-up factor [-] = 1 / (10 ^ ("Deviation from max., dB" / 10))

(Clause 5.2, 2.4GHz SAR Procedures, in KDB248227 D01 (v02r02))

5.2.1 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel (section 3.1) for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

5.2.2 2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.