



FCC Test Report

FOR:

Crane Payment Innovations

Model Name:

AIO2210-US101

Product Description:

ALIO Note is a card reader bezel that incorporates mag stripe, contact, and contactless card reader capabilities in support of unattended cashless sales. It is mechanically mounted on a bill acceptor during normal use further enhancing payment capability at the POS. It utilizes 4g CAT M (Telit module ME910G1WW) cellular radio, NFC (13.56 MHz) to read cards, and BLE (QUALCOMM CSR1010) to support diagnostic capability.

FCC ID: QP8ALIONOTEVZ

Applied Rules and Standards

Title 47 CFR: Part 15.225

REPORT #: EMC_MEIGR_011_21001_FCC_15.225_NFC

DATE: 2021-04-23



A2LA Accredited

IC recognized #
3462B-1

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecom.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

TABLE OF CONTENTS

1	ASSESSMENT	3
2	ADMINISTRATIVE DATA.....	4
2.1	IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT	4
2.2	IDENTIFICATION OF THE CLIENT	4
2.3	IDENTIFICATION OF THE MANUFACTURER	4
3	EQUIPMENT UNDER TEST (EUT)	5
3.1	EUT SPECIFICATIONS	5
3.2	EUT SAMPLE DETAILS	6
3.3	ACCESSORY EQUIPMENT DETAILS	6
3.4	SUPPORT EQUIPMENT	6
3.5	TEST SAMPLE CONFIGURATION	7
3.6	MODE OF OPERATION DETAILS	7
3.7	JUSTIFICATION FOR WORST CASE MODE OF OPERATION	7
4	SUBJECT OF INVESTIGATION	8
4.1	MEASUREMENT UNCERTAINTY	8
4.2	ENVIRONMENTAL CONDITIONS DURING TESTING:	8
4.3	DATES OF TESTING:	8
5	MEASUREMENT RESULTS SUMMARY	9
6	MEASUREMENT PROCEDURES.....	10
6.1	RADIATED MEASUREMENT	10
7	TEST RESULT DATA.....	13
7.1	FIELD STRENGTH.....	13
7.2	FREQUENCY STABILITY	16
7.3	TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BANDS.....	20
7.4	AC POWER LINE CONDUCTED EMISSIONS	25
8	TEST SETUP PHOTOS	27
9	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING	27
10	REVISION HISTORY	28

1 Assessment

The following device as further described in section 3 of this report was evaluated for unlicensed radio according to criteria specified in Code of Federal Regulations Title 47 CFR: Part 15.225.

No deviations were ascertained.

According to section 5 of this report, the overall result is PASS.

Company	Description	Model #
Crane Payment Innovations	ALIO Note is a card reader bezel that incorporates mag stripe, contact, and contactless card reader capabilities in support of unattended cashless sales. It is mechanically mounted on a bill acceptor during normal use further enhancing payment capability at the POS. It utilizes 4g CAT M (Telit module ME910G1WW) cellular radio, NFC (13.56 MHz) to read cards, and BLE (QUALCOMM QualCom CSR1010) to support diagnostic capability.	AIO2210-US101

Responsible for Testing Laboratory:

2021-04-23	Compliance	Kevin Wang (Lab Manager)	
Date	Section	Name	Signature

Responsible for the Report:

2021-04-23	Compliance	Yuchan Lu (Test Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Lab Manager:	Kevin Wang
Responsible Project Leader:	Rami Saman

2.2 Identification of the Client

Applicant's Name:	Crane Payment Innovations
Street Address:	3222 Phoenixville Pike, Suite 200
City/Zip Code	Malvern, PA 19355
Country	USA

2.3 Identification of the Manufacturer

Manufacturer's Name:	Same as Client
Manufacturers Address:	
City/Zip Code	
Country	

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Firmware Version Identification Number (FVIN):	N/A
Hardware Version Identification Number (HVIN):	AIO2210-US101
Product Marketing Name (PMN):	ALIO
Frequency Range / number of channels:	13.56 MHz / 1 Channel
Type(s) of Modulation:	ASK
Modes of Operation:	RFID
Antenna Information as declared:	The RFID antenna is a two loop antenna located inside the ALIO Note enclosure and wraps around the outer edges of the display glass. The antenna utilizes magnetic-field coupling in the near field to read the card tag in the RFID Card presented.
Max. Output Powers:	1.4 W
Power Supply/ Rated Operating Voltage Range:	Vmin: 20 VDC/ Vnom: 24 VDC / Vmax: 42 VDC
Operating Temperature Range:	Low -15°C, Nominal 25°C, High 60°C
Sample Revision:	<input type="checkbox"/> Prototype Unit; <input checked="" type="checkbox"/> Production Unit; <input type="checkbox"/> Pre-Production
EUT Dimensions [mm]:	167.6 x 76.2 x 88.9
EUT Diameter:	<input checked="" type="checkbox"/> < 60 cm <input type="checkbox"/> Other _____

RFID Module Information	
Module Name:	ST25R3911B
Other Radios included in the device:	<ul style="list-style-type: none">❖ <u>LTE</u><ul style="list-style-type: none">• Manufacture: Telit• Module name/number: ME910G1-WW• FCC ID: RI7ME910G1WW❖ <u>Classic BT, BLE, ANT</u><ul style="list-style-type: none">• Manufacture: Qualcomm• Module name/number: CRS 1010 QFN

3.2 EUT Sample details

EUT #	Serial Number	HW Version	SW Version	Notes / Comments
1	42000000149	G1	5.X	Radiated Emissions

3.3 Accessory Equipment details

AE #	Type	Manufacture	Model	P/N
1	Switching Adapter	Sunny Computer Technology	SYS1548-6524-T2	G160305126068
2	Vending demo tester	-	-	-
3	RXIA PCB	-	-	-

3.4 Support Equipment

SE #	Description
1	Router, Manufacture: tp-link, Model: TL-WR841N
2	BLE interface PCB
3	Laptop, Manufacture: DELL, Model: Latitude E5470

3.5 Test Sample Configuration

Set-up #	Combination of AE used for test set up	Comments
1	EUT#1 + AE#1 + AE#2 + AE#3	-

3.6 Mode of Operation details

Mode of Operation	Description of Operating modes	Additional Information
Op. 1	RFID ASK	<p>Client provided a test mode and instructions to get the ability to configure the radio to:</p> <ul style="list-style-type: none">• CW mode.• Highest possible duty cycle. <p>Instructions and commands provided by the client will not be available to the end user.</p> <p>For Radiated measurements: The internal antenna was connected.</p>

3.7 Justification for Worst Case Mode of Operation

During the testing process the EUT was tested with transmitter sets the highest duty cycle, maximum output power and worst case of protocols supported.

For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in Code of Federal Regulations Title 47 CFR: Part 15.225.

This test report is to support a request for new equipment authorization under the:

- FCC ID: QP8ALIONOTEVZ

4.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor $k=1$.

Radiated measurement

9 kHz to 30 MHz	± 2.5 dB (Magnetic Loop Antenna)
30 MHz to 1000 MHz	± 2.0 dB (Biconilog Antenna)
1 GHz to 40 GHz	± 2.3 dB (Horn Antenna)

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error. Also used: <http://physics.nist.gov/cuu/Uncertainty/typeb.html>. The above calculated uncertainties apply to direct application of the Substitution method. The Substitution method is always used when the EUT comes closer than 3 dB to the limit.

4.2 Environmental Conditions during Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25° C
- Relative humidity: 40-60%

4.3 Dates of Testing:

03/11/2021 – 03/16/2021

5 Measurement Results Summary


Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	NA	NP	Result
§15.225 (a), (b), (c)	Field Strength (Fundamental)	Nominal	ASK	■	□	□	Complies
§15.225 (d) §15.209 (a)	TX Spurious emissions-Radiated	Nominal	ASK	■	□	□	Complies
§15.225(e)	Frequency stability	Extreme temperature and voltage conditions	ASK	■	□	□	Complies

6 Measurement Procedures


6.1 Radiated Measurement

The radiated measurement is performed according to ANSI C63.10 (2013)


- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 360° continuous measurement of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.



Radiated Emissions Test Setup 30MHz-1GHz Measurements



Radiated Emissions Test Setup above 1GHz Measurements



6.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dB μ V
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

$$\text{FS (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:

Frequency (MHz)	Measured SA (dB μ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB μ V/m)
1000	80.5	3.5	14	98.0

7 Test Result Data

7.1 Field strength

7.1.1 References

- **FCC Part 15 Subpart C-Intentional Radiators**
§15.225 Operation within the band 13.110-14.010 MHz
 - (a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
 - (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
 - (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- **RSS-210 – License-Exempt Radio Apparatus:**
 Category I Equipment

B.6 Band 13.110-14.010 MHz

- a. the field strength of any emission shall not exceed the following limits:
 - i. 15.848 mV/m (84 dBμV/m) at 30 m, within the band 13.553-13.567 MHz
 - ii. 334 μV/m (50.5 dBμV/m) at 30 m, within the bands 13.410-13.553 MHz and 13.567-13.710 MHz
 - iii. 106 μV/m (40.5 dBμV/m) at 30 m, within the bands 13.110-13.410 MHz and 13.710-14.010 MHz
 - iv. RSS-Gen general field strength limits for frequencies outside the band 13.110-14.010 MHz

7.1.2 Limits

According to ANSI C63.10-2013 Section 6.4.4

- Equation (1):
 $d_{\text{near field}} = 47.77 / f \text{ MHz}$
 $d_{\text{near field}} \approx 3.5 \text{ meters}$
- Equation (2)
 $FS_{\text{limit}} = FS_{\text{max}} - 40\log(d_{\text{near field}} / d_{\text{measure}}) - 20\log(d_{\text{limit}} / d_{\text{near field}})$

The limit applied to the measurement result, is converted to 3 meters, by using:

- 40 dB/decade extrapolation factor for distance $< \lambda/2\pi$ and;
- 20 dB/decade extrapolation factor for distance $> \lambda/2\pi$

Where:

- **FS_{limit}** : is the calculation of field strength at the limit distance, expressed in dBμV/m
- **FS_{max}** : is the measured field strength, expressed in dBμV/m $\approx 84 \text{ dBμV/m}$ (See note 1)
- **d_{near field}** : is the $\lambda/2\pi$ distance $\approx 3.5 \text{ meters}$
- **d_{measure}** : is the distance of the measurement point from the EUT = 3 meters
- **d_{limit}** : is the reference limit distance = 30 meters

Note 1: The maximum allowed field strength; 15.848 mV/m (84 dBμV/m), were used as **FS_{max}** to adjust the mask limit at the measured distance, so equation (2) will be:

$$FS_{limit} = FS_{max} + 40\log(d_{near\ field} / d_{measure}) + 20\log(d_{limit} / d_{near\ field})$$

- Within the band 13.553-13.567 MHz

$$FS_{limit} = 84 + 18.7 + 2.7$$

$$FS_{limit} = 105.4\text{ dB}\mu\text{V/m at 3 meters}$$

- Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz

$$FS_{limit} = 50.5 + 18.7 + 2.7$$

$$FS_{limit} = 71.9\text{ dB}\mu\text{V/m at 3 meters}$$

- Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz

$$FS_{limit} = 40.5 + 18.7 + 2.7$$

$$FS_{limit} = 61.9\text{ dB}\mu\text{V/m at 3 meters}$$

7.1.3 Test conditions and setup:

Ambient Temperature	EUT operating mode	Power Input
22° C	Op.1	110 VAC


7.1.4 Measurement plots:

Plot # 1 Field strength

NFC 13.56 MHz

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
13.349	54.23	62.04	7.81	1000.0	3.000	140.0	H	93.0	-17.5	
13.453	54.93	71.97	17.04	1000.0	3.000	140.0	H	284.0	-17.5	
13.772	57.74	61.76	4.02	1000.0	3.000	140.0	H	88.0	-17.6	



Preview Result 1-PK+ FCC 15.225 Fundamental converted to 3m_updated Final_Result PK+

7.2 Frequency Stability

7.2.1 References and limits

- **FCC Part 15 Subpart C-Intentional Radiators**

§15.225 Operation within the band 13.110-14.010 MHz

(e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

- **RSS-210 – License-Exempt Radio Apparatus:**
Category I Equipment

B.6 Band 13.110-14.010 MHz: the carrier frequency stability shall not exceed ± 100 ppm

7.2.2 Measurement procedure

Measurements were done according to ANSI C63.10-2013 Section 6.8 Frequency stability tests

7.2.3 Measurement results

The following formula used for PPM calculation:

$$\text{PPM} = ((\text{RCF} / \text{ACF}) - 1) * 10^6$$

Where:

RCF : Reference Center Frequency.

ACF : Assigned Center Frequency.

Variation = RCF – ACF


Frequency stability with respect to ambient temperature

Plot #	Temperature	RCF	ACF	Variation	PPM
2	-	13.56	-	-	-
3	60	13.56	13.56	0.000000	0
4	50		13.5616025	-0.001602	-118.1645016
5	40		13.56	0.000000	0
6	30		13.5616025	-0.001602	-118.1645016
7	20		13.56	0.000000	0
8	10		13.5616025	-0.001602	-118.1645016
9	0		13.5616026	-0.001603	-118.1718745
10	-5		13.56	0.000000	0
11	-15		13.5616026	-0.001603	-118.1718745

Plot #2

13.56 MHz

Reference Measurement




Date: 16.MAR.2021 14:59:19

Plot #3

13.56 MHz

Temperature: 60°C




Date: 16.MAR.2021 15:27:43

Plot #4

13.56 MHz

Temperature: 50°C




Date: 16.MAR.2021 15:21:01

Plot #5

13.56 MHz

Temperature: 40°C




Date: 16.MAR.2021 15:14:47

Plot #6

13.56 MHz

Temperature: 30°C




Date: 16.MAR.2021 15:06:14

Plot #7

13.56 MHz

Temperature: 20°C




Date: 16.MAR.2021 14:59:19

Plot #8

13.56 MHz

Temperature: 10°C




Date: 16.MAR.2021 14:53:19

Plot #9

13.56 MHz

Temperature: 0°C




Date: 16.MAR.2021 14:47:29

Plot #10

13.56 MHz

Temperature: -10°C




Date: 16.MAR.2021 14:42:27

Plot #11

13.56 MHz

Temperature: -20°C



Date: 16.MAR.2021 14:39:06

7.3 Transmitter Spurious Emissions and Restricted Bands

7.3.1 Measurement according to ANSI C63.10

Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector = Peak

- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW = 120 KHz (<1 GHz)

- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1MHz

Plots reported here represent the worst case emissions for horizontal and vertical antenna polarizations and for three orientations of the EUT. Unless mentioned otherwise, the emissions outside the limit lines in the plots are from the transmit signal.

7.3.2 Limits: FCC 15.247(d)/15.209(a) /RSS-Gen 6.13

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
- PEAK LIMIT= 74dB μ V/m
- AVG. LIMIT= 54dB μ V/m
- Except as shown in CFR 47 Part 15.205 paragraph (d), only spurious emissions are permitted in any of the frequency bands listed below

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements described in 5.4.

The highest (or worst-case) data rate shall be recorded for each measurement.


For testing at distance other than the specified in the standard, the limit conversion is calculated by using 40 dB/decade extrapolation as follow:

Conversion factor (CF) = $40 \log (D/d) = 40 \log (300 \text{ m} / 3 \text{ m}) = 80 \text{ dB}$

7.3.3 Test conditions and setup:

Ambient Temperature	EUT operating mode	Power Input
22° C	Op.1	110 VAC

7.3.4 Measurement Plots:




Plot # 2 Radiated Emissions: 30MHz – 1GHz

NFC 13.56 MHz

Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
34.818	29.40	40.00	10.60	1000.0	100.000	170.0	V	276.0	-16.9	
119.984	38.58	43.50	4.92	1000.0	100.000	202.0	H	291.0	-22.4	
188.110	39.25	43.50	4.25	1000.0	100.000	140.0	H	281.0	-20.7	
331.993	37.45	46.02	8.57	1000.0	100.000	140.0	H	144.0	-15.6	
528.030	37.97	46.02	8.05	1000.0	100.000	170.0	H	-12.0	-9.2	
792.032	37.66	46.02	8.36	1000.0	100.000	161.0	V	11.0	-5.8	



7.4 AC Power Line Conducted Emissions

7.4.1 Measurement according to ANSI C63.10 (2013)

Analyzer Settings:

- RBW = 9 KHz (CISPR Bandwidth)
- Pre-scan Detector = Peak / Average for
- Final Measurements Detector = Quasi-Peak / Average

7.4.2 Limits: FCC 15.207

(a) Except as shown in paragraphs (b) and (c) of this section of the CFR, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table (1), as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

7.4.3 Test conditions and setup:

Ambient Temperature (C)	EUT Set-Up #	EUT operating mode	Power line (L1, L2, L3, N)	Power Input
22	1	Op.1	Line & Neutral	110 V / 60 Hz

7.4.4 Measurement Result:

Plot #	Port	EUT Set-Up #	EUT operating mode	Scan Frequency	Limit	Result
1	AC Mains	1	Op.1	150 kHz – 30 MHz	See section 7.4.2	Pass


7.4.5 Measurement Plots:

Plot # 1

Disclaimer: Any measurement data within 2dB from the limit line is conditional PASS/FAIL due to measurement uncertainty considerations.

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	PE	Corr. (dB)	Comment
0.176	---	24.99	54.66	29.67	500.0	9.000	L1	GND	10.6	
0.176	42.31	---	64.66	22.35	500.0	9.000	L1	GND	10.6	
0.563	---	13.83	46.00	32.17	500.0	9.000	L1	GND	10.0	
0.563	17.04	---	56.00	38.96	500.0	9.000	L1	GND	10.0	
1.700	---	16.12	46.00	29.88	500.0	9.000	L1	GND	10.1	
1.700	19.80	---	56.00	36.20	500.0	9.000	L1	GND	10.1	
13.556	---	48.32	50.00	1.68	500.0	9.000	L1	GND	10.2	
13.556	50.11	---	60.00	9.89	500.0	9.000	L1	GND	10.2	



Preview Result 1-PK+
Final_Result QPK

EN 55032 Voltage on Mains QP
Final_Result CAV

EN 55032 Voltage on Mains AV

8 Test setup photos

Setup photos are included in supporting file name: "EMC_MEIGR_011_21001_FCC_Setup_Photos.pdf"

9 Test Equipment And Ancillaries Used For Testing

Equipment Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
ACTIVE LOOP ANTENNA	ETS LINDGREN	6507	00161344	3 YEARS	10/30/2020
BILOG ANTENNA	ETS.LINDGREN	3142E	00166067	3 YEARS	03/12/2020
HORN ANTENNA	EMCO	3115	00035114	3 YEARS	08/10/2020
HORN ANTENNA	ETS.LINDGREN	3117	00215984	3 YEARS	01/31/2021
HORN ANTENNA	ETS.LINDGREN	3116	00070497	3 YEARS	11/23/2020
SPECTRUM ANALYZER	R&S	FSU26	200065	3 YEARS	07/16/2019
SIGNAL ANALYZER	R&S	FSV 40	101022	3 YEARS	07/15/2019
TEST RECEIVER	R&S	ESU.EMI	100256	3 YEARS	07/16/2019
COMPACT DIGITAL BAROMETER	CONTROL COMPANY	10510-922	200236891	3 YEARS	04/13/2020
DIGITAL THERMOMETER	CONTROL COMPANY	36934-164	181230565	3 YEARS	01/10/2019
LINE IMPEDANCE STABILIZATION NETWORK	FCC	FCC-LISN-50-25-2-08	08014	3 YEARS	07/19/2019

Note: Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.

10 Revision History

Date	Report Name	Changes to report	Report prepared by
2021-04-23	EMC_MEIGR_011_21001_FCC_15.225_NFC	Initial Version	Yuchan Lu

<<The End>>