



# Maximum Permissible Exposure Evaluation

## FCC ID: 2A50S-G02

### 1. Client Information

Applicant	:	Shenzhen Tino Security Corp., LTD
Address	:	201, No.7, HeDian Industry Park FuMin Community, FuCheng Street, LongHua District, Shenzhen, China
Manufacturer	:	Shenzhen Tino Security Corp., LTD
Address	:	201, No.7, HeDian Industry Park FuMin Community, FuCheng Street, LongHua District, Shenzhen, China

### 2. General Description of EUT

EUT Name	:	AI Bird Camera
Models No.	:	G02, G01, G03, G04, G05, G06, G07, G08, G09, G10, G11, G12, G13, G14, G15, G16, G17, G18, G19, G20
Model Different	:	All PCB boards and circuit diagrams are the same, the only difference is that appearance and color.
Product Description	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz Bluetooth LE 5.0: 2402-2480MHz
	Number of Channel:	802.11b/g/n(HT20):11 channels 40 channels for Bluetooth LE
	Antenna Gain:	-2.49dBi Iron Plate Antenna for 2.4G WiFi 0.5dBi PCB Antenna for Bluetooth LE
Power Rating	:	Input: DC 5V
Li-ion Polymer Battery	:	DC 3.6V by 5000mAh Rechargeable Li-ion battery
Software Version	:	V0.6.1
Hardware Version	:	CG621_C03_V2
Connecting I/O Port(S)	:	Please refer to the User's Manual
Remark	:	the evaluation report used the EUT(RW-C-202304-0103-6-2#).



## MPE Calculations for WIFI

### 1. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 2. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

**S:** power density

**P:** power input to the antenna

**G:** power gain of the antenna in the direction of interest relative to an isotropic radiator.

**R:** distance to the center of radiation of the antenna

### 3. Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is  $\leq 1.0$ .

This means that:

$$\sum \text{ of MPE ratios } \leq 1.0$$

### 4. Test Result:

**2.4G WiFi & Bluetooth LE worst reported.**

Mode	Frequency (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]	Limit of Power Density (mW/ cm <sup>2</sup> ) (S)
Bluetooth LE	2402	-0.149	0±1	1	0.5	20	0.0003	1
	2440	-1.365	-1±1	0	0.5	20	0.0002	1
	2480	-1.463	-1±1	0	0.5	20	0.0002	1





Mode	Frequency (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]	Limit of Power Density (mW/ cm <sup>2</sup> ) (S)
802.11b	2412	17.128	17±1	18	-2.49	20	0.0071	1
	2437	17.552	18±1	19	-2.49	20	0.0089	1
	2462	16.874	17±1	18	-2.49	20	0.0071	1
802.11g	2412	16.019	16±1	17	-2.49	20	0.0056	1
	2437	16.267	16±1	17	-2.49	20	0.0056	1
	2462	16.606	17±1	18	-2.49	20	0.0071	1
802.11n(HT20)	2412	16.407	16±1	17	-2.49	20	0.0056	1
	2437	17.024	17±1	18	-2.49	20	0.0071	1
	2462	16.536	17±1	18	-2.49	20	0.0071	1

Maximum Simultaneous transmission MPE Ratios for 2.4GHz WiFi and Bluetooth LE.

Maximum MPE ratio 2.4GWiFi	Maximum MPE ratio Bluetooth LE	ΣMPE	Limit	Results
0.0089	0.0003	0.0092	1.0	PASS

## 5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

### Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm <sup>2</sup> )
300-1,500	F/1500
1,500-100,000	1.0

For 2.4WIFI&Bluetooth LE

MPE limit S: 1mW/ cm<sup>2</sup>

The MPE is calculated as **0.0092 < limit 1mW / cm<sup>2</sup>**. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

## Note

For a more detailed features description, please refer to the RF Test Report.

## 6. Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF REPORT-----

