



MEASUREMENT REPORT

FCC PART 15.247 WLAN 802.11b/g/n

FCC ID: 2AKWYPFB201

APPLICANT: DynaScan Technology Corp.

Application Type: Certification

Product: Control Board

Model No.: PFB201

Brand Name: **DynaScan**

FCC Classification: (DTS) Digital Transmission System

FCC Rule Part(s): Part 15.247

Test Procedure(s): ANSI C63.10-2013, KDB 558074 D01v03r05
KDB 996369 D01 v01r04

Test Date: January 17~19, 2017

Reviewed By :

Paddy Chen

(Paddy Chen)

Approved By :

Chenz Ker

(Chenz Ker)



Testing Laboratory
3261

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01v03r05. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1701TW0701-U1	1.0	Original Report	2017.01.19	

CONTENTS

Description	Page
§2.1033 General Information	5
1. INTRODUCTION	6
1.1. Scope.....	6
1.2. MRT Test Location	6
2. PRODUCT INFORMATION	7
2.1. Equipment Description	7
2.2. Working Frequencies for this Report	8
2.3. Test Mode	8
2.4. Test Software	8
2.5. Test Configuration.....	9
2.6. EMI Suppression Device(s)/Modifications	9
2.7. Labeling Requirements	9
3. DESCRIPTION of TEST	10
3.1. Evaluation Procedure	10
3.2. AC Line Conducted Emissions	10
3.3. Radiated Emissions	11
4. ANTENNA REQUIREMENTS.....	12
5. TEST EQUIPMENT CALIBRATION DATE	13
6. MEASUREMENT UNCERTAINTY	14
7. TEST RESULT	15
7.1. Summary.....	15
7.2. 6dB Bandwidth Measurement	16
7.2.1. Test Limit.....	16
7.2.2. Test Procedure used	16
7.2.3. Test Setting	16
7.2.4. Test Setup	16
7.2.5. Test Result	17
7.3. Output Power Measurement.....	20
7.3.1. Test Limit.....	20
7.3.2. Test Procedure Used.....	20
7.3.3. Test Setting	20
7.3.4. Test Setup	20
7.3.5. Test Result of Output Power	21
7.4. Power Spectral Density Measurement.....	22
7.4.1. Test Limit.....	22
7.4.2. Test Procedure Used.....	22
7.4.3. Test Setting	22
7.4.1. Test Setup	22
7.4.2. Test Result	23
7.5. Out-of-Band Spurious Emissions Emissions Measurement	26

7.5.1.	Test Limit	26
7.5.2.	Test Procedure Used.....	26
7.5.3.	Test Settintg	26
7.5.4.	Test Setup	27
7.5.5.	Test Result	28
7.6.	Radiated Spurious Emission Measurement.....	37
7.6.1.	Test Limit	37
7.6.2.	Test Procedure Used.....	37
7.6.3.	Test Setting	37
7.6.4.	Test Setup	39
7.6.5.	Test Result	41
7.7.	Radiated Restricted Band Edge Measurement.....	67
7.7.1.	Test Limit	67
7.7.2.	Test Procedure Used.....	67
7.7.3.	Test Setting	67
7.7.4.	Test Setup	69
7.7.5.	Test Result	70
7.8.	AC Conducted Emissions Measurement.....	88
7.8.1.	Test Limit	88
7.8.2.	Test Setup	88
7.8.3.	Test Result	89
8.	CONCLUSION	91
	Appendix A - Test Photograph.....	92
	Appendix B - External Photograph.....	94
	Appendix C - internal Photograph.....	98

§2.1033 General Information

Applicant:	DynaScan Technology Corp.
Applicant Address:	7F, 66 Huaya 1st Road, Guishan, Taoyuan 33383, Taiwan
Manufacturer:	DynaScan Technology Corp.
Manufacturer Address:	7F, 66 Huaya 1st Road, Guishan, Taoyuan 33383, Taiwan
Test Site:	MRT Technology (Taiwan) Co., Ltd
Test Site Address:	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT FCC Registration No.:	291082
FCC Rule Part(s):	Part 15.247
Model No.:	PFB201
FCC ID:	2AKWYPFB201
Host Product Number	Liquid crystal display devices
Host Model Number	DI551ST2
Test Device Serial No.:	N/A ☐ Production ☒ Pre-Production ☐ Engineering

Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Film.
2. MRT facility is an IC registered (MRT Reg. No. 21723-1) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (TAF) under the American Association for Laboratory Accreditation Program (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC, Industry Taiwan, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	Control Board
FCC ID	2AKWYPFB201
Model No.	PFB201
Brand Name	DynaScan
Supports Radios Spec.	WLAN : 2.4G : 802.11b/g/n-20/n-40
Wi-Fi Specification	802.11b/g/n
Frequency Range	<u>2.4GHz:</u> For 802.11b/g/n-20M: 2412 ~ 2462 MHz For 802.11n-40M: 2422 ~ 2452 MHz
2.4GHz Maximum Output Peak Power	802.11b: 18.05dBm 802.11g: 23dBm 802.11n-20M: 22.18dBm 802.11n-40M: 22.14 dBm
Type of Modulation	802.11b: DSSS, DBPSK, DQPSK, CCK 802.11g/n-20M/n-40M: OFDM(BPSK, QPSK, 16QAM, 64QAM)

Note: Since KDB 996369 D01 , If the module is limited because it is not shielded, only the module grantee can make the test evaluation that the module is compliant in the host (Product Number :Liquid crystal display devices; Model Number : DI551ST2).

2.2. Working Frequencies for this Report

802.11b/g/n-20M

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-40M

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

2.3. Test Mode

Test Mode	Mode 1: Transmit by 802.11b
	Mode 2: Transmit by 802.11g
	Mode 3: Transmit by 802.11n-20M
	Mode 4: Transmit by 802.11n-40M

2.4. Test Software

The test utility software used during testing was "REALTEK WLAN Test_V1.9.0".

2.5. Test Configuration

This device was tested per the guidance of KDB 558074 D01v03r05. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.6. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.7. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01v03r05 were used in the measurement of this device.

Deviation from measurement procedure.....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 9'x4'x3' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment which determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.8.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, which produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

Radiated emissions test results are shown in Section 7.6 & 7.7 .

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna is permanently attached.
- There are no provisions for connection to an external antenna.

Conclusion:

This device unit complies with the requirement of §15.203.

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	Walsin	WE9G650002	Metal	0.87 dBi

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2017/03/16
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2017/03/23
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2017/03/23
Cable	Rosnol	N1C50-RG400-B1 C50-500CM	MRTTWE00013	1 year	2017/05/19

Radiated Emissions – AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2017/03/16
Broadband TRILOG Antenna	Schwarzbeck	VULB 9162	MRTTWA00001	1 year	2017/04/05
Active Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2017/04/05
Broadband Horn antenna	Schwarzbeck	BBHA 9120D	MRTTWA00003	1 year	2017/04/05
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2017/04/05
Broadband Preamplifier	Schwarzbeck	BBV 9718	MRTTWA00005	1 year	2017/04/05
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2017/04/05
Signal Analyzer	R&S	FSV40	MRTTWA00007	1 year	2017/03/02
Cable	HUBERSUH NER	SF106	MRTTWA00010	1 year	2017/05/19
Cable	Rosnol	K1K50-UP026 4-K1K50-4M	MRTTWA00012	1 year	2017/05/19

Conducted Test Equipment – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2017/07/10
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00014	1 year	2017/03/17

Software	Version	Function
e3	9.160520a	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement – SR2	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$):	
150kHz~30MHz: 2.42dB	
Conducted Measurement– SR1	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 1.3dB	
Radiated Emission Measurement – AC1	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$):	
Horizontal:	9K~30MHz: 4.14dB
	30MHz~1GHz: 4.22dB
	1GHz~40GHz: 4.05dB
Vertical:	9K~30MHz: 4.14dB
	30MHz~1GHz: 3.37dB
	1GHz~40GHz: 4.08dB

7. TEST RESULT

7.1. Summary

Product Name: Control Board
FCC ID: 2AKWYPFB201
FCC Classification: (DTS) Digital Transmission System
Data Rate(s) Tested: 1Mbps ~ 11Mbps (b); 6Mbps ~ 54Mbps (g);
6.5/7.2Mbps ~ 65/72.2Mbps (n-20M);
13.5/15.0Mbps ~ 135/150Mbps (n-40M)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	$\geq 500\text{kHz}$	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	$\leq 30.00\text{dBm}$		Pass	Section 7.3
15.247(e)	Power Spectral Density	$\leq 8.00\text{dBm}/3\text{kHz}$		Pass	Section 7.4
15.247(d)	Out-of-Band Emissions	Conducted $\geq 20\text{dBc}$		Pass	Section 7.5
15.205 15.209	Spurious Emission	$< \text{FCC 15.209 limits}$	Radiated	Pass	Section 7.6
15.205 15.209	Band Edge Measurement	$\leq 74\text{dBuV}/\text{m}(\text{Peak})$ $\leq 54\text{dBuV}/\text{m}(\text{Average})$		Pass	Section 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	$< \text{FCC 15.207 limits}$	Line Conducted	Pass	Section 7.8

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


7.2.2. Test Procedure used

KDB 558074 D01v03r05- Section 8.2 Option 2

7.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace was allowed to stabilize


7.2.4. Test Setup




7.2.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)	Result
802.11b	01	2412	10.11	15.472	≥ 0.5	Pass
802.11b	06	2437	10.11	15.470	≥ 0.5	Pass
802.11b	11	2462	10.11	15.476	≥ 0.5	Pass
802.11g	01	2412	16.60	16.554	≥ 0.5	Pass
802.11g	06	2437	16.60	16.562	≥ 0.5	Pass
802.11g	11	2462	16.60	16.566	≥ 0.5	Pass
802.11n-20M	01	2412	17.86	17.802	≥ 0.5	Pass
802.11n-20M	06	2437	17.86	17.799	≥ 0.5	Pass
802.11n-20M	11	2462	17.85	17.797	≥ 0.5	Pass
802.11n-40M	03	2422	36.48	36.092	≥ 0.5	Pass
802.11n-40M	06	2437	36.48	36.108	≥ 0.5	Pass
802.11n-40M	09	2452	36.47	36.096	≥ 0.5	Pass


802.11 b CH01 (2412MHz)




802.11 b CH06 (2437MHz)




802.11 b CH11 (2462MHz)




802.11 g CH01 (2412MHz)




802.11 g CH06 (2437MHz)




802.11 g CH11 (2462MHz)




802.11 n-20M CH01 (2412MHz)




802.11 n-20M CH06 (2437MHz)




802.11 n-20M CH11 (2462MHz)




802.11 n-40M CH03 (2422MHz)



802.11 n-40M CH 06 (2437MHz)



802.11 n-40M CH 09 (2452MHz)



7.3. Output Power Measurement

7.3.1. Test Limit

The maximum out power shall be less 1 Watt (30dBm).

7.3.2. Test Procedure Used

KDB 558074 D01v03r05 - Section 9.1.2 & 9.2.3.2

7.3.3. Test Setting


Peak Power Measurement

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

7.3.4. Test Setup



7.3.5. Test Result of Output Power

2.4GHz 802.11b RF Output Power (dBm)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)				Peak Power	Required Limit				
		1	2	5.5	11						
01	2412	15.75	--	--	--	17.74	1Watt= 30 dBm				
06	2437	16.02	16.01	16	15.99	18.05	1Watt= 30 dBm				
11	2462	15.95	--	--	--	17.9	1Watt= 30 dBm				
2.4GHz 802.11g RF Output Power (dBm)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		6	9	12	18	24	36	48	54		
01	2412	14.06	--	--	--	--	--	--	--	22.77	1Watt= 30 dBm
06	2437	14.15	14.08	14.03	14.08	14.01	13.95	13.96	13.96	22.88	1Watt= 30 dBm
11	2462	14.18	--	--	--	--	--	--	--	23	1Watt= 30 dBm
2.4GHz 802.11n-20M RF Output Power (dBm)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
01	2412	13.31	--	--	--	--	--	--	--	22	1Watt= 30 dBm
06	2437	13.36	13.22	13.25	13.25	13.24	13.2	13.21	13.33	22.04	1Watt= 30 dBm
11	2462	13.47	--	--	--	--	--	--	--	22.18	1Watt= 30 dBm
2.4GHz 802.11n-40M RF Output Power (dBm)											
Channel No.	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7		
03	2422	13.08	--	--	--	--	--	--	--	22.14	1Watt= 30 dBm
06	2437	13.2	13.09	13.05	13.04	13.04	12.92	12.97	12.88	21.31	1Watt= 30 dBm
09	2452	13.08	--	--	--	--	--	--	--	21.54	1Watt= 30 dBm

Note: Output power =Reading value on power meter + cable loss °

7.4. Power Spectral Density Measurement

7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

7.4.2. Test Procedure Used


KDB 558074 D01v03r05 - Section 10.2 Method PKPSD

7.4.3. Test Setting

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: 3 kHz.
- d) Set the VBW $\geq 3 \times$ RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.


7.4.1. Test Setup



7.4.2. Test Result

Test Mode	Channel No.	Freq. (MHz)	PSD (dBm)	Limit (dBm)	Result
11b	1	2412	-14.550	≤ 8	Pass
11b	6	2437	-14.570	≤ 8	Pass
11b	11	2462	-14.564	≤ 8	Pass
11g	1	2412	-15.215	≤ 8	Pass
11g	6	2437	-14.737	≤ 8	Pass
11g	11	2462	-14.649	≤ 8	Pass
11n-20M	1	2412	-15.234	≤ 8	Pass
11n-20M	6	2437	-14.813	≤ 8	Pass
11n-20M	11	2462	-15.191	≤ 8	Pass
11n-40M	3	2422	-15.396	≤ 8	Pass
11n-40M	6	2437	-16.089	≤ 8	Pass
11n-40M	9	2452	-17.459	≤ 8	Pass


802.11 b CH01 (2412MHz)




802.11 b CH06 (2437MHz)




802.11 b CH11 (2462MHz)




802.11 g CH01 (2412MHz)




802.11 g CH06 (2437MHz)




802.11 g CH11 (2462MHz)




802.11 n-20M CH01 (2412MHz)



802.11 n-20M CH06 (2437MHz)



802.11 n-20M CH11 (2462MHz)



7.5. Out-of-Band Spurious Emissions Emissions Measurement

7.5.1. Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.


7.5.2. Test Procedure Used

KDB 558074 D01v03r05- Section 11.1 & 11.2

7.5.3. Test Settling

- (a) Set instrument center frequency to DTS channel center frequency
- (b) Set the span to ≥ 1.5 times the DTS bandwidth
- (c) Set the RBW = 100 kHz
- (d) Set the VBW $\geq 3 \times$ RBW
- (e) Detector = peak
- (f) Sweep time = auto couple
- (g) Trace mode = max hold
- (h) Allow trace to fully stabilize

7.5.4. Test Setup




7.5.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	Limit	Result
802.11b	01	2412	20dBc	Pass
802.11b	06	2437	20dBc	Pass
802.11b	11	2462	20dBc	Pass
802.11g	01	2412	20dBc	Pass
802.11g	06	2437	20dBc	Pass
802.11g	11	2462	20dBc	Pass
802.11n-20M	01	2412	20dBc	Pass
802.11n-20M	06	2437	20dBc	Pass
802.11n-20M	11	2462	20dBc	Pass
802.11n-40M	03	2422	20dBc	Pass
802.11n-40M	06	2437	20dBc	Pass
802.11n-40M	09	2452	20dBc	Pass


802.11 b CH01 (2412MHz)




802.11 b CH01 (2412MHz)



802.11 b CH01 (2412MHz)




802.11 b CH01 (2412MHz)




802.11 b CH06 (2437MHz)




802.11 b CH06 (2437MHz)



802.11 b CH06 (2437MHz)




802.11 b CH06 (2437MHz)




802.11 b CH11 (2462MHz)




802.11 b CH11 (2462MHz)



802.11 b CH11 (2462MHz)




802.11 b CH11 (2462MHz)




802.11 g CH01 (2412MHz)




802.11 g CH01 (2412MHz)




802.11 g CH01 (2412MHz)




802.11 g CH01 (2412MHz)




802.11 g CH06 (2437MHz)




802.11 g CH06 (2437MHz)




802.11 g CH06 (2437MHz)




802.11 g CH06 (2437MHz)




802.11 g CH11 (2462MHz)




802.11 g CH11 (2462MHz)




802.11 g CH11 (2462MHz)




802.11 g CH11 (2462MHz)




802.11 n-20 CH01 (2412MHz)




802.11 n-20 CH01 (2412MHz)




802.11 n-20 CH01 (2412MHz)




802.11 n-20 CH01 (2412MHz)




802.11 n-20 CH06 (2437MHz)




802.11 n-20 CH06 (2437MHz)




802.11 n-20 CH06 (2437MHz)




802.11 n-20 CH06 (2437MHz)




802.11 n-20 CH11 (2462MHz)




802.11 n-20 CH11 (2462MHz)



802.11 n-20 CH11 (2462MHz)




802.11 n-20 CH11 (2462MHz)




802.11 n-40 CH03 (2422MHz)




802.11 n-40 CH03 (2422MHz)



802.11 n-40 CH03 (2422MHz)




802.11 n-40 CH03 (2422MHz)




802.11 n-40 CH06 (2437MHz)




802.11 n-40 CH06 (2437MHz)



802.11 n-40 CH06 (2437MHz)




802.11 n-40 CH06 (2437MHz)




802.11 n-20 CH09 (2452MHz)




802.11 n-20 CH09 (2452MHz)



802.11 n-20 CH09 (2452MHz)



802.11 n-20 CH09 (2452MHz)



7.6. Radiated Spurious Emission Measurement

7.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

7.6.2. Test Procedure Used

KDB 558074 D01v03r05- Section 12.2.3 (quasi-peak measurements)

KDB 558074 D01v03r05- Section 12.2.4 (peak power measurements)

KDB 558074 D01v03r05- Section 12.2.5 (average power measurements)

7.6.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple

6. Trace mode = max hold

7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. RBW = 1MHz

3. VBW $\geq 1/T$

4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to “Voltage” regardless of the display mode

5. Detector = Peak


6. Sweep time = auto

7. Trace mode = max hold


8. Allow max hold to run for at least 50 times (1/duty cycle) traces

7.6.4. Test Setup


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:



1GHz ~ 18GHz Test Setup:




18GHz ~25GHz Test Setup:



7.6.5. Test Result

EUT	Liquid crystal display devices	Test Date	2017/01/16
Factor	VULB 9162 (30MHz~8GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH06	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	95.627	18.5	12.64	31.14	-12.36	43.5	200	-10	QP
2	125.151	20.32	10.59	30.91	-12.59	43.5	100	375	QP
3	451.677	16.05	17.68	33.73	-12.27	46	150	260	QP
4	594.176	15.74	20.24	35.98	-10.02	46	200	165	QP
5	* 742.617	16.47	22.44	38.91	-7.09	46	150	-30	QP
6	890.936	14.52	24.35	38.87	-7.13	46	200	195	QP

Note :

- "*" means the worst value in this measurement data .
- Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB) .
- Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
- The emission levels of other frequencies are very lower than the limit and not show in test report .
- Other channel/mode was also verified. The test results shown represent the worst case emissions .
- No emission found between lowest internal used/generated frequency to 30MHz .

EUT	Liquid crystal display devices	Test Date	2017/01/16
Factor	VULB 9162 (30MHz~8GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH06	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	74.741	20.6	9.34	29.94	-10.06	40	100	175	QP
2	123.181	20.23	10.82	31.05	-12.45	43.5	150	-20	QP
3	439.946	18.8	17.48	36.28	-9.72	46	150	320	QP
4	594.388	19.58	20.24	39.82	-6.18	46	100	140	QP
5	* 742.253	19.12	22.43	41.55	-4.45	46	100	75	QP
6	891.542	12.08	24.37	36.45	-9.55	46	150	210	QP

Note :

- " * " means the worst value in this measurement data .
- Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
- Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
- The emission levels of other frequencies are very lower than the limit and not show in test report .
- Other channel/mode was also verified. The test results shown represent the worst case emissions .
- No emission found between lowest internal used/generated frequency to 30MHz .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4824	40.07	3.67	43.74	-30.26	74	400	400	Peak
2		7236	33.23	12.19	45.42	-28.58	74	400	400	Peak
3	*	9648	30.37	15.67	46.04	-27.96	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4824	35.83	3.67	39.5	-34.5	74	400	400	Peak
2		7236	32.25	12.19	44.44	-29.56	74	400	400	Peak
3	*	9648	30.06	15.67	45.73	-28.27	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH06	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4874	38.44	3.65	42.09	-31.91	74	400	400	Peak
2		7311	33.28	12.34	45.62	-28.38	74	400	400	Peak
3	*	9748	30.59	16.02	46.61	-27.39	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH06	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4874	35.36	3.65	39.01	-34.99	74	400	400	Peak
2		7311	30.9	12.34	43.24	-30.76	74	400	400	Peak
3	*	9748	31.43	16.02	47.45	-26.55	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH11	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4924	41.25	3.65	44.9	-29.1	74	400	400	Peak
2		7386	30.83	12.53	43.36	-30.64	74	400	400	Peak
3	*	9848	32.34	16.34	48.68	-25.32	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH11	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4924	37.47	3.65	41.12	-32.88	74	400	400	Peak
2		7386	30.83	12.53	43.36	-30.64	74	400	400	Peak
3	*	9848	30.19	16.34	46.53	-27.47	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4824	36.75	3.67	40.42	-33.58	74	400	400	Peak
2		7236	31.1	12.19	43.29	-30.71	74	400	400	Peak
3	*	9648	30.83	15.67	46.5	-27.5	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4824	34.02	3.67	37.69	-36.31	74	400	400	Peak
2		7236	31.41	12.19	43.6	-30.4	74	400	400	Peak
3	*	9648	30.9	15.67	46.57	-27.43	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH06	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4874	33.98	3.65	37.63	-36.37	74	400	400	Peak
2		7311	31.01	12.34	43.35	-30.65	74	400	400	Peak
3	*	9748	28.73	16.02	44.75	-29.25	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH06	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4874	32.88	3.65	36.53	-37.47	74	400	400	Peak
2		7311	32.18	12.34	44.52	-29.48	74	400	400	Peak
3	*	9748	29.28	16.02	45.3	-28.7	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH11	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4924	34.48	3.65	38.13	-35.87	74	400	400	Peak
2		7386	30.31	12.53	42.84	-31.16	74	400	400	Peak
3	*	9848	31.76	16.34	48.1	-25.9	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH11	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4924	33.35	3.65	37	-37	74	400	400	Peak
2		7386	30.95	12.53	43.48	-30.52	74	400	400	Peak
3	*	9848	30.66	16.34	47	-27	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE3-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4824	33.74	3.67	37.41	-36.59	74	400	400	Peak
2		7236	32.9	12.19	45.09	-28.91	74	400	400	Peak
3	*	9648	29.6	15.67	45.27	-28.73	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE3-CH01	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824	34.28	3.67	37.95	-36.05	74	400	400	Peak
2	7236	31.89	12.19	44.08	-29.92	74	400	400	Peak
3	* 9648	30.12	15.67	45.79	-28.21	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE3-CH06	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4874	33.05	3.65	36.7	-37.3	74	400	400	Peak
2		7311	30.6	12.34	42.94	-31.06	74	400	400	Peak
3	*	9748	29.9	16.02	45.92	-28.08	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE3-CH06	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874	33.25	3.65	36.9	-37.1	74	400	400	Peak
2	7311	30.49	12.34	42.83	-31.17	74	400	400	Peak
3	* 9748	29.33	16.02	45.35	-28.65	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE3-CH11	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924	34.6	3.65	38.25	-35.75	74	400	400	Peak
2	7386	30.17	12.53	42.7	-31.3	74	400	400	Peak
3	* 9848	31.09	16.34	47.43	-26.57	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE3-CH11	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924	33.29	3.65	36.94	-37.06	74	400	400	Peak
2	7386	29.83	12.53	42.36	-31.64	74	400	400	Peak
3	* 9848	30.25	16.34	46.59	-27.41	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE4-CH03	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4844	35.68	3.68	39.36	-34.64	74	400	400	Peak
2		7266	31.96	12.25	44.21	-29.79	74	400	400	Peak
3	*	9688	31.5	15.81	47.31	-26.69	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE4-CH03	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4844	33.98	3.68	37.66	-36.34	74	400	400	Peak
2		7266	30.39	12.25	42.64	-31.36	74	400	400	Peak
3	*	9688	30.83	15.81	46.64	-27.36	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data .
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) .
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) .
4. The emission levels of other frequencies are very lower than the limit and not show in test report .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH06	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874	33.72	3.65	37.37	-36.63	74	400	400	Peak
2	7311	30.56	12.34	42.9	-31.1	74	400	400	Peak
3	* 9748	30.61	16.02	46.63	-27.37	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH06	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4874	33.19	3.65	36.84	-37.16	74	400	400	Peak
2		7311	30.61	12.34	42.95	-31.05	74	400	400	Peak
3	*	9748	30.38	16.02	46.4	-27.6	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH09	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		4904	33.02	3.64	36.66	-37.34	74	400	400	Peak
2		7356	30.94	12.44	43.38	-30.62	74	400	400	Peak
3	*	9808	31.45	16.24	47.69	-26.31	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	20°C / 58%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE4-CH09	Test Voltage	AC 120V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4904	33.73	3.64	37.37	-36.63	74	400	400	Peak
2	7356	31.21	12.44	43.65	-30.35	74	400	400	Peak
3	* 9808	30.33	16.24	46.57	-27.43	74	400	400	Peak

Note :

1. " * " means the worst value in this measurement data °
2. Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB) °
3. Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) °
4. The emission levels of other frequencies are very lower than the limit and not show in test report °

7.7. Radiated Restricted Band Edge Measurement

7.7.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 – 30	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

7.7.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.12.1

7.7.3. Test Setting

Peak Field Strength Measurements

8. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

9. RBW = as specified in Table 1

10. VBW = 3 * RBW

11. Detector = peak

12. Sweep time = auto couple

13. Trace mode = max hold

14. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency


Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements


9. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
10. RBW = 1MHz
11. VBW $\geq 1/T$
12. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
13. Detector = Peak
14. Sweep time = auto
15. Trace mode = max hold
16. Allow max hold to run for at least 50 times (1/duty cycle) traces

7.7.4. Test Setup

1GHz ~ 18GHz Test Setup:




18GHz ~40GHz Test Setup:



7.7.5. Test Result

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2373.75	57.11	-1.79	55.32	-18.68	74	170	395	Peak
2		2390	40.1	-1.84	38.26	-35.74	74	170	395	Peak
3		2412	83.55	-1.92	81.63	7.63	74	170	395	Peak

Note :

- "*" means the worst value in this measurement data °
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) °
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2373.75	32	-1.79	30.21	-23.79	54	170	395	Average
2		2390	25.27	-1.84	23.43	-30.57	54	170	395	Average
3		2412	78.02	-1.92	76.1	22.1	54	170	395	Average

Note :

1. " * " means the worst value in this measurement data .
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2376.5	50.37	-1.81	48.56	-25.44	74	150	340	Peak
2		2390	37.95	-1.84	36.11	-37.89	74	150	340	Peak
3		2412.125	82.68	-1.92	80.76	6.76	74	150	340	Peak

Note :

- "*" means the worst value in this measurement data .
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
- Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH11	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2462.08	83.05	-2.08	80.97	6.97	74	160	290	Peak
2	2483.5	42.04	-2.08	39.96	-34.04	74	160	290	Peak
3	* 2488.24	43.01	-2.07	40.94	-33.06	74	160	290	Peak

Note :

- "*" means the worst value in this measurement data °
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) °
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE1-CH11	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2462.02	77.43	-2.08	75.35	1.35	74	150	40	Peak
2	2483.5	36.85	-2.08	34.77	-39.23	74	150	40	Peak
3	* 2488	40.75	-2.07	38.68	-35.32	74	150	40	Peak

Note :

1. " * " means the worst value in this measurement data .
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2376.25	57.23	-1.81	55.42	-18.58	74	170	395	Peak
2		2390	41.12	-1.84	39.28	-34.72	74	170	395	Peak
3		2413.5	82.9	-1.92	80.98	6.98	74	170	395	Peak

Note :

- "*" means the worst value in this measurement data .
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2376.25	32.38	-1.81	30.57	-23.43	54	170	395	Average
2		2390	26.97	-1.84	25.13	-28.87	54	170	395	Average
3		2413.5	72.67	-1.92	70.75	16.75	54	170	395	Average

Note :

- "*" means the worst value in this measurement data °
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) °
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2374.75	50	-1.79	48.21	-25.79	74	150	345	Peak
2		2390	40.61	-1.84	38.77	-35.23	74	150	345	Peak
3		2415.375	82.52	-1.93	80.59	6.59	74	150	345	Peak

Note :

- "*" means the worst value in this measurement data .
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH11	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2468.74	84.04	-2.08	81.96	7.96	74	150	290	Peak
2	2483.5	45.35	-2.08	43.27	-30.73	74	150	290	Peak
3	* 2484.22	46.21	-2.08	44.13	-29.87	74	150	290	Peak

Note :

- "*" means the worst value in this measurement data °
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) °
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) °

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE2-CH11	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2468.68	77.41	-2.08	75.33	1.33	74	150	40	Peak
2	2483.5	39.39	-2.08	37.31	-36.69	74	150	40	Peak
3	* 2488.48	40.73	-2.07	38.66	-35.34	74	150	40	Peak

Note :

- "*" means the worst value in this measurement data .
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE3-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2375	54.1	-1.8	52.3	-21.7	74	170	395	Peak
2		2390	44.98	-1.84	43.14	-30.86	74	170	395	Peak
3		2409	82.66	-1.91	80.75	6.75	74	170	395	Peak

Note :

1. " *" means the worst value in this measurement data .
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE3-CH01	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2376	49.03	-1.81	47.22	-26.78	74	150	345	Peak
2		2390	41.02	-1.84	39.18	-34.82	74	150	345	Peak
3		2415.25	80.98	-1.93	79.05	5.05	74	150	345	Peak

Note :

1. " *" means the worst value in this measurement data .
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE3-CH11	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1		2469.46	82.82	-2.07	80.75	6.75	74	150	290	Peak
2	*	2483.5	46.19	-2.08	44.11	-29.89	74	150	290	Peak
3		2484.82	45.22	-2.08	43.14	-30.86	74	150	290	Peak

Note :

1. " * " means the worst value in this measurement data .
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE3-CH11	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2458.96	76.76	-2.07	74.69	0.69	74	150	40	Peak
2	2483.5	39.98	-2.08	37.9	-36.1	74	150	40	Peak
3	* 2488.66	40.35	-2.07	38.28	-35.72	74	150	40	Peak

Note :

- "*" means the worst value in this measurement data .
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE4-CH03	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2376.22	53.56	-1.81	51.75	-22.25	74	170	395	Peak
2		2390	41.36	-1.84	39.52	-34.48	74	170	395	Peak
3		2414.3	79	-1.92	77.08	3.08	74	170	395	Peak

Note :

1. " *" means the worst value in this measurement data .
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE4-CH03	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2377.48	49.34	-1.81	47.53	-26.47	74	150	345	Peak
2		2390	38.83	-1.84	36.99	-37.01	74	150	345	Peak
3		2419.9	78.8	-1.96	76.84	2.84	74	150	345	Peak

Note :

- "*" means the worst value in this measurement data .
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Horizontal	Site / Engineer	AC1 / Kevin
Test Mode	MODE4-CH09	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2468.56	80.28	-2.08	78.2	4.2	74	150	290	Peak
2	2483.5	46.02	-2.08	43.94	-30.06	74	150	290	Peak
3	* 2485.12	48.1	-2.08	46.02	-27.98	74	150	290	Peak

Note :

- "*" means the worst value in this measurement data .
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) .
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor) .

EUT	Liquid crystal display devices	Test Date	2017/01/17
Factor	BBHA 9120D (1GHz~18GHz)	Temp. / Humidity	21°C / 57%
Polarity	Vertical	Site / Engineer	AC1 / Kevin
Test Mode	MODE4-CH09	Test Voltage	AC 120V/60Hz



No	Frequency (MHz)	Reading (dBUV)	C.F (dB)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2462.24	73.27	-2.08	71.19	-2.81	74	150	40	Peak
2	2483.5	38.39	-2.08	36.31	-37.69	74	150	40	Peak
3	* 2488.24	41.33	-2.07	39.26	-34.74	74	150	40	Peak

Note :

- "*" means the worst value in this measurement data °
- C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB) °
- Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor) °

7.8. AC Conducted Emissions Measurement


7.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 / RSS-Gen Limits		
Frequency (MHz)	QP (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.8.2. Test Setup



7.8.3. Test Result

EUT	Liquid crystal display devices	Test Date	2017/01/19
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	24°C / 55%
Polarity	Line1	Site / Engineer	SR2 / Kevin
Test Mode	MODE1	Test Voltage	AC120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1		0.195	32	10	42	-21.82	63.82	QP
2		0.195	17.82	10	27.82	-26	53.82	Average
3	*	0.47847	29	10.08	39.08	-17.29	56.37	QP
4	*	0.47847	25.32	10.08	35.4	-10.97	46.37	Average
5		1.068	29.72	9.89	39.61	-16.39	56	QP
6		1.068	19.82	9.89	29.71	-16.29	46	Average
7		2.017	30.28	9.86	40.14	-15.86	56	QP
8		2.017	17.52	9.86	27.38	-18.62	46	Average
9		8.96	32.95	9.81	42.76	-17.24	60	QP
10		8.96	23.69	9.81	33.5	-16.5	50	Average
11		24.115	21.67	10.01	31.68	-28.32	60	QP
12		24.115	14.89	10.01	24.9	-25.1	50	Average

Note :

- "*" means the worst value in this measurement data .
- C.F (Correction Factor) = Factor (dB)+ Cable Loss (dB) .
- Measurement (dBuV) = Reading(dBuV)+ C.F (Correction Factor) .
- Other mode was also verified. The test results shown represent the worst case emissions .

EUT	Liquid crystal display devices	Test Date	2017/01/19
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	24°C / 55%
Polarity	Neutral	Site / Engineer	SR2 / Kevin
Test Mode	MODE1	Test Voltage	AC120V/60Hz



No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1		0.48297	29.04	10.11	39.15	-17.14	56.29	QP
2		0.48297	25.84	10.11	35.95	-10.34	46.29	Average
3		0.67645	29.65	10.04	39.69	-16.31	56	QP
4		0.67645	25.52	10.04	35.56	-10.44	46	Average
5	*	1.45	30.65	9.87	40.52	-15.48	56	QP
6	*	1.45	21.84	9.87	31.71	-14.29	46	Average
7		2.593	29.89	9.85	39.74	-16.26	56	QP
8		2.593	15.96	9.85	25.81	-20.19	46	Average
9		9.334	33.11	9.85	42.96	-17.04	60	QP
10		9.334	22.64	9.85	32.49	-17.51	50	Average
11		14.387	25.07	9.98	35.05	-24.95	60	QP
12		14.387	17.72	9.98	27.7	-22.3	50	Average

Note :

- "*" means the worst value in this measurement data .
- C.F (Correction Factor) = Factor (dB)+ Cable Loss (dB) .
- Measurement (dBuV) = Reading(dBuV)+ C.F (Correction Factor) .
- Other channel was also verified. The test results shown represent the worst case emissions.

8. CONCLUSION

The data collected relate only the item(s) tested and show that the Control Board , FCC ID:

2AKWYPFB201 is in compliance with Part 15C of the FCC Rules.