

SPURIOUS EMISSION RADIATE

EUT: WML-C06 / 24.10.2001
Manufacturer: Mitsumi
Operating Condition: TX on 2480 MHz
Test Site: 7 Layers Ratingen
Operator: gal
Test Specification: FCC 15.247 (15.35b, 15.209)
Comment: vertical + horizontal antenna polarisation
vertical EUT position

SCAN TABLE: "FCC 15.209 C Field m"

Short Description:		FCC ClassA		Field Strength		Transducer
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	
Frequency	Frequency	Width				
30.0 MHz	1000.0 MHz	60.0 kHz	MaxPeak	100.0 ms	120 kHz	HL562
1.0 GHz	2.4 GHz	500.0 kHz	MaxPeak	100.0 ms	1 MHz	HF 906 / 001
			Average			
2.5 GHz	7.0 GHz	500.0 kHz	MaxPeak	100.0 ms	1 MHz	HF 906 / 001
			Average			
7.0 GHz	18.0 GHz	500.0 kHz	MaxPeak	100.0 µs	1 MHz	HF 906 / 001
			Average			
18.0 GHz	25.0 GHz	500.0 kHz	MaxPeak	100.0 ms	1 MHz	EMCO 3160-09
			Average			

