

Choose Scandinavian trust

RADIO TEST REPORT

Report ID: REP055009

Type of assessment:

SAR Exemption report

Manufacturer:

Sensormatic USA LLC

Project number:

PRJ52103356

Hardware Version Identification Number (HVIN):

LFAMB2102

Product Marketing Name (PMN):

Label Deactivator Controller

FCC ID:

BVCAMB9012

ISED certification number:

3506A-AMB9012

Specifications:

- FCC 47 CFR Part 2 Subpart J, §2.1093
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- ISED Canada RSS-102 Issue 5 Amendment 1, (February 2021)
- Supplementary Procedure SPR-002, Issue 2
- Health Canada Safety Code 6

RSS-102 Annex C Attestation:

I attest that the radiocommunication apparatus meets the exemption from the routine evaluation limits in these standards; that the Technical Brief was prepared and the information contained therein is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed; and that the device meets the SAR and/or RF field strength limits of the above standards.

Date of issue: September 5, 2024

Tarek Elkholy

Tarek Elkholy, EMC/RF Specialist

Prepared by

Signature

Nemko Canada Inc., a testing laboratory, is accredited by ANSI National Accreditation Board (ANAB). The tests included in this report are within the scope of this accreditation. The ANAB symbol is an official symbol of the ANSI National Accreditation Board, used under licence.



ANAB File Number: AT-3195 (Ottawa/Almonte); AT-3193 (Pointe-Claire); AT-3194 (Cambridge)



Lab locations

Company name	Nemko Canada Ir	าс.					
Facilities	Ottawa site: 303 River Road Ottawa, Ontario Canada K1V 1H2		<i>Montréal site:</i> 292 Labrosse Ave Pointe-Claire, Que Canada H9R 5L8	nue ébec	<i>Cambridge site:</i> 1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2		
	Tel: +1 613 737 9680 Fax: +1 613 737 9691		Tel: +1 514 694 2684 Fax: +1 514 694 3528		Tel: +1 519 650 4811		
Test site identifier	Organization	Ottawa	Montreal	Cambridge			
	FCC:	CA2040	CA2041	CA0101			
	ISED:	2040A-4	2040G-5	24676			
Website	www.nemko.con	<u>n</u>					

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. © Nemko Canada Inc.



Table of Contents

Table of C	able of Contents						
Section 1	Evaluation summary4	ļ					
1.1	SAR exemption for standalone transmission, FCC						
1.2	Nerve Stimulation test, ISED	1					

Section 1 Evaluation summary

1.1 SAR exemption for standalone transmission, FCC

1.1.1 References, definitions and limits

FCC §2.1093

(2) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

FCC KDB 447498 D01

lèmko

- 4.3.1 Standalone SAR test exclusion considerations
 - c For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C)
 - For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by [1 + log(100/f(MHz))]
 - 2) For test separation distances < 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by ½
 - 3) SAR measurement procedures are not established below 100 MHz.

Appendix C

Table 1.1-1: SAR Test Exclusion Thresholds (mW) for < 100 MHz and < 200 mm

	<50	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190
Separation:	mm															
100 MHz	237	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567
50 MHz	308	617	625	634	643	651	660	669	677	686	695	703	712	721	729	738
10 MHz	474	948	961	975	988	1001	1015	1028	1041	1055	1068	1081	1095	1108	1121	1135
1 MHz	711	1422	1442	1462	1482	1502	1522	1542	1562	1582	1602	1622	1642	1662	1682	1702
0.1 MHz	948	1896	1923	1949	1976	2003	2029	2056	2083	2109	2136	2163	2189	2216	2243	2269
0.05 MHz	1019	2039	2067	2096	2125	2153	2182	2211	2239	2268	2297	2325	2354	2383	2411	2440
0.01 MHz	1185	2370	2403	2437	2470	2503	2537	2570	2603	2637	2670	2703	2737	2770	2803	2837

Notes: Values in the table are in mW

1.1.2 Justification for Standalone SAR test exclusion

Using linear interpolation method, the threshold at 58 kHz at separation distance 5 mm is 1008 mW. 5 mm separating distance was chosen to represent the worst-case scenario.

1.1.3 Verdict

The EUT has two main types of antennas ANAMB-2402 antenna and DEAC STP-SD antenna.

ANAMB-2402 antenna

The measured field strength at 3 meters is 110.8 dBµV/m or 15.6 dBm (36.3 mW), which is significantly below the threshold of 1008 mW.

DEAC STP-SD antenna

The measured field strength at 3 meters is 101.1 dBµV/m or 5.9 dBm (3.9 mW), which is significantly below the threshold of 1008 mW.

Based on this calculation, the product is exempt from the SAR test requirements.

1.2 Nerve Stimulation test, ISED

1.2.1 References, definitions, and limits

This evaluation of the instantaneous requirements for Radio Frequency (RF) field strengths (reference levels) based on the effects of internal electric fields was done in accordance with SPR-002, Issue 2. The limits for Uncontrolled Environment are found in RSS 102, Issue 6, Table 5 & 6 (Instantaneous).

Table 1.2-1: Electric field strength reference levels							
Frequency range (MHz)	Reference level basis	Reference level (E _{RL}) for uncontrolled	Reference period				
		environment (V _{RMS} /m)					
0.003 -10	NS	83	Instantaneous				
Notes: None							
	Table 1.2-2: M	lagnetic field strength reference levels					
Frequency range (MHz)	Reference level basis	Reference level (H _{RL}) for uncontrolled	Reference period				
		environment (A _{RMS} /m)					
0.003 -10	NS	90	Instantaneous				
Notes: None							
Start date August 16, 202	4						
122 Observations sattings	and spacial notas						

The testing was performed as per SPR-002, Issue 2.

- a) The measurement probe is set a fixed separation distance of 5 mm
- b) The X, Y, and Z axis are measured simultaneously, and summed by the measurement probe software
- c) The maximum emission level is measured using an appropriate resolution bandwidth.
- d) The EUT has two main types of antennas ANAMB-2402 antenna and DEAC STP-SD antenna. Both antennas were verified, worst case test data were observed while testing the EUT attached to ANAMB-2402 antenna, such worst-case test data were recorded in the tables in the test data section.
- e) The Nerve stimulation test was performed at multiple distances at all sides, 5 mm separating distance was chosen to represent the worst-case scenario.



1.2.3 Test data

quipment	Manufacturer	Model no.	Test Software	Asset no.	Cal cycle	Next cal.
lectric & Magnetic field	Narda	EHP200AC	EHP200-TS	FA003508	3 years	March 25, 2027
obe analyzer						
vpe of evaluation		Ner	ve Stimulation Exposure Ev	aluation (SPR-002	2)	
		Eva	uated against exposure lim	nits: 🖂 General Pu	ublic Use	Controlled Use
		Mea	surement distance:	5 mm		
		Field	d Strength:	4.7 🛛 V	/m (electric) 🛛 🛛 A	A/m (magnetic)
erve Stimulation Evaluation	(SPR-002)			× N	1easured 🛛 Comput	ted
	(51 11 002)	Field	d Strength:	0.5 🗆 V	/m (electric) 🛛 🛛 A	A/m (magnetic)
				× N	1easured 🛛 Comput	ted 🗆 Calculated
		Exp	osure condition:	🛛 Whole body	r/Torso/Head	Leg
				🛛 Arm		Hand/Foot
2040						
2 kHz/Div						V/m A/m
						- 1000 300
						-
						100 30
						_
			\sim			- 10 3
		\sim	12mm			
	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	$\checkmark$			~ ~	1 0.3
					~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	
					~	
						0.1 0.03
		F.C	050 1411		0.0	

Table 1.2-4: Instantaneous E-Field & H-Field measurements

Frequency, kHz	Antenna Position referencing EUT	Measurement distance mm	Measured Electric Field Strength V/m (r.m.s) instantaneous	RSS-102 Limit Electric Field Strength V/m (r.m.s) instantaneous	Margin, dB
57.8	All sides	5	47.9	83.0	35.1

Table 1.2-5: Maximum instantaneous H-Field							
Frequency, kHz	Antenna Position referencing EUT	Measurement distance mm	Measured Magnetic Field Strength A/m (r.m.s) instantaneous	RSS-102 Limit Magnetic Field Strength A/m (r.m.s) instantaneous	Margin, dB		
57.8	All sides	5	5.4	90.0	84.6		

Report reference ID: REP055009



1.2.4 Test setup photos



End of the test report