

RF EXPOSURE REPORT

Product: Integrated Smart Terminal

Model Name: E500

FCC ID: V5PE500

Applicant: PAX Technology Limited

Address: Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour Road,
Wanchai, Hong Kong

Manufacturer: PAX Computer Technology (Shenzhen) Co., Ltd.

Address: 4/F, No.3 Building, Software Park, Second Central
Science-Tech Road, High-Tech industrial Park, Shenzhen,
Guangdong, P.R.C.

Prepared by: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

Lab Location: No. 34, Chenwulu Section, Guantai Rd., Houjie Town,
Dongguan City, Guangdong 523942, China

TEL: +86 769 8593 5656

FAX: +86 769 8593 1080

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: SA170629W002

Received Date: Jun. 29, 2017

Test Date: Jun. 30, 2017 ~ Jul. 10, 2017

Issued Date: Jul. 11, 2017

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

TABLE OF CONTENTS

RF EXPOSURE REPORT	1
RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
3 RF EXPOSURE	6
3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	6
3.2 MPE CALCULATION FORMULA	6
3.3 CLASSIFICATION	6
3.4 CONDUCTED POWER	7
3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	9



Test Report No.: SA170629W002

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA170629W002	Original release	Jul. 11, 2017



Test Report No.: SA170629W002

1 CERTIFICATION

PRODUCT: Integrated Smart Terminal
BRAND NAME: PAX
MODEL NAME: E500
APPLICANT: PAX Technology Limited
TESTED: Jun. 30, 2017 ~ Jul. 10, 2017
TEST SAMPLE: Production Unit
STANDARDS: FCC Part 2 (Section 2.1091)
FCC OET Bulletin 65, Supplement C (01-01)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : _____, **DATE:** Jul. 11, 2017
(Harry Li/ Engineer)

APPROVED BY : _____, **DATE:** Jul. 11, 2017
(Sam Tung / Manager)

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Integrated Smart Terminal	
MODEL NAME	E500	
NOMINAL VOLTAGE	24Vdc (adapter or host equipment) 3.7Vdc (Li-ion, battery)	
OPERATING TEMPERATURE RANGE	0 ~ 50°C	
MODULATION TYPE	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
	Bluetooth	GFSK, $\pi/4$ -DQPSK, 8DPSK
	BT_LE	BT-LE(GFSK) for DTS
	RFID	ASK
OPERATING FREQUENCY	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20)
	Bluetooth/BT_LE	2402MHz ~ 2480MHz
	RFID	13.56MHz
ANTENNA GAIN	PIFA Antenna with 1.5dBi gain	
HW VERSION	E500-XXXXXX-XXXX-XXX-XX	
SW VERSION	e500_PayDroid_6.0.1_Taurus_V05.1.00_20170627	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT was powered by the following adapter:

ADAPTER	
BRAND:	HONOR
MODEL:	ADS-65HI-19A-3
INPUT:	AC 100-240V, 1500mA
OUTPUT:	DC 24V, 2700mA
MANUFACTURER:	SHENZHEN HONOR ELECTRONIC CO.,LTD

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3 RF EXPOSURE

3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

3.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile device**.



3.4 CONDUCTED POWER

WIFI 2.4G

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	13.03	N/A
6	2437	12.73	N/A
11	2462	13.15	N/A

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	12.50	N/A
6	2437	12.37	N/A
11	2462	12.76	N/A

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	11.11	N/A
6	2437	10.97	N/A
11	2462	11.14	N/A

Bluetooth

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	6.79	N/A
39	2441	6.95	N/A
78	2480	6.16	N/A

DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	4.45	N/A
39	2441	4.49	N/A
78	2480	3.06	N/A

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	4.48	N/A
39	2441	4.56	N/A
78	2480	3.09	N/A

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	4.92	N/A
19	2440	5.20	N/A
39	2480	4.32	N/A

3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

BT & WIFI 2.4G

Band	Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Tune-up Power (dBm)	E.I.R.P Power (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
Bluetooth	2480	BT_GFSK	1.5	7.0	7.079	0.001	1.00	PASS
WIFI 2.4G	2462	11b	1.5	13.5	31.623	0.006	1.00	PASS