

SONY

Sony Imaging Products & Solutions Inc

4-14-1, Asahi-cho, Atsugi-shi, Kanagawa-ken, 243-0014 Japan

Declaration Letter of FCC 17-95

September 6, 2018

Federal Communication Commission
Equipment Authorization Division
Application Processing Branch
7435 Oakland Mills Road
Columbia, Maryland 21046

FCC ID : AK8DWM02N
Applicant : Sony Corporation

To Whom It May Concern:

We inform on the website that users of current devices already sold must be required to cease operating no later than July 13, 2020. Please refer to next page for details of website notice.

In addition, we will limit the transmit frequency of the devices upon request from users.

We, manufacturer declared together, to review and understand the requirements of FCC 17-95. After transition period, it is the manufacturer's responsibility to have nonconforming items in the market.

Thank you for your attention to this matter.

Sincerely,



Ryui Tatsumi
Senior Manager
Product Safety Section
Product Compliance Department
Sony Imaging Products and Solutions Inc.

DWM-02N

DWX N series digital wireless microphone
with interchangeable head mechanism



Overview

High quality flexible microphone system works with DWX N series transmitters and receivers

The DWM-02N digital wireless microphone forms part of the DWX N series system that offers high-quality full-digital operation, shorter audio latency and a more reliable RF transmission mode — ideal for a variety of high-quality applications, including broadcast studio, theater and live sound.

Maximizing flexibility for users, the DWM-02N is not supplied with a microphone capsule as the DWM-02N interchangeable head mechanism supports Sony and other third-party capsules. Sony offers three microphone heads—the CU-C31, CU-F31 and CU-F32—and there is also a wide variety of third-party capsules to choose from — ensuring whatever your requirements, the DWM-02N wireless handheld microphone is an ideal choice.

The DWX N series system, which consists of the DWT-B01N body-pack transmitter, DWM-02N microphone and DWR-R02DN receiver, delivers superb-quality wireless transmission of 24-bit digital audio. Thanks to its improved codec and new hardware, it can provide higher sound quality with lower audio latency.

The DWX N series works with Sony control software Wireless Studio 4.2 or later for PC and Wireless Studio Mobile for smartphones* to give users flexible control of the system. Remote control of up to 82 transmitters can be achieved using the Cross Remote™ function combined with the RMU-01 remote control unit.

NOTE: This model is available in multiple versions to support the widest possible range of operating frequencies. Please refer to product specifications for more information.

* Wireless Studio Mobile supported OS: iOS Ver.8.0 or later and Android Ver.4.1 or later.

Operation is not guaranteed on all smartphones.

DWX N series provides more reliable RF transmission, low audio latency and higher sampling rate

DWM-02N forms part of DWX N series digital wireless microphone system, working with the DWT-B01N body-pack transmitter and DWT-R02N receiver.

Compatibility with DWX series

The DWM-02N has full compatibility with its predecessor DWX series equipment.

Smartphone control*

Wireless Studio Mobile software gives users remote control of the DWX N series

system via a smartphone.

Wide frequency coverage with choice of channels available

The extra wide switching bandwidth covers a wide area, with a wide choice of channels available across multiple models - please refer to product specifications for more information.

UC14: 470.125 MHz to 541.875 MHz (UHF-TV channels 14 to 25)

UC30: 566.125 MHz to 607.875 MHz and 614.125 MHz to 637.875 MHz (UHF-TV channels 30 - 36 and 38 - 41) (not available in Brazil)

UC42: 638.125 MHz to 697.875 MHz (UHF-TV channels 42 - 51)

For customers in North America

The DWM-02N/30 and DWM-02N/42 models operate in portions of the 617-652 MHz or 663-698 MHz frequencies. As of 2017, these frequencies are being transitioned by the Federal Communications Commission (FCC) to the 600 MHz service to meet increasing demand for wireless broadband services. Users of these models must cease operating on these frequencies no later than July 13, 2020. In addition, users may be required to cease operations before that date if their operations could cause harmful interference to a 600 MHz service licensee's wireless operations on these frequencies. For more information, contact the FCC.

For customers in Canada, please consult ISED's Spectrum Advisory Bulletin for recent information related to the 600 MHz band transition.

Features

Three codec modes designed for wide variety of applications

MODE1 for compatibility with DWX series applications, MODE2 with higher quality sound and low latency ideal for theater, tour and broadcast applications, and MODE3 with more reliable RF transmission ideal for speech applications.

Superb quality wireless transmission and reception

The digital wireless microphone system transmits and receives high-quality 24-bit digital audio in a specific frequency bandwidth that meets the Wireless Communication Regulations of each country. Utilizing the Sony original codec based on Sony's years of experience in engineering audio products, the system delivers a wide dynamic range of more than 106 dB, a wide frequency response of 20 Hz to 22 kHz, and an excellent transient response.

Stable and secure transmission and reception

Incorporating the improved digital modulator, the digital wireless microphone system allows highly stable wireless transmission that is extremely tolerant to unwanted interference. In addition, the system transmits and receives digitally modulated and encrypted data to minimize the risk of interception, providing highly secure transmission and reception.

Simultaneous multi-channel operation

The digital wireless microphone system allows for large-scale multi-channel operations. Thanks to the digital modulator, the system realizes an intermodulation-free, equally spaced channel allocation. The digital wireless transmission technology used in this system enables a significant increase in the number of simultaneous operations in comparison with current analog wireless systems. For example, up to 16 channels of simultaneous operation is possible in an 8-MHz operating band.

Three interchangeable heads and third party support

The DWM-02N operates with three heads. The CU-F31 microphone head with dynamic capsule has a super cardioid pick-up and range from 60 Hz to 18 kHz. The CU-F32

microphone head with wide dynamic capsule has a wide cardioid pick-up and range from 70 Hz – 18 kHz. The CU-C31 microphone head with condenser capsule has a cardioid pick-up and range from 60 Hz to 20 kHz. The DWM-02N also supports a wide variety of third party heads.

Quick open/closed mechanism for microphone heads

A robust 31.3mm/pitch 1.0mm threading interchangeable mechanism allows microphone heads to be changed easily and quickly.

Selectable output power

Output power selectable between 1/10/50 mW. Chose the minimum power necessary for a venue, lengthening battery life, and reducing the already low possibility of interference. Allows the microphone to work effectively in a very wide range of venues.

Remote control of transmitter functions from the receiver

Input attenuation, RF frequency selection, RF power output, Audio Low-pass cutoff frequency and transmitter Sleep Mode can all be controlled remotely from the digital wireless receiver. Remote control of up to 82 transmitters can be achieved using the Cross Remote™ function and RMU-01 remote control unit.

Smartphone control using Wireless Studio Mobile software

The DWX N series works with Sony control software Wireless Studio 4.2 or later for PC and Wireless Studio Mobile for smartphones* to give users flexible control of the system.

* Wireless Studio Mobile supported OS: iOS Ver.8.0 or later and Android Ver.4.1 or later. Operation is not guaranteed on all smartphones.

Specifications

Important Note

*

This product is available in a variety of different frequency range models to suit the regulatory requirements of individual countries. Please contact your Sony reseller for more information on which product will best suit your specific needs.

Specifications

Wireless Interface	WiDIF-HP
Oscillator Type	Crystal-controlled PLL Synthesizer
Antenna Type	$\lambda/4$ flexible wire
Type of Emission	G1E or G1D
Carrier Frequencies - UC	14UC: 470.125 MHz to 541.875 MHz (UHF-TV channels 14 to 25), 25 kHz steps 30A UC: 566.125 MHz to 607.875 MHz (UHF-TV channels 30 to 36), 25 kHz steps 42LA: 638.125 MHz to 697.875 MHz (UHF-TV channels 42 to 51), 25 kHz steps (not available in the US or Canada)

Carrier Frequencies - CE7	CE21: 470.025 MHz to 542.000 MHz (TV-21 to TV-29 channels) 25 kHz steps CE33: 566.025 MHz to 630.000 MHz (TV-33 to TV-40 channels), 25 kHz steps CE42: 638.025 MHz to 710.000 MHz (TV-42 to TV-50 channels), 25 kHz steps
Carrier Frequencies - J	WL: 470.150 MHz to 542.000 MHz (TV-13 to TV-24 channels), 25 kHz steps WM: 566.025 MHz to 638.000 MHz (TV-29 to TV-40 channels), 25 kHz steps WH: 638.025 MHz to 713.850 MHz (TV-41 to TV-52 and 53 channels), 25 kHz steps G: 1240.150 MHz to 1251.825 MHz, 1253.175 MHz to 1259.850 MHz, 25 kHz steps
RF Power	1 mW/10 mW/50 mW (e.r.p) selectable
Maximum Input Level	-16 dBu (with 0 dB attenuator)
Audio Attenuator Adjustment Range	0 dB to 21 dB (in 3-dB steps)
Frequency Response	Transmission: 20Hz to 22kHz (typical)
Audio Delay	MODE1: 1.5 msec (total: 3.4msec) /MODE2: 1.0 msec (total: 1.5msec)/MODE3: 2.1 msec (total 4.0msec)
Wireless Remote Control	Cross Remote (2.4- GHz IEEE802.15.4 compliant)
Display	OLED
Power Requirements	DC 3.0 V (with two AA-size alkaline (LR6) batteries)
Battery Operating Time	Approx. 5 hours with Sony's AA-size alkaline (LR6) batteries at 25°C(77°F) at 10-mW output (with the wireless remote control function off and DIMMER MODE set to AUTO OFF)
Operating Temperature	0°C to 50°C / 32°F to 122°F
Storage/Transport Temperature	-20°C to +60°C / -4°F to +140°F
Dimensions	Φ37.1 x 194 mm
Mass	Approx. 235 g (including batteries)
Supplied Accessories	Identification ring (1 set) Microphone holder (1) USB adapter cable (1) Carrying case (1) Stand adaptor (1) For the model available in the U.S.A.: PF1/2 to W5/8 type For the model available in Europe.: PF1/2 to W3/8 type

Related products



DWR-S02D

Digital wireless receiver



DWR-R02DN

DWX N series digital wireless receiver

Gallery

