

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

EXHIBIT 5-3

FCC ID # CFS8DL5821

Date : _03/25/2004_____ Tested by : _G.Barbato___ Approved by : __K.Addy_____

Test Sample (model) : _____5821_____

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	LPA # 365				729
345	H	78.69	1.4	16.95	71121.4	10%	7112.1	7292
690	H	23.89	2.2	21.18	230.9	10%	23.1	729
1035	H	15.00	2.8	25.51	146.4	10%	14.6	500
1380	V	29.76	3.7	29.91	1474.0	10%	147.4	500
1725	V	37.53	4.2	31.3	4482.3	10%	448.2	729
2070	H	33.00	4.7	27.91	1907.7	10%	190.8	729
2415	H	25.87	5.5	28.59	995.4	10%	99.5	729
2760	H	25.67	6.1	29.45	1150.8	10%	115.1	729
3105	H	25.87	7.4	30.13	1479.1	10%	147.9	729
3450	H	25.87	9.1	30.28	1830.2	10%	183.0	729
4000			CABLE "A"	HORN #3127				