Modular Approval Request FCC (KDB 996369 D01 & Part 15.212)

FCC ID: TLZ-CB250NF

Items to be covered by Single modular transmitters.			
		Answer from applicant	
1.	The modular transmitter must have its own RF shielding.	Please refer to external	
		photos. The modular	
		transmitter has its own RF	
		shielding.	
2.	The modular transmitter must have buffered modulation/data inputs	Buffered data inputs	
	(if such inputs are provided) to ensure that the module will comply	stage has been	
	with Part 15 requirements under conditions of excessive data rates or	integrated in chip	
	over-modulation.	88W8997P.	
3.	The modular transmitter must have its own power supply regulation.	The part number of the	
		power regulator is	
		88PG823.	
4.	The modular transmitter must comply with the antenna requirements	The requirements of	
	of Section 15.203 and 15.204(b)(c). The antenna must either be	antenna connector and	
	permanently attached or employ a "unique" antenna coupler (at all	spurious emission have	
	connections between the module and the antenna, including the	been fulfilled. Please	
	cable).	reference the exhibition	
		Test Report.	
5.	The modular transmitter must be tested in a stand-alone	Please reference	
	configuration, i.e., the module must not be inside another device	exhibition Test	
	during testing. This is intended to demonstrate that the module is	Configuration	
	capable of complying with Part 15 emission limits regardless of the	Photo for the stand-alone	
	device into which it is eventually installed.	test configuration.	
6.	The modular transmitter must be equipped with either a permanently affixed	The instruction on the	
	label or must be capable of electronically displaying its FCC identification	labeling rule of the end	
	number in accordance with 15.212 (a)(1)(vi)(A) / (B).	product has been stated	
		in the users manual of this	
		module. Please also see	
		the exhibition Label	
		Sample.	
7.	The modular transmitter must comply with any specific rule or operating	The required FCC rule has	
	requirements applicable to the transmitter and the manufacturer must provide	been fulfilled and all the	
	adequate instructions along with the module to explain any such requirements.	instructions for	
	A copy of these instructions must be included in the application for equipment	maintaining compliance	
	authorization. For example, there are very strict operational and timing	has been clearly stated in	
	requirements that must be met before a transmitter is authorized for operation	the Users	

under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.

Manual.

8. The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 1.1310, 2.1091, 2.1093, and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance. Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.

Please refer exhibition RF Exposure for the compliance of MPE RF exposure rule.

Name and surname of applicant (or <u>authorized</u> representative): Leo Huang			
Date: _2019/11/22	Signature:		
Leo Huang			

Note: A limited modular approval (LMA) may be granted for *single* or *split* modular transmitters that

comply partially with the requirements above.