4
117.
CENTURION

<u>Confidential</u> PRODUCT SPECIFICATIONS

Pa	ge	
1	of	(21)

WIRELESS TECHNOLOGIES, INC.	:		
Specification No.	Description		
	PN-320 - Antenna	Product Sp	ecification
Customer	Date	Rev	Reference
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1	

Antenna Specifications

F							
E							
D							
С							
B							
A	06/04/05	Initial Release	BH				
Rev.	Date	Changes	Initiator	RF approval	ME approval	Approval	Approval

CENTURION	<u>Confidential</u> PRODUCT SPECIFICATIONS		DNS	Page 2 of (21)
Specification No.	Description			
	PN-320 - Antenna	Product Sp	ecification	
Customer	Date	Rev	Reference	
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1		

Contents

1	Gene	eral	3
	1.1	Product Description	3
	1.2	Product Number	3
	1.3	Print Acceptance	3
	1.4	Units, Definitions, and Abbreviations	3
	1.5	Interface	3
	1.6	Conditions	4
	1.7	Coordinate System	4
2	Elect	trical Properties	5
	2.1	Samples Size	5
	2.2	Frequency Bands	5
	2.3	Impedance	5
	2.4	The Radio (Phone / Handset)	5
	2.5	VSWR	6
	2.6	Gain	9
	2.7	Power Rating	19
3	Spec	ifications Drawing	20

(G.
CENTURION

Confidential PRODUCT SPECIFICATIONS

Page 3 of (21)

 WIRELESS TECHNOLOGIES INC.
 Description

 Specification No.
 PN-320 - Antenna Product Specification

 Customer
 Date
 Rev
 Reference

 CURITEL Co.,Ltd., Korea Communications,
 APR ,5, 2006
 1,1
 Image: Customer

1 GENERAL

1.1 PRODUCT DESCRIPTION

A stuby antenna system.

1.2 PRODUCT NUMBER

Centurion Product Number Customer Product Number

PN-320 Antenna

1.3 PRINT ACCEPTANCE

Samples and a Page one drawing was sent to customer. When they are approved, the approval form should be completed, signed, and sent back to Centurion before further mass production batches can be delivered.

1.4 UNITS, DEFINITIONS, AND ABBREVIATIONS

Unless otherwise stated, SI units are used.

Tx	Transmit Band
Rx	Receive Band
PCB	Printed Circuit Board
VSWR	Voltage Standing Wave Ratio
dBi	Antenna gain in dB (Isotropic)
CW	Continuous Wave
g	Acceleration of gravity (approx. 9.8 m/s^2)
RH	Relative Humidity

1.4.1 "Without mechanical damage"

Implies full mechanical functionality according to specification and compliance with visual requirements according to specification drawing.

1.4.2 "Without permanent mechanical damage"

As above but allows reversible misalignment or deformation and minor visual damage (no through-cuts or holes).

1.4.3 "Unimpaired functionality"

Implies full mechanical functionality according to specification but allows visual damage (no through-cuts or holes).

1.5 INTERFACE

All properties are guaranteed under the condition that antenna/handset interface is designed in accordance with instructions provided by Centurion. The hole interface should be included in the specification.

	<u>Confidential</u> PRODUCT SPECIFICATIONS		ONS	Page 4 of (21)
Specification No.	Description			
	PN-320 - Antenna Product Specification		pecification	
Customer	Date	Rev	Reference	
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1		

Functionality with other equipment (such as couplers etc.) is not guaranteed unless this has been agreed upon separately.

1.6 CONDITIONS

Unless otherwise stated all temperature tolerances are $\pm 3^{\circ}$ C and all RH tolerances are ± 5 percentage units.

Unless otherwise stated all values are valid at +20°C and 50% RH.

Unless otherwise stated all values are valid for the radio defined in 2.4

1.7 COORDINATE SYSTEM

The coordinate system for the phone is defined as follows:

- Origin in center of gravity.
- Positive X axis is perpendicular to, and directed from, front plane.
- Positive Y axis is perpendicular to, and directed from, right side plane (as seen from front).
- Positive Z axis is perpendicular to, and directed from, top plane.



Figure 1-1: a) E2-plane b) E1-plane c) H-plane

(4	<u>Confidential</u>			Page	
CENTURION	PRODUCT SPECIFICATIONS		ONS	5 of (21)	
WIRELESS TECHNOLOGIES, INC.	-				
Specification No.	Description				
	PN-320 - Antenn	a Product Sp	pecification		
Customer	Date	Rev	Reference		
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1			

2 ELECTRICAL PROPERTIES

2.1 SAMPLES SIZE

All the tests will be conducted as below:

- The VSWR will be measured for 30 samples and a Cpk analysis will be conducted,
- The radiation patterns will be measured on one sample,
- The Power rating test will be conducted on 5 samples.

2.2 FREQUENCY BANDS

CDMA/:	Tx:	824 – 849 MHz
AMPS	Rx:	869 – 894 MHz
GPS:	Rx:	1575 MHz
PCS :	Tx:	1850 – 1910 MHz
	Rx:	1930 – 1990 MHz

2.3 IMPEDANCE

2.3.1 Nominal Value

50 Ohms

2.3.2 Method

Centurion will supply engineering assistance to ensure that the impedance over the frequency bands is as close to 50 ohms as possible after matching, both in flip open and flip close status and in extended and retracted modes.

2.4 THE RADIO (PHONE / HANDSET)

2.4.1 Radio Revision

Customer chassis I.D. number

CURITEL PN-320

	<u>Confidential</u>			Page
CENTURION	PRODUCT SPECIFICATIONS		ONS	6 of (21)
WIRELESS TECHNOLOGIES, INC.	Description			
Specification No.	Description			
	PN-320 - Antenna	a Product Sp	ecification	
Customer	Date	Rev	Reference	
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1		

2.5 **VSWR**

Typical value of VSWR tested with engineering samples.

2.5.1 VSWR Value (Free Space) - Specifications

See below table

Mode	Band	Freq. f in MHz	CLOSE	OPEN
CDMA	Tx	824< f <849	5.3	2.7
CDMA	Rx	869< f <894	3.2	2.3
GPS	Rx	f = 1575	3.3	3.0
DCS	Tx	1850< f <1910	2.7	3.0
PCS	Rx	1930< f <1990	2.7	2.5

2.5.2 Method of Measurement

A 50 ohms coaxial cable is connected (soldered) to the 50 ohms feeding point on the PCB. The connection of the coaxial cable is done so as to introduce a minimum of mismatch. In the other end, the coaxial cable is connected to a network analyzer. The analyzer is calibrated so that the reference plane is at the 50 ohms feeding point. The radio, including the PCB must not in any significant way differ from the mass produced radio, e.g. the antenna feeding parts have to be equivalent to the parts in mass production. Free space means that the radio is attached to a nonconductive surface.

2.5.3 Electrical Performance Assurance

In order to guarantee the specified electrical performance in mass production the following procedure is used (example given for a single band antenna). During the development phase, two antennas are selected; one defining the lowest allowable resonance frequency (when measured on the handset), marked "low freq.", and one defining the highest allowable resonance frequency, marked "high freq.", see Figure 2-1.

These antennas are reference antennas. These antennas are then measured on a ground plane used in mass production and define the highest and lowest allowable resonance frequencies on this ground plane and each produced antenna is automatically tested on this ground plane.

Only the retracted mode is considered when finding the reference antennas, since the production variation of the extended mode is negligible.

(4	<u>Confidential</u>		Page	
CENTURION	PRODUCT SPECIFICATIONS			7 of (21)
WIRELESS TECHNOLOGIES, INC.				
Specification No.	Description			
	PN-320 - Antenna	a Product Sp	ecification	
Customer	Date	Rev	Reference	
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1		





allowable resonance frequencies for a single band antenna

2.5.4 VSWR Plots (Free Space)



Figure 2-2: VSWR Plot - Open

((),	<u>Confidential</u>		Page
CENTURION	PRODUCT SPE	CIFICATIO	DNS 8 of (21)
Specification No.	Description		
	PN-320 - Antenna	a Product Sp	ecification
Customer	Date	Rev	Reference
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1	



Figure 2-3: VSWR Plot - Close

	<u>Confidential</u> PRODUCT SPECIFICATIONS			Page 9 of (21)
Specification No.	Description			
	PN-320 - Anteni	na Product S	Specification	
Customer	Date	Rev	Reference	
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1		

2.6 GAIN

Below are typical maximum peak gain values for flip close and open and for extracted and retracted positions.

2.6.1 Typical Peak Values (in dBi) – E2 plan

		OPEN	CLOSE
CDMA	Тх	-0.5	-4.0
	Rx	0.0	-1.5
GPS	1575 MHz	0.5	-3.0
PCS	Тx	-2.0	-3.0
	Rx	-1.5	-3.5

2.6.2 Typical Peak Values (in dBi) – E1 plan

		OPEN	CLOSE
CDMA	Тx	-0.5	-2.0
	Rx	-1.5	-3.0
GPS	1575 MHz	0.0	-0.5
PCS	Тx	-0.5	-0.5
	Rx	-1.0	-1.5

2.6.3 Typical Average Values (in dBi) – H plan

		EXT / OP	RET / CL
CDMA	Тx	0.5	-4.0
	Rx	-1.5	-3.0
GPS	1575 MHz	-5.0	-5.5
PCS	Тx	-9.0	-6.5
	Rx	-11.0	-6.0

2.6.4 Method of Measurement and Radiation Patterns

The connection is done according to 2.5.2, Radiation patterns are measured at the Tx and Rx band edges for each band defined in 2.2. The measurements are performed so as to minimize the influence of the cables. The total electric field is measured, i.e. the vector sum of two orthogonal polarization. 3 orthogonal planes in free space, according to Figure 1-1. The gain is also measured in a horizontal plan. Calibration for absolute measurements is done with a reference antenna, which is in turn calibrated by a certified calibration company.

	<u>Confidential</u>	Page		
CENTURION	PRODUCT SPECIFICATIONS			10 of (21)
WIRELESS TECHNOLOGIES, INC.				
Specification No.	Description			
	PN-320 - Antenr	na Product Sp	pecification	
Customer	Date	Rev	Reference	
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1		

2.6.5 Radiation Patterns



Figure 2-4: OPEN CDMA - E2



Figure 2-5: OPEN GPS – E2

(<i>t</i> .	<u>Confidential</u>		Page	
CENTURION	PRODUCT SPE	CIFICATIO	DNS	11 of (21)
Specification No.	Description			
	PN-320 - Antenna	Product Sp	ecification	
Customer	Date	Rev	Reference	
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1		



Figure 2-6: OPEN PCS-E2



Figure 2-7: OPEN CDMA-E1

CENTURION	Confidential PRODUCT SPECIFICATIONS			Page 12 of (21)
Specification No.				
	PN-520 - Anten	na Product S	specification	
Customer	Date	Rev	Reference	
CURITEL Co Ltd Korea Communications	APR 5 2006	11		



Figure 2-8: OPEN GPS-E1



Figure 2-9: OPEN PCS-E1

CENTURION	<u>Confidential</u> PRODUCT SPE	ONS Page 13 of (21)	
WIRELESS TECHNOLOGIES, INC. Specification No.	Description PN-320 - Antenna Product Specification		
Customer	Date	Rev	Reference
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1	



Figure 2-10: OPEN CDMA-H



Figure 2-14: OPEN GPS-H

CENTURION	Confidential PRODUCT SPE	ONS	Page 14 of (21)	
WIRELESS TECHNOLOGIES INC. Specification No.	Description PN-320 - Antenna Product Specification		ecification	
Customer	Date	Rev	Reference	
CURITEL Co.,Ltd., Korea Communications,	APR ,5, 2006	1,1		



Figure 2-15: OPEN PCS-H



Figure 2-16: CLOSE CDMA - E2

	<u>Confidential</u> PRODUCT SPECIFICATIONS			Page 15 of (21)	
WIRELESS TECHNOLOGIES, INC.	Description				
	PN-320 - Antenna Product Specification				
Customer	Date	Rev	Reference		
CURITEL Co Ltd Korea Communications	APR 5 2006	11			



Figure 2-17: CLOSE GPS – E2



Figure 2-18: CLOSE PCS-E2

CENTURION	<u>Confidential</u> PRODUCT SPF	Page DNS 16 of (21)	
WIRELESS TECHNOLOGIES, INC. Specification No.	Description		
	PN-320 - Antenna Product Specification		
Customer	Date	Rev	Reference
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1	



Figure 2-19: CLOSE CDMA-E1



Figure 2-20: CLOSE GPS-E1

((),	<u>Confidential</u>		Page	
CENTURION	PRODUCT SPE	CIFICATIO	ONS	17 of (21)
Specification No.	Description			
	PN-320 - Antenna Product Specification			
Customer	Date	Rev	Reference	
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1		



Figure 2-21: CLOSE PCS-E1



Figure 2-22: CLOSE CDMA-H

CENTURION	<u>Confidential</u> PRODUCT SPECIFICATIONS			Page 18 of (21)	
Specification No.	Description PN-320 - Anten	na Product S	Specification		
Customer	Date	Rev	Reference		
CURITEL Co Ltd Korea Communications	APR 5 2006	11			



Figure 2-23: CLOSE GPS-H



Figure 2-24: CLOSE PCS-H

CENTURION	Confidential PRODUCT SPECIFICATIONS			Page 19 of (21)	
wireLESS TECHNOLOGIES INC. Specification No.	Description				
	PN-320 - Antenna Product Specification				
Customer	Date	Rev	Reference		
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1			

2.7 POWER RATING

2.7.1 Maximum Value

P=2W (CW)

2.7.2 Post Test Requirements

Nor mechanical damage (ref. 1.4.1) neither electrical performance reduction (ref. 2.5.1) should be observed after the test.

2.7.3 Method of Measurement

The connection is done according to 2.5.2. The specified power, P, is applied for 10 minutes at the middle frequency of each Tx band defined in 2.2. Immediately after the test the VSWR is measured.

	<u>Confidential</u> PRODUCT SPE	DNS	Page 20 of (21)	
Specification No.	Description			
	PN-320 - Antenna Product Specification			
Customer	Date	Rev	Reference	
CURITEL Co., Ltd., Korea Communications,	APR ,5, 2006	1,1		

SPECIFICATIONS DRAWING

