



TEST Report

Applicant: Shenzhen Hanyin Technology Development Co., Ltd.

Address of Applicant: 1909, Block A, Rongchuang Zhihui Building, Shangfen Community, Minzhi Street, Longhua District Shenzhen China

Manufacturer : Shenzhen Hanyin Technology Development Co., Ltd.

Address of Manufacturer : 1909, Block A, Rongchuang Zhihui Building, Shangfen Community, Minzhi Street, Longhua District Shenzhen China

Equipment Under Test (EUT)

Product Name: True Wireless Earphones

Model No.: Voglobuds 5Pro

Series model: N/A

Trade Mark: HYUNDAI

FCC ID: 2BEWA-VOGBUDS5PRO

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: Apr. 10, 2025

Date of Test: Apr. 10, 2025 ~ Apr. 16, 2025

Date of report issued: Apr. 16, 2025

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.



Report No.: HTT202504427F01

1. Version

| Version No. | Date | Description |
|-------------|---------------|-------------|
| 00 | Apr. 16, 2025 | Original |
| | | |
| | | |
| | | |
| | | |

Tested/ Prepared By

Heber He

Date:

Apr. 16, 2025

Project Engineer

Check By:

Bruce Zhu

Date:

Apr. 16, 2025

Reviewer

Approved By :

Kevin Yang

Date:

Apr. 16, 2025

Authorized Signature





2. Contents

Page

| | |
|---|-----------|
| 1. VERSION..... | 2 |
| 2. CONTENTS | 3 |
| 3. TEST SUMMARY | 4 |
| 4. GENERAL INFORMATION..... | 5 |
| 4.1. GENERAL DESCRIPTION OF EUT | 5 |
| 4.2. TEST MODE | 7 |
| 4.3. DESCRIPTION OF SUPPORT UNITS | 7 |
| 4.4. DEVIATION FROM STANDARDS | 7 |
| 4.5. ABNORMALITIES FROM STANDARD CONDITIONS..... | 7 |
| 4.6. TEST FACILITY | 7 |
| 4.7. TEST LOCATION..... | 7 |
| 4.8. ADDITIONAL INSTRUCTIONS | 7 |
| 5. TEST INSTRUMENTS LIST..... | 8 |
| 6. TEST RESULTS AND MEASUREMENT DATA | 9 |
| 6.1. CONDUCTED EMISSIONS | 9 |
| 6.2. CONDUCTED PEAK OUTPUT POWER | 12 |
| 6.3. 20DB EMISSION BANDWIDTH | 13 |
| 6.4. FREQUENCIES SEPARATION | 17 |
| 6.5. HOPPING CHANNEL NUMBER..... | 19 |
| 6.6. DWELL TIME | 21 |
| 6.7. BAND EDGE | 26 |
| 6.7.1. Conducted Emission Method..... | 26 |
| 6.7.2. Radiated Emission Method..... | 30 |
| 6.8. SPURIOUS EMISSION..... | 32 |
| 6.8.1. Conducted Emission Method..... | 32 |
| 6.8.2. Radiated Emission Method..... | 37 |
| 6.9. ANTENNA REQUIREMENT..... | 44 |
| 7. TEST SETUP PHOTO | 45 |
| 8. EUT CONSTRUCTIONAL DETAILS | 45 |



3. Test Summary

| Test Item | Section in CFR 47 | Result |
|----------------------------------|--------------------|--------|
| Antenna Requirement | 15.203/15.247 (c) | Pass |
| AC Power Line Conducted Emission | 15.207 | Pass |
| Conducted Peak Output Power | 15.247 (b)(1) | Pass |
| 20dB Occupied Bandwidth | 15.247 (a)(1) | Pass |
| Carrier Frequencies Separation | 15.247 (a)(1) | Pass |
| Hopping Channel Number | 15.247 (a)(1)(iii) | Pass |
| Dwell Time | 15.247 (a)(1)(iii) | Pass |
| Radiated Emission | 15.205/15.209 | Pass |
| Band Edge | 15.247(d) | Pass |

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013

Measurement Uncertainty

| Test Item | Frequency Range | Measurement Uncertainty | Notes |
|-----------------------|-----------------|-------------------------|-------|
| Radiated Emission | 9KHz~30MHz | 3.12 dB | (1) |
| Radiated Emission | 30~1000MHz | 4.37 dB | (1) |
| Radiated Emission | 1~18GHz | 5.40 dB | (1) |
| Radiated Emission | 18-40GHz | 5.45 dB | (1) |
| Conducted Disturbance | 0.15~30MHz | 2.68 dB | (1) |

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.



4. General Information

4.1. General Description of EUT

| | |
|---|--|
| Product Name: | True Wireless Earphones |
| Model No.: | Vogbuds 5Pro |
| Series model: | N/A |
| Test sample(s) ID: | HTT202504427-1(Engineer sample) HTT202504427-2(Normal sample) |
| Operation Frequency: | 2402MHz~2480MHz |
| Channel numbers: | 79 |
| Channel separation: | 1MHz |
| Modulation type: | GFSK, $\pi/4$ -DQPSK, 8-DPSK |
| Antenna Type: | Chip Antenna |
| Antenna gain: | 2.70 dBi |
| Power Supply: | Headphone battery capacity:3.7V/50mAh (polymer battery) Charging bin battery capacity:3.7V/230mAh (polymer battery) Charging interface :USB Type-C |
| Adapter Information (Auxiliary test provided by the lab): | Mode: GS-0500200 Input: AC100-240V, 50/60Hz, 0.3A max Output: DC 5V, 2A |
| Note: Left and Right earphones were tested, only recorded the worst case data in the test report. The left and right earphone components are the same, but the components location are difference. | |



| Operation Frequency each of channel | | | | | | | |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1 | 2402MHz | 21 | 2422MHz | 41 | 2442MHz | 61 | 2462MHz |
| 2 | 2403MHz | 22 | 2423MHz | 42 | 2443MHz | 62 | 2463MHz |
| 3 | 2404MHz | 23 | 2424MHz | 43 | 2444MHz | 63 | 2464MHz |
| 4 | 2405MHz | 24 | 2425MHz | 44 | 2445MHz | 64 | 2465MHz |
| 5 | 2406MHz | 25 | 2426MHz | 45 | 2446MHz | 65 | 2466MHz |
| 6 | 2407MHz | 26 | 2427MHz | 46 | 2447MHz | 66 | 2467MHz |
| 7 | 2408MHz | 27 | 2428MHz | 47 | 2448MHz | 67 | 2468MHz |
| 8 | 2409MHz | 28 | 2429MHz | 48 | 2449MHz | 68 | 2469MHz |
| 9 | 2410MHz | 29 | 2430MHz | 49 | 2450MHz | 69 | 2470MHz |
| 10 | 2411MHz | 30 | 2431MHz | 50 | 2451MHz | 70 | 2471MHz |
| 11 | 2412MHz | 31 | 2432MHz | 51 | 2452MHz | 71 | 2472MHz |
| 12 | 2413MHz | 32 | 2433MHz | 52 | 2453MHz | 72 | 2473MHz |
| 13 | 2414MHz | 33 | 2434MHz | 53 | 2454MHz | 73 | 2474MHz |
| 14 | 2415MHz | 34 | 2435MHz | 54 | 2455MHz | 74 | 2475MHz |
| 15 | 2416MHz | 35 | 2436MHz | 55 | 2456MHz | 75 | 2476MHz |
| 16 | 2417MHz | 36 | 2437MHz | 56 | 2457MHz | 76 | 2477MHz |
| 17 | 2418MHz | 37 | 2438MHz | 57 | 2458MHz | 77 | 2478MHz |
| 18 | 2419MHz | 38 | 2439MHz | 58 | 2459MHz | 78 | 2479MHz |
| 19 | 2420MHz | 39 | 2440MHz | 59 | 2460MHz | 79 | 2480MHz |
| 20 | 2421MHz | 40 | 2441MHz | 60 | 2461MHz | | |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel | Frequency |
|---------------------|-----------|
| The lowest channel | 2402MHz |
| The middle channel | 2441MHz |
| The Highest channel | 2480MHz |



4.2. Test mode

| | |
|--|---|
| Transmitting mode | Keep the EUT in continuously transmitting mode. |
| <i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i> | |

4.3. Description of Support Units

| |
|-------|
| None. |
|-------|

4.4. Deviation from Standards

| |
|-------|
| None. |
|-------|

4.5. Abnormalities from Standard Conditions

| |
|-------|
| None. |
|-------|

4.6. Test Facility

| |
|--|
| The test facility is recognized, certified, or accredited by the following organizations: FCC-Registration No.: 779513 Designation Number: CN1319 Shenzhen HTT Technology Co.,Ltd. has been accredited on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. A2LA-Lab Cert. No.: 6435.01 Shenzhen HTT Technology Co.,Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement. The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010. |
|--|

4.7. Test Location

| |
|--|
| All tests were performed at: |
| Shenzhen HTT Technology Co.,Ltd. 1F, Building B, Huafeng International Robotics Industrial Park, Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China Tel: 0755-23595200 Fax: 0755-23595201 |

4.8. Additional Instructions

| | |
|-------------------|---|
| Test Software | Special AT test command provided by manufacturer to Keep the EUT in continuously transmitting mode and hopping mode |
| Power level setup | Default |




5. Test Instruments list

| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
|------|----------------------------------|-------------------------------------|--------------------|---------------|---------------------|-------------------------|
| 1 | 3m Semi- Anechoic Chamber | Shenzhen C.R.T technology co., LTD | 9*6*6 | HTT-E028 | Aug. 10 2024 | Aug. 09 2027 |
| 2 | Control Room | Shenzhen C.R.T technology co., LTD | 4.8*3.5*3.0 | HTT-E030 | Aug. 10 2024 | Aug. 09 2027 |
| 3 | EMI Test Receiver | Rohde&Schwar | ESCI7 | HTT-E022 | Apr. 26 2024 | Apr. 25 2025 |
| 4 | Spectrum Analyzer | Rohde&Schwar | FSP | HTT-E037 | Apr. 26 2024 | Apr. 25 2025 |
| 5 | Coaxial Cable | ZDecl | ZT26-NJ-NJ-0.6M | HTT-E018 | Apr. 26 2024 | Apr. 25 2025 |
| 6 | Coaxial Cable | ZDecl | ZT26-NJ-SMAJ-2M | HTT-E019 | Apr. 26 2024 | Apr. 25 2025 |
| 7 | Coaxial Cable | ZDecl | ZT26-NJ-SMAJ-0.6M | HTT-E020 | Apr. 26 2024 | Apr. 25 2025 |
| 8 | Coaxial Cable | ZDecl | ZT26-NJ-SMAJ-8.5M | HTT-E021 | Apr. 26 2024 | Apr. 25 2025 |
| 9 | Composite logarithmic antenna | Schwarzbeck | VULB 9168 | HTT-E017 | May. 21 2024 | May. 20 2025 |
| 10 | Horn Antenna | Schwarzbeck | BBHA9120D | HTT-E016 | May. 20 2024 | May. 19 2025 |
| 11 | Loop Antenna | Zhinan | ZN30900C | HTT-E039 | Apr. 26 2024 | Apr. 25 2025 |
| 12 | Horn Antenna | Beijing Hangwei Dayang | OBH100400 | HTT-E040 | Apr. 26 2024 | Apr. 25 2025 |
| 13 | low frequency Amplifier | Sonoma Instrument | 310 | HTT-E015 | Apr. 26 2024 | Apr. 25 2025 |
| 14 | high-frequency Amplifier | HP | 8449B | HTT-E014 | Apr. 26 2024 | Apr. 25 2025 |
| 15 | Variable frequency power supply | Shenzhen Anbiao Instrument Co., Ltd | ANB-10VA | HTT-082 | Apr. 26 2024 | Apr. 25 2025 |
| 16 | EMI Test Receiver | Rohde & Schwarz | ESCS30 | HTT-E004 | Apr. 26 2024 | Apr. 25 2025 |
| 17 | Artificial Mains | Rohde & Schwarz | ESH3-Z5 | HTT-E006 | May. 23 2024 | May. 22 2025 |
| 18 | Artificial Mains | Rohde & Schwarz | ENV-216 | HTT-E038 | May. 23 2024 | May. 22 2025 |
| 19 | Cable Line | Robinson | Z302S-NJ-BNCJ-1.5M | HTT-E001 | Apr. 26 2024 | Apr. 25 2025 |
| 20 | Attenuator | Robinson | 6810.17A | HTT-E007 | Apr. 26 2024 | Apr. 25 2025 |
| 21 | Variable frequency power supply | Shenzhen Yanghong Electric Co., Ltd | YF-650 (5KVA) | HTT-E032 | Apr. 26 2024 | Apr. 25 2025 |
| 22 | Control Room | Shenzhen C.R.T technology co., LTD | 8*4*3.5 | HTT-E029 | Aug. 10 2024 | Aug. 09 2027 |
| 23 | DC power supply | Agilent | E3632A | HTT-E023 | Apr. 26 2024 | Apr. 25 2025 |
| 24 | EMI Test Receiver | Agilent | N9020A | HTT-E024 | Apr. 26 2024 | Apr. 25 2025 |
| 25 | Analog signal generator | Agilent | N5181A | HTT-E025 | Apr. 26 2024 | Apr. 25 2025 |
| 26 | Vector signal generator | Agilent | N5182A | HTT-E026 | Apr. 26 2024 | Apr. 25 2025 |
| 27 | Power sensor | Keysight | U2021XA | HTT-E027 | Apr. 26 2024 | Apr. 25 2025 |
| 28 | Temperature and humidity meter | Shenzhen Anbiao Instrument Co., Ltd | TH10R | HTT-074 | Apr. 28 2024 | Apr. 27 2025 |
| 29 | Radiated Emission Test Software | Farad | EZ-EMC | N/A | N/A | N/A |
| 30 | Conducted Emission Test Software | Farad | EZ-EMC | N/A | N/A | N/A |
| 31 | RF Test Software | panshanrf | TST | N/A | N/A | N/A |

6. Test results and Measurement Data


6.1. Conducted Emissions

| | | | | | | | |
|--|--|-------|--------------|-----|-----------|----------|--|
| Test Requirement: | FCC Part15 C Section 15.207 | | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | | |
| Test Frequency Range: | 150KHz to 30MHz | | | | | | |
| Class / Severity: | Class B | | | | | | |
| Receiver setup: | RBW=9KHz, VBW=30KHz, Sweep time=auto | | | | | | |
| Limit: | Frequency range (MHz) | | Limit (dBuV) | | | | |
| | | | Quasi-peak | | Average | | |
| | 0.15-0.5 | | 66 to 56* | | 56 to 46* | | |
| | 0.5-5 | | 56 | | 46 | | |
| | 5-30 | | 60 | | 50 | | |
| * Decreases with the logarithm of the frequency. | | | | | | | |
| Test setup: | <div><p style="text-align: center;">Reference Plane</p><p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p></div> | | | | | | |
| Test procedure: | <div><div>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</div></div> | | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar | |
| Test voltage: | AC 120V, 60Hz | | | | | | |
| Test results: | Pass | | | | | | |

Remark: Based on all tested data, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case as below:


Measurement data:

Line:



| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | |
|-----|-----|--------|---------|---------|----------|-------|--------|----------|
| | | MHz | Level | Factor | ment | | | Detector |
| | | | | | dBuV | dBuV | dB | |
| 1 | * | 0.1507 | 35.87 | 10.08 | 45.95 | 65.96 | -20.01 | QP |
| 2 | | 0.1507 | 18.82 | 10.08 | 28.90 | 55.96 | -27.06 | AVG |
| 3 | | 0.1661 | 33.89 | 10.07 | 43.96 | 65.15 | -21.19 | QP |
| 4 | | 0.1661 | 17.29 | 10.07 | 27.36 | 55.15 | -27.79 | AVG |
| 5 | | 0.1943 | 30.86 | 10.17 | 41.03 | 63.85 | -22.82 | QP |
| 6 | | 0.1943 | 14.75 | 10.17 | 24.92 | 53.85 | -28.93 | AVG |
| 7 | | 0.2290 | 25.97 | 10.21 | 36.18 | 62.49 | -26.31 | QP |
| 8 | | 0.2290 | 11.23 | 10.21 | 21.44 | 52.49 | -31.05 | AVG |
| 9 | | 0.6281 | 9.77 | 10.22 | 19.99 | 56.00 | -36.01 | QP |
| 10 | | 0.6281 | 3.26 | 10.22 | 13.48 | 46.00 | -32.52 | AVG |
| 11 | | 5.9028 | 15.50 | 10.12 | 25.62 | 60.00 | -34.38 | QP |
| 12 | | 5.9028 | 5.59 | 10.12 | 15.71 | 50.00 | -34.29 | AVG |

Neutral:




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | |
|-----|-----|--------|---------------|----------------|-------------|-------|--------|----------|
| | | MHz | | dB | dBuV | dBuV | dB | Detector |
| 1 | * | 0.1528 | 36.46 | 10.16 | 46.62 | 65.85 | -19.23 | QP |
| 2 | | 0.1528 | 19.32 | 10.16 | 29.48 | 55.85 | -26.37 | AVG |
| 3 | | 0.1678 | 34.64 | 10.21 | 44.85 | 65.07 | -20.22 | QP |
| 4 | | 0.1678 | 18.01 | 10.21 | 28.22 | 55.07 | -26.85 | AVG |
| 5 | | 0.1920 | 31.74 | 10.21 | 41.95 | 63.95 | -22.00 | QP |
| 6 | | 0.1920 | 15.39 | 10.21 | 25.60 | 53.95 | -28.35 | AVG |
| 7 | | 0.2354 | 26.97 | 10.20 | 37.17 | 62.26 | -25.09 | QP |
| 8 | | 0.2354 | 13.21 | 10.20 | 23.41 | 52.26 | -28.85 | AVG |
| 9 | | 0.6301 | 19.78 | 10.19 | 29.97 | 56.00 | -26.03 | QP |
| 10 | | 0.6301 | 13.08 | 10.19 | 23.27 | 46.00 | -22.73 | AVG |
| 11 | | 5.9092 | 21.46 | 10.13 | 31.59 | 60.00 | -28.41 | QP |
| 12 | | 5.9092 | 10.97 | 10.13 | 21.10 | 50.00 | -28.90 | AVG |

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Los

6.2. Conducted Peak Output Power

| | | | | | | |
|-------------------|---|-------|---------|-----|---------|----------|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Limit: | 30dBm(for GFSK),20.97dBm(for EDR) | | | | | |
| Test setup: | <p>Power sensor and Spectrum analyzer</p>  <p>Non-Conducted Table</p> <p>Ground Reference Plane</p> | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

Measurement Data

Left side:


| Mode | TX Type | Frequency (MHz) | Packet Type | Maximum Peak Conducted Output Power (dBm) | | Verdict |
|-----------|---------|-----------------|-------------|---|---------|---------|
| | | | | ANT1 | Limit | |
| GFSK | SISO | 2402 | DH5 | 2.18 | <=30 | Pass |
| | | 2441 | DH5 | 2.28 | <=30 | Pass |
| | | 2480 | DH5 | 1.94 | <=30 | Pass |
| Pi/4DQPSK | SISO | 2402 | 2DH5 | 2.91 | <=20.97 | Pass |
| | | 2441 | 2DH5 | 2.94 | <=20.97 | Pass |
| | | 2480 | 2DH5 | 2.62 | <=20.97 | Pass |
| 8DPSK | SISO | 2402 | 3DH5 | 3.16 | <=20.97 | Pass |
| | | 2441 | 3DH5 | 3.28 | <=20.97 | Pass |
| | | 2480 | 3DH5 | 3.00 | <=20.97 | Pass |

Right side:

| Mode | TX Type | Frequency (MHz) | Packet Type | Maximum Peak Conducted Output Power (dBm) | | Verdict |
|-----------|---------|-----------------|-------------|---|---------|---------|
| | | | | ANT1 | Limit | |
| GFSK | SISO | 2402 | DH5 | 0.25 | <=30 | Pass |
| | | 2441 | DH5 | 0.31 | <=30 | Pass |
| | | 2480 | DH5 | -0.45 | <=30 | Pass |
| Pi/4DQPSK | SISO | 2402 | 2DH5 | 0.16 | <=20.97 | Pass |
| | | 2441 | 2DH5 | 0.88 | <=20.97 | Pass |
| | | 2480 | 2DH5 | 0.57 | <=20.97 | Pass |
| 8DPSK | SISO | 2402 | 3DH5 | 1.58 | <=20.97 | Pass |
| | | 2441 | 3DH5 | 1.15 | <=20.97 | Pass |
| | | 2480 | 3DH5 | 1.26 | <=20.97 | Pass |



6.3. 20dB Emission Bandwidth

| | | | | | | |
|-------------------|--|-------|---------|-----|---------|----------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Limit: | N/A | | | | | |
| Test setup: |  | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

Measurement Data


| Mode | TX Type | Frequency (MHz) | Packet Type | ANT | 20dB Bandwidth (MHz) | | Verdict |
|-----------|---------|-----------------|-------------|-----|----------------------|-------|---------|
| | | | | | Result | Limit | |
| GFSK | SISO | 2402 | DH5 | 1 | 0.946 | / | Pass |
| | | 2441 | DH5 | 1 | 0.949 | / | Pass |
| | | 2480 | DH5 | 1 | 0.961 | / | Pass |
| Pi/4DQPSK | SISO | 2402 | 2DH5 | 1 | 1.271 | / | Pass |
| | | 2441 | 2DH5 | 1 | 1.269 | / | Pass |
| | | 2480 | 2DH5 | 1 | 1.271 | / | Pass |
| 8DPSK | SISO | 2402 | 3DH5 | 1 | 1.291 | / | Pass |
| | | 2441 | 3DH5 | 1 | 1.294 | / | Pass |
| | | 2480 | 3DH5 | 1 | 1.291 | / | Pass |




Report No.: HTT202504427F01

Test plot as follows:


| | |
|------------|-----------|
| Test mode: | GFSK mode |
|------------|-----------|



Lowest channel



Middle channel




Highest channel




Report No.: HTT202504427F01

Test mode:


$\pi/4$ -DQPSK mode



Lowest channel



Middle channel




Highest channel




Report No.: HTT202504427F01

Test mode:


8-DPSK mode



Lowest channel




Middle channel



Highest channel

6.4. Frequencies Separation

| | | | | | | |
|-------------------|---|-------|---------|-----|---------|----------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Receiver setup: | RBW=100KHz, VBW=300KHz, detector=Peak | | | | | |
| Limit: | GFSK: 20dB bandwidth $\pi/4$ -DQPSK : 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater) | | | | | |
| Test setup: |  | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

Measurement Data


| Ant1 | | | | | | | |
|---------------|---------|-----------------|-------------|--------------------------|----------------------|--------------|---------|
| Mode | TX Type | Frequency (MHz) | Packet Type | Channel Separation (MHz) | 20dB Bandwidth (MHz) | Limit (MHz) | Verdict |
| GFSK | SISO | HOPP | DH5 | 1.000 | 0.961 | ≥ 0.961 | Pass |
| $\pi/4$ DQPSK | SISO | HOPP | 2DH5 | 1.001 | 1.271 | ≥ 0.847 | Pass |
| 8DPSK | SISO | HOPP | 3DH5 | 1.032 | 1.294 | ≥ 0.863 | Pass |

Remark: We have tested all mode at high, middle and low channel, and recorded worst case at middle




Test plot as follows:


| | |
|------------------|------|
| Modulation mode: | GFSK |
|------------------|------|




| | |
|------------|----------------|
| Test mode: | $\pi/4$ -DQPSK |
|------------|----------------|



| | |
|------------------|--------|
| Modulation mode: | 8-DPSK |
|------------------|--------|



6.5. Hopping Channel Number

| | | | | | | |
|-------------------|--|-------|---------|-----|---------|----------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)(iii) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Receiver setup: | RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak | | | | | |
| Limit: | 15 channels | | | | | |
| Test setup: |  | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

Measurement Data:


| Mode | Hopping channel numbers | Limit | Result |
|----------------|-------------------------|-------|--------|
| GFSK | 79 | ≥15 | Pass |
| $\pi/4$ -DQPSK | 79 | | Pass |
| 8-DPSK | 79 | | Pass |




Report No.: HTT202504427F01

Test plot as follows:


| | |
|------------|------|
| Test mode: | GFSK |
|------------|------|




| | |
|------------|----------------|
| Test mode: | $\pi/4$ -DQPSK |
|------------|----------------|



| | |
|------------|--------|
| Test mode: | 8-DPSK |
|------------|--------|



6.6. Dwell Time

| | | | | | | |
|-------------------|--|-------|---------|-----|---------|----------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)(iii) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Receiver setup: | RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak | | | | | |
| Limit: | 0.4 Second | | | | | |
| Test setup: |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p> | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |

**Measurement Data**

| Modulation | Packet | Burst time (ms) | Dwell time (ms) | Limit (ms) | Result |
|---------------|--------|--------------------|--------------------|------------|--------|
| GFSK | DH1 | 0.412 | 131.840 | 400 | Pass |
| | DH3 | 1.668 | 266.880 | | |
| | DH5 | 2.918 | 318.062 | | |
| $\pi/4$ DQPSK | 2-DH1 | 0.422 | 135.040 | 400 | Pass |
| | 2-DH3 | 1.674 | 282.906 | | |
| | 2-DH5 | 2.922 | 327.264 | | |
| 8DPSK | 3-DH1 | 0.422 | 135.040 | 400 | Pass |
| | 3-DH3 | 1.674 | 261.144 | | |
| | 3-DH5 | 2.924 | 280.704 | | |

Note: We have tested all mode at high, middle and low channel, and recorded worst case at middle channel.

Dwell time = Pulse time (ms) \times (1600 \div 2 \div 79) \times 31.6 Second for DH1, 2-DH1, 3-DH1


Dwell time = Pulse time (ms) \times (1600 \div 4 \div 79) \times 31.6 Second for DH3, 2-DH3, 3-DH3

Dwell time = Pulse time (ms) \times (1600 \div 6 \div 79) \times 31.6 Second for DH5, 2-DH5, 3-DH5




Test plot as follows:


GFSK mode



DH1



DH3




DH5




Report No.: HTT202504427F01


$\pi/4$ -DQPSK mode



2DH1




2DH3




2DH5




8-DPSK mode



3DH1




3DH3



3DH5

6.7. Band Edge


6.7.1. Conducted Emission Method

| | | | | | | |
|-------------------|---|-------|---------|-----|---------|----------|
| Test Requirement: | FCC Part15 C Section 15.247 (d) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Receiver setup: | RBW=100kHz, VBW=300kHz, Detector=Peak | | | | | |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. | | | | | |
| Test setup: |  <p>The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p> | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |




Test plot as follows:
GFSK Mode:

| Test channel | Lowest channel |
|--------------|----------------|
|--------------|----------------|




No-hopping mode




Hopping mode

| Test channel: | Highest channel |
|---------------|-----------------|
|---------------|-----------------|



No-hopping mode




Hopping mode




Report No.: HTT202504427F01

$\pi/4$ -DQPSK Mode:

| Test channel | Lowest channel |
|--------------|----------------|
|--------------|----------------|




No-hopping mode




Hopping mode

| Test channel: | Highest channel |
|---------------|-----------------|
|---------------|-----------------|



No-hopping mode




Hopping mode




8-DPSK Mode:

| Test channel: | Lowest channel |
|---------------|----------------|
|---------------|----------------|




No-hopping mode




Hopping mode

| Test channel: | Highest channel |
|---------------|-----------------|
|---------------|-----------------|




No-hopping mode



Hopping mode

6.7.2. Radiated Emission Method

| | | | | | | | |
|-----------------------|--|----------|---------|--------------------|---------|---------------|--|
| Test Requirement: | FCC Part15 C Section 15.209 and 15.205 | | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | | |
| Test Frequency Range: | All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed. | | | | | | |
| Test site: | Measurement Distance: 3m | | | | | | |
| Receiver setup: | Frequency | Detector | | RBW | VBW | Remark | |
| | Above 1GHz | Peak | | 1MHz | 3MHz | Peak Value | |
| | | Peak | | 1MHz | 10Hz | Average Value | |
| Limit: | Frequency | | | Limit (dBuV/m @3m) | | Remark | |
| | Above 1GHz | | | 54.00 | | Average Value | |
| | | | | 74.00 | | Peak Value | |
| Test setup: |  | | | | | | |
| Test Procedure: | <ol style="list-style-type: none">1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. | | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | | |
| Test results: | Pass | | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar | |

**Measurement Data**


Remark: GFSK, Pi/4 DQPSK,8-DPSK all have been tested, only worse case GFSK is reported.

Operation Mode: GFSK

| Frequency(MHz): | | | 2402 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2390.00 | 59.66 | PK | 74 | 14.34 | 61.05 | 27.2 | 4.31 | 32.9 | -1.39 |
| 2390.00 | 45.15 | AV | 54 | 8.85 | 46.54 | 27.2 | 4.31 | 32.9 | -1.39 |
| Frequency(MHz): | | | 2402 | | Polarity: | | VERTICAL | | |
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2390.00 | 59.82 | PK | 74 | 14.18 | 61.21 | 27.2 | 4.31 | 32.9 | -1.39 |
| 2390.00 | 46.08 | AV | 54 | 7.92 | 47.47 | 27.2 | 4.31 | 32.9 | -1.39 |
| Frequency(MHz): | | | 2480 | | Polarity: | | HORIZONTAL | | |
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2483.50 | 56.54 | PK | 74 | 17.46 | 57.47 | 27.4 | 4.47 | 32.8 | -0.93 |
| 2483.50 | 46.29 | AV | 54 | 7.71 | 47.22 | 27.4 | 4.47 | 32.8 | -0.93 |
| Frequency(MHz): | | | 2480 | | Polarity: | | VERTICAL | | |
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2483.50 | 54.59 | PK | 74 | 19.41 | 55.52 | 27.4 | 4.47 | 32.8 | -0.93 |
| 2483.50 | 43.82 | AV | 54 | 10.18 | 44.75 | 27.4 | 4.47 | 32.8 | -0.93 |


6.8. Spurious Emission

6.8.1. Conducted Emission Method


| | | | | | | |
|-------------------|---|-------|---------|-----|---------|----------|
| Test Requirement: | FCC Part15 C Section 15.247 (d) | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. | | | | | |
| Test setup: |  <p>The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p> | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test results: | Pass | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |




Reference



GFSK




$\pi/4$ DQPSK




8-DPSK




GFSK



CH00



CH39




CH78




Report No.: HTT202504427F01


$\pi/4$ DQPSK



CH00



CH39




CH78




Report No.: HTT202504427F01


8-DPSK



CH00






CH39



CH78

6.8.2. Radiated Emission Method

| | | | | | |
|-----------------------|--|--------------|---------|----------------------|------------|
| Test Requirement: | FCC Part15 C Section 15.209 | | | | |
| Test Method: | ANSI C63.10:2013 | | | | |
| Test Frequency Range: | 9kHz to 25GHz | | | | |
| Test site: | Measurement Distance: 3m | | | | |
| Receiver setup: | Frequency | Detector | RBW | VBW | Value |
| | 9KHz-150KHz | Quasi-peak | 200Hz | 600Hz | Quasi-peak |
| | 150KHz-30MHz | Quasi-peak | 9KHz | 30KHz | Quasi-peak |
| | 30MHz-1GHz | Quasi-peak | 120KHz | 300KHz | Quasi-peak |
| | Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| | | Peak | 1MHz | 10Hz | Average |
| Limit: | Frequency | Limit (uV/m) | Value | Measurement Distance | |
| | 0.009MHz-0.490MHz | 2400/F(KHz) | QP | 300m | |
| | 0.490MHz-1.705MHz | 24000/F(KHz) | QP | 30m | |
| | 1.705MHz-30MHz | 30 | QP | 30m | |
| | 30MHz-88MHz | 100 | QP | 3m | |
| | 88MHz-216MHz | 150 | QP | | |
| | 216MHz-960MHz | 200 | QP | | |
| | 960MHz-1GHz | 500 | QP | | |
| | Above 1GHz | 500 | Average | | |
| | | 5000 | Peak | | |
| Test setup: | For radiated emissions from 9kHz to 30MHz | | | | |
| |  | | | | |

| | |
|------------------------|---|
| | <p>For radiated emissions from 30MHz to 1GHz</p>  <p>For radiated emissions above 1GHz</p>  |
| <p>Test Procedure:</p> | <ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. |



Report No.: HTT202504427F01

| | | | | | | |
|-------------------|---|-------|---------|-----|---------|----------|
| | 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |
| Test voltage: | AC 120V, 60Hz | | | | | |
| Test results: | Pass | | | | | |

Measurement data:


Remarks:

1. During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
4. Tested all modes and saved the worst data in DH5 2402MHz as below:




For 30MHz-1GHz

Horizontal



| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | |
|-----|-----|----------|---------|---------|----------|-------|--------|----------|
| | | MHz | Level | Factor | ment | | | Detector |
| | | | dBuV | dB/m | dBuV/m | dB/m | dB | |
| 1 | | 43.0505 | 28.21 | -10.25 | 17.96 | 40.00 | -22.04 | peak |
| 2 | | 230.0985 | 30.51 | -12.48 | 18.03 | 46.00 | -27.97 | peak |
| 3 | | 490.7447 | 29.48 | -5.56 | 23.92 | 46.00 | -22.08 | peak |
| 4 | | 663.4729 | 28.85 | -2.55 | 26.30 | 46.00 | -19.70 | peak |
| 5 | * | 776.8778 | 28.95 | -0.18 | 28.77 | 46.00 | -17.23 | peak |
| 6 | | 968.9338 | 27.95 | 3.34 | 31.29 | 54.00 | -22.71 | peak |

Final Level =Receiver Read level + Correct Factor



**For 1GHz to 25GHz**

Remark: For test above 1GHz GFSK, Pi/4 DQPSK and 8-DPSK were test at Low, Middle, and High channel; only the worst result of GFSK was reported as below:

| Frequency(MHz): | | | 2402 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4804.00 | 58.97 | PK | 74 | 15.03 | 53.27 | 31 | 6.5 | 31.8 | 5.7 |
| 4804.00 | 43.03 | AV | 54 | 10.97 | 37.33 | 31 | 6.5 | 31.8 | 5.7 |
| 7206.00 | 53.97 | PK | 74 | 20.03 | 41.32 | 36 | 8.15 | 31.5 | 12.65 |
| 7206.00 | 43.36 | AV | 54 | 10.64 | 30.71 | 36 | 8.15 | 31.5 | 12.65 |

| Frequency(MHz): | | | 2402 | | Polarity: | | VERTICAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4804.00 | 59.88 | PK | 74 | 14.12 | 54.18 | 31 | 6.5 | 31.8 | 5.7 |
| 4804.00 | 43.13 | AV | 54 | 10.87 | 37.43 | 31 | 6.5 | 31.8 | 5.7 |
| 7206.00 | 53.80 | PK | 74 | 20.20 | 41.15 | 36 | 8.15 | 31.5 | 12.65 |
| 7206.00 | 43.12 | AV | 54 | 10.88 | 30.47 | 36 | 8.15 | 31.5 | 12.65 |

| Frequency(MHz): | | | 2441 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4882.00 | 59.42 | PK | 74 | 14.58 | 53.26 | 31.2 | 6.61 | 31.65 | 6.16 |
| 4882.00 | 44.96 | AV | 54 | 9.04 | 38.80 | 31.2 | 6.61 | 31.65 | 6.16 |
| 7323.00 | 52.69 | PK | 74 | 21.31 | 39.74 | 36.2 | 8.23 | 31.48 | 12.95 |
| 7323.00 | 44.52 | AV | 54 | 9.48 | 31.57 | 36.2 | 8.23 | 31.48 | 12.95 |



Report No.: HTT202504427F01

| Frequency(MHz): | | | 2441 | | Polarity: | | VERTICAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4882.00 | 60.56 | PK | 74 | 13.44 | 54.40 | 31.2 | 6.61 | 31.65 | 6.16 |
| 4882.00 | 43.74 | AV | 54 | 10.26 | 37.58 | 31.2 | 6.61 | 31.65 | 6.16 |
| 7323.00 | 54.20 | PK | 74 | 19.80 | 41.25 | 36.2 | 8.23 | 31.48 | 12.95 |
| 7323.00 | 44.48 | AV | 54 | 9.52 | 31.53 | 36.2 | 8.23 | 31.48 | 12.95 |

| Frequency(MHz): | | | 2480 | | Polarity: | | HORIZONTAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4960.00 | 62.37 | PK | 74 | 11.63 | 55.71 | 31.4 | 6.76 | 31.5 | 6.66 |
| 4960.00 | 42.83 | AV | 54 | 11.17 | 36.17 | 31.4 | 6.76 | 31.5 | 6.66 |
| 7440.00 | 53.42 | PK | 74 | 20.58 | 40.12 | 36.4 | 8.35 | 31.45 | 13.3 |
| 7440.00 | 45.25 | AV | 54 | 8.75 | 31.95 | 36.4 | 8.35 | 31.45 | 13.3 |

| Frequency(MHz): | | | 2480 | | Polarity: | | VERTICAL | | |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) | | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4960.00 | 64.44 | PK | 74 | 9.56 | 57.78 | 31.4 | 6.76 | 31.5 | 6.66 |
| 4960.00 | 43.86 | AV | 54 | 10.14 | 37.20 | 31.4 | 6.76 | 31.5 | 6.66 |
| 7440.00 | 54.59 | PK | 74 | 19.41 | 41.29 | 36.4 | 8.35 | 31.45 | 13.3 |
| 7440.00 | 44.45 | AV | 54 | 9.55 | 31.15 | 36.4 | 8.35 | 31.45 | 13.3 |

Remark:

- (1) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (2) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed.



6.9. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Antenna Connected Construction

The maximum gain of antenna was 2.70 dBi.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen HTT Technology Co., Ltd. does not assume any responsibility.



7. Test Setup Photo

Reference to the **appendix I** for details.

8. EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----