




TEST REPORT

Report No. : CHTEW19070119 Project Verification: 
Project No. : SHT1906063205EW
FCC ID..... : 2ALV5-LE-202
Applicant's name..... : Origins Technology Limited
Address..... : Laku Hutong #20. Dongcheng District, Beijing, China
Manufacturer..... : Origins Technology Limited
Address..... : Laku Hutong #20. Dongcheng District, Beijing, China
Test item description : Laser Egg+ CO2 Smart Air Quality Monitor
Trade Mark : Kaiterra
Model/Type reference..... : LE-202
Listed Model(s) : -
Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of receipt of test sample..... : Jun.28, 2019
Date of testing..... : Jun.28, 2019- Jul.19, 2019
Date of issue..... : Jul.22, 2019
Result..... : PASS

Compiled by
(position+printedname+signature).... : File administrators Fanghui Zhu

Fanghui Zhu

Supervised by
(position+printedname+signature).... : Project Engineer Tom Ouyang

Tom ouyang

Approved by
(position+printedname+signature)..... : RF Manager Hans Hu

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road,
Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>11</u>
5.1.	Antenna requirement	11
5.2.	Conducted Emissions (AC Main)	12
5.3.	Conducted Peak Output Power	15
5.4.	Power Spectral Density	16
5.5.	6dB bandwidth	20
5.6.	Restricted band	24
5.7.	Band edge and Spurious Emissions (conducted)	28
5.8.	Spurious Emissions (radiated)	41
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	<u>50</u>
<u>7.</u>	<u>EXTERANAL AND INTERNAL PHOTOS</u>	<u>51</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 15.247 Meas Guidance v05](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2019-07-23	Original

2. TEST DESCRIPTION

Test Item	FCC Rule	Result	Test Engineer
Antenna requirement	15.203/15.247(c)	PASS	Bruce Wong
Line Conducted Emissions (AC Main)	15.207	PASS	Kang Yang
Conducted Peak Output Power	15.247(b)(3)	PASS	Bruce Wong
Power Spectral Density	15.247(e)	PASS	Bruce Wong
6dB Bandwidth	15.247(a)(2)	PASS	Bruce Wong
Restricted band	15.247(d)/15.205	PASS	Bruce Wong
Spurious Emissions	15.247(d)/15.209	PASS	Tony Duan

Note: The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

Applicant:	Origins Technology Limited
Address:	Laku Hutong #20. Dongcheng District, Beijing, China
Manufacturer:	Origins Technology Limited
Address:	Laku Hutong #20. Dongcheng District, Beijing, China

3.2. Product Description

Name of EUT:	Laser Egg+ CO2 Smart Air Quality Monitor
Trade Mark:	Kaiterra
Model No.:	LE-202
Listed Model(s):	-
Power supply:	DC3.7V from battery
Adapter information:	Model: MF-05001000 Input: 100-240Va.c., 50/60Hz, 0.4A Output: 5Vd.c., 1.0A
Hardware version:	V4.2
Software version:	1.5.0
WIFI	
Supported type:	802.11b/802.11g/802.11n(HT20)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)
Operation frequency:	2412MHz~2462MHz
Channel number:	11
Channel separation:	5MHz
Antenna type:	Onboard antenna
Antenna gain:	0dbi

3.3. Operation state

➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

802.11b/g/n(HT20)	
Channel	Frequency (MHz)
01	2412
02	2417
...	...
06	2437
...	...
10	2457
11	2462

➤ Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit (duty cycle>98%).
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated suprious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit(duty cycle>98%). The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data Recorded in the report.

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○	/	Manufacturer:	/
		Model No.:	/
○	/	Manufacturer:	/
		Model No.:	/

3.5. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

4.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

IC-Registration No.:5377A

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377A.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.51 dB	(1)
Conducted spurious emissions 9kHz~40GHz	0.51 dB	(1)
Conducted Disturbance 150kHz~30MHz	3.02 dB	(1)
Radiated Emissions below 1GHz	4.90 dB	(1)
Radiated Emissions above 1GHz	4.96 dB	(1)
Occupied Bandwidth	70 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.5. Equipments Used during the Test

● Conducted Emission						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	ESCI	101247	2018/10/27	2019/10/26
●	Artificial Mains	SCHWARZBECK	NNLK 8121	573	2018/10/27	2019/10/26
●	Pulse Limiter	R&S	ESH3-Z2	100499	2018/10/27	2019/10/26
●	RF Connection Cable	HUBER+SUHNER	EF400	N/A	2018/11/15	2019/11/14
●	Test Software	R&S	ES-K1	N/A	N/A	N/A
○	Single Balanced Telecom Pair ISN	FCC	FCC-TLISN-T2-02	20371	2018/10/28	2019/10/27
○	Two Balanced Telecom Pairs ISN	FCC	FCC-TLISN-T4-02	20373	2018/10/28	2019/10/27
○	Four Balanced Telecom Pairs ISN	FCC	FCC-TLISN-T8-02	20375	2018/10/28	2019/10/27
○	V-Network	R&S	ESH3-Z6	100211	2018/10/27	2019/10/26
○	V-Network	R&S	ESH3-Z6	100210	2018/10/27	2019/10/26
○	2-Line V-Network	R&S	ESH3-Z5	100049	2018/10/27	2019/10/26

● Radiated Emission-6th test site						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	SAC-3m-02	N/A	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	ESCI	100900	2018/10/28	2019/10/27
●	Loop Antenna	R&S	HFH2-Z2	100020	2017/11/20	2020/11/19
●	Ultra-Broadband Antenna	SCHWARZBECK	VULB9163	546	2017/04/05	2020/04/04
●	Pre-Amplifier	SCHWARZBECK	BBV 9742	N/A	2018/11/15	2019/11/14
●	RF Connection Cable	HUBER+SUHNER	N/A	N/A	2018/09/28	2019/09/27
●	RF Connection Cable	HUBER+SUHNER	SUCOFLEX104	501184/4	2018/09/28	2019/09/27
●	Test Software	R&S	ES-K1	N/A	N/A	N/A
●	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
●	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A

● Radiated emission-7th test site						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	SAC-3m-01	N/A	2018/09/30	2021/09/29
●	Spectrum Analyzer	R&S	FSP40	100597	2018/10/27	2019/10/26
●	Horn Antenna	SCHWARZBECK	9120D	1011	2017/03/27	2020/03/26
●	Pre-amplifier	BONN	BLWA0160-2M	1811887	2018/11/14	2019/11/13
●	Pre-amplifier	CD	PAP-0102	12004	2018/11/14	2019/11/13
●	Broadband Pre-amplifier	SCHWARZBECK	BBV 9718	9718-248	2019/04/26	2020/04/25
●	RF Connection Cable	HUBER+SUHNER	RE-7-FH	N/A	2018/11/15	2019/11/14
●	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	2018/11/15	2019/11/14
●	Test Software	Audix	E3	N/A	N/A	N/A

●	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
●	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A

● **RF Conducted Method**

Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2018/10/28	2019/10/27
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2018/09/29	2019/09/28
●	OSP	R&S	OSP120	101317	N/A	N/A
○	Radio communication tester	R&S	CMW500	137688-Lv	2018/09/29	2019/09/28
○	Test software	Tonscend	JS1120-1(LTE)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-2(WIFI)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-3(WCDMA)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-4(GSM)	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna requirement

REQUIREMENT:

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. Conducted Emissions (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS


☒ Passed ☐ Not Applicable

Note:

- 1) Transd=Cable lose+ Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit -Level

Test Line:

L

**MEASUREMENT RESULT: "GM1907015033_fin"**


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	45.80	9.9	66	20.2	QP	L1	GND
0.388500	33.50	9.9	58	24.6	QP	L1	GND
0.879000	28.30	9.9	56	27.7	QP	L1	GND
2.620500	25.60	9.9	56	30.4	QP	L1	GND
5.244000	27.40	10.0	60	32.6	QP	L1	GND
22.528500	22.50	10.3	60	37.5	QP	L1	GND

MEASUREMENT RESULT: "GM1907015033_fin2"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.325500	25.40	9.9	50	24.2	AV	L1	GND
0.393000	23.00	9.9	48	25.0	AV	L1	GND
0.870000	17.70	9.9	46	28.3	AV	L1	GND
2.499000	15.70	9.9	46	30.3	AV	L1	GND
5.100000	16.40	10.0	50	33.6	AV	L1	GND
22.375500	14.80	10.3	50	35.2	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM1907015034_fin"**

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.190500	42.00	9.9	64	22.0	QP	N	GND
0.393000	33.50	9.9	58	24.5	QP	N	GND
0.919500	24.80	9.9	56	31.2	QP	N	GND
2.674500	19.30	9.9	56	36.7	QP	N	GND
6.031500	18.70	10.0	60	41.3	QP	N	GND
21.799500	18.20	10.2	60	41.8	QP	N	GND

MEASUREMENT RESULT: "GM1907015034_fin2"


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.334500	27.80	9.9	49	21.5	AV	N	GND
0.393000	23.70	9.9	48	24.3	AV	N	GND
1.000500	16.80	9.9	46	29.2	AV	N	GND
2.737500	13.80	9.9	46	32.2	AV	N	GND
6.346500	14.50	10.0	50	35.5	AV	N	GND
23.127000	13.60	10.3	50	36.4	AV	N	GND

5.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 for compliance to FCC 47 CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector
4. Record the measurement data.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Type	Channel	Peak Output power (dBm)	Limit (dBm)	Result
802.11b	01	13.20	≤30.00	Pass
	06	13.90		
	11	14.50		
802.11g	01	18.08	≤30.00	Pass
	06	18.55		
	11	18.64		
802.11n(HT20)	01	16.26	≤30.00	Pass
	06	16.65		
	11	16.73		


5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:


Please refer to the clause 3.3


TEST RESULTS


☒ Passed ☐ Not Applicable

Type	Channel	Power Spectral Density (dBm/30KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-2.21	≤8.00	Pass
	06	-1.96		
	11	-1.34		
802.11g	01	-5.83	≤8.00	Pass
	06	-4.58		
	11	-5.18		
802.11n(HT20)	01	-8.03	≤8.00	Pass
	06	-7.79		
	11	-7.74		

Test plot as follows:








5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
 Center Frequency = DTS channel center frequency
 Span = 2 x DTS bandwidth
 RBW = 100 kHz, VBW ≥ 3 x RBW
 Sweep time = auto couple
 Detector = Peak
 Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:


Please refer to the clause 3.3


TEST RESULTS


☒ Passed ☐ Not Applicable

Type	Channel	6dB Bandwidth (MHz)	Limit (kHz)	Result
802.11b	01	9.66	≥500	Pass
	06	10.08		
	11	10.14		
802.11g	01	16.62	≥500	Pass
	06	16.62		
	11	16.44		
802.11n(HT20)	01	17.88	≥500	Pass
	06	17.64		
	11	17.67		

Test plot as follows:








5.6. Restricted band

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

- 1) The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2) The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3) The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- 4) The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
- 5) The receiver set as follow:
 RBW=1MHz, VBW=3MHz PEAK detector for Peak value.
 RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor

802.11b				CH01			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	16.23	35.78	52.01	74.00	21.99	Horizontal	PK
2310.000	14.38	35.78	50.16	54.00	3.84	Horizontal	AV
2390.009	16.19	35.50	51.69	54.00	2.31	Horizontal	AV
2390.009	16.51	35.50	52.01	74.00	21.99	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.000	14.53	35.78	50.31	74.00	23.69	Vertical	PK
2310.000	13.42	35.78	49.20	54.00	4.80	Vertical	AV
2390.009	16.03	35.50	51.53	74.00	22.47	Vertical	PK
2390.009	15.47	35.50	50.97	54.00	3.03	Vertical	AV

802.11b				CH11			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.500	15.47	35.31	50.78	74.00	23.22	Horizontal	PK
2483.500	14.07	35.31	49.38	54.00	4.62	Horizontal	AV
2500.000	15.44	35.28	50.72	74.00	23.28	Horizontal	PK
2500.000	13.34	35.28	48.62	54.00	5.38	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.500	14.47	35.31	49.78	74.00	24.22	Vertical	PK
2483.500	12.84	35.31	48.15	54.00	5.85	Vertical	AV
2500.000	14.57	35.28	49.85	54.00	4.15	Vertical	AV
2500.000	15.23	35.28	50.51	74.00	23.49	Vertical	PK

802.11g					CH01		
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.003	12.66	35.78	48.44	54.00	5.56	Horizontal	AV
2310.003	13.01	35.78	48.79	74.00	25.21	Horizontal	PK
2390.002	13.19	35.50	48.69	54.00	5.31	Horizontal	AV
2390.002	13.67	35.50	49.17	74.00	24.83	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.003	15.65	35.78	51.43	74.00	22.57	Vertical	PK
2310.003	14.61	35.78	50.39	54.00	3.61	Vertical	AV
2390.002	12.98	35.50	48.48	54.00	5.52	Vertical	AV
2390.002	12.04	35.50	47.54	74.00	26.46	Vertical	PK

802.11g					CH11		
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.504	12.31	35.31	47.62	54.00	6.38	Horizontal	AV
2483.504	12.21	35.31	47.52	74.00	26.48	Horizontal	PK
2500.000	15.63	35.28	50.91	74.00	23.09	Horizontal	PK
2500.000	12.20	35.28	47.48	54.00	6.52	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.504	12.97	35.31	48.28	74.00	25.72	Vertical	PK
2483.504	11.45	35.31	46.76	54.00	7.24	Vertical	AV
2500.000	13.16	35.28	48.44	54.00	5.56	Vertical	AV
2500.000	14.11	35.28	49.39	74.00	24.61	Vertical	PK

802.11n(HT20)					CH01		
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.003	12.64	35.78	48.42	74.00	25.58	Horizontal	PK
2310.003	13.06	35.78	48.84	54.00	5.16	Horizontal	AV
2390.002	11.81	35.50	47.31	54.00	6.69	Horizontal	AV
2390.002	12.08	35.50	47.58	74.00	26.42	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2310.003	11.78	35.78	47.56	74.00	26.44	Vertical	PK
2310.003	12.60	35.78	48.38	54.00	5.62	Vertical	AV
2390.002	13.15	35.50	48.65	54.00	5.35	Vertical	AV
2390.002	12.53	35.50	48.03	74.00	25.97	Vertical	PK

802.11n(HT20)					CH11		
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.504	13.37	35.31	48.68	74.00	25.32	Horizontal	PK
2483.504	10.91	35.31	46.22	54.00	7.78	Horizontal	AV
2500.000	14.90	35.28	50.18	54.00	3.82	Horizontal	AV
2500.000	16.27	35.28	51.55	74.00	22.45	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
2483.504	11.42	35.31	46.73	54.00	7.27	Vertical	AV
2483.504	11.89	35.31	47.20	74.00	26.80	Vertical	PK
2500.000	14.65	35.28	49.93	74.00	24.07	Vertical	PK
2500.000	13.30	35.28	48.58	54.00	5.42	Vertical	AV


5.7. Band edge and Spurious Emissions (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure
Center frequency=DTS channel center frequency
The span = 1.5 times the DTS bandwidth.
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum PSD level


Note: the channel found to contain the maximum PSD level can be used to establish the reference level.
3. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.


TEST MODE:


Please refer to the clause 3.3




TEST RESULTS

☒ Passed ☐ Not Applicable









Test Item:	SE	Type:	802.11 b
CH01 Reference level	 <p>Spectrum</p> <p>Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100</p> <p>IPK Max</p> <p>M1[1] 0.63 dBm 2.4124780 GHz</p> <p>CF 2.412 GHz 691 pts Span 30.0 MHz</p> <p>Date: 15 JUL 2019 21:05:55</p>		
CH01 30MHz~1000MHz	 <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10</p> <p>IPK Max</p> <p>M1[1] -53.17 dBm 909.6800 MHz</p> <p>Start 30.0 MHz 30001 pts Stop 1.0 GHz</p> <p>Date: 15 JUL 2019 21:05:51</p>		
CH01 1GHz~26GHz	 <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10</p> <p>IPK Max</p> <p>M1[1] -45.13 dBm 15.890000 GHz</p> <p>Start 1.0 GHz 30001 pts Stop 26.0 GHz</p> <p>Date: 15 JUL 2019 21:06:07</p>		


CH06
Reference level









CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH11
Reference levelCH11
30MHz~1000MHzCH11
1GHz~26GHz

Test Item:	SE	Type:	802.11 g
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			


CH06
Reference level




CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH11
Reference level






CH11
30MHz~1000MHz




CH11
1GHz~26GHz




Test Item:	SE	Type:	802.11 n(HT20)
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			


CH06
Reference level




CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH11
Reference level



CH11
30MHz~1000MHz



CH11
1GHz~26GHz



5.8. Spurious Emissions (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


➤ 9kHz ~30MHz



➤ 30MHz ~ 1GHz



➤ Above 1GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

Note:

- 1) Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.

➤ **9kHz ~ 30MHz**

The EUT was pre-scanned the frequency band (9kHz~30MHz), found the radiated level lower than the limit, so don't show on the report.


➤ **30MHz ~1000MHz**

Have pre-scan all modulation mode, found the 802.11b mode CH01 which it was worst case, so only the worst case's data on the test report.

➤ 30MHz ~ 1GHz

Polarization:

Vertical


**MEASUREMENT RESULT: "GM1907046083_red"**

7/4/2019 10:17PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
49.400000	22.80	-4.8	40.0	17.2	QP	100.0	171.00	VERTICAL
59.100000	29.20	-5.9	40.0	10.8	QP	100.0	0.00	VERTICAL
86.260000	24.90	-10.2	40.0	15.1	QP	100.0	0.00	VERTICAL
179.380000	28.70	-8.5	43.5	14.8	QP	100.0	0.00	VERTICAL
532.460000	30.00	2.6	46.0	16.0	QP	100.0	360.00	VERTICAL
895.240000	38.80	10.3	46.0	7.2	QP	100.0	271.00	VERTICAL

Polarization:

Horizontal

**MEASUREMENT RESULT: "GM1907046084_red"**

7/4/2019 10:21PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
47.460000	22.50	-4.9	40.0	17.5	QP	300.0	193.00	HORIZONTAL
57.160000	22.00	-5.5	40.0	18.0	QP	100.0	155.00	HORIZONTAL
159.980000	29.00	-9.6	43.5	14.5	QP	100.0	257.00	HORIZONTAL
179.380000	36.70	-8.5	43.5	6.8	QP	100.0	257.00	HORIZONTAL
340.400000	31.20	-1.9	46.0	14.8	QP	100.0	125.00	HORIZONTAL
881.660000	38.40	10.0	46.0	7.6	QP	300.0	107.00	HORIZONTAL

➤ 1 GHz ~ 25 GHz

802.11b				CH01			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1148.343	24.91	-6.38	18.53	54.00	35.47	Horizontal	AV
1155.687	34.70	-6.30	28.40	74.00	45.60	Horizontal	PK
3163.468	23.04	0.65	23.69	54.00	30.31	Horizontal	AV
3172.281	33.08	0.70	33.78	74.00	40.22	Horizontal	PK
4823.156	35.34	7.08	42.42	54.00	11.58	Horizontal	AV
4823.156	40.61	7.08	47.69	74.00	26.31	Horizontal	PK
6816.250	30.63	13.35	43.98	74.00	30.02	Horizontal	PK
7186.375	20.30	15.91	36.21	54.00	17.79	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1185.062	25.15	-5.99	19.16	54.00	34.84	Vertical	AV
1214.437	34.94	-5.79	29.15	74.00	44.85	Vertical	PK
2824.187	20.11	1.70	21.81	54.00	32.19	Vertical	AV
3147.312	33.73	0.57	34.30	74.00	39.70	Vertical	PK
4823.156	35.78	7.08	42.86	54.00	11.14	Vertical	AV
4823.156	41.86	7.08	48.94	74.00	25.06	Vertical	PK
7027.750	31.08	15.24	46.32	74.00	27.68	Vertical	PK
7449.281	20.39	16.39	36.78	54.00	17.22	Vertical	AV

802.11b				CH06			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1163.031	34.57	-6.22	28.35	74.00	45.65	Horizontal	PK
1186.531	24.66	-5.97	18.69	54.00	35.31	Horizontal	AV
2871.187	29.69	0.93	30.62	74.00	43.38	Horizontal	PK
3001.906	22.29	-0.11	22.18	54.00	31.82	Horizontal	AV
4924.500	40.93	7.34	48.27	74.00	25.73	Horizontal	PK
4924.500	36.39	7.34	43.73	54.00	10.27	Horizontal	AV
7446.343	31.99	16.39	48.38	74.00	25.62	Horizontal	PK
7815.000	20.02	17.28	37.30	54.00	16.70	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1207.093	24.81	-5.81	19.00	54.00	35.00	Vertical	AV
1220.312	34.47	-5.78	28.69	74.00	45.31	Vertical	PK
2242.562	31.90	-2.70	29.20	74.00	44.80	Vertical	PK
2244.031	21.73	-2.69	19.04	54.00	34.96	Vertical	AV
4873.093	42.06	7.15	49.21	74.00	24.79	Vertical	PK
4873.093	35.98	7.15	43.13	54.00	10.87	Vertical	AV
7064.468	30.35	15.34	45.69	74.00	28.31	Vertical	PK
7071.812	20.71	15.36	36.07	54.00	17.93	Vertical	AV

802.11b				CH11			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1198.281	34.44	-5.85	28.59	74.00	45.41	Horizontal	PK
1215.906	24.94	-5.79	19.15	54.00	34.85	Horizontal	AV
2850.625	29.77	1.26	31.03	74.00	42.97	Horizontal	PK
3004.843	21.90	-0.10	21.80	54.00	32.20	Horizontal	AV
4873.093	34.87	7.15	42.02	54.00	11.98	Horizontal	AV
4874.562	40.76	7.15	47.91	74.00	26.09	Horizontal	PK
7950.125	30.70	17.75	48.45	74.00	25.55	Horizontal	PK
8051.468	21.28	18.27	39.55	54.00	14.45	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1210.031	24.82	-5.80	19.02	54.00	34.98	Vertical	AV
1223.250	34.81	-5.77	29.04	74.00	44.96	Vertical	PK
3131.156	33.61	0.48	34.09	74.00	39.91	Vertical	PK
3176.687	23.38	0.72	24.10	54.00	29.90	Vertical	AV
4924.500	41.39	7.34	48.73	74.00	25.27	Vertical	PK
4924.500	36.69	7.34	44.03	54.00	9.97	Vertical	AV
8005.937	21.33	18.20	39.53	54.00	14.47	Vertical	AV
8016.218	31.05	18.21	49.26	74.00	24.74	Vertical	PK

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11g				CH01			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1141.000	24.94	-6.46	18.48	54.00	35.52	Horizontal	AV
1174.781	34.83	-6.10	28.73	74.00	45.27	Horizontal	PK
3160.531	34.13	0.63	34.76	74.00	39.24	Horizontal	PK
3167.875	22.77	0.67	23.44	54.00	30.56	Horizontal	AV
4821.687	27.38	7.08	34.46	54.00	19.54	Horizontal	AV
4826.093	37.32	7.08	44.40	74.00	29.60	Horizontal	PK
7568.250	30.77	16.72	47.49	74.00	26.51	Horizontal	PK
8038.250	21.09	18.25	39.34	54.00	14.66	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1199.750	35.23	-5.83	29.40	74.00	44.60	Vertical	PK
1233.531	25.00	-5.74	19.26	54.00	34.74	Vertical	AV
2821.250	31.01	1.74	32.75	74.00	41.25	Vertical	PK
2841.812	20.61	1.41	22.02	54.00	31.98	Vertical	AV
4823.156	39.26	7.08	46.34	74.00	27.66	Vertical	PK
4826.093	29.27	7.08	36.35	54.00	17.65	Vertical	AV
7436.062	30.72	16.38	47.10	74.00	26.90	Vertical	PK
7713.656	20.05	17.43	37.48	54.00	16.52	Vertical	AV

802.11g				CH06			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1180.656	34.57	-6.04	28.53	74.00	45.47	Horizontal	PK
1218.843	25.13	-5.78	19.35	54.00	34.65	Horizontal	AV
3181.093	23.22	0.74	23.96	54.00	30.04	Horizontal	AV
3198.718	32.68	0.83	33.51	74.00	40.49	Horizontal	PK
4873.093	38.19	7.15	45.34	74.00	28.66	Horizontal	PK
4873.093	28.10	7.15	35.25	54.00	18.75	Horizontal	AV
7368.500	20.56	16.27	36.83	54.00	17.17	Horizontal	AV
7528.593	31.29	16.54	47.83	74.00	26.17	Horizontal	PK
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1248.218	34.24	-5.70	28.54	74.00	45.46	Vertical	PK
1265.843	24.68	-5.66	19.02	54.00	34.98	Vertical	AV
3090.031	33.64	0.28	33.92	74.00	40.08	Vertical	PK
3141.437	23.77	0.54	24.31	54.00	29.69	Vertical	AV
4873.093	40.18	7.15	47.33	74.00	26.67	Vertical	PK
4873.093	28.33	7.15	35.48	54.00	18.52	Vertical	AV
7703.375	30.53	17.44	47.97	74.00	26.03	Vertical	PK
7869.343	20.35	17.30	37.65	54.00	16.35	Vertical	AV

802.11g				CH11			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1196.812	34.31	-5.86	28.45	74.00	45.55	Horizontal	PK
1215.906	24.70	-5.79	18.91	54.00	35.09	Horizontal	AV
3184.031	33.06	0.76	33.82	74.00	40.18	Horizontal	PK
3197.250	22.82	0.83	23.65	54.00	30.35	Horizontal	AV
4920.093	36.91	7.31	44.22	74.00	29.78	Horizontal	PK
4921.562	27.52	7.32	34.84	54.00	19.16	Horizontal	AV
7651.968	30.17	17.17	47.34	74.00	26.66	Horizontal	PK
7997.125	21.52	18.16	39.68	54.00	14.32	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1186.531	25.23	-5.97	19.26	54.00	34.74	Vertical	AV
1190.937	34.71	-5.93	28.78	74.00	45.22	Vertical	PK
3175.218	23.53	0.71	24.24	54.00	29.76	Vertical	AV
3184.031	33.10	0.76	33.86	74.00	40.14	Vertical	PK
4920.093	28.55	7.31	35.86	54.00	18.14	Vertical	AV
4925.968	37.83	7.35	45.18	74.00	28.82	Vertical	PK
7440.468	31.05	16.39	47.44	74.00	26.56	Vertical	PK
8025.031	21.81	18.23	40.04	54.00	13.96	Vertical	AV

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11n(HT20)				CH01			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1190.937	34.45	-5.93	28.52	74.00	45.48	Horizontal	PK
1195.343	24.65	-5.88	18.77	54.00	35.23	Horizontal	AV
3166.406	32.58	0.67	33.25	74.00	40.75	Horizontal	PK
3175.218	22.94	0.71	23.65	54.00	30.35	Horizontal	AV
4823.156	27.47	7.08	34.55	54.00	19.45	Horizontal	AV
4826.093	36.61	7.08	43.69	74.00	30.31	Horizontal	PK
7187.843	29.83	15.92	45.75	74.00	28.25	Horizontal	PK
7531.531	20.49	16.56	37.05	54.00	16.95	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1232.062	24.93	-5.75	19.18	54.00	34.82	Vertical	AV
1265.843	34.89	-5.66	29.23	74.00	44.77	Vertical	PK
3126.750	33.46	0.46	33.92	74.00	40.08	Vertical	PK
3175.218	23.79	0.71	24.50	54.00	29.50	Vertical	AV
4821.687	39.60	7.08	46.68	74.00	27.32	Vertical	PK
4821.687	29.16	7.08	36.24	54.00	17.76	Vertical	AV
7468.375	31.74	16.40	48.14	74.00	25.86	Vertical	PK
7989.781	21.01	18.10	39.11	54.00	14.89	Vertical	AV

802.11n(HT20)				CH06			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1186.531	34.52	-5.97	28.55	74.00	45.45	Horizontal	PK
1193.875	24.60	-5.89	18.71	54.00	35.29	Horizontal	AV
3159.062	23.09	0.63	23.72	54.00	30.28	Horizontal	AV
3162.000	33.03	0.64	33.67	74.00	40.33	Horizontal	PK
4871.625	28.05	7.14	35.19	54.00	18.81	Horizontal	AV
4873.093	36.99	7.15	44.14	74.00	29.86	Horizontal	PK
7374.375	30.76	16.29	47.05	74.00	26.95	Horizontal	PK
7813.531	19.85	17.28	37.13	54.00	16.87	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1141.000	36.10	-6.46	29.64	74.00	44.36	Vertical	PK
1186.531	25.29	-5.97	19.32	54.00	34.68	Vertical	AV
3166.406	23.85	0.67	24.52	54.00	29.48	Vertical	AV
3188.437	33.61	0.78	34.39	74.00	39.61	Vertical	PK
4871.625	39.51	7.14	46.65	74.00	27.35	Vertical	PK
4876.031	28.90	7.15	36.05	54.00	17.95	Vertical	AV
7533.000	30.85	16.56	47.41	74.00	26.59	Vertical	PK
8014.750	21.17	18.21	39.38	54.00	14.62	Vertical	AV

802.11n(HT20)				CH11			
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1146.875	25.24	-6.39	18.85	54.00	35.15	Horizontal	AV
1173.312	35.25	-6.11	29.14	74.00	44.86	Horizontal	PK
3182.562	23.35	0.75	24.10	54.00	29.90	Horizontal	AV
3256.000	33.21	0.17	33.38	74.00	40.62	Horizontal	PK
4925.968	28.21	7.35	35.56	54.00	18.44	Horizontal	AV
4933.312	36.54	7.40	43.94	74.00	30.06	Horizontal	PK
7502.156	31.34	16.42	47.76	74.00	26.24	Horizontal	PK
8027.968	21.58	18.23	39.81	54.00	14.19	Horizontal	AV
Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1188.000	35.55	-5.96	29.59	74.00	44.41	Vertical	PK
1210.031	24.85	-5.80	19.05	54.00	34.95	Vertical	AV
3182.562	23.77	0.75	24.52	54.00	29.48	Vertical	AV
3192.843	35.35	0.80	36.15	74.00	37.85	Vertical	PK
4924.500	38.59	7.34	45.93	74.00	28.07	Vertical	PK
4924.500	29.97	7.34	37.31	54.00	16.69	Vertical	AV
7580.000	30.71	16.78	47.49	74.00	26.51	Vertical	PK
8038.250	21.03	18.25	39.28	54.00	14.72	Vertical	AV

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

6. TEST SETUP PHOTOS

Conducted Emissions (AC Mains)









Radiated Emissions



7. EXTERNAL AND INTERNAL PHOTOS



External Photos












Internal Photos








WiFi Antenna





-----End of Report-----