



EMC TEST REPORT

Report No.: SET2021-01786

Product Name: LTE/WCDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone

Model No. : ZTE Blade A31 Lite

FCC ID: SRQ-ZTEA31LITE

Applicant: ZTE Corporation

Address: ZTE Plaza, Keji Road South, Shenzhen, China

Received Date: 2021.01.21

Tested Date: 2021.01.21-2021.02.03

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No. 43 Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of **20** pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product Name.....: LTE/WCDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone

Model No.: ZTE Blade A31 Lite

Applicant.....: ZTE Corporation

Applicant Address.....: ZTE Plaza, Keji Road South, Shenzhen, China

Manufacturer: ZTE Corporation

Manufacturer Address: ZTE Plaza, Keji Road South, Shenzhen, China

Test Standards.....: 47 CFR Part 15 Subpart B: Radio Frequency Devices

Test Result.....: PASS

Tested by: Zhang Pei Sen
Pei Sen Zhang Test Engineer 2021.02.03

Reviewed by: Chris You
Chris You Senior Engineer 2021.02.03

Approved by: Shuangwen Zhang
Shuangwen Zhang, Manager 2021.02.03



TABLE OF CONTENTS

- 1. GENERAL INFORMATION4**
- 1.1 EUT Description4**
- 1.2 Test Standards and Results6**
- 1.3 Facilities and Accreditations7**
 - 1.3.1 Facilities7
 - 1.3.2 Test Environment Conditions7
 - 1.3.3 Measurement Uncertainty7
- 2. TEST CONDITIONS SETTING8**
- 2.1 Test Peripherals8**
- 2.2 Test Mode8**
- 2.3 Test Setup and Equipments List8**
 - 2.3.1 Conducted Emission8
 - 2.3.2 Radiated Emission9
- 3. 47 CFR PART 15B REQUIREMENTS12**
- 3.1 Conducted Emission12**
 - 3.1.1 Requirement12
 - 3.1.2 Test Description12
 - 3.1.3 Test Result12
- 3.2 Radiated Emission15**
 - 3.2.1 Requirement15
 - 3.2.2 Test Description16
 - 3.2.3 Test Result16

Change History		
Issue	Date	Reason for change
1.0	2021.02.03	First edition



1. GENERAL INFORMATION

1.1 EUT Description

EUT Name : LTE/WCDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone
 Trade Name..... : ZTE
 Brand Name..... : ZTE
 Hardware Version..... : ujuB
 Software Version : GEN_LA_F_A31_Lite_V1.0
 Battery
 Battery Type: Li-Ion
 Model No.: Li3820T43P4h695945
 Manufacturer 1#: Zhaoqing Fenghua Lithium Battery Co.,Ltd.
 Manufacturer 2#: NINGBAO VEKEN BATTERY CO.,LTD
 Ancillary Equipment : AC Adapter
 Model No.: STC-A505D-Z
 I/p: 100-240V ~ 50/60Hz ,250mA
 O/p: 5.0V --- 550mA
 Manufacturer 1#:MADE IN CHINA BY BJD
 Manufacturer 2#:MADE IN CHINA BY PUAN
 Model No.: STC-A51D-A
 I/p: 100-240V ~ 50/60Hz ,250mA
 O/p: 5.0V --- 1000mA
 Manufacturer 3#:MADE IN CHINA BY RUIJING
 Model No.: STC-A505D-A
 I/p: 100-240V ~ 50/60Hz ,250mA
 O/p: 5.0V --- 550mA
 Manufacturer 4#:MADE IN CHINA BY PUAN
 Model No.: S14B081
 I/p: 100-240V ~ 50/60Hz ,200mA
 O/p: 5.0V --- 1000mA
 Manufacturer 5#:MADE IN CHINA BY RUIJING
 Headset..... : Model No.: DEM-8A/JWEP1091-Z01
 Manufacturer 1#: Shen zhen FDC Electronic Co.,Ltd.
 Manufacturer 2#: JUWEI ELECTRONICS CO.,LTD
 Model No.: DEM-66/ JWEP1036-Z01R
 Manufacturer 3#: Shen zhen FDC Electronic Co.,Ltd.
 Manufacturer 4#: JUWEI ELECTRONICS CO.,LTD



Data line : Model No.: USB-MU5-B-70-M-L
Manufacturer 1#: Dongguan Guojun Plastic Electronic Co.,Ltd
Manufacturer 2#: Shen Zhen Shi Yi HUA XING Electron Co.,Ltd
Model No.: USB-MU5-W-70-M-L
Manufacturer 3#: Dongguan Guojun Plastic Electronic Co.,Ltd
Manufacturer 4#: Shen Zhen Shi Yi HUA XING Electron Co.,Ltd

*Note 1:*The EUT is a LTE/WCDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone;
*Note 2:*All adapter has been tested, only the worst AC Adapter1 was recorded in this report.
*Note 3:*For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B 2017	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE:

(1) The EUT has been tested according to 47 CFR Part 15 Subpart B, Class B. The test procedure is according to ANSI C63.4:2014.



1.3 Facilities and Accreditations

1.3.1 Facilities

FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until June 30th, 2021.

ISED Registration: 11185A-1

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until June 30th, 2021

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 °C - 35 °C
Relative Humidity (%):	25% -75%
Atmospheric Pressure (kPa):	86kPa-106kPa

1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	Uc = 3.6 dB (k=2)
Uncertainty of Radiated Emission:	Uc = 4.5 dB (k=2)



2. TEST CONDITIONS SETTING

2.1 Test Peripherals

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Support Equipment:

Description	Brand name	Model	Serial No.	FCCID
Notebook	ThinkPad	E430C	A131101550	N/A
Mouse	Logitech	M100r	25011051	DOC

Support Cable:

Description	Shield Type	Ferrite Core	Length
USB Cable	shielding	Yes	1.2m
RJ45 Cable	shielding	No	2m
PC Power adapter Cable	Un- shielding	No	1.2m
Mouse Cable	Un- shielding	No	1m

2.2 Test Mode

The EUT have the following typical setups during the test:


Setup1: EUT (Data Link)+ Notebook PC

Setup2: EUT+ AC Adapter

2.3 Test Setup and Equipments List

2.3.1 Conducted Emission

A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu\text{H}$ of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.


B. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
Test Receiver	KEYSIGHT	ESR3	A181103297	2020.07.14	2021.07.14
LISN	ROHDE&SCHWARZ	ENV216	A140701847	2020.11.20	2021.09.21
Cable	MATCHING PAD	W7	/	2021.01.02	2022.01.01


2.3.2 Radiated Emission

A. Test Setup:

- 1) For radiated emissions from 30MHz to 1GHz



2) For radiated emissions above 1GHz



B. Test Procedure

The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a



variable-height antenna master tower.

For the test Antenna:

- 1) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

C. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
EMI Test Receiver	ROHDE&SCHWARZ	ESR3	A181103297	2020.07.14	2021.07.14
LISN	ROHDE&SCHWARZ	ENV216	A140701847	2020.11.20	2021.09.21
Shield Room	/	L7300*W4500 *H3100	A181003226	2018.09.06	2021.09.05
EMI Test Receiver	ROHDE&SCHWARZ	ESIB7	A0501375	2020.06.24	2021.06.23
Broadband Ant.	2786	ETC	A150402239	2018.09.17	2021.09.16
3M Anechoic Chamber	Albatross	SAC-3MAC 9*6*6m	A0412375	2019.03.26	2023.03.25
EMI Test Receiver	ROHDE&SCHWARZ	ESIB26	A180502935	2020.09.23	2021.08.12
System Simulator	ROHDE&SCHWARZ	CMW500	A150802214	2019.07.30	2021.07.29
5M Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4m	A0304210	2019.03.25	2023.03.24
EMI Horn Ant.	ROHDE&SCHWARZ	HF906	A0304225	2019.04.17	2022.04.17



3. 47 CFR PART 15B REQUIREMENTS

3.1 Conducted Emission

3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2 Test Description


See section 2.3.1 of this report.

3.1.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

Note:


Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a Nominal 120V AC,50/60Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Test voltage and frequency
A. Mains terminal disturbance voltage, L phase


(Plot A: L Phase)

Conducted Disturbance at Mains Terminals							
L Test Data							
QP				AV			
Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)	Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)
0.204000	63.4	52.33	11.07	0.204000	53.4	41.24	12.16
0.271500	61.1	51.07	10.03	0.271500	51.1	39.99	11.11
1.846500	56.0	44.27	11.73	1.846500	46.0	38.53	7.47
2.184000	56.0	44.77	11.23	2.184000	46.0	37.20	8.80
3.349500	56.0	46.63	9.37	3.349500	46.0	37.38	8.62
3.759000	56.0	45.61	10.39	3.759000	46.0	38.15	7.85

B. Mains terminal disturbance voltage, N phase



(Plot B: N Phase)

Conducted Disturbance at Mains Terminals							
N Test Data							
QP				AV			
Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)	Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)
0.204000	63.4	56.82	6.58	0.204000	53.4	44.76	8.64
0.276000	60.9	55.57	5.33	0.276000	50.9	43.51	7.39
0.343500	59.1	45.02	14.08	0.343500	49.1	33.95	15.15
2.193000	56.0	41.48	14.52	2.193000	46.0	32.85	13.15
2.467500	56.0	40.64	15.36	2.467500	46.0	31.23	14.77
2.688000	60.0	38.25	21.75	2.688000	46.0	27.49	18.51

3.2 Radiated Emission

3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength		Field Strength Limitation at 3m Measurement Dist	
	$\mu\text{V/m}$	Dist	($\mu\text{V/m}$)	(dBuV/m)
0.009 - 0.490	$2400/F(\text{kHz})$	300m	$10000 * 2400/F(\text{kHz})$	$20\log 2400/F(\text{kHz}) + 80$
0.490 - 1.705	$2400/F(\text{kHz})$	30m	$100 * 2400/F(\text{kHz})$	$20\log 2400/F(\text{kHz}) + 40$
1.705 - 30.00	30	30m	$100 * 30$	$20\log 30 + 40$
30.0 - 88.0	100	3m	100	$20\log 100$
88.0 - 216.0	150	3m	150	$20\log 150$
216.0 - 960.0	200	3m	200	$20\log 200$
Above 960.0	500	3m	500	$20\log 500$

- a) As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.
- b) Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.
- c) For below 1G :QP detector RBW 120kHz ,VBW 300kHz.
- d) For Above 1G: PK detector RBW 1MHz,VBW 3MHz for PK value ;AV detector RBW 1MHz, VBW 10Hz for AV value.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dBuV/m is calculated by $20\log$ Emission Level($\mu\text{V/m}$).
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of $Ld1 = Ld2 * (d2/d1)^2$.

Example:

F.S Limit at 30m distance is $30\mu\text{V/m}$, then F.S Limitation at 3m distance is adjusted as

$$Ld1 = L1 = 30\mu\text{V/m} * (10)^2 = 100 * 30\mu\text{V/m}.$$



3.2.2 Test Description

See section 2.3.2 of this report.

3.2.3 Test Result


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.



A.Radiation disturbances, antenna polarization:Vertical




(Plot C: Test Antenna Vertical 30M - 1G)

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBµV/m)	Margin (dB)	Antenna	Verdict
30.00	35.24	120.000	116	40.0	4.76	Vertical	Pass
31.92	31.69	120.000	208	40.0	8.31	Vertical	Pass
45.52	24.68	120.000	162	40.0	15.32	Vertical	Pass
105.60	24.61	120.000	280	43.5	18.89	Vertical	Pass
159.96	23.25	120.000	180	43.5	20.25	Vertical	Pass
243.40	26.45	120.000	185	46.0	19.55	Vertical	Pass



B.Radiation disturbances, antenna polarization: Horizontal




(Plot D: Test Antenna Horizontal 30M - 1G)

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBµV/m)	Margin (dB)	Antenna	Verdict
30.00	34.49	120.000	154	40.00	5.51	Horizontal	Pass
33.88	27.48	120.000	129	40.00	12.52	Horizontal	Pass
107.78	22.42	120.000	137	43.50	21.08	Horizontal	Pass
243.25	29.34	120.000	131	46.00	16.66	Horizontal	Pass
685.72	36.12	120.000	114	46.00	9.88	Horizontal	Pass
730.34	36.21	120.000	195	46.00	9.79	Horizontal	Pass

Test Result: PASS


A.Radiation disturbances, antenna polarization: Horizontal



(Plot E: Test Antenna Horizontal 1G – 18G)

NO.	Freq. [MHz]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Trace	Height [cm]	Angle [°]	Polarity
1	1499.90	35.10	74.00	38.90	PK	100	220	Horizontal
2	1533.90	27.58	54.00	26.42	AV	100	90	Horizontal
3	2900.98	36.01	54.00	17.99	AV	100	30	Horizontal
4	2900.98	42.90	74.00	31.10	PK	100	30	Horizontal
5	3978.99	38.29	54.00	15.71	AV	100	300	Horizontal
6	4081.01	45.42	74.00	28.58	PK	100	260	Horizontal

B.Radiation disturbances, antenna polarization: Vertical



(Plot F: Test Antenna Vertical 1G – 18G)

NO.	Freq. [MHz]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Trace	Height [cm]	Angle [°]	Polarity
1	1720.94	28.61	54.00	25.39	AV	100	40	Vertical
2	1778.75	36.47	74.00	37.53	PK	100	90	Vertical
3	3411.08	36.21	54.00	17.79	AV	100	80	Vertical
4	3417.88	43.47	74.00	30.53	PK	100	40	Vertical
5	4295.25	38.70	54.00	15.30	AV	100	60	Vertical
6	4366.67	44.96	74.00	29.04	PK	100	110	Vertical

-----End of Report-----