

## 7. Measurement Data (continued)

### 7.12. Public Exposure to Radio Frequency Energy Levels ((1.1307 (b)(1)) RSS-GEN, ISSUE 5, RSS-102 continued)

#### 7.12.2. RSS-102 Issue 5 Requirements

Requirement: Requirement: RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} \times f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz.

Results: Compliant

Frequency	Separation Distance	Maximum Power <sup>1</sup>		RSS-102 Exemption Limit <sup>2</sup>	Result
(MHz)	(cm)	(mW)	(Watts)	(Watts)	
2402	≥ 20	24.55	0.025	2.68	Compliant
2440	≥ 20	23.66	0.024	2.71	Compliant
2480	≥ 20	23.50	0.023	2.74	Compliant

<sup>1</sup> Reference Section 6.2 of this report.

<sup>2</sup> Reference RSS-102, § 2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation for distances greater than 20 cm.

The following formula was used to determine the exemption limit (W):

$$1.31 \times 10^{-2} \times f^{0.6834} \quad (f = \text{frequency (MHz)})$$