

RF EXPOSURE EVALUATION

EUT Specification

EUT	Nanoleaf BLE&Thread-Matter module
Model Number	HM-BT4531
FCC ID	2ASEO-HM-BT4531
Antenna gain (Max)	0.5dBi
Operation Frequency	2402-2480MHz
Input Rating	DC 1.8V-3.6V
Max. output power	BLE: 8.15dBm(0.0065W)

Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

$$11.1 \text{ Friis transmission formula: } P_d = (P_{out} * G) / (4 * \pi * R^2)$$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm^2 . If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.


11.2 Measurement Result

Antenna gain: 0.5 dBi

BLE:

Mode	Channe l Freq. (MHz)	Measu red power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeri c)	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
GFSK	2402	7.90	8±1	9	1.122	0.001773	1
GFSK	2440	7.99	8±1	9	1.122	0.001773	1
GFSK	2480	8.15	8±1	9	1.122	0.001773	1
$\pi/4$ -DQPSK	2402	7.65	8±1	9	1.122	0.001773	1
$\pi/4$ -DQPSK	2440	7.66	8±1	9	1.122	0.001773	1
$\pi/4$ -DQPSK	2480	7.68	8±1	9	1.122	0.001773	1

Signature:



Tiger Xu

Date: 2023-05-26