



RF Exposure Evaluation Declaration

FCC ID: PIDAV2700
Applicant: Airspan Networks Inc

Application Type: Certification
Product: AirVelocity2700, 3.55-3.7GHz (n48),FM,PoE/DC
Model No.: AV27-N48-P4CXP-FM-C
Brand Name: Airspan
Test Procedure(s): FCC part 2.1091

Reviewed By:

Sunny Sun

Approved By:

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2106RSU047-U3	Rev. 01	Initial Report	10-18-2021	Valid

CONTENTS

Description	Page
1. General Information	4
1.1. Applicant	4
1.2. Manufacturer	4
1.3. Testing Facility	4
1.4. Product Information	5
1.5. Description of Available Antennas	5
2. RF Exposure Evaluation	6
2.1. Limit of Maximum Permissible Exposure	6
2.2. Calculated Results	7
Appendix A - EUT Photograph	8

1.4. Product Information

Product Name	AirVelocity2700, 3.55-3.7GHz (n48),FM,PoE/DC
Model No.	AV27-N48-P4CXP-FM-C
Operating Band (s)	5G NR n48 Band
CBSD Category	Category A CBSD
Frequency Range	3550 ~ 3700 MHz
Modulation Type	QPSK, 16QAM, 64QAM, 256QAM
Max EIRP Density	2Tx Mode: 26.56 dBm/10MHz; 4Tx Mode: 23.51 dBm/10MHz
Antenna Information	Refer to section 1.5

1.5. Description of Available Antennas

Band Support	Antenna Type	Manufacturer	Antenna Gain
n48	Omni Internal	Galtronics	5.00 dBi
<p>Remark:</p> <ol style="list-style-type: none"> 1. This device can operate with 2Tx and 4Tx mode. 2. This device operate with Multiple Antennas Using Multiple-input, Multiple-output (MIMO) Technology for Uncorrelated Transmission. 3. The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer. 			

2. RF Exposure Evaluation

2.1. Limit of Maximum Permissible Exposure

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Calculated Results

Product	AirVelocity2700, 3.55-3.7GHz (n48),FM,PoE/DC
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Maximum EIRP (dBm)	Tune-up Factor	Pd (mW/cm ²)	Limit (mW/cm ²)	Compliance Distance (cm)
n48	3550 ~ 3700	28	2	0.1989	1	20

CONCLUSION:

The Compliance Distance is 20cm for AirVelocity2700, 3.55-3.7GHz (n48),FM,PoE/DC installed without any other radio equipment.

_____ The End _____

Appendix A - EUT Photograph

Refer to "2106RSU047-UE" file.