



KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdksign.cn Website: www.gdksign.com

RF Exposure Evaluation

FCC ID: 2AHYV-GMOUSE

Applicable Standard

According to FCC part 2.1093 and part 1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

KDB447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.2 1-mW Test Exemption:

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

TEST RESULT

☒ **Passed**

☐ **Not Applicable**

BT

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Maximum Output Power (mW)	Exemption Limit (mW)
BDR	2402-2480	-1.35	-0.35	0.92	1.00

BLE

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Maximum Output Power (mW)	Exemption Limit (mW)
BLE 1M	2402-2480	-1.14	-0.14	0.97	1.00

Note:

-The BLE and BT can not be transmit simultaneously.

Result: Compliant

--THE END--