



Report No.: SZEM190101051702

Page: 1 of 7

## RF Exposure Evaluation Report

**Application No.:** SZEM1901010517CR  
**Applicant:** Sunwave Communications Co., Ltd.  
**Manufacturer:** Sunwave Communications Co., Ltd.  
**Factory:** Sunwave Communications Co., Ltd.  
**Product Name:** Remote Unit  
**Product Description:** The RU conducts digital-analog conversion and power amplification of the input signals.  
**Model No.(EUT):** iDAS-R211  
**Trade Mark:** CROSSFIRE,SUNWAVE  
**FCC ID:** 2AEJ4R2112626  
**Standards:** 47 CFR Part 1.1307 (2018)  
47 CFR Part 1.1310 (2018)  
**Date of Receipt:** 2019-01-03  
**Date of Test:** 2019-01-03 to 2019-01-18  
**Date of Issue:** 2019-01-25

|                      |              |
|----------------------|--------------|
| <b>Test Result :</b> | <b>PASS*</b> |
|----------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu  
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8397 1443, or email: CN.Doccheck@sgs.com**

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012033 f (86-755) 26710694 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012033 f (86-755) 26710694 sgs.china@sgs.com




**SGS-CSTC Standards Technical Services Co., Ltd.**  
**Shenzhen Branch**

Report No.: SZEM190101051702

Page: 2 of 7

## 2 Version

| Revision Record |         |            |          |          |
|-----------------|---------|------------|----------|----------|
| Version         | Chapter | Date       | Modifier | Remark   |
| 01              |         | 2019-01-25 |          | Original |
|                 |         |            |          |          |
|                 |         |            |          |          |

|                          |  |                                                                                      |  |            |
|--------------------------|--|--------------------------------------------------------------------------------------|--|------------|
| Authorized for issue by: |  |                                                                                      |  |            |
| Tested By                |  |   |  | 2019-01-25 |
|                          |  |                                                                                      |  | Date       |
| Checked By               |  |  |  | 2019-01-25 |
|                          |  |                                                                                      |  | Date       |
|                          |  | Edison Li /Project Engineer                                                          |  |            |
|                          |  | Eric Fu /Reviewer                                                                    |  |            |



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (Testing Center) EEC Laboratory.

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)



### 3 Contents

|                                                       | Page |
|-------------------------------------------------------|------|
| 1 COVER PAGE.....                                     | 1    |
| 2 VERSION .....                                       | 2    |
| 3 CONTENTS .....                                      | 3    |
| 4 GENERAL INFORMATION.....                            | 4    |
| 4.1 CLIENT INFORMATION.....                           | 4    |
| 4.2 GENERAL DESCRIPTION OF EUT .....                  | 4    |
| 4.3 TEST LOCATION .....                               | 4    |
| 4.4 TEST FACILITY .....                               | 5    |
| 4.5 DEVIATION FROM STANDARDS.....                     | 5    |
| 4.6 ABNORMALITIES FROM STANDARD CONDITIONS .....      | 5    |
| 4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER ..... | 5    |
| 5 RF EXPOSURE EVALUATION .....                        | 6    |
| 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....          | 6    |
| 5.1.1 Limits .....                                    | 6    |
| 5.1.2 Test Procedure.....                             | 6    |
| 4.1.3 EUT RF EXPOSURE EVALUATION.....                 | 7    |



## 4 General Information

### 4.1 Client Information

|                          |                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------|
| Applicant:               | Sunwave Communications Co., Ltd.                                                      |
| Address of Applicant:    | Sunwave Building 581 Huoju Avenue, Binjiang District, Hangzhou, P.R.China Zip: 310053 |
| Manufacturer:            | Sunwave Communications Co., Ltd.                                                      |
| Address of Manufacturer: | Sunwave Building 581 Huoju Avenue, Binjiang District, Hangzhou, P.R.China Zip: 310053 |
| Factory:                 | Sunwave Communications Co., Ltd.                                                      |
| Address of Factory:      | Sunwave Building 581 Huoju Avenue, Binjiang District, Hangzhou, P.R.China Zip: 310053 |

### 4.2 General Description of EUT

|                     |                                                                     |
|---------------------|---------------------------------------------------------------------|
| Product Name:       | Remote Unit                                                         |
| Model No.:          | iDAS-R211                                                           |
| Trade Mark:         | CROSSFIRE,SUNWAVE                                                   |
| Sample Type:        | Fixed production                                                    |
| Power Supply:       | AC120V 60Hz                                                         |
| Optical Fiber:      | 200cm (unshielded)                                                  |
| AC Cable:           | 200cm (unshielded)                                                  |
| Type of Modulation: | LTE , WCDMA, CDMA                                                   |
| Frequency Band:     | Downlink 862MHz to 894MHz include the Modulation: LTE , WCDMA, CDMA |

### 4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

## 4.5 Deviation from Standards

None.

## 4.6 Abnormalities from Standard Conditions

None.

## 4.7 Other Information Requested by the Customer

None.





## 5 RF Exposure Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz)                                          | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|----------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(A) Limits for Occupational/Controlled Exposures</b>        |                               |                               |                                     |                          |
| 0.3–3.0 .....                                                  | 614                           | 1.63                          | * (100)                             | 6                        |
| 3.0–30 .....                                                   | 1842/f                        | 4.89/f                        | * (900/f <sup>2</sup> )             | 6                        |
| 30–300 .....                                                   | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300–1500 .....                                                 | .....                         | .....                         | f/300                               | 6                        |
| 1500–100,000 .....                                             | .....                         | .....                         | 5                                   | 6                        |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3–1.34 .....                                                 | 614                           | 1.63                          | * (100)                             | 30                       |
| 1.34–30 .....                                                  | 824/f                         | 2.19/f                        | * (180/f <sup>2</sup> )             | 30                       |
| 30–300 .....                                                   | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1500 .....                                                 | .....                         | .....                         | f/1500                              | 30                       |
| 1500–100,000 .....                                             | .....                         | .....                         | 1.0                                 | 30                       |

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

According to FCC Part22.913: the ERP of base stations and repeaters must not exceed 500 watts per emission

According to FCC Part27.50(c): the ERP of base stations and repeaters must not exceed 1000 watts per emission

According to FCC Part27.50(h): the ERP of base stations and repeaters must not exceed 1004 watts per emission

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

#### 4.1.3 EUT RF Exposure Evaluation

##### 1) exposure conditions for standalone operations for Band 26

Output Power Into Antenna & RF Exposure Evaluation Antenna Gain:

| Operating frequency range: 862~894MHz |                         |                        |                                     |                                     |                                |                            |
|---------------------------------------|-------------------------|------------------------|-------------------------------------|-------------------------------------|--------------------------------|----------------------------|
| Frequency (MHz)                       | Peak Output Power (dBm) | Peak Output Power (mW) | Minimum Distance to Human body (cm) | Power density (mW/cm <sup>2</sup> ) | Maximun Antenna Gain (Numeric) | Maximun Antenna Gain (dBi) |
| 862                                   | 47                      | 50118.72               | 200                                 | 2.87                                | 28.78                          | 14.59                      |
| 878                                   | 47                      | 50118.72               | 200                                 | 2.93                                | 29.39                          | 14.68                      |
| 894                                   | 47                      | 50118.72               | 200                                 | 2.98                                | 29.89                          | 14.75                      |

| Operating frequency range: 862~894MHz |                        |                     |                       |                                |                            |
|---------------------------------------|------------------------|---------------------|-----------------------|--------------------------------|----------------------------|
| Peak Output Power (dBm)               | Peak Output Power (mW) | ERP Power Limit (W) | ERP Power Limit (dBm) | Maximun Antenna Gain (Numeric) | Maximun Antenna Gain (dBi) |
| 47                                    | 50118.72               | 500                 | 56.99                 | 65.16                          | 18.14                      |

Conclusion:

When used at a distance of 2m, the antenna gain should not exceed 14.59dBi.

- End of the Report -

