

Notes:

- 1) Material : Black Text on White Polyester or equivalent with Permanent adhesive
- 2) All dimensions are in mm
- 3) The serial number will be of the Format
DDDY-XXXXXX-NNNN where:
DDD = the Julian date of the day manufacture. Example January 1 is 001,
Feb 1 is 032, December 31 = 365. Tolerance = +/- 3 days
Y= the significant digit of the Year of manufacture. Example 2010 = 0, 2011=1, 2017=7.
XXXXXX= the exact Model Number of the Product. (MG7540)
= a sequential number from 0001
to 9999 that indicates the number of the unit produced of that type, on that day.
- 4) Printing and material must meet UL Rub Test requirements
- 5) Sheet 2 of 2 is artwork in EPS format, for all static elements.
- 6) SSID to be MOTOSSSS where SSSS is the last 4 digits of the CM MAC.
- 7) Wireless Security Key/Password "nnnnnnnnnn" is 10 random numbers and lower case letters excluding b,g,i,j,l,o,q
- 8) All barcodes are code 128 and minimum height is 4 mm
- 9) Label Size is 148 mm x 55 mm, three 1mm radiused corners and one wedge-cut corner as shown
- 10) FFFF is to be 4-letter Factory ID for the product as specified by Bureau Veritas



