

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5800TM-1**

Date : 2/9/2005

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5800TM-1

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	81.10	1.3	14.78	72277.0	10.0%	7227.7	7292
690	H	44.00	1.7	19.10	1737.8	10.0%	173.8	729
1035	H	43.00	2.3	22.70	2511.9	10.0%	251.2	500
1380	H	36.00	3.0	25.10	1603.2	10.0%	160.3	500
1725	H	44.00	3.3	27.55	5527.1	10.0%	552.7	729
2070	H	41.00	3.8	29.42	5140.4	10.0%	514.0	729
2415	H	37.00	4.1	31.85	4441.2	10.0%	444.1	729
2760	H	38.00	4.1	32.20	5188.0	10.0%	518.8	729
3105	H	36.00	5.7	31.75	4704.4	10.0%	470.4	729
3450	H	36.00	6.2	32.28	5296.6	10.0%	529.7	729
4000			CABLE "A"	BICONILOG				