

RF Exposure Evaluation

MPE Calculations

in co-locating with a Bluetooth transmitter

Systems operating under the provision of 47 CFR 1.1307(b)(1) shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b). The MPE calculation for this exposure is shown below.

Using the Antennas with highest output power:

The applying modular device (FCC ID: PD9LEN3945ABG) has a capability to co-locate with the following Bluetooth transmitter.

The peak radiated output power (EIRP) is calculated as follows:

<i>Antenna</i>	<i>Frequency (GHz)</i>	<i>Power input to the antenna (P) (dBm)</i>	<i>Power gain of the antenna (G) (dBi)</i>	<i>EIRP (P+G) (dBm)</i>	<i>EIRP $\text{Log}^{-1}(\text{dBm}/10)$ (mW)</i>
WNC (3945ABG WLAN)	2.4	24.81	1.40	26.21	417.83
WNC (3945ABG WLAN)	5	19.71	2.73	22.44	175.39
<u>Co-located transmitter</u>					
HON HAI Precision Ind. Co., Ltd. BT	2.4	4.90	2.00	6.90	4.90

*Power input and gain of the Bluetooth antenna is based on approved BT module (FCC ID: MCLJ07H081) previous filing with the FCC.

$$\text{EIRP} = P + G$$

Where

P = Power input to the antenna (mW).

G = Power gain of the antenna (dBi)

The numeric gain (G) of the antenna with a gain specified in dB is determined by:

<i>Antenna</i>	<i>Frequency (GHz)</i>	<i>Antenna Gain (G) (dBi)</i>	<i>Numeric Antenna Gain $\text{Log}^{-1}(\text{dBm}/10)$ (dB)</i>
WNC (3945ABG WLAN)	2.4	1.40	1.38
WNC (3945ABG WLAN)	5	2.73	1.87
<u>Co-located transmitter</u>			
HON HAI Precision Ind. Co., Ltd. BT	2.4	2.00	1.58

$$G = \text{Log}^{-1} (\text{dB antenna gain}/10)$$

Power density at the specific separation:

<i>Antenna</i>	<i>Frequency (GHz)</i>	<i>Power input to the antenna (P) (mW)</i>	<i>Numeric Power Gain of the Antenna (G) (dB)</i>	<i>Maximum Power Spectral Density $S=PG/(4R^2\pi)$ (mW/cm²)</i>	<i>Maximum Power Spectral Density Limit (mW/cm²)</i>
WNC (3945ABG WLAN)	2.4	302.69	1.38	0.083	1.00
WNC (3945ABG WLAN)	5	93.54	1.87	0.035	1.00
<u>Co-located transmitter</u>					
HON HAI Precision Ind. Co., Ltd. BT	2.4	3.09	1.58	0.001	1.00

$$S = PG/(4R^2\pi)$$

Where

S = Maximum power density (mW/cm²)

P = Power input to the antenna (mW).

G = Numeric power gain of the antenna

R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)

The maximum permissible exposure (MPE) for the general population is 1mW/cm².

The power density at 20cm does not exceed the 1mW/cm² limit. Therefore, the exposure condition is compliant with FCC rules.