



A8. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT

Note: (1) Spurious emissions which are attenuated by more than 20dB below the permissible value for frequency below 1000MHz.

(2) Above 3.5GHz amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value

(3) Test is divided into three directions, X/Y/Z. X pattern for the worst.

GSM 850: (30-9000)MHz							
The Worst Test Results Channel 128/824.2 MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1648.12	-40.46	9.40	4.75	-35.81	-13.00	-22.81	H
2472.23	-39.56	10.60	8.39	-37.35	-13.00	-24.35	H
3296.79	-31.08	12.00	11.79	-30.87	-13.00	-17.87	H
1648.07	-44.54	9.40	4.75	-39.89	-13.00	-26.89	V
2472.61	-44.18	10.60	8.39	-41.97	-13.00	-28.97	V
3296.70	-43.06	12.00	11.79	-42.85	-13.00	-29.85	V
The Worst Test Results Channel 190/836.6 MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1673.14	-40.33	9.50	4.76	-35.59	-13.00	-22.59	H
2509.65	-39.50	10.70	8.40	-37.20	-13.00	-24.20	H
3345.95	-31.33	12.20	11.80	-30.93	-13.00	-17.93	H
1673.11	-44.29	9.40	4.75	-39.64	-13.00	-26.64	V
2509.53	-43.98	10.60	8.39	-41.77	-13.00	-28.77	V
3346.16	-42.51	12.20	11.82	-42.13	-13.00	-29.13	V
The Worst Test Results Channel 251/848.8 MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1697.31	-40.64	9.60	4.77	-35.81	-13.00	-22.81	H
2546.35	-40.47	10.80	8.50	-38.17	-13.00	-25.17	H
3395.17	-31.88	12.50	11.90	-31.28	-13.00	-18.28	H
1697.32	-44.22	9.60	4.77	-39.39	-13.00	-26.39	V
2546.07	-45.27	10.80	8.50	-42.97	-13.00	-29.97	V
3395.09	-43.26	12.50	11.90	-42.66	-13.00	-29.66	V



GPRS 850: (30-9000)MHz							
The Worst Test Results Channel 128/824.2 MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1648.41	-41.42	9.40	4.75	-36.77	-13.00	-23.77	H
2472.37	-39.31	10.60	8.39	-37.10	-13.00	-24.10	H
3296.46	-31.03	12.00	11.79	-30.82	-13.00	-17.82	H
1648.34	-43.49	9.40	4.75	-38.84	-13.00	-25.84	V
2472.49	-44.34	10.60	8.39	-42.13	-13.00	-29.13	V
3296.53	-42.97	12.00	11.79	-42.76	-13.00	-29.76	V
The Worst Test Results Channel 190/836.6 MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.89	-40.98	9.50	4.76	-36.24	-13.00	-23.24	H
2509.78	-39.77	10.70	8.40	-37.47	-13.00	-24.47	H
3346.05	-31.95	12.20	11.80	-31.55	-13.00	-18.55	H
1673.05	-43.40	9.40	4.75	-38.75	-13.00	-25.75	V
2509.84	-44.50	10.60	8.39	-42.29	-13.00	-29.29	V
3346.44	-43.41	12.20	11.82	-43.03	-13.00	-30.03	V
The Worst Test Results Channel 251/848.8 MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1697.28	-41.41	9.60	4.77	-36.58	-13.00	-23.58	H
2546.46	-39.70	10.80	8.50	-37.40	-13.00	-24.40	H
3394.86	-31.67	12.50	11.90	-31.07	-13.00	-18.07	H
1697.21	-43.46	9.60	4.77	-38.63	-13.00	-25.63	V
2546.12	-44.47	10.80	8.50	-42.17	-13.00	-29.17	V
3395.23	-42.73	12.50	11.90	-42.13	-13.00	-29.13	V



EGPRS 850: (30-9000)MHz							
The Worst Test Results Channel 128/824.2 MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1648.18	-40.49	9.40	4.75	-35.84	-13.00	-22.84	H
2472.62	-40.57	10.60	8.39	-38.36	-13.00	-25.36	H
3296.68	-32.02	12.00	11.79	-31.81	-13.00	-18.81	H
1648.18	-44.19	9.40	4.75	-39.54	-13.00	-26.54	V
2472.23	-43.98	10.60	8.39	-41.77	-13.00	-28.77	V
3296.89	-42.89	12.00	11.79	-42.68	-13.00	-29.68	V
The Worst Test Results Channel 190/836.6 MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1673.26	-40.53	9.50	4.76	-35.79	-13.00	-22.79	H
2509.82	-40.15	10.70	8.40	-37.85	-13.00	-24.85	H
3346.05	-31.41	12.20	11.80	-31.01	-13.00	-18.01	H
1673.18	-43.78	9.40	4.75	-39.13	-13.00	-26.13	V
2509.65	-43.95	10.60	8.39	-41.74	-13.00	-28.74	V
3346.39	-42.58	12.20	11.82	-42.20	-13.00	-29.20	V
The Worst Test Results Channel 251/848.8 MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1697.32	-40.37	9.60	4.77	-35.54	-13.00	-22.54	H
2546.42	-40.47	10.80	8.50	-38.17	-13.00	-25.17	H
3395.03	-32.17	12.50	11.90	-31.57	-13.00	-18.57	H
1697.47	-43.29	9.60	4.77	-38.46	-13.00	-25.46	V
2546.53	-44.04	10.80	8.50	-41.74	-13.00	-28.74	V
3394.94	-43.28	12.50	11.90	-42.68	-13.00	-29.68	V



DCS 1900: (30-20000)MHz							
The Worst Test Results for Channel 512/1850.2MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3700.37	-33.88	12.60	12.93	-34.21	-13.00	-21.21	H
5550.40	-34.96	13.10	17.11	-38.97	-13.00	-25.97	H
7400.69	-33.13	11.50	22.20	-43.83	-13.00	-30.83	H
3700.25	-34.60	12.60	12.93	-34.93	-13.00	-21.93	V
5550.39	-35.12	13.10	17.11	-39.13	-13.00	-26.13	V
7400.66	-32.36	11.50	22.20	-43.06	-13.00	-30.06	V
The Worst Test Results for Channel 661/1880.0MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3759.93	-34.48	12.60	12.93	-34.81	-13.00	-21.81	H
5640.05	-35.10	13.10	17.11	-39.11	-13.00	-26.11	H
7520.23	-32.46	11.50	22.20	-43.16	-13.00	-30.16	H
3760.09	-34.66	12.60	12.93	-34.99	-13.00	-21.99	V
5639.94	-34.28	13.10	17.11	-38.29	-13.00	-25.29	V
7520.21	-32.81	11.50	22.20	-43.51	-13.00	-30.51	V
The Worst Test Results for Channel 810/1909.8MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3819.45	-33.54	12.60	12.93	-33.87	-13.00	-20.87	H
5729.43	-34.27	13.10	17.11	-38.28	-13.00	-25.28	H
7639.19	-33.25	11.50	22.20	-43.95	-13.00	-30.95	H
3819.63	-35.40	12.60	12.93	-35.73	-13.00	-22.73	V
5729.28	-34.44	13.10	17.11	-38.45	-13.00	-25.45	V
7639.13	-32.68	11.50	22.20	-43.38	-13.00	-30.38	V



GPRS1900: (30-20000)MHz							
The Worst Test Results for Channel 512/1850.2MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3700.26	-34.41	12.60	12.93	-34.74	-13.00	-21.74	H
5550.26	-35.41	13.10	17.11	-39.42	-13.00	-26.42	H
7400.65	-33.60	11.50	22.20	-44.30	-13.00	-31.30	H
3700.15	-35.05	12.60	12.93	-35.38	-13.00	-22.38	V
5550.64	-33.97	13.10	17.11	-37.98	-13.00	-24.98	V
7400.79	-32.00	11.50	22.20	-42.70	-13.00	-29.70	V
The Worst Test Results for Channel 661/1880.0MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3759.81	-34.19	12.60	12.93	-34.52	-13.00	-21.52	H
5640.19	-35.31	13.10	17.11	-39.32	-13.00	-26.32	H
7520.17	-32.99	11.50	22.20	-43.69	-13.00	-30.69	H
3760.29	-35.58	12.60	12.93	-35.91	-13.00	-22.91	V
5639.85	-34.49	13.10	17.11	-38.50	-13.00	-25.50	V
7519.82	-32.29	11.50	22.20	-42.99	-13.00	-29.99	V
The Worst Test Results for Channel 810/1909.8MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3819.24	-33.84	12.60	12.93	-34.17	-13.00	-21.17	H
5729.24	-34.64	13.10	17.11	-38.65	-13.00	-25.65	H
7638.88	-33.27	11.50	22.20	-43.97	-13.00	-30.97	H
3819.37	-34.93	12.60	12.93	-35.26	-13.00	-22.26	V
5729.27	-35.16	13.10	17.11	-39.17	-13.00	-26.17	V
7638.98	-33.06	11.50	22.20	-43.76	-13.00	-30.76	V



EGPRS 1900: (30-20000)MHz							
The Worst Test Results for Channel 512/1850.2MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3700.44	-34.87	12.60	12.93	-35.20	-13.00	-22.20	H
5550.31	-34.32	13.10	17.11	-38.33	-13.00	-25.33	H
7400.76	-32.50	11.50	22.20	-43.20	-13.00	-30.20	H
3700.41	-34.59	12.60	12.93	-34.92	-13.00	-21.92	V
5550.23	-34.48	13.10	17.11	-38.49	-13.00	-25.49	V
7400.89	-32.43	11.50	22.20	-43.13	-13.00	-30.13	V
The Worst Test Results for Channel 661/1880.0MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3760.11	-34.43	12.60	12.93	-34.76	-13.00	-21.76	H
5639.82	-34.53	13.10	17.11	-38.54	-13.00	-25.54	H
7520.24	-33.22	11.50	22.20	-43.92	-13.00	-30.92	H
3760.04	-35.48	12.60	12.93	-35.81	-13.00	-22.81	V
5640.31	-34.38	13.10	17.11	-38.39	-13.00	-25.39	V
7520.09	-33.05	11.50	22.20	-43.75	-13.00	-30.75	V
The Worst Test Results for Channel 810/1909.8MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3819.72	-34.66	12.60	12.93	-34.99	-13.00	-21.99	H
5729.18	-34.29	13.10	17.11	-38.30	-13.00	-25.30	H
7638.98	-33.48	11.50	22.20	-44.18	-13.00	-31.18	H
3819.60	-35.24	12.60	12.93	-35.57	-13.00	-22.57	V
5729.46	-34.12	13.10	17.11	-38.13	-13.00	-25.13	V
7639.13	-31.74	11.50	22.20	-42.44	-13.00	-29.44	V



WCDMA Band 5: (30-9000)MHz							
The worst testresults channel 4132/826.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1652.07	-40.81	9.40	4.75	-36.16	-13.00	-23.16	H
2479.60	-40.29	10.60	8.39	-38.08	-13.00	-25.08	H
3305.75	-31.81	12.00	11.79	-31.60	-13.00	-18.60	H
1652.11	-44.47	9.40	4.75	-39.82	-13.00	-26.82	V
2479.23	-45.43	10.60	8.39	-43.22	-13.00	-30.22	V
3305.88	-43.33	12.00	11.79	-43.12	-13.00	-30.12	V
The Worst Test Results Channel 4183/836.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1673.18	-40.68	9.40	4.75	-36.03	-13.00	-23.03	H
2509.81	-39.40	10.60	8.39	-37.19	-13.00	-24.19	H
3346.01	-31.48	12.00	11.79	-31.27	-13.00	-18.27	H
1672.83	-44.56	9.40	4.75	-39.91	-13.00	-26.91	V
2509.52	-44.13	10.60	8.39	-41.92	-13.00	-28.92	V
3346.07	-43.50	12.00	11.79	-43.29	-13.00	-30.29	V
The Worst Test Results Channel 4233/846.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1693.56	-41.61	9.40	4.75	-36.96	-13.00	-23.96	H
2539.45	-40.33	10.60	8.39	-38.12	-13.00	-25.12	H
3386.24	-32.02	12.00	11.79	-31.81	-13.00	-18.81	H
1693.61	-44.10	9.40	4.75	-39.45	-13.00	-26.45	V
2539.28	-44.49	10.60	8.39	-42.28	-13.00	-29.28	V
3386.25	-43.70	12.00	11.79	-43.49	-13.00	-30.49	V



HSUPA Band 5: (30-9000)MHz							
The worst testresults channel 4132/826.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1652.31	-41.21	9.40	4.75	-36.56	-13.00	-23.56	H
2479.67	-40.11	10.60	8.39	-37.90	-13.00	-24.90	H
3305.73	-31.72	12.00	11.79	-31.51	-13.00	-18.51	H
1652.25	-44.52	9.40	4.75	-39.87	-13.00	-26.87	V
2479.23	-45.29	10.60	8.39	-43.08	-13.00	-30.08	V
3305.58	-43.69	12.00	11.79	-43.48	-13.00	-30.48	V
The Worst Test Results Channel 4183/836.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.89	-40.66	9.40	4.75	-36.01	-13.00	-23.01	H
2509.78	-39.64	10.60	8.39	-37.43	-13.00	-24.43	H
3346.36	-31.05	12.00	11.79	-30.84	-13.00	-17.84	H
1672.94	-43.88	9.40	4.75	-39.23	-13.00	-26.23	V
2509.87	-45.34	10.60	8.39	-43.13	-13.00	-30.13	V
3346.19	-43.31	12.00	11.79	-43.10	-13.00	-30.10	V
The Worst Test Results Channel 4233/846.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1693.64	-40.79	9.40	4.75	-36.14	-13.00	-23.14	H
2539.29	-40.12	10.60	8.39	-37.91	-13.00	-24.91	H
3386.15	-31.29	12.00	11.79	-31.08	-13.00	-18.08	H
1693.20	-43.68	9.40	4.75	-39.03	-13.00	-26.03	V
2539.08	-44.07	10.60	8.39	-41.86	-13.00	-28.86	V
3386.11	-42.87	12.00	11.79	-42.66	-13.00	-29.66	V



HSDPA Band 5: (30-9000)MHz							
The worst testresults channel 4132/826.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1652.03	-40.51	9.40	4.75	-35.86	-13.00	-22.86	H
2479.70	-39.97	10.60	8.39	-37.76	-13.00	-24.76	H
3305.80	-31.66	12.00	11.79	-31.45	-13.00	-18.45	H
1652.13	-44.62	9.40	4.75	-39.97	-13.00	-26.97	V
2479.66	-45.30	10.60	8.39	-43.09	-13.00	-30.09	V
3305.83	-43.04	12.00	11.79	-42.83	-13.00	-29.83	V
The Worst Test Results Channel 4183/836.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.81	-40.75	9.40	4.75	-36.10	-13.00	-23.10	H
2509.80	-40.22	10.60	8.39	-38.01	-13.00	-25.01	H
3346.19	-32.28	12.00	11.79	-32.07	-13.00	-19.07	H
1673.24	-43.78	9.40	4.75	-39.13	-13.00	-26.13	V
2509.83	-45.04	10.60	8.39	-42.83	-13.00	-29.83	V
3346.27	-43.09	12.00	11.79	-42.88	-13.00	-29.88	V
The Worst Test Results Channel 4233/846.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1693.19	-40.78	9.40	4.75	-36.13	-13.00	-23.13	H
2539.27	-40.20	10.60	8.39	-37.99	-13.00	-24.99	H
3386.28	-31.01	12.00	11.79	-30.80	-13.00	-17.80	H
1693.38	-43.78	9.40	4.75	-39.13	-13.00	-26.13	V
2539.29	-44.30	10.60	8.39	-42.09	-13.00	-29.09	V
3386.29	-43.54	12.00	11.79	-43.33	-13.00	-30.33	V



WCDMA Band 2: (30-20000)MHz							
The Worst Test Results for Channel 9262/1852.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3704.20	-34.49	12.60	12.93	-34.82	-13.00	-21.82	H
5557.21	-34.67	13.10	17.11	-38.68	-13.00	-25.68	H
7409.84	-33.38	11.50	22.20	-44.08	-13.00	-31.08	H
3704.47	-35.96	12.60	12.93	-36.29	-13.00	-23.29	V
5557.27	-34.22	13.10	17.11	-38.23	-13.00	-25.23	V
7409.75	-32.42	11.50	22.20	-43.12	-13.00	-30.12	V
The Worst Test Results for Channel 9400/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3759.85	-33.79	12.60	12.93	-34.12	-13.00	-21.12	H
5639.97	-34.05	13.10	17.11	-38.06	-13.00	-25.06	H
7519.82	-32.18	11.50	22.20	-42.88	-13.00	-29.88	H
3759.97	-35.83	12.60	12.93	-36.16	-13.00	-23.16	V
5640.17	-34.85	13.10	17.11	-38.86	-13.00	-25.86	V
7520.08	-32.54	11.50	22.20	-43.24	-13.00	-30.24	V
The Worst Test Results for Channel 9538/1907.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3815.42	-34.56	12.60	12.93	-34.89	-13.00	-21.89	H
5722.32	-34.72	13.10	17.11	-38.73	-13.00	-25.73	H
7630.22	-32.67	11.50	22.20	-43.37	-13.00	-30.37	H
3815.62	-34.53	12.60	12.93	-34.86	-13.00	-21.86	V
5722.42	-34.13	13.10	17.11	-38.14	-13.00	-25.14	V
7630.23	-32.11	11.50	22.20	-42.81	-13.00	-29.81	V



HSUPA Band 2: (30-20000)MHz							
The Worst Test Results for Channel 9262/1852.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3704.13	-34.79	12.60	12.93	-35.12	-13.00	-22.12	H
5557.56	-35.30	13.10	17.11	-39.31	-13.00	-26.31	H
7409.54	-32.21	11.50	22.20	-42.91	-13.00	-29.91	H
3704.17	-35.58	12.60	12.93	-35.91	-13.00	-22.91	V
5557.41	-34.74	13.10	17.11	-38.75	-13.00	-25.75	V
7409.58	-32.91	11.50	22.20	-43.61	-13.00	-30.61	V
The Worst Test Results for Channel 9400/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3759.87	-34.46	12.60	12.93	-34.79	-13.00	-21.79	H
5639.85	-34.26	13.10	17.11	-38.27	-13.00	-25.27	H
7520.14	-33.17	11.50	22.20	-43.87	-13.00	-30.87	H
3760.32	-35.15	12.60	12.93	-35.48	-13.00	-22.48	V
5640.28	-35.00	13.10	17.11	-39.01	-13.00	-26.01	V
7520.25	-31.88	11.50	22.20	-42.58	-13.00	-29.58	V
The Worst Test Results for Channel 9538/1907.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3815.31	-33.81	12.60	12.93	-34.14	-13.00	-21.14	H
5722.26	-34.84	13.10	17.11	-38.85	-13.00	-25.85	H
7630.15	-33.44	11.50	22.20	-44.14	-13.00	-31.14	H
3815.66	-35.59	12.60	12.93	-35.92	-13.00	-22.92	V
5722.24	-33.91	13.10	17.11	-37.92	-13.00	-24.92	V
7630.29	-32.31	11.50	22.20	-43.01	-13.00	-30.01	V



HSDPA Band 2: (30-20000)MHz							
The Worst Test Results for Channel 9262/1852.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3704.31	-34.70	12.60	12.93	-35.03	-13.00	-22.03	H
5557.39	-34.54	13.10	17.11	-38.55	-13.00	-25.55	H
7409.92	-32.57	11.50	22.20	-43.27	-13.00	-30.27	H
3704.43	-35.56	12.60	12.93	-35.89	-13.00	-22.89	V
5557.32	-35.04	13.10	17.11	-39.05	-13.00	-26.05	V
7409.50	-32.36	11.50	22.20	-43.06	-13.00	-30.06	V
The Worst Test Results for Channel 9400/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3760.25	-33.70	12.60	12.93	-34.03	-13.00	-21.03	H
5640.23	-34.63	13.10	17.11	-38.64	-13.00	-25.64	H
7519.85	-33.63	11.50	22.20	-44.33	-13.00	-31.33	H
3759.90	-35.21	12.60	12.93	-35.54	-13.00	-22.54	V
5640.27	-34.84	13.10	17.11	-38.85	-13.00	-25.85	V
7519.88	-32.71	11.50	22.20	-43.41	-13.00	-30.41	V
The Worst Test Results for Channel 9538/1907.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
3815.31	-33.80	12.60	12.93	-34.13	-13.00	-21.13	H
5722.29	-34.67	13.10	17.11	-38.68	-13.00	-25.68	H
7629.99	-33.02	11.50	22.20	-43.72	-13.00	-30.72	H
3815.56	-34.82	12.60	12.93	-35.15	-13.00	-22.15	V
5722.16	-34.11	13.10	17.11	-38.12	-13.00	-25.12	V
7629.98	-32.16	11.50	22.20	-42.86	-13.00	-29.86	V



APPENDIX-PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

*****END OF THE REPORT*****

