

CFR 47 FCC PART 15 SUBPART C

TEST REPORT

For

Air Combat Helicopter

MODEL NUMBER: PL-1170R

REPORT NUMBER: 4790800561.1-RF-1

ISSUE DATE: May 5, 2023

FCC ID: 2ASK3PL-1170R

Prepared for

**AMAX INDUSTRIAL GROUP CHINA CO.,LTD
OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L TUNG CHOI STREET
MONGKOK KOWLOON HONG KONG**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	May 5, 2023	Initial Issue	

Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	20dB Bandwidth and 99% Occupied Bandwidth	CFR 47 FCC §15.215 (c)	Pass
2	Radiated Emission	CFR 47 FCC §15.249 (a)(d)(e) CFR 47 FCC §15.205 and §15.209	Pass
3	Conducted Emission Test for AC Power Port	CFR 47 FCC §15.207	Pass
4	Antenna Requirement	CFR 47 FCC §15.203	Pass
<p>Note 1: This test report is only published to and used by the applicant, and it is not for evidence purpose in China.</p> <p>Note 2: The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C > when <Accuracy Method> decision rule is applied.</p>			

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY.....	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
5. EQUIPMENT UNDER TEST	8
5.1. <i>DESCRIPTION OF EUT</i>	<i>8</i>
5.2. <i>CHANNEL LIST</i>	<i>8</i>
5.3. <i>MAXIMUM EIRP</i>	<i>8</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>8</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>9</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>9</i>
5.7. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>10</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	11
7. ANTENNA PORT TEST RESULTS	13
7.1. <i>20DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....</i>	<i>13</i>
7.2. <i>DUTY CYCLE</i>	<i>20</i>
8. RADIATED TEST RESULTS.....	22
8.1. <i>RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS</i>	<i>31</i>
8.2. <i>SPURIOUS EMISSIONS (1 GHZ ~ 3 GHZ)</i>	<i>34</i>
8.3. <i>SPURIOUS EMISSIONS (3 GHZ ~ 18 GHZ)</i>	<i>40</i>
8.4. <i>SPURIOUS EMISSIONS (9 KHZ ~ 30 MHZ).....</i>	<i>46</i>
8.5. <i>SPURIOUS EMISSIONS (18 GHZ ~ 26 GHZ)</i>	<i>49</i>
8.6. <i>SPURIOUS EMISSIONS (30 MHZ ~ 1 GHZ)</i>	<i>51</i>
9. AC POWER LINE CONDUCTED EMISSION	53
10. ANTENNA REQUIREMENT	56

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD
Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L
TUNG CHOI STREET MONGKOK KOWLOON HONG KONG

Manufacturer Information


Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD
Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L
TUNG CHOI STREET MONGKOK KOWLOON HONG KONG

EUT Information

EUT Name: Air Combat Helicopter
Model: PL-1170R
Sample Received Date: April 10, 2023
Sample Status: Normal
Sample ID: 5967822
Date of Tested: April 11, 2023 to May 5, 2023


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:



Denny Huang
Senior Project Engineer

Checked By:



Kebo Zhang
Senior Project Engineer

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 414788 D01 Radiated Test Site v01r01, FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1:

All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Air Combat Helicopter		
Model	PL-1170R		
Product Description	Operation Frequency	2415 MHz ~ 2472 MHz	
	Modulation Type	GFSK	
Battery	DC 3.7 V		

5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2415	2	2450	3	2472	/	/

5.3. MAXIMUM EIRP

Test Mode	Frequency (MHz)	Channel Number	Max Peak field strength (dB μ V/m)
GFSK	2415 ~ 2472	1-3[3]	77.02

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK	CH 1(Low Channel), CH 2(MID Channel), CH 3(High Channel)	2415 MHz, 2450 MHz, 2472 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2415 MHz ~ 2472 MHz Band				
Test Software Version		/		
Modulation Type	Transmit Antenna Number	Test Channel		
		CH 1	CH 2	CH 3
GFSK	1	Default	Default	Default

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	Maximum Antenna Gain (dBi)
1	2415 ~ 2472	Line Antenna	2

Test Mode	Transmit and Receive Mode	Description
GFSK	<input checked="" type="checkbox"/> 1TX	Antenna 1 can be used as transmitting/receiving antenna.

Note: The value of the antenna gain was declared by customer.

5.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
/	/	/	/	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	DC	USB	Unshielded	0.4	/

ACCESSORY


Item	Equipment	Mfr/Brand	Model/Type No.	Specification	Series No.
1	Adapter	/	MDY-11-EX	Input: AC 100-240 V, 50/60 Hz, 0.7 A Output: DC 5 V, 3 A	/

TEST SETUP


The EUT have the engineer mode inside.

SETUP DIAGRAM FOR TEST

For AC power line conducted emission test:



For other tests:



6. MEASURING EQUIPMENT AND SOFTWARE USED

Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.17, 2022	Oct.16, 2023
Attenuator	Agilent	8495B	2814a12853	Oct.18, 2022	Oct.17, 2023
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		2.6.77.0518	

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Oct.17, 2022	Oct.16, 2023
Two-Line V-Network	R&S	ENV216	101983	Oct.17, 2022	Oct.16, 2023
Software					
Description		Manufacturer	Name	Version	
Test Software for Conducted Emissions		Farad	EZ-EMC	Ver. UL-3A1	

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.17, 2022	Oct.16, 2023
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.17, 2022	Oct.16, 2023
EMI Measurement Receiver	R&S	ESR26	101377	Oct.17, 2022	Oct.16, 2023
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.17, 2022	Oct.16, 2023
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.17, 2022	Oct.16, 2023
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.17, 2022	Oct.16, 2023
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.17, 2022	Oct.16, 2023
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01202035	Oct.17, 2022	Oct.16, 2023
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	/	/
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	/	/
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

7. ANTENNA PORT TEST RESULTS

7.1. 20DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.249) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.215 (c)	20dB Bandwidth	for reporting purposes only	2400-2483.5
ISED RSS-Gen Clause 6.7 Issue 5	99% Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1% to 5% of the occupied bandwidth
VBW	approximately 3×RBW
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB/99% relative to the maximum level measured in the fundamental emission.

TEST SETUP

Refer to clause 8 radiated test.


TEST ENVIRONMENT

Temperature	23.6 °C	Relative Humidity	54 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

TEST RESULTS


Frequency (MHz)	99% Bandwidth (MHz)	20dB Bandwidth (MHz)	Result
2415	2.7173	2.446	PASS

99% OCCUPIED BANDWIDTH LOW CH



Date: 11.APR.2023 14:17:06


20 dB BANDWIDTH AND LOW CH



Date: 5.MAY.2023 10:35:22


Frequency (MHz)	99% Bandwidth (MHz)	20dB Bandwidth (MHz)	Result
2450	1.4585	1.398	PASS

99% OCCUPIED BANDWIDTH MID CH



Date: 11.APR.2023 14:30:02


20 dB BANDWIDTH AND MID CH



Date: 11.APR.2023 14:35:03


Frequency (MHz)	99% Bandwidth (MHz)	20dB Bandwidth (MHz)	Result
2472	0.7592	0.999	PASS

99% OCCUPIED BANDWIDTH MID CH



Date: 11.APR.2023 14:45:59

20 dB BANDWIDTH AND MID CH



Date: 11.APR 2023 14:49:19

7.2. DUTY CYCLE

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP

Refer to clause 8 radiated test.

TEST ENVIRONMENT

Temperature	23.6 °C	Relative Humidity	54 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V


TEST RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)
GFSK	17.787	100	0.1779	17.79	-15.00

Note: Duty Cycle Correction Factor= $20\log(x)$.


Where: x is Duty Cycle

ON TIME AND DUTY CYCLE MID CH PLOT



Date: 11.APR.2023 14:25:30

ON TIME AND DUTY CYCLE MID CH PLOT-2



Date: 11.APR.2023 14:26:30

Note: All the modes had been tested, but only the worst duty cycle recorded in the report.

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

The field strength of emissions from intentional radiators operated within these frequency bands			
Frequency (MHz)	Field strength of Fundamental	Field strength of Harmonics	Distance (m)
902 - 928	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
2400 – 2483.5	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
5725 – 5875	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements. Where necessary, average emission are determined by applying the Duty Cycle Correction Factor to the peak measurements. For the Duty Cycle and Correction Factor please refer to clause 7.2. ON TIME AND DUTY CYCLE.

For Restricted Bandedge and field strength of intentional emission:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG Result=Peak Result + Duty Cycle Correction Factor.
5. For the transmitting duration, please refer to clause 7.2.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes, channels and antennas have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes, channels and antennas have been tested, only the worst data was recorded in the report.

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes, channels and antennas have been tested, only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG Result=Peak Result + Duty Cycle Correction Factor.
5. For the transmitting duration, please refer to clause 7.2.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes, channels and antennas have been tested, only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG Result=Peak Result + Duty Cycle Correction Factor.
5. For the transmitting duration, please refer to clause 7.2.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes, channels and antennas have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes, channels and antennas have been tested, only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz




TEST ENVIRONMENT

Temperature	25.3 °C	Relative Humidity	65 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

TEST RESULTS


8.1. RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS

Test Mode:	GFSK	Channel:	2415 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2398.550	18.31	32.19	50.50	74.00	-23.50	peak
2	2415.455	44.40	32.24	76.64	114.00	-37.36	Fundamental

Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2450.000	44.68	32.34	77.02	114.00	-36.98	Fundamental
2	2490.250	15.72	32.46	48.18	74.00	-25.82	peak


Test Mode:	GFSK	Channel:	2472 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2472.000	43.92	32.41	76.33	114.00	-37.67	Fundamental
2	2488.300	19.06	32.46	51.52	74.00	-22.48	peak


8.2. SPURIOUS EMISSIONS (1 GHZ ~ 3 GHZ)

Test Mode:	GFSK	Channel:	2415 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1368.000	46.87	-13.32	33.55	74.00	-40.45	peak
2	1850.000	44.72	-11.55	33.17	74.00	-40.83	peak
3	2360.000	44.12	-9.21	34.91	74.00	-39.09	peak
4	2472.000	44.58	-8.63	35.95	74.00	-38.05	peak
5	2576.000	43.92	-8.26	35.66	74.00	-38.34	peak
6	2638.000	43.83	-8.07	35.76	74.00	-38.24	peak

Test Mode:	GFSK	Channel:	2415 MHz
Polarity:	Vertical	Test Voltage:	DC 3.7 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1270.000	45.84	-13.78	32.06	74.00	-41.94	peak
2	2086.000	45.11	-10.62	34.49	74.00	-39.51	peak
3	2188.000	44.89	-10.09	34.80	74.00	-39.20	peak
4	2340.000	44.09	-9.31	34.78	74.00	-39.22	peak
5	2562.000	43.74	-8.31	35.43	74.00	-38.57	peak
6	2782.000	43.37	-7.63	35.74	74.00	-38.26	peak

Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1222.000	46.60	-14.00	32.60	74.00	-41.40	peak
2	1588.000	45.08	-12.42	32.66	74.00	-41.34	peak
3	2068.000	44.69	-10.70	33.99	74.00	-40.01	peak
4	2470.000	44.65	-8.65	36.00	74.00	-38.00	peak
5	2602.000	44.04	-8.19	35.85	74.00	-38.15	peak
6	2810.000	43.78	-7.55	36.23	74.00	-37.77	peak

Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Vertical	Test Voltage:	DC 3.7 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1324.000	45.88	-13.53	32.35	74.00	-41.65	peak
2	1726.000	45.40	-11.97	33.43	74.00	-40.57	peak
3	2036.000	45.98	-10.87	35.11	74.00	-38.89	peak
4	2404.000	43.90	-8.99	34.91	74.00	-39.09	peak
5	2450.000	44.38	-8.74	35.64	74.00	-38.36	peak
6	2648.000	44.55	-8.04	36.51	74.00	-37.49	peak

Test Mode:	GFSK	Channel:	2472 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1470.000	45.08	-12.85	32.23	74.00	-41.77	peak
2	1782.000	44.72	-11.78	32.94	74.00	-41.06	peak
3	2302.000	44.10	-9.50	34.60	74.00	-39.40	peak
4	2508.000	49.27	-8.47	40.80	74.00	-33.20	peak
5	2544.000	57.20	-8.36	48.84	74.00	-25.16	peak
6	2726.000	43.87	-7.80	36.07	74.00	-37.93	peak


Test Mode:	GFSK	Channel:	2472 MHz
Polarity:	Vertical	Test Voltage:	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1620.000	45.47	-12.31	33.16	74.00	-40.84	peak
2	2294.000	44.63	-9.55	35.08	74.00	-38.92	peak
3	2450.000	45.43	-8.74	36.69	74.00	-37.31	peak
4	2508.000	49.87	-8.47	41.40	74.00	-32.60	peak
5	2544.000	55.98	-8.36	47.62	74.00	-26.38	peak
6	2904.000	44.24	-7.27	36.97	74.00	-37.03	peak


8.3. SPURIOUS EMISSIONS (3 GHZ ~ 18 GHZ)

Test Mode:	GFSK	Channel:	2415 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	41.49	-0.20	41.29	74.00	-32.71	peak
2	7965.000	37.35	6.31	43.66	74.00	-30.34	peak
3	9150.000	36.06	10.54	46.60	74.00	-27.40	peak
4	10170.000	35.92	12.34	48.26	74.00	-25.74	peak
5	13860.000	28.20	21.67	49.87	74.00	-24.13	peak
6	17955.000	24.45	25.42	49.87	74.00	-24.13	peak

Test Mode:	GFSK	Channel:	2415 MHz
Polarity:	Vertical	Test Voltage:	DC 3.7 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	49.88	-0.20	49.68	74.00	-24.32	peak
2	9240.000	36.44	10.58	47.02	74.00	-26.98	peak
3	10440.000	34.41	12.87	47.28	74.00	-26.72	peak
4	13425.000	29.06	20.58	49.64	74.00	-24.36	peak
5	13920.000	28.85	21.79	50.64	74.00	-23.36	peak
6	18000.000	24.32	25.69	50.01	74.00	-23.99	peak

Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4890.000	49.01	0.03	49.04	74.00	-24.96	peak
2	7305.000	37.83	6.47	44.30	74.00	-29.70	peak
3	9135.000	37.03	10.55	47.58	74.00	-26.42	peak
4	11070.000	33.03	15.03	48.06	74.00	-25.94	peak
5	13530.000	29.47	20.96	50.43	74.00	-23.57	peak
6	17985.000	25.13	25.60	50.73	74.00	-23.27	peak

Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Vertical	Test Voltage:	DC 3.7 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4890.000	50.19	0.03	50.22	74.00	-23.78	peak
2	7005.000	36.38	6.69	43.07	74.00	-30.93	peak
3	8970.000	37.54	10.26	47.80	74.00	-26.20	peak
4	11205.000	33.30	15.52	48.82	74.00	-25.18	peak
5	13680.000	28.91	21.29	50.20	74.00	-23.80	peak
6	17940.000	24.20	25.34	49.54	74.00	-24.46	peak

Test Mode:	GFSK	Channel:	2472 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8085.000	39.18	6.40	45.58	74.00	-28.42	peak
2	8925.000	38.73	9.94	48.67	74.00	-25.33	peak
3	10875.000	35.62	14.32	49.94	74.00	-24.06	peak
4	11715.000	32.23	17.19	49.42	74.00	-24.58	peak
5	13560.000	29.37	21.03	50.40	74.00	-23.60	peak
6	17985.000	23.70	25.60	49.30	74.00	-24.70	peak


Test Mode:	GFSK	Channel:	2472 MHz
Polarity:	Vertical	Test Voltage:	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4935.000	49.99	0.20	50.19	74.00	-23.81	peak
2	9570.000	36.33	10.87	47.20	74.00	-26.80	peak
3	10860.000	33.76	14.27	48.03	74.00	-25.97	peak
4	13635.000	29.12	21.19	50.31	74.00	-23.69	peak
5	13905.000	28.98	21.76	50.74	74.00	-23.26	peak
6	18000.000	24.15	25.69	49.84	74.00	-24.16	peak


8.4. SPURIOUS EMISSIONS (9 KHZ ~ 30 MHZ)

Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Loop Antenna Face On To The EUT	Test Voltage	DC 3.7 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	77.72	-101.40	-23.68	47.60	-71.28	peak
2	0.0131	73.97	-101.38	-27.41	45.25	-72.66	peak
3	0.0200	71.86	-101.34	-29.48	41.58	-71.06	peak
4	0.0279	70.17	-101.38	-31.21	38.69	-69.90	peak
5	0.0656	62.86	-101.55	-38.69	31.26	-69.95	peak
6	0.0922	60.51	-101.74	-41.23	28.31	-69.54	peak

Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Loop Antenna Face On To The EUT	Test Voltage	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1595	77.86	-101.65	-23.79	23.55	-47.34	peak
2	0.1794	75.27	-101.68	-26.41	22.53	-48.94	peak
3	0.2190	71.27	-101.75	-30.48	20.79	-51.27	peak
4	0.2530	70.14	-101.80	-31.66	19.54	-51.20	peak
5	0.3084	65.45	-101.86	-36.41	17.82	-54.23	peak
6	0.3714	62.28	-101.93	-39.65	16.20	-55.85	peak


Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Loop Antenna Face On To The EUT	Test Voltage	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5039	64.93	-62.07	2.86	33.56	-30.70	peak
2	0.7861	62.83	-62.14	0.69	29.69	-29.00	peak
3	3.7100	57.20	-61.41	-4.21	29.54	-33.75	peak
4	5.5952	57.05	-61.41	-4.36	29.54	-33.90	peak
5	13.0907	55.63	-60.93	-5.30	29.54	-34.84	peak
6	16.6021	56.02	-60.96	-4.94	29.54	-34.48	peak


8.5. SPURIOUS EMISSIONS (18 GHZ ~ 26 GHZ)

Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19392.000	52.62	-5.57	47.05	74.00	-26.95	peak
2	20016.000	52.06	-5.47	46.59	74.00	-27.41	peak
3	20696.000	51.71	-5.16	46.55	74.00	-27.45	peak
4	22160.000	50.08	-4.31	45.77	74.00	-28.23	peak
5	23664.000	49.82	-3.18	46.64	74.00	-27.36	peak
6	25000.000	48.86	-2.10	46.76	74.00	-27.24	peak


Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Vertical	Test Voltage:	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18224.000	49.58	-5.53	44.05	74.00	-29.95	peak
2	19984.000	49.21	-5.44	43.77	74.00	-30.23	peak
3	21264.000	48.85	-4.76	44.09	74.00	-29.91	peak
4	22792.000	47.61	-3.65	43.96	74.00	-30.04	peak
5	23848.000	47.18	-3.03	44.15	74.00	-29.85	peak
6	25728.000	45.11	-0.72	44.39	74.00	-29.61	peak


8.6. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)

Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Horizontal	Test Voltage:	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	37.7599	32.71	-19.67	13.04	40.00	-26.96	QP
2	107.6000	28.85	-20.58	8.27	43.50	-35.23	QP
3	250.1900	29.66	-18.91	10.75	46.00	-35.25	QP
4	542.1599	25.09	-10.49	14.60	46.00	-31.40	QP
5	838.0100	25.39	-6.52	18.87	46.00	-27.13	QP
6	947.6200	26.77	-4.43	22.34	46.00	-23.66	QP

Test Mode:	GFSK	Channel:	2450 MHz
Polarity:	Vertical	Test Voltage:	DC 3.7 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	37.7599	34.37	-19.67	14.70	40.00	-25.30	QP
2	90.1400	33.19	-21.95	11.24	43.50	-32.26	QP
3	206.5399	28.68	-16.97	11.71	43.50	-31.79	QP
4	699.3000	24.63	-8.31	16.32	46.00	-29.68	QP
5	881.6600	26.36	-5.48	20.88	46.00	-25.12	QP
6	945.6800	26.84	-4.44	22.40	46.00	-23.60	QP

9. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP




TEST ENVIRONMENT

Temperature	23.3 °C	Relative Humidity	59.8 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Test Mode:	GFSK	Channel:	2450 MHz
Line:	L1		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.3463	-1.19	9.54	8.35	59.05	-50.70	QP
2	0.3463	-5.66	9.54	3.88	49.05	-45.17	AVG
3	4.9751	-2.21	9.62	7.41	56.00	-48.59	QP
4	4.9751	-4.57	9.62	5.05	46.00	-40.95	AVG
5	7.9469	2.05	9.61	11.66	60.00	-48.34	QP
6	7.9469	-3.65	9.61	5.96	50.00	-44.04	AVG
7	10.5750	3.89	9.63	13.52	60.00	-46.48	QP
8	10.5750	-3.47	9.63	6.16	50.00	-43.84	AVG
9	12.6055	4.18	9.66	13.84	60.00	-46.16	QP
10	12.6055	-3.55	9.66	6.11	50.00	-43.89	AVG
11	14.9474	0.82	9.66	10.48	60.00	-49.52	QP
12	14.9474	-4.63	9.66	5.03	50.00	-44.97	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Test Mode:	GFSK	Channel:	2450 MHz
Line:	N		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1580	3.61	9.51	13.12	65.57	-52.45	QP
2	0.1580	-2.51	9.51	7.00	55.57	-48.57	AVG
3	0.7395	-5.13	9.50	4.37	56.00	-51.63	QP
4	0.7395	-6.84	9.50	2.66	46.00	-43.34	AVG
5	3.1154	-3.67	9.62	5.95	56.00	-50.05	QP
6	3.1154	-5.59	9.62	4.03	46.00	-41.97	AVG
7	4.0595	-2.65	9.60	6.95	56.00	-49.05	QP
8	4.0595	-4.78	9.60	4.82	46.00	-41.18	AVG
9	11.1127	4.80	9.64	14.44	60.00	-45.56	QP
10	11.1127	-3.29	9.64	6.35	50.00	-43.65	AVG
11	13.3100	2.77	9.66	12.43	60.00	-47.57	QP
12	13.3100	-4.01	9.66	5.65	50.00	-44.35	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

10. ANTENNA REQUIREMENT

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

RESULTS

Complies

END OF REPORT