



# RF TEST REPORT

**Applicant**      Quectel Wireless Solutions Co., Ltd

**FCC ID**          XMR201910BG95M3

**Product**        LTE Cat M1 & Cat NB2 & EGPRS Module

**Brand**           Quectel

**Model**           BG95-M3, BG95-M3 MINIPCIE

**Report No.**     R2106A0549-R4

**Issue Date**     September 6, 2021

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2020)/ FCC CFR 47 Part 22H (2020)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

*Peng Tao*

*Prepared by: Peng Tao*

*Kai Xu*

*Approved by: Kai Xu*

---

## TA Technology (Shanghai) Co., Ltd.

*No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*



## TABLE OF CONTENT

1. Test Laboratory .....	4
1.1. Notes of the Test Report .....	4
1.2. Test facility .....	4
1.3. Testing Location .....	4
2. General Description of Equipment under Test .....	5
3. Applied Standards .....	6
4. Test Configuration .....	7
5. Test Case Results .....	8
5.1. RF Power Output and Effective Radiated Power .....	8
5.2. Occupied Bandwidth .....	10
Band Edge Compliance .....	15
5.3. Peak-to-Average Power Ratio (PAPR) .....	18
5.4. Frequency Stability .....	20
5.5. Spurious Emissions at Antenna Terminals .....	24
5.6. Radiates Spurious Emission .....	26
6. Main Test Instruments .....	33
ANNEX A: The EUT Appearance .....	35
ANNEX B: Test Setup Photos .....	36
ANNEX C: Product Change Description .....	37

## Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF Power Output and Effective Radiated Power	2.1046 22.913(a)(5)	PASS
2	Occupied Bandwidth	2.1049	PASS
3	Band Edge Compliance	2.1051 / 22.917(a)	PASS
4	Peak-to-Average Power Ratio	22.913(d)/ KDB 971168 D01(5.7)	PASS
5	Frequency Stability	2.1055 / 22.355	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
7	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS
Date of Testing(original): March 5, 2020 ~March 30, 2020 and June 6, 2020 (variant): July 14, 2021 ~ August 9, 2021			
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard. All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

**BG95-M3, BG95-M3 MINIPCIE (Report No.: R2106A0549-R4) is a variant model of BG95-M3, BG95-M3 MINIPCIE (Report No.: R2006A0361-R4V1). The product only changes PA components. Test values duplicated from Original for variant. Test items tested see the table below.**

Test Case	original	variant
RF Power Output and Effective Isotropic Radiated Power	PASS	Retest
Occupied Bandwidth	PASS	Refer to original
Band Edge Compliance	PASS	Refer to original
Peak-to-Average Power Ratio	PASS	Refer to original
Frequency Stability	PASS	Refer to original
Spurious Emissions at Antenna Terminals	PASS	Refer to original
Radiates Spurious Emission	PASS	Refer to original

**The detailed product change description please refers to the Difference Declaration Letter.**



## 1. Test Laboratory

### 1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2. Test facility

#### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

#### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

### 1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [xukai@ta-shanghai.com](mailto:xukai@ta-shanghai.com)

## 2. General Description of Equipment under Test

### Client Information

Applicant	Quectel Wireless Solutions Co., Ltd
Applicant address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233
Manufacturer	Quectel Wireless Solutions Co., Ltd
Manufacturer address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233

### General Information

EUT Description			
Model	BG95-M3, BG95-M3 MINIPCIE		
IMEI	BG95-M3: 864475048391303 BG95-M3 MINIPCIE: 864475048389810		
Hardware Version	R2.1		
Software Version	BG95M3LAR02A03		
Power Supply	External Power Supply		
Antenna Type	External Antenna		
Antenna Gain	3dBi		
Test Mode(s)	NB-IoT Band 5		
Test Modulation	BPSK, QPSK		
Category	NB2		
Deployment	stand-alone		
Sub-carrier spacing	3.75KHz, 15KHz		
Ntones	single-tone, multi-tone		
Maximum E.R.P.	NB-IoT Band 5	21.50dBm	
Rated Power Supply Voltage	3.8V		
Extreme Voltage	Minimum: 3.3V	Maximum: 4.3V	
Extreme Temperature	Lowest: -40°C	Highest: +85°C	
Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	NB-IoT Band 5	824 ~ 849	869 ~ 894
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.			
2. The series model number is: BG95-M3 MINIPCIE. The difference of these models are have different marketing requirement.			



### 3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**Test standards:**

**FCC CFR 47 Part 22H (2020)**

**ANSI C63.26 (2015)**

**Reference standard:**

**FCC CFR47 Part 2 (2020)**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

## 4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, horizontal polarization) and the worst case was recorded.

All modes as Subcarrier Spacing, modulations, Channel were investigated.

Subsequently, only the worst case emissions are reported.

The following testing in NB-IoT is set based on the maximum RF Output Power.

The following testing in different mode is set to detail in the following table:

Test modes are chosen as the worst case configuration below for NB-IoT Band 5.

Test items	Deployment mode	Subcarrier Spacing (kHz)		Modulation		Test Channel		
	Stand-alone	3.75	15	BPSK	QPSK	L	M	H
RF Power Output and Effective Radiated Power	O	O	O	O	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	O	O
Band Edge Compliance	O	O	O	O	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	-	O	-
Frequency Stability	O	O	O	O	O	O	O	O
Spurious Emissions at Antenna Terminals	O	-	O	-	O	O	O	O
Radiates Spurious Emission	O	-	O	-	O	O	O	O
Note 1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.								

## 5. Test Case Results

### 5.1. RF Power Output and Effective Radiated Power

#### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Methods of Measurement

During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.


ERP can then be calculated as follows:

$$\text{EIRP (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBi)}$$

where:dBd refers to gain relative to an ideal dipole.

$$\text{EIRP (dBm)} = \text{ERP (dBm)} + 2.15 \text{ (dB)}.$$

#### Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

#### Limits

No specific RF power output requirements in part 2.1046.

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4 \text{ dB}$ .

**Test Results****Original**

NB-IOT Band 5 Standalone					
Modulation	Sub-carrier spacing (KHz)	Ntones	Conducted Power (dBm) for low/middle/high channel		
			20402/824.2	20525/836.5	20648/848.8
BPSK	3.75	1@0	20.71	20.67	20.62
		1@47	20.64	20.64	20.57
	15	1@0	20.68	20.52	20.74
		1@11	20.67	20.41	20.73
QPSK	3.75	1@0	20.71	20.70	20.63
		1@47	20.72	20.48	20.59
	15	1@0	20.65	20.47	20.68
		1@11	20.64	20.55	20.73
	15	12@0	19.51	19.54	19.35

**Variant**

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Maximum Output Power(dBm)			ERP (dBm)		
				20402/ 824.2	20525/ 836.5	20648/ 848.8	20402/ 824.2	20525/ 836.5	20648/ 848.8
Band 5 Standalone	BPSK	3.75	1@0	20.48	20.33	20.36	21.33	21.18	21.21
			1@47	20.40	20.28	20.35	21.25	21.13	21.20
		15	1@0	20.65	20.39	20.40	21.50	21.24	21.25
			1@11	20.57	20.32	20.32	21.42	21.17	21.17
	QPSK	3.75	1@0	20.43	20.37	20.42	21.28	21.22	21.27
			1@47	20.35	20.30	20.39	21.20	21.15	21.24
		15	1@0	20.60	20.37	20.40	21.45	21.22	21.25
			1@11	20.61	20.38	20.42	21.46	21.23	21.27
		15	12@0	18.62	18.44	18.51	19.47	19.29	19.36

## 5.2. Occupied Bandwidth

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 2kHz, VBW is set to 6.2kHz.

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

### Test Setup



### Limits

No specific occupied bandwidth requirements in part 2.1049.


### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 624\text{Hz}$ .

# Test Result

Mode	Modulation	Sub-carrier spacing (KHz)	Ntones	Bandwidth(KHz) for low/mid/high channel					
				20402/824.2		20525/836.5		20648/848.8	
				99% Power	-26dBc	99% Power	-26dBc	99% Power	-26dBc
NB-IoT Band 5 Standalone	BPSK	3.75	1@0	57.59	40.29	58.23	40.77	59.52	41.02
	QPSK	3.75	1@0	68.43	43.44	66.56	41.16	66.09	42.57
	BPSK	15	1@0	129.44	113.00	119.66	100.70	115.91	104.00
	QPSK	15	1@0	117.04	118.00	117.23	116.10	115.89	116.00
	QPSK	15	12@0	185.17	238.50	184.41	235.90	184.47	256.60


## NB-IoT Band 5 BPSK 3.75kHz 1@0 CH-Low




## NB-IoT Band 5 BPSK 15kHz 1@0 CH-Low




## NB-IoT Band 5 BPSK 3.75kHz 1@0 CH-Middle




## NB-IoT Band 5 BPSK 15kHz 1@0 CH-Middle



## NB-IoT Band 5 BPSK 3.75kHz 1@0 CH-High




## NB-IoT Band 5 BPSK 15kHz 1@0 CH-High







## NB-IoT Band 5 QPSK 3.75kHz 1@0 CH-Low



## NB-IoT Band 5 QPSK 15kHz 1@0 CH-Low




## NB-IoT Band 5 QPSK 3.75kHz 1@0 CH-Middle




## NB-IoT Band 5 QPSK 15kHz 1@0 CH-Middle




## NB-IoT Band 5 QPSK 3.75kHz 1@0 CH-High




## NB-IoT Band 5 QPSK 15kHz 1@0 CH-High




### NB-IoT Band 5 QPSK 15kHz 12@0 CH-Low



### NB-IoT Band 5 QPSK 15kHz 12@0 CH-Middle



### NB-IoT Band 5 QPSK 15kHz 12@0 CH-High



## Band Edge Compliance

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used.


RBW is set to 750Hz, VBW is set to 2.4kHz for 3.75KHz single carrier,

RBW is set to 1.3kHz, VBW is set to 3.9kHz for 15KHz single carrier,

RBW is set to 2kHz, VBW is set to 6.2KHz for 15KHz full carrier.

Spectrum analyzer plots are included on the following pages.

### Test Setup



### Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.”

Limit	-13 dBm
-------	---------


### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U=0.684$ dB.




## Test Result:


NB-IoT Band 5 BPSK 3.75kHz 1@0 CH-Low




NB-IoT Band 5 BPSK 3.75kHz 1@47 CH-High




NB-IoT Band 5 BPSK 15kHz 1@0 CH-Low




NB-IoT Band 5 BPSK 15kHz 1@11 CH-High



NB-IoT Band 5 QPSK 3.75kHz 1@0 CH-Low




NB-IoT Band 5 QPSK 3.75kHz 1@47 CH-High







## NB-IoT Band 5 QPSK 15kHz 1@0 CH-Low




## NB-IoT Band 5 QPSK 15kHz 1@11 CH-High



## NB-IoT Band 5 QPSK 15kHz 12@0 CH-Low



## NB-IoT Band 5 QPSK 15kHz 12@0 CH-High



### 5.3. Peak-to-Average Power Ratio (PAPR)

#### Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Methods of Measurement

Measure the total peak power and record as  $P_{Pk}$ . And measure the total average power and record as  $P_{Avg}$ . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).$$

#### Test Setup



#### Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4$  dB.

**Test Results**

Mode	Modulation	Sub-carrier spacing (KHz)	Channel/ Frequency (MHz)	Peak-to-Average Power Ratio (PAPR)			Limit (dB)	Conclusion
				Peak(dBm)	Avg(dBm)	PAPR(dB)		
NB-IoT Band 5 Standalone	BPSK	3.75	20525/836.5	21.69	17.92	3.77	≤13	PASS
	QPSK	3.75	20525/836.5	21.26	17.88	3.38	≤13	PASS
	BPSK	15	20525/836.5	21.69	15.27	6.42	≤13	PASS
	QPSK	15	20525/836.5	21.65	15.26	6.39	≤13	PASS

## 5.4. Frequency Stability

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

### Method of Measurement

#### Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -40°C to +85°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -40°C to +85°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.3 V and 4.3 V, with a nominal voltage of 3.8V.

### Test setup



**Limits**

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	$\leq 2.5$ ppm
--------	----------------

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor  $k = 3$ ,  $U = 0.01$  ppm.



## Test Result

NB-IoT Band 5						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability(ppm)	Frequency Stability(ppm)	Verdict
Sub-carrier spacing (KHz)	3.75					
Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
Normal(25℃)	Normal	15.69	2.25	0.00834	0.00120	PASS
Extreme(85℃)		12.85	5.11	0.00684	0.00272	PASS
Extreme(80℃)		12.96	12.48	0.00689	0.00664	PASS
Extreme(70℃)		8.41	4.26	0.00447	0.00226	PASS
Extreme(60℃)		3.48	6.31	0.00185	0.00335	PASS
Extreme(50℃)		6.99	4.38	0.00372	0.00233	PASS
Extreme(40℃)		11.70	1.88	0.00622	0.00100	PASS
Extreme(30℃)		3.12	12.24	0.00166	0.00651	PASS
Extreme(20℃)		14.19	6.77	0.00755	0.00360	PASS
Extreme(10℃)		4.45	9.27	0.00237	0.00493	PASS
Extreme(0℃)		15.70	2.42	0.00835	0.00129	PASS
Extreme(-10℃)		5.83	12.55	0.00310	0.00668	PASS
Extreme(-20℃)		17.86	11.39	0.00950	0.00606	PASS
Extreme(-30℃)		11.24	9.63	0.00598	0.00512	PASS
Extreme(-40℃)		13.00	10.67	0.00691	0.00568	PASS
25℃	LV	5.63	6.47	0.00299	0.00344	PASS
	HV	15.44	9.40	0.00821	0.00500	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability(ppm)	Frequency Stability(ppm)	Verdict
Sub-carrier spacing (KHz)	15					
Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
Normal(25℃)	Normal	3.28	16.57	0.00174	0.00881	PASS
Extreme(85℃)		15.29	3.28	0.00813	0.00174	PASS
Extreme(80℃)		16.76	1.41	0.00892	0.00075	PASS
Extreme(70℃)		10.42	16.01	0.00554	0.00852	PASS
Extreme(60℃)		13.32	1.43	0.00708	0.00076	PASS
Extreme(50℃)		5.94	4.28	0.00316	0.00228	PASS
Extreme(40℃)		6.36	17.66	0.00339	0.00939	PASS
Extreme(30℃)		17.11	6.43	0.00910	0.00342	PASS
Extreme(20℃)		6.94	7.53	0.00369	0.00400	PASS
Extreme(10℃)		14.69	6.29	0.00781	0.00335	PASS
Extreme(0℃)		6.32	3.47	0.00336	0.00185	PASS
Extreme(-10℃)		9.86	13.35	0.00524	0.00710	PASS

**RF Test Report****Report No.: R2106A0549-R4**

Extreme(-20℃)		11.51	7.77	0.00612	0.00413	PASS
Extreme(-30℃)		5.21	13.97	0.00277	0.00743	PASS
Extreme(-40℃)		14.72	6.05	0.00783	0.00322	PASS
25℃	LV	11.54	8.37	0.00614	0.00445	PASS
	HV	14.79	7.79	0.00786	0.00414	PASS

## 5.5. Spurious Emissions at Antenna Terminals

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier.

The peak detector is used. RBW are set to 100 kHz and VBW are set to 300 kHz for below 1G, RBW are set to 1MHz and VBW are set to 3MHz for above 1G, Sweep is set to ATUO.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

### Test setup



### Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.”

Limit	-13 dBm
-------	---------

### Measurement Uncertainty


The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .

Frequency	Uncertainty
30MHz-1GHz	0.684 dB
1GHz-18GHz	1.407 dB

## Test Result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.

The signal beyond the limit is carrier.



## 5.6. Radiates Spurious Emission

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

### Method of Measurement

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26.
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW= 100kHz, VBW=300kHz, and the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:  
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$

The measurement results are amend as described below:


$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP

= EIRP-2.15dBi.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

## Test setup


### 9KHz ~ 30MHz



### 30MHz ~ 1GHz



### Above 1GHz



Note: Area side:2.4mX3.6m

**Limits**

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.”

Limit	-13 dBm
-------	---------

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U = 3.55$  dB.

## Test Result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

### BG95-M3:

#### NB-IoT Band 5 CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1648.2	-59.30	2.00	10.75	Horizontal	-52.70	-13.00	39.70	225
3	2472.3	-56.99	2.51	11.05	Horizontal	-50.60	-13.00	37.60	225
4	3296.4	-55.04	4.20	11.15	Horizontal	-50.24	-13.00	37.24	315
5	4120.5	-59.59	5.20	11.15	Horizontal	-55.79	-13.00	42.79	180
6	4944.6	-59.26	5.50	11.95	Horizontal	-54.96	-13.00	41.96	90
7	5768.7	-60.02	5.70	13.55	Horizontal	-54.32	-13.00	41.32	45
8	6592.8	-56.52	6.30	13.75	Horizontal	-51.22	-13.00	38.22	90
9	7416.9	-54.08	6.80	13.85	Horizontal	-49.18	-13.00	36.18	135
10	8241.0	-54.27	6.90	14.25	Horizontal	-49.07	-13.00	36.07	180

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

#### NB-IoT Band 5 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-56.47	2.00	10.75	Horizontal	-49.87	-13.00	36.87	90
3	2509.5	-53.26	2.51	11.05	Horizontal	-46.87	-13.00	33.87	90
4	3346.0	-58.60	4.20	11.15	Horizontal	-53.80	-13.00	40.80	45
5	4182.5	-60.86	5.20	11.15	Horizontal	-57.06	-13.00	44.06	225
6	5019.0	-59.53	5.50	11.95	Horizontal	-55.23	-13.00	42.23	180
7	5855.5	-60.94	5.70	13.55	Horizontal	-55.24	-13.00	42.24	180
8	6692.0	-59.01	6.30	13.75	Horizontal	-53.71	-13.00	40.71	90
9	7528.5	-55.53	6.80	13.85	Horizontal	-50.63	-13.00	37.63	45
10	8365.0	-56.31	6.90	14.25	Horizontal	-51.11	-13.00	38.11	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



## NB-IoT Band 5 CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1697.8	-55.59	2.00	10.75	Horizontal	-48.99	-13.00	35.99	45
3	2546.7	-52.38	2.51	11.05	Horizontal	-45.99	-13.00	32.99	270
4	3395.6	-62.49	4.20	11.15	Horizontal	-57.69	-13.00	44.69	135
5	4244.5	-60.04	5.20	11.15	Horizontal	-56.24	-13.00	43.24	180
6	5093.4	-59.22	5.50	11.95	Horizontal	-54.92	-13.00	41.92	315
7	5942.3	-60.58	5.70	13.55	Horizontal	-54.88	-13.00	41.88	135
8	6791.2	-58.24	6.30	13.75	Horizontal	-52.94	-13.00	39.94	225
9	7640.1	-55.88	6.80	13.85	Horizontal	-50.98	-13.00	37.98	90
10	8489.0	-56.05	6.90	14.25	Horizontal	-50.85	-13.00	37.85	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

**BG95-M3 MINIPCIE:**

## NB-IoT Band 5 CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1648.2	-36.89	2.00	10.75	Horizontal	-30.29	-13.00	17.29	315
3	2472.3	-51.30	2.51	11.05	Horizontal	-44.91	-13.00	31.91	0
4	3296.4	-58.72	4.20	11.15	Horizontal	-53.92	-13.00	40.92	0
5	4120.5	-59.06	5.20	11.15	Horizontal	-55.26	-13.00	42.26	0
6	4944.6	-59.49	5.50	11.95	Horizontal	-55.19	-13.00	42.19	315
7	5768.7	-60.16	5.70	13.55	Horizontal	-54.46	-13.00	41.46	90
8	6592.8	-57.66	6.30	13.75	Horizontal	-52.36	-13.00	39.36	225
9	7416.9	-53.51	6.80	13.85	Horizontal	-48.61	-13.00	35.61	180
10	8241.0	-52.82	6.90	14.25	Horizontal	-47.62	-13.00	34.62	0

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

## NB-IoT Band 5 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1668.2	-36.96	2.00	10.75	Horizontal	-30.36	-13.00	17.36	180
3	2502.3	-49.85	2.51	11.05	Horizontal	-43.46	-13.00	30.46	45
4	3345.8	-58.79	4.20	11.15	Horizontal	-53.99	-13.00	40.99	45
5	4170.5	-58.56	5.20	11.15	Horizontal	-54.76	-13.00	41.76	90
6	5004.6	-57.33	5.50	11.95	Horizontal	-53.03	-13.00	40.03	180
7	5838.7	-59.27	5.70	13.55	Horizontal	-53.57	-13.00	40.57	0
8	6672.8	-55.99	6.30	13.75	Horizontal	-50.69	-13.00	37.69	315
9	7506.9	-53.81	6.80	13.85	Horizontal	-48.91	-13.00	35.91	270
10	8341.0	-53.48	6.90	14.25	Horizontal	-48.28	-13.00	35.28	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

## NB-IoT Band 5 CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1697.8	-38.62	2.00	10.75	Horizontal	-32.02	-13.00	19.02	315
3	2546.7	-47.63	2.51	11.05	Horizontal	-41.24	-13.00	28.24	225
4	3395.6	-62.73	4.20	11.15	Horizontal	-57.93	-13.00	44.93	315
5	4244.5	-59.36	5.20	11.15	Horizontal	-55.56	-13.00	42.56	315
6	5093.4	-57.00	5.50	11.95	Horizontal	-52.70	-13.00	39.70	225
7	5942.3	-58.01	5.70	13.55	Horizontal	-52.31	-13.00	39.31	180
8	6791.2	-56.68	6.30	13.75	Horizontal	-51.38	-13.00	38.38	45
9	7640.1	-54.17	6.80	13.85	Horizontal	-49.27	-13.00	36.27	270
10	8489.0	-54.86	6.90	14.25	Horizontal	-49.66	-13.00	36.66	0
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2.The worst emission was found in the antenna is Horizontal position.									



## 6. Main Test Instruments

June 6, 2020:

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	113824	2020-05-18	2021-05-17
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	/	/
Spectrum Analyzer	Key sight	N9010A	MY50210259	2020-05-18	2021-05-17
Universal Radio Communication Tester	Key sight	E5515C	MY48367192	2020-05-27	2021-05-26
Signal Analyzer	R&S	FSV30	100815	2019-12-15	2020-12-14
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2017-09-26	2020-09-25
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	102723	2018-08-11	2021-08-10
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2021-06-19
Signal generator	R&S	SMB 100A	102594	2020-05-18	2021-05-17
Climatic Chamber	ESPEC	SU-242	93000506	2017-12-17	2020-12-16
Preamplifier	R&S	SCU18	102327	2020-05-18	2021-05-17
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2020-05-18	2021-05-17
RF Cable	Agilent	SMA 15cm	0001	2020-06-12	2020-12-11
Software	R&S	EMC32	9.26.0	/	/
Wireless Test Set	StarPoint	SP8315	SP8315-1202	2020-05-18	2021-05-17
Wireless Test Set	StarPoint	SP8315	SP8315-1203	2020-05-18	2021-05-17



Date of Testing (variant): July 14, 2021 ~ August 9, 2021

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	113645	2021-05-15	2022-05-14
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	/	/
Spectrum Analyzer	Key sight	N9010A	MY50210259	2021-05-15	2022-05-14
Universal Radio Communication Tester	Key sight	E5515C	MY48367192	2021-05-15	2022-05-14
Signal Analyzer	R&S	FSV3030	101411	2020-12-13	2021-12-12
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2020-04-02	2023-04-01
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	391	2019-12-16	2021-12-15
Horn Antenna	R&S	HF907	102723	2018-08-11	2021-08-10
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2023-06-19
Signal generator	R&S	SMB 100A	180235	2021-05-15	2022-05-14
Climatic Chamber	ESPEC	SU-242	93000506	2020-12-13	2021-12-12
Preamplifier	R&S	SCU18	102327	2021-05-15	2022-05-14
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2021-05-15	2022-05-14
RF Cable	Agilent	SMA 15cm	0001	2020-06-12	2020-12-11
Software	R&S	EMC32	9.26.0	/	/
Wireless Test Set	StarPoint	SP8315	SP8315-1202	2021-05-15	2022-05-14
Wireless Test Set	StarPoint	SP8315	SP8315-1203	2021-05-15	2022-05-14

\*\*\*\*\*END OF REPORT \*\*\*\*\*



## **ANNEX A: The EUT Appearance**

The EUT Appearance are submitted separately.



## **ANNEX B: Test Setup Photos**

The Test Setup Photos are submitted separately.



## **ANNEX C: Product Change Description**

The Product Change Description are submitted separately.