

RF Exposure Report

Report No.: AGC12849240701FH01

FCC ID	:	2AI02-BTD0140
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Bluetooth Dongle
BRAND NAME	:	DEQING®
MODEL NAME	:	BTD0140 (Series model name please see page 5)
APPLICANT	:	Dellking Industrial Co., Ltd
DATE OF ISSUE	:	Jul. 18, 2024
STANDARD(S)	:	FCC KDB 447498 D01 V06
REPORT VERSION	:	V1.0







Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jul. 18, 2024	Valid	Initial Release



Table of Contents

1. General Information	
2. Product Information	5
2.1 Product Technical Description	5
3. Test Environment	6
3.1 Address Of The Test Laboratory	6
3.2 Test Facility	6
3.3 Environmental Conditions	
4. Portable Device Evaluation Method and Limit	8
5. Mobile Device Evaluation Method and Limit	9
6. Measurement Results	10
7. Measurement Evaluation	



1. General Information

Applicant	Dellking Industrial Co., Ltd
Address	4 / F, building 8, phase I, Lianchuang Science Park, Bulan Road, Longgang District, Shenzhen, China
Manufacturer	Dellking Industrial Co., Ltd
Address	4 / F, building 8, phase I, Lianchuang Science Park, Bulan Road, Longgang District, Shenzhen, China
Factory	Dellking Industrial Co., Ltd
Address	4 / F, building 8, phase I, Lianchuang Science Park, Bulan Road, Longgang District, Shenzhen, China
Product Designation	Bluetooth Dongle
Brand Name	DEQING®
Test Model	BTD0140
Series Model(s)	Please see page 5
Difference Description	Please see page 5
Date of receipt of test item	Jul. 03, 2024
Date of Test	Jul. 03, 2024~Jul. 18, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-RF Exposure-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By

Bibo zhang

Bibo Zhang (Project Engineer)

Jul. 18, 2024

Reviewed By

Calvin Liu (Reviewer)


Jul. 18, 2024

Approved By

Max Zhan

Max Zhang Authorized Officer

Jul. 18, 2024





2. Product Information

2.1 Product Technical Description

Frequency Band (Operating)	⊠Bluetooth: 2.402GHz ~ 2.480GHz ☐Other:		
Hardware Version	BTD0140-A_V9		
Software Version	BTD0140_PoliceRide_V181_BLE		
Modulation Type	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK BLE ⊠GFSK 1Mbps ⊡GFSK 2Mbps		
Maximum Transmitter Power	BT_BR: 5.161 dBm BT_BLE: 1.996 dBm		
Device Category	 Portable (<20cm separation) Mobile (>20cm separation) Others: 		
Antenna Diversity	□Single antenna Multiple antennas □Tx diversity □Rx diversity □Tx/Rx diversity		
Antenna Designation BT_BR: Wire Antenna BT_BLE: PCB Antenna			
Antenna Gain	BT_BR: 5.004dBi BT_BLE: 1.93dBi		
Minimum Assessment Distance	5mm		
Evaluation Applied	☐MPE Evaluation ☑SAR Evaluation		

Series Model List:

	BTD 0100 BTD 0120 BTD 0120 A BTD 0061 BTD 0087 BTD 0080
	BTD-0100, BTD-0129, BTD-0129-A, BTD-0061, BTD-0087, BTD-0089,
	BTD-0140AN, BTD-0140A, BTD-200, BTD-3000, BTD-3280, BTD-5800,
	BTD-5800-A, BTD-5800-B, BTD-5800-C, BTD-6800K, BTD-6800M1A, BTD-790,
	BTD-8038, BTD-815, BTD-850, BTD-850WA, BTA-002TC, BTD-R7, BTD-1200,
	BTD-1300, BTD-300, BTD-3688, BTD-400, BTD-405, BTD-410, BTD-415,
	BTD-450/BTD-452, BTD-455, BTD-500, BTD-500S, BTD-506, BTD-510, BTD-560,
	BTD-580H, BTD-585, BTD-590, BTD-596, BTD-600, BTD-610, BTD-612, BTD-620,
	BTD-630, BTD-636, BTD-650, BTD-6600, BTD-680, BTD-682, BTD-690, BTD-700,
	BTD-700G, BTD-720, BTD-820, BTD-8200, BTD-8268, BTD-860, BTD-8608,
	BTD-880, BTD-890, BTD-900, BTD-910, BTD-990, BTD-960, DB0100-DSP,
Series Model(s)	DB0129-DSP, DB0061-DSP, DB0087-DSP, DB0089-DSP, DB0140-DSP,
	DB200-DSP, DB3000-DSP, DB3280-DSP, DB5800-DSP, DB6800-DSP,
	DB790-DSP, DB8038-DSP, DB815-DSP, DB850-DSP, DB002-DSP, DBR7-DSP,
	DB1200-DSP, DB1300-DSP, DB300-DSP, DB3688-DSP, DB400-DSP, DB405-DSP,
	DB410-DSP, DB415-DSP, DB450-DSP/DB452-DSP, DB455-DSP, DB500-DSP,
	DB500S-DSP, DB506-DSP, DB510-DSP, DB560-DSP, DB580H-DSP, DB585-DSP,
	DB590-DSP, DB596-DSP, DB600-DSP, DB610-DSP, DB612-DSP, DB620-DSP,
	DB630-DSP, DB636-DSP, DB650-DSP, DB6600-DSP, DB680-DSP, DB682-DSP,
	DB690-DSP, DB700-DSP, DB700G-DSP, DB720-DSP, DB820-DSP, DB8200-DSP,
	DB8268-DSP, DB860-DSP, DB8608-DSP, DB880-DSP, DB890-DSP, DB900-DSP,
	DB910-DSP, DB960-DSP, DB990-DSP
Difference Description	All the same except for the model names.



3. Test Environment

3.1 Address Of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	NORMAL CONDITIONS		
Temperature range (℃)	15 - 35		
Relative humidity range	20 % - 75 %		
Pressure range (kPa)	86 - 106		
Power supply	DC 5V		
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.			



4. Portable Device Evaluation Method and Limit

Following FCC KDB 447498 D01 "General SAR test exclusion guidance" The corresponding SAR Exclusion Threshold condition, listed below:

- The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances <50 mm are determined by:</p>
 - > [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where
 - ➢ f(GHz) is the RF channel transmit frequency in GHz.
 - > Power and distance are rounded to the nearest mW and mm before calculation.
 - The result is rounded to one decimal place for comparison The test exclusions are applicable only when the minimum test separation distance is <50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.</p>
- At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:
 - [Threshold at 50 mm in step 1) + (test separation distance 50mm) (f(MHz)/150)] mW, at 100MHz to 1500 MHz;
 - [Threshold at 50 mm in step 1) + (test separation distance 50 mm)-10] mW at > 1500 MHz and <6 GHz;</p>
- At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
 - The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by [1 + log(100/f(MHz))] for test separation distances > 50 mm and < 200 mm.</p>
 - > The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by 1/2 for test separation distances \leq 50 mm.
 - SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.



5. Mobile Device Evaluation Method and Limit

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

Limits For General Population / Uncontrolled Exposure					
Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ² , H ² or S (Minutes)	
0.3 1.34	614	1.63	(100)*	30	
1.34 30	824/f	2.19/f	(180/f ²)*	30	
30 300	27.5	0.073	0.2	30	
300 1500			f/1500	30	
1500 100,000			1.0	30	

Limits For General Population / Uncontrolled Exposure

*Note:

1. f= Frequency in MHz * Plane-wave Equivalent Power Density

2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

The calculation formula of MPE measurement is as follows:

- S=PG/4πR²
- Where:
- S=power density
- P=power input to antenna
- G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna



6. Measurement Results

Test Mode	Channel Frequency (MHz)	Max Output power (dBm)	Max Output power (mW)	Calculation Value (Note 1)	Limit Value	
GFSK						
BT_BR	2480	5.161	3.282	1.034	3.0	
GFSK						
BT_BLE	2480	2.096	1.620	0.510	3.0	

Note:

- 1. Calculation Value =[(max. power of channel, mW)/(min. test separation distance, mm)] ·[√f(GHz)]. Fox example: 3.282 /5*√2.480=1.034 ≤ 3.0
- 2. The wireless function BT_BR and BT_BLE of the device can transmit at the same time, and the final exemption result is 1.034 + 0.510 < 3.0.

According to KDB447498 D01 V06, threshold at which no SAR required is ≤3.0 for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.

7. Measurement Evaluation

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.

-----End of Report-----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.