

MPE CALCULATION

FCC ID: 7280B-120502

RF Exposure Requirements:	47 CFR §1. 1307(b)
RF Radiation Exposure Limits:	47 CFR §1. 1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65
EUT Frequency Band:	802.11a: 5180-5320MHz; 5500-5700MHz; 5745-5825MHz 802.11n-20M: 5180-5320MHz; 5500-5700MHz; 5745-5825MHz 802.11n-40M: 5190-5310MHz; 5510-5670MHz; 5755-5795MHz 802.11ac-80M: 5210MHz, 5290MHz, 5530MHz, 5775MHz

Limits for General Population/Uncontrolled Exposure in the band of: 1500 - 100,000 MHz

Power Density Limit: 1 mW / cm²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$
Where, S = Power Density
P = Power Input to Antenna
G = Antenna Gain
R = distance to the center of radiated antenna

Prediction distance 20cm
Target power = 20.00 dBm
Tune up power tolerance = 1.05dBm
Max Tune up power = 21.05 dBm

MPE calculation: Max Tune up Power = 21.05 dBm, Directional antenna gain = 8.764 dBi, Power density= 0.1906 mW/cm²

Maximum MPE = 0.1906 mW/cm², which is less than 1 mW/cm².

The Above Result had shown that the device complied with MPE requirement.

Completed By: Angel Escamilla *Angel Escamilla*

SIEMIC, Inc
775 Montague Expressway, Milpitas, CA 95035
Phone: (408) 526-1188
Date: December 17, 2014