

TEST REPORT

Product Name : Car Multimedia Player
Brand Mark : Dual
Model No. : DV712
Extension model : XDVD176BT, DV715B, XDVD600,
XDVD156BT, DV517BT, DV171BT,
DV171B, AV7118Bi
FCC ID : 2AFXA-DV712
Report Number : BLA-EMC-202202-A4503
Date of Sample Receipt : 2022/3/4
Date of Test : 2022/3/4 to 2022/6/15
Date of Issue : 2022/6/15
Test Standard : 47 CFR Part 1.1307, Part 1.1310
Test Result : Pass

Prepared for:

FengShun Peiying Electro-Acoustic Co., Ltd
No.8, Fengda Road, Tangkeng Town Ind. Area, Fengshun
County, Guangdong, China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by:

Jozu

Approved by:

Blue Zhong

Review by:

Sueels

Date:

2022/6/15



REPORT REVISE RECORD

Version No.	Date	Description
00	2022/6/15	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY	4
2	GENERAL INFORMATION	5
3	GENERAL DESCRIPTION OF E.U.T.	5
4	LABORATORY LOCATION	6
5	RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.1	LIMITS	7
5.2	TEST PROCEDURE	7
5.3	EUT RF EXPOSURE EVALUATION	8

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 1.1310	CFR 47 Part 1.1310	CFR 47 Part 1.1310	PASS

2 GENERAL INFORMATION

Applicant	FengShun Peiying Electro-Acoustic Co., Ltd
Address	No.8, Fengda Road, Tangkeng Town Ind. Area, Fengshun County, Guangdong, China
Manufacturer	FengShun Peiying Electro-Acoustic Co., Ltd
Address	No.8, Fengda Road, Tangkeng Town Ind. Area, Fengshun County, Guangdong, China
Factory	FengShun Peiying Electro-Acoustic Co., Ltd
Address	No.8, Fengda Road, Tangkeng Town Ind. Area, Fengshun County, Guangdong, China
Product Name	Car Multimedia Player
Test Model No.	DV712
Extension model	XDVD176BT, DV715B, XDVD600, XDVD156BT, DV517BT, DV171BT, DV171B, AV7118Bi
Note	All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose.

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V02
Software Version	V712H.8201.13R
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, pi/4DQPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi(Provided by the applicant)

4 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 LIMITS

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.2 TEST PROCEDURE

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5.3 EUT RF EXPOSURE EVALUATION

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.000 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

EDR:

Channel	Frequency (MHz)	Max Conducted Peak Output	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Middle	2441	-1.876	0.649	0.0001	1.0	PASS

Note: Refer to report No. BLA-EMC-202202-A4501 for EUT test Max Conducted Peak Output Power value.

The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation Requirement

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.