



TESTING LABORATORY  
CERTIFICATE#4323.01



FCC PART 15.231

## TEST REPORT

For

**Micron Electronics LLC.**

1001 Yamato Road, Suite 400, Boca Raton, Florida 33431 United States

**FCC ID: ZKQ-PP0D4G**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Tracker
<b>Test Engineer:</b>	Stone Zhang <i>Stone Zhang</i>
<b>Report Number:</b>	RSHA200325001-00B
<b>Report Date:</b>	2020-08-06
<b>Reviewed By:</b>	Oscar Ye <i>Oscar Ye</i> EMC Manager
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY .....	3
MEASUREMENT UNCERTAINTY .....	4
TEST FACILITY .....	4
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
JUSTIFICATION .....	5
EUT EXERCISE SOFTWARE .....	5
EQUIPMENT MODIFICATIONS .....	5
SUPPORT EQUIPMENT LIST AND DETAILS .....	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP .....	6
<b>SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>8</b>
<b>FCC§15.203 - ANTENNA REQUIREMENT.....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
ANTENNA CONNECTED CONSTRUCTION .....	9
<b>FCC §15.205, §15.209, §15.231 (E) - RADIATED EMISSIONS .....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
EUT SETUP .....	10
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE .....	11
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	11
TEST RESULTS SUMMARY .....	12
TEST DATA .....	12
<b>FCC §15.231(C) - 20DB EMISSION BANDWIDTH TESTING.....</b>	<b>15</b>
APPLICABLE STANDARD .....	15
TEST PROCEDURE .....	15
TEST DATA .....	15
<b>FCC §15.231(E) - DEACTIVATION TESTING .....</b>	<b>17</b>
APPLICABLE STANDARD .....	17
EUT SETUP .....	17
TEST DATA .....	17

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Applicant	Micron Electronics LLC.
Tested Model	Pod1
Product Type	Tracker
Power Supply	DC 3.6V from Lithium battery pack
RF Function	SRD
Operating Band/Frequency	433 MHz
Channel Number	1
Modulation Type	FSK
Antenna Type	Helical Antenna
Maximum Antenna Gain	2.0 dBi

*\*All measurement and test data in this report was gathered from production sample serial number: 20200325001. (Assigned by the BACL. The EUT supplied by the applicant was received on 2020-03-25)*

### Objective

This test report is prepared on behalf of *Micron Electronics LLC*. All the test measurements were performed according to the measurement procedure described in ANSI C63.10 - 2013.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209, 15.35(c) and 15.231 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15B JAB and Part 15.247 DTS submittal with FCC ID: ZKQ-PPOD4G.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10 - 2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz ~18GHz	5.23dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

**SYSTEM TEST CONFIGURATION****Justification**

Channel List:

Channel	Frequency (MHz)
1	433

**EUT Exercise Software**

RF test software: SecureCRT

**Equipment Modifications**

No modification was made to the EUT.

**Support Equipment List and Details**

Manufacturer	Description	Model	Serial Number
/	/	/	/


**External I/O Cable**

Cable Description	Length (m)	From Port	To
/	/	/	/

## Block Diagram of Test Setup


For Radiated Emissions (Below 1GHz):

Turntable  
2m Diameter



For Radiated Emissions (Above 1GHz):

Turntable  
2m Diameter



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	Conducted Emissions	Not Applicable (See Note)
§15.205, §15.209, §15.231(e)	Radiated Emissions	Compliant
§15.231 (c)	20dB Emission Bandwidth	Compliant
§15.231 (e)	Deactivation	Compliant

Note: The EUT is powered by battery.

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test(Chamber 1#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-12-14	2020-12-13
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2019-08-05	2020-08-04
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2020-08-05	2021-08-04
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrunent	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
<b>Radiated Emission Test(Chamber 2#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
A.H.Systems,inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-12-12	2020-12-11
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).



---

## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **Antenna Connected Construction**

The EUT has a Helical antenna for 433MHz which was permanently attached and the antenna gain is 2.0 dBi; fulfill the requirement of this section. Please refer to EUT photos.

**Result:** Compliant.

**FCC §15.205, §15.209, §15.231 (e) - RADIATED EMISSIONS****Applicable Standard**


FCC §15.205, §15.209, §15.231 (e)


According to §15.231 (e), the field strength of emissions from intentional radiators operated under this section shall not exceed the following

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emission (microvolts/meter)
40.66-40.70	1,000	100
70-130	500	50
130-174	500 to 1,500 *	50 to 150 *
174-260	1,500	150
260-470	1,500 to 5,000 *	150 to 500*
Above 470	5,000	500

\*Linear interpolations.

The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

**EUT Setup****Below 1GHz:**

**Above 1 GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10 - 2013. The specification used was the FCC 15 § 15.209, 15.205 and 15.231.

**EMI Test Receiver Setup**

The system was investigated from 30 MHz to 5 GHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000MHz	100 kHz	300 kHz	/	QP
1000MHz – 5000MHz	1MHz	3MHz	/	PK

**Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

**Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB $\mu$ V /m) = Meter Reading (dB $\mu$ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V /m)}$$

**Test Results Summary**

According to the data in the following table, the EUT complied with the FCC §15.205, §15.209, §15.231 (e).

**Test Data****Environmental Conditions**


<b>Temperature:</b>	21.1 °C
<b>Relative Humidity:</b>	52 %
<b>ATM Pressure:</b>	101.6 kPa

*The testing was performed by Stone Zhang on 2020-04-15.*

*Test mode: Transmitting*

**30MHz-1GHz**

(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded.)




Frequency (MHz)	Corrected Amplitude MaxPeak (dBµV /m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)	Remark
		Height (cm)	Polar (H/V)					
30.97	30.25	200	V	257	-4.6	52.84	22.59	Spurious emission
66.25	17.06	100	V	211	-17.5	52.84	35.78	
128.94	22.73	200	H	324	-11.6	43.50	20.77	
202.05	22.49	100	V	77	-12.3	52.84	30.35	
866.00	50.11	100	H	247	-0.7	52.84	2.73	
433.00	61.39	100	V	124	-7.7	72.84	11.45	Fundamental

**Note:**

If the spurious emissions maximized peak measured value complies with the QP/Average limit, it is unnecessary to perform an QP/Average measurement.

**1GHz-5 GHz**

(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded.)



Frequency (MHz)	Corrected Amplitude MaxPeak (dBμV/m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
		Height (cm)	Polar (H/V)				
1300.5	34.07	150	V	5	-11.0	54.00	19.93
1734.0	33.78	200	V	249	-9.1	54.00	20.22
2167.5	35.02	200	H	30	-7.8	54.00	18.98
2601.0	36.57	150	V	144	-6.4	54.00	17.43
3034.5	38.51	150	V	183	-4.3	54.00	15.49
3468.0	40.34	200	V	317	-3.6	54.00	13.66

**Note 1:**

If the spurious emissions maximized peak measured value complies with the Average limit, it is unnecessary to perform an Average measurement.

**Note 2:**

Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

## **FCC §15.231(c) - 20dB EMISSION BANDWIDTH TESTING**

### **Applicable Standard**

Per 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	25.3 °C
<b>Relative Humidity:</b>	51 %
<b>ATM Pressure:</b>	101.2 kPa


*The testing was performed by Stone Zhang on 2020-08-06.*

*Test Mode: Transmitting*

Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (kHz)	Result
433	13.748	1082.5	Pass

**Note:** Limit = 0.25% \* Center Frequency = 0.25% \* 433 MHz = 1082.5 kHz

### 20 dB Emission Bandwidth






## FCC §15.231(e) - DEACTIVATION TESTING

### Applicable Standard

Per 15.231(e), devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

### EUT Setup



The deactivation test was performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10- 2013. The specification used was the FCC 15.231(e) limits.

### Test Data

#### Environmental Conditions

Temperature:	24.3 °C
Relative Humidity:	53 %
ATM Pressure:	101.2 kPa

The testing was performed by Stone Zhang on 2020-04-15.

Test mode: Transmitting

**Deactivation**

<b>duration (s)</b>	<b>Limit (s)</b>	<b>Result</b>
0.643	< 1	Pass

**Silent period**


<b>Silent period (s)</b>	<b>Limit (s)</b>	<b>Result</b>
24.351	>19.29	Pass

**Note:**

The silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.


The duration time is 0.643s,  $0.643 \times 30 = 19.29\text{s}$ .

### Silent period



Date: 15 APR 2020 09:30:49

### Duration



Date: 15 APR 2020 09:36:20

### **Declarations**

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '\*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***