

TEST REPORT

Applicant: Shantou Chenghai Lihuang Plastic Toys Co.,Ltd

Address of Applicant: No.1,1 Road, Huaihe Industrial park,Lianxia,Chenghai,Shantou, China

Manufacturer: Shantou Chenghai Lihuang Plastic Toys Co.,Ltd

Address of Manufacturer: No.1,1 Road, Huaihe Industrial park,Lianxia,Chenghai,Shantou, China

Equipment Under Test (EUT)

Product Name: remote controlled aircraft

Model No.: Refer to page 5.

Trade Mark: N/A

FCC ID: 2AJGILHWJX555

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249

Date of sample receipt: 13 August 2020

Date of Test: 13 August 2020 ~ 30 August 2020

Date of report issued: 31 August 2020

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue ink stamp from GTS Global United Technology Services Co., Ltd. is visible. The stamp contains the text "GTS", "GLOBAL UNITED TECHNOLOGY SERVICES CO., LTD.", and "LABORATORY TESTING". Overlaid on the stamp is a handwritten signature in blue ink that appears to read "Robinson Lo".

Robinson Lo


Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	Aug. 31, 2020	Original

Prepared By:




Date:

Aug. 31, 2020

Project Engineer

Check By:



Date:

Aug. 31, 2020

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 RADIATED EMISSION METHOD	11
7.2.1 Duty cycle measurement:	13
7.2.2 Field Strength of The Fundamental Signal	14
7.2.3 Spurious emissions	15
7.2.4 Bandedge emissions	20
7.3 20dB OCCUPY BANDWIDTH	21
8 TEST SETUP PHOTO	24
9 EUT CONSTRUCTIONAL DETAILS	24

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. Test according to ANSI C63.10: 2013.
2. Pass: The EUT complies with the essential requirements in the standard.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	remote controlled aircraft
Model No.:	LH-X55, LH-X54,LH-X53,LH-X52,LH-X51,LH-X49,LH-X43,LH-X41F,LH-X41WF,LH-X38,LH-X40,LH-X35,LH-X34,LH-X33,LH-X31,LH-X30,LH-X25,LH-X28,LH-X26,LH-X27,LH-X21,LH-X20,LH-X56,LH-X57,LH-X58,LH-X59,LH-X60,LH-X61,LH-X22,LH-X46,LH-X48,LH-X15,LH-X16,LH-X13,LH-X31,LH-C021A,LH-C022B,LH-C006,LH-C008,LH-C009,LH-C010,LH-C011,LH-C010B-1,LH-C010B-2,LH-C012,LH-C013,LH-C014,LH-C015,LH-C016S,LH-C019S,LH-C018,LH-C020,LH-C021B,LH-C022A,LH-C023A,LH-C023B,LH-C025,LH-C026,LH-C027,LH-C028,LH-C029,LH-C030,LH-C031,LH-C032,LH-C033,LH-C021S,LH-C022S,LH-C023SA,LH-C014S,LH-C013S,LH-C020S,LH-1302,LH-1303,1302,LH-1201,LH-1301,H002,LH-1206B,LH-1306,LH-1605,LH-1801,LH-1802,LH-1803,LH-1804,LH-1804R,F001,F014,F021,LH-1802R,LH-X50,LH-C009A,LH-1302,MT1324,JH115771,LH-1602,MT1322,JH996997,MT1323,JH115934,LH-1601,LH-C025A-2,LH-C025A-1,LH-C025A-3,H010
Test Model No.:	LH-X55
<i>Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The difference is product appearance and model name for commercial purpose.</i>	
Serial No.:	/
Hardware Version:	/
Software Version:	/
Test sample(s) ID:	GTS202008000225-01
Sample(s) Status	Engineered sample
Operation Frequency:	2441MHz~2476MHz
Channel numbers:	11
Modulation type:	GFSK
Antenna Type:	Integral antenna
Antenna gain:	0dBi(declare by applicant)
Power supply:	DC 6V("AA" Battery*4)

Operation Frequency each of channel			
Channel	Frequency	Channel	Frequency
1	2441MHz	7	2462MHz
2	2446MHz	8	2467MHz
3	2451MHz	9	2470MHz
4	2454MHz	10	2474MHz
5	2458MHz	11	2476MHz
6	2459MHz	-	-

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2441MHz
The middle channel	2459MHz
The Highest channel	2476MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: new battery is used during all test	

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	88.56	91.65	74.63

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

- **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 25 2020	June. 24 2021
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 25 2020	June. 24 2021
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 25 2020	June. 24 2021
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 25 2020	June. 24 2021
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 25 2020	June. 24 2021
9	Coaxial Cable	GTS	N/A	GTS211	June. 25 2020	June. 24 2021
10	Coaxial cable	GTS	N/A	GTS210	June. 25 2020	June. 24 2021
11	Coaxial Cable	GTS	N/A	GTS212	June. 25 2020	June. 24 2021
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 25 2020	June. 24 2021
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 25 2020	June. 24 2021
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 25 2020	June. 24 2021
15	Band filter	Amindeon	82346	GTS219	June. 25 2020	June. 24 2021
16	Power Meter	Anritsu	ML2495A	GTS540	June. 25 2020	June. 24 2021
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 25 2020	June. 24 2021
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 25 2020	June. 24 2021
19	Splitter	Agilent	11636B	GTS237	June. 25 2020	June. 24 2021
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 25 2020	June. 24 2021
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 25 2020	June. 24 2021

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 25 2020	June. 24 2021
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 25 2020	June. 24 2021
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 25 2020	June. 24 2021
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 25 2020	June. 24 2021
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 25 2020	June. 24 2021
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 25 2020	June. 24 2021
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 25 2020	June. 24 2021


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 25 2020	June. 24 2021
2	Barometer	ChangChun	DYM3	GTS255	June. 25 2020	June. 24 2021



7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
<i>The antenna is Integral antenna, the best case gain of the antenna is 0dBi, reference to the appendix II for details</i>	


7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	2400MHz-2483.5MHz		94.00		Average Value
			114.00		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (uV/m)		Remark
	0.009MHz-0.490MHz		2400/F(kHz) @300m		Quasi-peak Value
	0.490MHz-1.705MHz		24000/F(kHz) @30m		Quasi-peak Value
	1.705MHz-30.0MHz		30 @30m		Quasi-peak Value
	30MHz-88MHz		100 @3m		Quasi-peak Value
	88MHz-216MHz		150 @3m		Quasi-peak Value
	216MHz-960MHz		200 @3m		Quasi-peak Value
	960MHz-1GHz		500 @3m		Quasi-peak Value
	Above 1GHz		500 @3m		Average Value
			5000 @3m		Peak Value
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	For radiated emissions from 9kHz to 30MHz				
					
	For radiated emissions from 30MHz to 1GHz				

	 For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1012mbar
Test voltage:	DC 3V
Test results:	Pass

Measurement data:

7.2.1 Duty cycle measurement:



Dutycycle= 0.883778/3.963249= 0.223

7.2.2 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2441	92.14	-5.34	86.80	114.0 0	-27.20	Vertical
2441	96.99	-5.34	91.65	114.0 0	-22.35	Horizontal
2459	87.42	-5.21	82.21	114.0 0	-31.79	Vertical
2459	90.72	-5.21	85.51	114.0 0	-28.49	Horizontal
2476	88.39	-5.03	83.36	114.0 0	-30.64	Vertical
2476	90.47	-5.03	85.44	114.0 0	-28.56	Horizontal

Note:

For fundamental frequency , RBW >20dB BW , VBW>RBW ,PK detector for PK value correct

Factor= Antenna Factor + Cable Loss - Preamplifier Factor

Average value:

Frequency (MHz)	Read Level (dBuV)	Dutycycle Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2441	86.80	-13.03	73.77	94.00	-20.23	Vertical
2441	91.65		78.62	94.00	-15.38	Horizontal
2459	82.21		69.18	94.00	-24.82	Vertical
2459	85.51		72.48	94.00	-21.52	Horizontal
2476	83.36		70.33	94.00	-23.67	Vertical
2476	85.44		72.41	94.00	-21.59	Horizontal

Note: Dutycycle Factor=20log(Dutycycle)=20log0.223=-13.03

7.2.3 Spurious emissions


■ Below 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

■ Below 1GHz


Horizontal:

80.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		33.4449	26.38	-5.02	21.36	40.00	-18.64	peak
2		206.3976	25.09	-4.93	20.16	43.50	-23.34	peak
3		250.3012	31.45	-8.93	22.52	46.00	-23.48	peak
4		434.0651	26.65	-3.53	23.12	46.00	-22.88	peak
5		597.2234	24.39	3.03	27.42	46.00	-18.58	peak
6	*	787.8513	24.91	7.41	32.32	46.00	-13.68	peak

Vertical:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
		MHz	Level	Factor	ment		
			dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		39.8542	23.71	-1.96	21.75	40.00	-18.25 peak
2		159.7844	25.91	-6.54	19.37	43.50	-24.13 peak
3		250.3012	31.62	-8.93	22.69	46.00	-23.31 peak
4		434.0651	26.64	-0.95	25.69	46.00	-20.31 peak
5		528.2458	25.59	3.83	29.42	46.00	-16.58 peak
6	*	790.6188	25.10	7.67	32.77	46.00	-13.23 peak

■ Above 1GHz

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4888.151	51.39	5.15	56.54	74.00	-17.46	Vertical
7326.267	44.71	7.55	52.26	74.00	-21.74	Vertical
4888.151	59.18	5.15	64.33	74.00	-9.67	Horizontal
7326.267	48.45	7.55	56.00	74.00	-18.00	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Dutycycle Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4888.151	56.54	-13.03	43.51	54.00	-10.49	Vertical
7326.267	52.26	-13.03	39.23	54.00	-14.77	Vertical
4888.151	64.33	-13.03	51.3	54.00	-2.7	Horizontal
7326.267	56.00	-13.03	42.97	54.00	-11.03	Horizontal

Remarks:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *“*” means this data is too weak instrument of signal is unable to test.*
5. *Dutycycle Factor = 20log(Dutycycle)*

Test channel:	Middle
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4916.490	48.31	5.18	53.49	74.00	-20.51	Vertical
7390.070	46.11	7.84	53.95	74.00	-20.05	Vertical
4916.490	52.67	5.18	57.85	74.00	-16.15	Horizontal
7390.070	50.40	7.84	58.24	74.00	-15.76	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Dutycycle Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4916.490	53.49	-13.03	40.46	54.00	-13.54	Vertical
7390.070	53.95	-13.03	40.92	54.00	-13.08	Vertical
4916.490	57.85	-13.03	44.82	54.00	-9.18	Horizontal
7390.070	58.24	-13.03	45.21	54.00	-8.79	Horizontal

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. “*”, means this data is the too weak instrument of signal is unable to test.
5. Dutycycle Factor = $20\log(\text{Dutycycle})$

Test channel:	Highest
---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4959.307	45.75	5.22	50.97	74.00	-23.03	Vertical
7432.914	46.89	8.03	54.92	74.00	-19.08	Vertical
4959.307	50.33	5.22	55.55	74.00	-18.45	Horizontal
7432.914	51.73	8.03	59.76	74.00	-14.24	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Dutycycle Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4959.307	50.97	-13.03	37.94	54.00	-16.06	Vertical
7432.914	54.92	-13.03	41.89	54.00	-12.11	Vertical
4959.307	55.55	-13.03	42.52	54.00	-11.48	Horizontal
7432.914	59.76	-13.03	46.73	54.00	-7.27	Horizontal

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. “*”, means this data is the too weak instrument of signal is unable to test.
5. Dutycycle Factor = $20\log(\text{Dutycycle})$

7.2.4 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2390.000	39.18	-5.79	33.39	74.00	-40.61	Vertical
2400.000	39.60	-5.70	33.90	74.00	-40.10	Vertical
2390.000	39.52	-5.79	33.73	74.00	-40.27	Horizontal
2400.000	40.58	-5.70	34.88	74.00	-39.12	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Dutycycle Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
-	-	-	-	54.00	-	Vertical
-	-	-	-	54.00	-	Vertical
-	-	-	-	54.00	-	Horizontal
-	-	-	-	54.00	-	Horizontal

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2483.500	52.05	-4.98	47.07	74.00	-26.93	Vertical
2488.400	58.98	-4.93	54.05	74.00	-19.95	Vertical
2483.500	56.30	-4.98	51.32	74.00	-22.68	Horizontal
2488.200	63.47	-4.93	58.54	74.00	-15.46	Horizontal


Average value:

Frequency (MHz)	Read Level (dBuV)	Dutycycle Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2483.500	-	-	-	54.00	-	Vertical
2488.400	54.05	-13.03	41.02	54.00	-12.98	Vertical
2483.500	-	-	-	54.00	-	Horizontal
2488.200	58.54	-13.03	45.51	54.00	-8.49	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor
3. Dutycycle Factor = $20\log(\text{Dutycycle})$

7.3 20dB Occupy Bandwidth


Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data


Test channel	20dB bandwidth(MHz)	Result
Lowest	1.080	Pass
Middle	1.081	Pass
Highest	1.088	Pass

Test plot as follows:


Lowest channel



Middle channel



Highest channel



8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----