



Report Reference ID:	372837-2TRFWL
----------------------	---------------

Test specification:	<b>Title 47 – Telecommunication</b> Chapter I – Federal Communications Commission Subchapter D – Safety and special radio services Part 90 – Private land mobile services Subpart I – General technical standards
---------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Applicant:	TEKO Telecom Srl. Via Meucci, 24/a I-40024 Castel S. Pietro Terme (BO) (Italy)
Apparatus:	Medium Power Remote Unit
Model:	TRU7FL8P9PWM/AC-WT
FCC ID:	XM2-MP7FL8P9PP

Testing laboratory:	<b>Nemko Italy Spa</b> Via del Carroccio, 4 20853 Biassono (MB) – Italy Telephone: +39 039 2201201 Facsimile: +39 039 2201221
---------------------	-------------------------------------------------------------------------------------------------------------------------------------------

	Name and title	Date
Tested by:	 <hr/> P. Barbieri, Wireless/EMC Specialist	06/24/2019
Reviewed by:	 <hr/> R. Giampaglia, Wireless/EMC Specialist	06/24/2019

**Nemko Spa, 20853 Biassono (MB) - Italy. All rights reserved.**

This publication may be reproduced in whole for non-commercial purposes as long as Nemko Spa is acknowledged as copyright owner and source of the material. Nemko Spa takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. Nemko Spa accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This test report may not be partially reproduced, except with the prior written permission of Nemko Spa. The test report merely corresponds to the test sample. The phase of sampling / collection of equipment under test is carried out by the customer.

This Test Report, when bearing the Nemko name and logo is only valid when issued by a Nemko laboratory, or by a laboratory having special agreement with Nemko.

## Table of contents

<b>Section 1: Report summary .....</b>	<b>4</b>
1.1 Test specification.....	4
1.2 Statement of compliance .....	4
1.3 Exclusions .....	4
1.4 Registration number .....	4
1.5 Test report revision history .....	4
1.6 Limits of responsibility.....	4
<b>Section 2: Summary of test results .....</b>	<b>5</b>
2.1 FCC Part 90, test results .....	5
<b>Section 3: Equipment under test (EUT) and application details.....</b>	<b>6</b>
3.1 Applicant details .....	6
3.2 Modular equipment.....	6
3.3 Product details.....	6
3.4 Application purpose .....	6
3.5 Composite/related equipment .....	7
3.6 Sample information.....	7
3.7 EUT technical specifications .....	7
3.8 Accessories and support equipment.....	8
3.9 Operation of the EUT during testing.....	9
3.10 EUT setup diagram.....	9
<b>Section 4: Engineering considerations .....</b>	<b>11</b>
4.1 Modifications incorporated in the EUT .....	11
4.2 Deviations from laboratory tests procedures.....	11
4.3 Technical judgment .....	11
<b>Section 5: Test conditions .....</b>	<b>12</b>
5.1 Deviations from laboratory tests procedures.....	12
5.2 Test conditions, power source and ambient temperatures .....	12
5.3 Measurement uncertainty .....	13
5.4 Test equipment.....	14
<b>Appendix A: Test results.....</b>	<b>15</b>
Clause 935210 D05v01 (4.2) AGC threshold .....	15
Clause 935210 D05v01 (4.3) Out of band rejection .....	16
Clause 90.209, 90.219(e)(4) Occupied bandwidth .....	17
Clause 90.205, 90.219(e)(1) Output power at RF antenna connector .....	20
Clause 935210 D05v01 (4.6) Noise figure .....	23

Clause 90.543(c), 90.219(e)(3) Spurious emissions at the antenna terminal .....	24
Clause 90.543(c), 90.219(e)(3) Spurious emissions radiated.....	29
Clause 90.543(f) Radiated spurious emissions within 1559–1610 MHz band .....	35
<b>Appendix B: Block diagrams of test set-ups .....</b>	<b>38</b>
<b>Appendix C: EUT Photos.....</b>	<b>39</b>

## Section 1: Report summary

### 1.1 Test specification

<b>Specifications</b>	<b>Part 90 – Private land mobile services</b>
-----------------------	-----------------------------------------------

### 1.2 Statement of compliance

<b>Compliance</b>	<p>In the configuration tested the EUT was found compliant</p> <p>Yes <input checked="" type="checkbox"/> No <input type="checkbox"/></p> <p>This report contains an assessment of apparatus against specifications based upon tests carried out on samples submitted at Nemko Spa. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 90. Radiated tests were conducted in accordance with ANSI C63.26-2015.</p>
-------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### 1.3 Exclusions

<b>Exclusions</b>	None
-------------------	------

### 1.4 Registration number

<b>Test site FCC ID number</b>	682159
--------------------------------	--------

### 1.5 Test report revision history

Revision #	Details of changes made to test report
TRF	Original report issued
R1TRF	----

### 1.6 Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. Nemko Spa authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Spa accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

## Section 2: Summary of test results

### 2.1 FCC Part 90, test results

Part	Methods	Test description	Verdict
	§ 935210 D05v01r03 (4.2)	AGC threshold	Pass
	§ 935210 D05v01r03 (4.3)	Out of band rejection	Pass
§90.209 §90.219(e)(4)	§ 935210 D05v01r03 (4.4)	Occupied bandwidth	Pass
§90.205 §90.219(e)(1)	§ 935210 D05v01r03 (4.5)	Output power at RF antenna connector	Pass
§90.219(e)(2)	§ 935210 D05v01r03 (4.6)	Noise Figure	Pass
§90.543(c) §90.219(e)(3)	§ 935210 D05v01r03 (4.7)	Spurious emissions at RF antenna connector	Pass
§90.543(c) §90.219(e)(3)	§ 935210 D05v01r03 (4.9)	Radiated spurious emissions	Pass
§90.543(f) §90.219(e)(3)	§ 935210 D05v01r03 (4.9)	Radiated spurious emissions within 1559-1610 MHz band	Pass
§90.213	§ 935210 D05v01r03 (4.8)	Frequency stability	N/A a)
Notes: a) NOT APPLICABLE: Modulation/frequency conversion circuitry not in use. No frequency change in EUT (input and output have same frequency)			

## Section 3: Equipment under test (EUT) and application details

### 3.1 Applicant details

<b>Applicant complete business name</b>	Name:	Teko Telecom Srl
	Federal Registration Number (FRN):	0018963462
	Grantee code	XM2
<b>Mailing address</b>	Address:	Via Meucci, 24/a
	City:	Castel S. Pietro Terme
	Province/State:	Bologna
	Post code:	40024
	Country:	Italy

### 3.2 Modular equipment

<b>a) Single modular approval</b>	Single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>b) Limited single modular approval</b>	Limited single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>

### 3.3 Product details

<b>FCC ID</b>	Grantee code:	XM2
	Product code:	-MP7FL8P9PP
<b>Equipment class</b>	B9B	
<b>Description of product as it is marketed</b>	Booster	
	Model name/number:	TRU7FL8P9PWM/AC-WT
	Serial number:	1012793001

### 3.4 Application purpose

<b>Type of application</b>	<input checked="" type="checkbox"/>	Original certification
	<input type="checkbox"/>	Change in identification of presently authorized equipment
	<input type="checkbox"/>	Original FCC ID: Grant date:
	<input type="checkbox"/>	Class II permissive change or modification of presently authorized equipment

## Section 3: Equipment under test

### 3.5 Composite/related equipment

<b>a) Composite equipment</b>	The EUT is a composite device subject to an additional equipment authorization Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
<b>b) Related equipment</b>	The EUT is part of a system that operates with, or is marketed with, another device that requires an equipment authorization Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>c) Related FCC ID</b>	If either of the above is "yes": <input type="checkbox"/> has been granted under the FCC ID(s) listed below: <input type="checkbox"/> is in the process of being filled under the FCC ID(s) listed below: <input type="checkbox"/> is pending with the FCC ID(s) listed below: <input type="checkbox"/> has a mix of pending and granted statuses under the FCC ID(s) listed below: i FCC ID: XM2-MP7FL8P9PP ii FCC ID:

### 3.6 Sample information

<b>Receipt date:</b>	05/27/2019
<b>Nemko sample ID number:</b>	-----

### 3.7 EUT technical specifications

<b>Operating band:</b>	Down Link: 769–775 MHz, Up Link: 799-805 MHz
<b>Operating frequency:</b>	Narrowband
<b>Modulation type:</b>	P25, FM
<b>Occupied bandwidth:</b>	Standard
<b>Channel spacing:</b>	standard
<b>Emission designator:</b>	F1E, F1D, F3E
<b>RF Output</b>	Down Link: 33dBm (2W) Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)
<b>Gain</b>	Down Link: 38dB Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)
<b>Antenna type:</b>	External Antenna is not provided, equipment that has an external 50 $\Omega$ RF connector
<b>Power source:</b>	100-240 Vac

## Section 3: Equipment under test

### 3.8 Accessories and support equipment

The following information identifies accessories used to exercise the EUT during testing:

No other FCC-ID equipment are used to exercise the EUT during testing

#### Item # 1

Type of equipment: Master Unit - Subrack

Brand name: Teko Telecom srl

Model name or number: SUB-TRX-PSU

Serial number: 101083001

Nemko sample number: -----

Connection port: -----

Cable length and type: -----

#### Item # 2

Type of equipment: Master Unit – Management Module

Brand name: Teko Telecom srl

Model name or number: TSPV-R

Serial number: 110942253

Nemko sample number: -----

Connection port: LAN port

Cable length and type: -----

#### Item # 3

Type of equipment: Master Unit – Optical Module

Brand name: Teko Telecom srl

Model name or number: TTRU4W-S-M

Serial number: 110679007

Nemko sample number: -----

Connection port: DL/UL RF connector (to connect to the base station)  
Optical port (to connect to remote unit)

Cable length and type: -----

#### Item # 4

Type of equipment: Master Unit – Power Supply

Brand name: Teko Telecom srl

Model name or number: TPSU/AC

Serial number: 081063004

Nemko sample number: -----

Connection port: -----

Cable length and type: -----



### 3.9 Operation of the EUT during testing

<b>Details:</b>	In down-link direction, normal working at max gain with max RF power output.
-----------------	------------------------------------------------------------------------------

### 3.10 EUT setup diagram

In this system, Remote Unit is the EUT. Master Unit includes only management module and optical module (to convert RF signal in optical signal in down link direction and viceversa optical signal in RF signal in up link direction). As described in "Operational description", master unit is connected directly to base station, so the system doesn't use another equipment (under another FCC ID) to exercise the EUT. Signal generator is linked directly to the RF connector of optical module in the Master Unit.


#### Test setup for output power, occupied bandwidth, spurious emissions:



#### Procedure

Connect the signal modulated generator to the input of the EUT, so that the EUT works at the max gain. Raise the input level to the EUT until reach the maximum output power. Connect the spectrum analyzer to the RF output connector of the EUT.


#### Test setup for intermodulation:



#### Procedure

Connect two signal modulated generators to the input of the EUT, so that the two input signals are same level. The EUT works at the max gain. Raise the input level to the EUT until reach the maximum output power. Connect the spectrum analyzer to the RF output connector of the EUT. At maximum drive level, for each modulation applies two tones for fulfill two tests (high-band edge and low-band-edge)

### Test setup for Noise figure:



### Procedure

Connect the EUT with the spectrum analyzer as described in the picture below. Connect the "Output Noise Source" spectrum analyzer with the RF input connector of the Remote Unit. Connect the output RF connector with the spectrum analyzer. Between spectrum analyzer and Remote Unit use a "Noise Source" (Test probe), so the noise of reference is generated. Set the EUT at max gain.

## Section 4: Engineering considerations

### 4.1 Modifications incorporated in the EUT

**Modifications**

Modifications performed to the EUT during this assessment  
None ☒ Yes ☐, performed by Client ☐ or Nemko ☐  
Details:

### 4.2 Deviations from laboratory tests procedures

**Deviations**

Deviations from laboratory test procedures  
None ☒ Yes ☐ - details are listed below:

### 4.3 Technical judgment

**Judgment**

None

## Section 5: Test conditions

### 5.1 Deviations from laboratory tests procedures

No deviations were made from laboratory test procedures.

### 5.2 Test conditions, power source and ambient temperatures

Normal temperature, humidity and air pressure test conditions	<p>Temperature: 15–30 °C Relative humidity: 20–75 % Air pressure: 86–106 kPa</p> <p>When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.</p>
Power supply range:	<p>The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages <math>\pm 5</math> %, for which the equipment was designed.</p>

## Section 5: Test conditions, continued

## 5.3 Measurement uncertainty

EUT	Type	Test	Range and Setup features	Measurement Uncertainty	Notes
Transmitter	Conducted	Frequency error	0.001 MHz ÷ 40 GHz	0.08 ppm	(1)
		Carrier power RF Output Power	10 kHz ÷ 30 MHz	1.0 dB	(1)
			30 MHz ÷ 18 GHz	1.5 dB	(1)
			18 MHz ÷ 40 GHz	3.0 dB	(1)
		Adjacent channel power	1 MHz ÷ 18 GHz	1.6 dB	(1)
		Conducted spurious emissions	10 kHz ÷ 26 GHz	3.0 dB	(1)
			26 GHz ÷ 40 GHz	4.5 dB	(1)
		Intermodulation attenuation	1 MHz ÷ 18 GHz	2.2 dB	(1)
		Attack time – frequency behaviour	1 MHz ÷ 18 GHz	2.0 ms	(1)
		Attack time – power behaviour	1 MHz ÷ 18 GHz	2.5 ms	(1)
		Release time – frequency behaviour	1 MHz ÷ 18 GHz	2.0 ms	(1)
		Release time – power behaviour	1 MHz ÷ 18 GHz	2.5 ms	(1)
		Transient behaviour of the transmitter– Transient frequency behaviour	1 MHz ÷ 18 GHz	0.2 kHz	(1)
		Transient behaviour of the transmitter – Power level slope	1 MHz ÷ 18 GHz	9%	(1)
		Frequency deviation - Maximum permissible frequency deviation	0.001 MHz ÷ 18 GHz	1.3%	(1)
		Frequency deviation - Response of the transmitter to modulation frequencies above 3 kHz	0.001 MHz ÷ 18 GHz	0.5 dB	(1)
		Dwell time	-	3%	(1)
		Hopping Frequency Separation	0.01 MHz ÷ 18 GHz	1%	(1)
		Occupied Channel Bandwidth	0.01 MHz ÷ 18 GHz	2%	(1)
		Modulation Bandwidth	0.01 MHz ÷ 18 GHz	2%	(1)
Receiver	Radiated	Radiated spurious emissions	10 kHz ÷ 26.5 GHz	6.0 dB	(1)
			26.5 GHz ÷ 40 GHz	8.0 dB	(1)
		Effective radiated power transmitter	10 kHz ÷ 26.5 GHz	6.0 dB	(1)
			26,5 GHz ÷ 40 GHz	8.0 dB	(1)
	Conducted	Conducted spurious emissions	10 kHz ÷ 26 GHz	3.0 dB	(1)
			26 GHz ÷ 40 GHz	4.5 dB	(1)

(1) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k = 2$  which has been derived from the assumed normal probability distribution with infinite degrees of freedom and for a coverage probability of 95 %

## 5.4 Test equipment

Equipment	Manufacturer	Model No.	Asset/Serial No.	Next cal.
Vector Signal Generator	Agilent	E4432B ESG	GB38450308	08/2019
Vector Signal Generator	Agilent	E4438C ESG	MY45094485	08/2019
Spectrum Analyzer	Agilent	N9030A PXA	MY53120882	12/2019
Trilog Broad Band Antenna 25-8000 MHz	Schwarzbeck	VULB 9162	VULB 9162-25	07/2021
Antenna 1-18 GHz	Schwarzbeck	STLP 9148	STPL 9148-123	07/2021
Double ridge horn antenna (4 ÷ 40 GHz)	RFSpin	DRH40	061106A40	02/2020
Broadband preamplifier (18 ÷ 40 GHz)	Miteq	JS44-18004000-35-8P-R	1.627	09/2019
Broadband preamplifier 1-18 GHz	Schwarzbeck	BBV 9718	9718-137	08/2019
EMI receiver 20 Hz ÷ 8 GHz	R&S	ESU8	100202	01/2020
EMI receiver 2 Hz ÷ 44 GHz	R&S	ESW44	101620	05/2019
Hydraulic revolving platform	Nemko	RTPL 01	4.233	NCR
Turning-table	R&S	HCT	835 803/03	NCR
Antenna mast	R&S	HCM	836 529/05	NCR
Controller	R&S	HCC	836 620/7	NCR
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	530	09/2021
Shielded room	Siemens	10m control room	1947	NCR
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	70	NCR
Shielded Room	Siemens	3m semi-anechoic chamber	3	NCR
Motor controller	Emco	1051-25	9012-1559	NCR
Motor controller	Emco	1061-1.521	9012-1508	NCR
Antenna Tower	Emco	2071-2	9601-1940	NCR
Controller pole/table	Emco	2090	9511-1099	NCR

Note: N/A = Not Applicable, NCR = No Cal Required, COU = CAL On Use  
(\*) Equipment supplied by manufacturer's

## Appendix A: Test results

### Clause 935210 D05v01 (4.2) AGC threshold


Measure of EUT AGC Threshold

Test date: 05/27/2019 to 06/24/2019


Test results: Pass

### Special notes

### Test data



CW signal, nominal input signal



CW signal, nominal input signal +1 dB

## Clause 935210 D05v01 (4.3) Out of band rejection


Out of Band Rejection – Test for rejection of out of band signals.

Test date: 05/27/2019 to 06/24/2019

Test results: Pass

Special notes

## Test data





## Clause 90.209, 90.219(e)(4) Occupied bandwidth

### § 90.219(e)(4)

A signal booster must be designed such that all signals that it retransmits meet the following requirements:

(i) The signals are retransmitted on the same channels as received. Minor departures from the exact provider or reference frequencies of the input signals are allowed, *provided that* the retransmitted signals meet the requirements of § 90.213.

(ii) There is no change in the occupied bandwidth of the retransmitted signals.

(iii) The retransmitted signals continue to meet the unwanted emissions limits of § 90.210 applicable to the corresponding received signals (assuming that these received signals meet the applicable unwanted emissions limits by a reasonable margin).

Test date: 05/27/2019 to 06/24/2019


Test results: Pass

Special notes


## Occupied bandwidth, continued

### Test data

#### 11K signal, nominal input signal




Output




Input

#### 11K signal, nominal input signal + 3dB




Output




Input

## P25 signal, nominal input signal




Output




Input

## P25 signal, nominal input signal + 3dB



Output



Input

## Clause 90.205, 90.219(e)(1) Output power at RF antenna connector

### § 90.205

Applicants for licenses must request and use no more power than the actual power necessary for satisfactory operation. Except where otherwise specifically provided for, the maximum power that will be authorized to applicants whose license applications for new stations are filed after August 18, 1995 is as follows in FCC Part 90.205 (a) through (r).

### § 90.219(e)(1)

The output power capability of a signal booster must be designed for deployments providing a radiated power not exceeding 5 Watts ERP for each retransmitted channel.

Test date: 05/27/2019 to 06/24/2019


Test results: Pass

Special notes

## Output power at RF antenna connector

### CW signal, nominal input signal

Test data				
Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)
Down-link	CW	772,0	33,166	2,07



### Test result


Gmax antenna gain (dBi) = 39 - 33.166 = 5.834 dBi

EIRP = 33.166 + 5.834 = 39 dBm

ERP = 39 - 2.14 = 36.86dBm = 4.85W < 5 W ERP

## CW signal, nominal input signal + 3dB

Test data				
Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)
Down-link	CW	772,0	33,682	2,33



## Clause 935210 D05v01 (4.6) Noise figure

### § 90.219(e)(2)


The noise figure of a signal booster must not exceed 9 dB in either direction.

Test date: 05/27/2019 to 06/24/2019

Test results: Pass

### Special notes

In the Remote Unit, only up-link measurement can be performed (test probe is connect to antenna port)



**Clause 90.543(c), 90.219(e)(3) Spurious emissions at the antenna terminal****§ 90.543(c)**

Out-of-band emission limit. On any frequency outside of the frequency ranges covered by the ACP tables in this section, the power of any emission must be reduced below the mean output power (P) by at least  $43 + 10\log(P)$  dB measured in a 100 kHz bandwidth for frequencies less than 1 GHz, and in a 1 MHz bandwidth for frequencies greater than 1 GHz.

**§ 90.219(e)(3)**

Spurious emissions from a signal booster must not exceed  $-13\text{dBm}$  within any 100 kHz measurement bandwidth.

Test date: 05/27/2019 to 06/24/2019





Test results: Pass

Special notes




Test data: Spurious emissions at RF antenna connector


## CW signal – First Channel (769,025MHz)




## CW signal – Middle Channel (772,0MHz)




9kHz-150kHz



150kHz-30MHz




30MHz -1GHz




1GHz -8GHz


## CW signal – Last Channel (774,975MHz)




9kHz-150kHz



150kHz-30MHz




30MHz -1GHz




1GHz -8GHz

Test data: Spurious emissions at RF antenna connector: intermodulation

### Nominal input signal



### Nominal input signal + 3dB



**Clause 90.543(c), 90.219(e)(3) Spurious emissions radiated****§ 90.543(c)**

Out-of-band emission limit. On any frequency outside of the frequency ranges covered by the ACP tables in this section, the power of any emission must be reduced below the mean output power (P) by at least  $43 + 10\log(P)$  dB measured in a 100 kHz bandwidth for frequencies less than 1 GHz, and in a 1 MHz bandwidth for frequencies greater than 1 GHz.

**§ 90.219(e)(3)**

Spurious emissions from a signal booster must not exceed  $-13\text{dBm}$  within any 100 kHz measurement bandwidth.

Test date: 05/27/2019 to 06/24/2019

Test results: Pass

**Special notes**

## Radiated spurious emissions, continued

## Test data

The D.U.T. was positioned according to the radiated emissions set-up

The D.U.T. antenna connector was terminated by a 50  $\Omega$  shielded dummy load.


The spectrum was searched from 30 MHz to 1 GHz (RBW 100 kHz) & 1 GHz (RBW 1 MHz) to the tenth harmonic of the carrier.

There were no emissions detected above the noise floor which was at least 20 dB below the specification limit.

## Spurious emissions measurement results:


Frequency (MHz)	Polarization. V/H	Field strength (dBm)	Limit (dBm)	Margin (dB)
Low channel				
First Channel	V/H	Negligible	-13	
Mid channel				
772.0	V/H	Negligible	-13	
High channel				
Last Channel	V/H	Negligible	-13	

Note: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.



Date: 19.JUN.2019 11:35:28


### 30MHz-1GHz – H Pol




Date: 19.JUN.2019 11:36:04

### 30MHz-1GHz – V Pol





1GHz-10GHz – H Pol



09:52:07 18.06.2019

Page 1/1

1GHz-10GHz – V Pol

## Clause 90.543(f) Radiated spurious emissions within 1559–1610 MHz band

### § 90.543(f)

For operations in the 758-775 MHz and, 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to –70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and –80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation

#### Note:

Method of measurement according to TIA-603-C (EIRP in GNSS band: 1.556 to 1.610 GHz) .  
 $\Delta$  Band = 51 MHz, Correction Factor calculated at central band 1604.5 MHz. in Fraunhofer Region.

Test date: 05/27/2019 to 06/24/2019

Test results: Pass

### Special notes


Method of measurement according to TIA-603-C (EIRP in GNSS band: 1.556 to 1.610 GHz) .

$\Delta$  Band = 51 MHz, Correction Factor calculated at central band 1604.5 MHz. in Fraunhofer Region.

Limit used for discrete emissions: -80 dBw = -50 dBm

# Clause 90.543(f) Radiated spurious emissions within 1559–1610 MHz band, continued


## Test data



10:58:54 18.06.2019

Page 1/1

1559MHz-1610MHz – H Pol




10:58:34 18.06.2019

Page 1/1


1559MHz-1610MHz – V Pol

## Appendix B: Block diagrams of test set-ups

### Radiated emissions set-up



### Substitution method set-up



## Appendix C: EUT Photos

### Photo Set up









Photo EUT







## Label EUT



**WARNING.** This is NOT a CONSUMER device. It is designed for Installation by FCC LICENSEES and QUALIFIED INSTALLERS. You MUST have an FCC LICENSE or express consent of an FCC Licensee to operate this device. Unauthorized use may result in significant forfeiture penalties, including penalties in excess of \$100,000 for each continuing violation.

**WARNING.** This is NOT a CONSUMER device. This is a 90.219 Class B signal booster. It is designed for Installation by FCC LICENSEES and QUALIFIED INSTALLERS. You MUST have an FCC LICENSE or express consent of an FCC Licensee to operate this device. You MUST register Class B signal boosters (as defined in 47 CFR 90.219) online at [www.fcc.gov/signal-boosters/registration](http://www.fcc.gov/signal-boosters/registration). Unauthorized use may result in significant forfeiture penalties, including penalties in excess of \$100,000 for each continuing violation.

END OF REPORT