



Test Report No.:  
**FCC2022-0038-H1**

## **RF Test Report**

**EUT** : **IoT Display**  
**MODEL** : **DS7610-915M**  
**BRAND NAME** : **Milesight**  
**APPLICANT** : **Xiamen Milesight IoT Co., Ltd.**  
**CLASSIFICATION OF TEST** : **N/A**

**CVC Testing Technology Co., Ltd.**



# CVC Testing Technology Co., Ltd.

Test Report No.: FCC2022-0038-H1

Page 2 of 10

<b>Applicant</b>		Name: Xiamen Milesight IoT Co., Ltd. Address: Building C09, Software Park Phase III, Xiamen 361024, Fujian, China	
<b>Manufacturer</b>		Name: Xiamen Milesight IoT Co., Ltd. Address: Building C09, Software Park Phase III, Xiamen 361024, Fujian, China	
<b>Equipment Under Test</b>		Name: IoT Display Model/Type: DS7610-915M Additional Models/Types: See Section 2 Brand: Milesight Serial NO.: N/A Sampe NO.: 4-2	
Date of Receipt.	2022.07.11	Date of Testing	2022.07.11~2022.12.06
<b>Test Specification</b>		<b>Test Result</b>	
FCC Part 2 (Section 2.1091) KDB 447498 D04 IEEE C95.1		PASS	
<b>Evaluation of Test Result</b>		The equipment under test was found to comply with the requirements of the standards applied.  Seal of CVC <b>Issue Date: 2022.12.10</b>	
Tested by:  <b>Xu ZhenFei</b> Name                      Signature		Reviewed by:  <b>Liu YongHai</b> Name                      Signature	Approved by:  <b>Chen HuaWen</b> Name                      Signature
<b>Other Aspects: NONE.</b>			
Abbreviations:OK,    Pass= passed    Fail = failed    N/A= not applicable    EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



## **TABLE OF CONTENTS**

RELEASE CONTROL RECORD .....	4
1. GERTIFICATION .....	5
2. ADDITIONAL MODELS/TYPES .....	5
3. RF EXPOSURE LIMIT .....	6
4. CLASSIFICATION .....	8
5. ANTENNA GAIN .....	8
6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER .....	8



## **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCC2022-0038-H1	Original release	2022.12.10



## 1. GERTIFICATION

<b>PRODUCT</b>	IoT Display
<b>BRAND</b>	Milesight
<b>MODEL</b>	DS7610-915M
<b>ADDITIONAL MODEL</b>	See Section 2
<b>FCC ID</b>	2AYHY-DS7610
<b>POWER SUPPLY</b>	1. DC 5V from USB host unit 2. DC 56V from POE 3. DC 12V from Adapter
<b>OPERATING FREQUENCY</b>	902.3MHz~927.6MHz for LORA_125kHz
	903MHz~927.5MHz for LORA_500kHz
	2402MHz~2480MHz for BT
	2412MHz ~ 2462MHz for 2.4G WiFi
	5180MHz ~ 5825MHz for 5G WiFi
	13.56MHz for NFC
<b>HARDWARE VERSION:</b>	UD00-00-V1.2
<b>SOFTWARE VERSION:</b>	72.0.0.5-r1
<b>I/O PORTS</b>	Refer to user's manual
<b>CABLE SUPPLIED</b>	N/A
Remark: 1. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report. 3. EUT photo refer to the report (Report NO.: FCC2022-0038-E).	

## 2. ADDITIONAL MODELS/TYPES

Models	
1	DS7610-9M
2	NH7610-915M
3	NH7610-9M
Note: The only differences are silk-screen 、 trade name and model no. for trading purpose.	

## 3. RF EXPOSURE LIMIT

(Option B) According to FCC Part2.1091 and FCC Part1.1307b, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where:

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz;

and

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

(Option C) Or using Table 1 and the minimum separation distance ( $R$  in meters) from the body of a nearby person for the frequency ( $f$  in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply,  $R$  must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to §1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency (MHz)	Threshold ERP (W)
0.3 - 1.34	$1920R^2$
1.34 - 30	$3450R^2 / f^2$
30 - 300	$3.38R^2$
300 - 1500	$0.0128R^2 / f^2$
1500 - 100000	$19.2R^2$



For multiple RF sources: Multiple RF sources are exempt if:

- a) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).
- b) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

Pi = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i = the exemption threshold power (Pth) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERPj = the ERP of fixed, mobile, or portable RF source j.

ERPth,j = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluatedk = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limitk = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.



## 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

## 5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
LORA	-10.6	PCB Antenna
BT	2.26	Ceramic Antenna
2.4G WiFi	2.26	Ceramic Antenna
5G WiFi	0.06	Ceramic Antenna
NFC	/	Loop Antenna

This is provided by the manufacturer. The laboratory is not responsible for technical data provided by the customer.

## 6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The measured Conducted Average Power

Option	Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
B	LORA (125KHz)	902.3 ~ 927.6	0	+1	-1	1
	LORA (500KHz)	903 ~ 927.5	0	+1	-1	1
	BT	2402 ~ 2480	3	+1	2	4
	2.4G WiFi	2412 ~ 2462	15	+1	14	16
	5G WiFi	5180 ~ 5825	16	+1	15	17

Option	Mode	Frequency (MHz)	ERP(dBm)
C	NFC	13.56	-58.15

NOTE:

- The NFC Field strength is -2.95dBμV at 30m or is 37.05dBμV at 3m.
- $E[dB\mu V/m] = EIRP[dBm] + 95.2$ , for  $d = 3$  m.





The tuned Conducted Average Power (declared by client)

Option	Technology	Maximum conducted power (dBm)	Maximum Antenna Gain (dBi)	EIRP (dBm)	ERP (dBm)	ERP (mW)	Part1.1307b Threshold (mW)	Verify
B	LORA (125KHz)	0.31	-10.6	/	-10.29	0.094	1840.692	PASS
	LORA (500KHz)	0.33	-10.6	/	-10.27	0.094	1842.120	PASS
	BT	5.16	2.26	7.42	5.27	3.365	3060	PASS
	2.4G WiFi	16.87	2.26	19.13	16.98	49.888	3060	PASS
	5G WiFi	16.71	0.06	16.77	14.62	29.973	3060	PASS

Option	Technology	ERP(dBm)	ERP(W)	Threshold ERP (W)	Verify
C	NFC	-58.15	1.53e-9	76.8	PASS

**Note:** This device can operate simultaneously in LORA, BT, NFC, 2.4G WIFI or 5G WIFI.

## CALCULATION FOR SIMULTANEOUS TRANSMISSION:

LORA, BT, NFC and WiFi can transmit simultaneously, the formula of calculated the MPE is

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Max:  $(0.094/1840.692) + (3.365/3060) + (1.53e-9/76.8) + (49.888/3060) = 0.01745 < 1$ ,

which is less than the "1" limit.



## Important

- (1) The test report is valid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

*\*\*The test data and test results given in this test report should only be used for purposes of scientific research, teaching and internal quality control when the CMA symbol is not presented.\*\**

Laboratory: CVC Testing Technology Co., Ltd.

Address: No.3, TiantaiyiRoad, KaitaiAvenue, ScienceCity, Guangzhou, China

Post Code: 510663

Tel: 020-32293888

FAX: 020-32293889

E-mail: [office@cvc.org.cn](mailto:office@cvc.org.cn)