WIFI Bulb camera



Email: usservice@isecugroup.com



Before operating this unit please read these instructions carefully and save them for future use.

Interface description

This manual is suitable for various types of cameras.

(The appearance may be different due to different batches. details are subject to the receipt This manual is only for the installation instructions of this series of equipment)

WIFI Bulb camera



Description

The working state of the device, long press 5 seconds to restore the factory settings, the camera will have a voice prompt broadcast.

2. SD card slot

Power supply

Power input.

Installation and placement

TF card, storage video and playback

WIFI Bulb camera



Connected to an E27 connector for AC110V-240V

Software Installation

APP Download and Installation

Users can search "EseeCloud(IP Pro VR Cam)" on APP store or Google Play, or scan the QR code below to install the APP. Note: For iOS system, it requires iOS 9.0 version or above. For Android, Android 5.1 or above.





If you are prompted to open certain permissions (such as location, message notification, etc.) during APP installation, click Allow (agree).

Account register: Open the APP. click"Register", enter your email or phone number Eseeclount to create an account. Wekame to EverCond

Account login: On the login interface, enter the account/ phone number/email, and the corresponding password, and click the "OK" button to

Third-party login: APP supports third-party login Click the third-party social software icon, jump to the APP to complete the



Bluetooth adding process with network

*"Before adding a camera, please make sure that the Bluetooth function of the mobile phone has been turned on, and do not turn off the Bluetooth during the adding process. If a prompt box pops up during the adding process to enable Bluetooth or Bluetooth authorization please follow the steps in the prompt to enable it:

Step 1

After the camera is powered on open and click the "+" icon in the upper right corner to enter the interface of adding

the "EseeCloud "APP Device Group

(If the permission prompt pops up, click agree)

The APP will automatically search for a new device and click the Add button when it finds





(If you do not see the pop-up device box, please

click "scan to add" to scan the QR code on the

Scan the device body code with

If you can't find the device in the above

steps, press and hold the reset button for

5 seconds, restore the camera to factory

your mobile phone to add

Scan to add

Enter the WIFI name and password on the distribution network screen.

settings, and try again.



configured successfully, the system prompts you to enter the device name. Click Next.



After the network is



Users can choose to enable or disable message push according to your own preferences

(generally recommended to enable)

Conaratulations, you have successfully connected the device.

Or vou can add camera by WiFi configuration

Open the APP, click the "+" icon in the middle of the interface to enter the scan code interface:







Step 4

Select the WiFi that the camera needs to connect to, enter the password, and click

Check whether the camera light is blinking




After the network configuration is successful, set a name for the camera.



Point the camera at the OR code that appears on the screen of the phone




General Michigan Stranger



Q1: Why is the pairing network unsuccessful?

I. Please make sure that the distance among the camera. the router and the mobile phone should be close enough when configuring WLANiasistant the network.





* ChinaNot-stbA button for 5 seconds and try again after restoring the camera to the factory settings.

has been inserted into the camera and try to turn on/off the camera.

menu to check the storage status 'in good condition (if the status is abnormal click to "Format the



Q3: Why is the camera offline?


- 1. It may caused by router WIFI signal interference or network reasons. Power off and restart the optical modem. router or camera.
- 2. The camera maybe too far away from the WIFI router, try to aet the camera next to the WIFI router.
- the camera and try pairing again.

Help FAQ



Available networks 10

Y KDM-1.50 🗆



4. Please long press the reset

O2: Why is there no playback?

1. Make sure that the TF card











NAME OF TAXABLE PARTY. accommon E D D D . Open vour phone's Settings > Apps and Notifications,

04: Why my phone does not have an alarm push function







find the "EseeCloud" app.

and turn on all permissions

or two way audio?



Email: usservice@isecugroup.com





































authorization and log in.

. . .


Acel Certon











Jerrechen binerti tra horse and mores Ton Shall St. (Reported) Considerate de profesionales el l'occupation de profesionales de Main Docker

Mediania



Click "Camera scan code add" method



wast no com then a comment




B ... ×









3. Whether the WIFI password has been changed, try to reset









FCC Warning

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interferenceto radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -Reorient or relocate the receiving antenna.
- •Increase the separation between the equipment and receiver.
- •Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.