

## EUT OPERATING CONDITIONS

The Wireless Speaker System was powered from 110V, 60Hz mains supply.

Tests	Description Of Operation
1. Conducted Emissions 2. Radiated Emissions 3. Carrier Frequency Separation 4. Spectrum Bandwidth (20dB Bandwidth Measurement) 5. Number Of Hopping Frequencies 6. Average Frequency Dwell Time 7. Maximum Peak Power 8. RF Conducted Spurious Emissions at the Transmitter Antenna Terminal 9. Band Edge Compliance at the Transmitter Antenna Terminal 10. Peak Power Spectral Density 11. Maximum Permissible Exposure 12. Duty Cycle Correction Factor	<p>The EUT was exercised by operating in the test mode with maximum transmitting power and following configuration during the tests:</p> <p><u>Carrier Frequency Separation, Number of Hopping Frequency, Average Frequency Dwell Time, Band Edge at the Transmitting Antenna and Maximum Permissible Exposure:</u></p> <p>Frequency hopping and modulation are on.</p> <p><u>Conducted Emissions, Radiated Emissions, Spectrum Bandwidth (20dB Bandwidth Measurement), Maximum Peak Power, RF Conducted Spurious Emissions at the Transmitter Antenna Terminal, Peak Power Spectral Density, Maximum Permissible Exposure and Duty Cycle Correction Factor</u></p> <p>Frequency hopping is off and the modulation is on.</p>