

Exposure limit according to §90(i)

The device is classified as mobile.

Limit for power density for general population/uncontrolled exposure is $f/1500 \text{ mW/cm}^2$ for 300 – 1500 MHz frequency range:

$$P = 450/1500 = 0.3 \text{ mW/cm}^2$$

The power density $P \text{ (mW/cm}^2\text{)} = P_T / 4\pi r^2$

P_T is the transmitted power, which is equal to the peak transmitter output power in 4GFSK modulation mode of 32.56 dBm plus maximum antenna gain(-2) dBi, the maximum equivalent isotopically radiated power EIRP is:

$$P_T = 32.56 \text{ dBm} + (-2) \text{ dBi} = 30.56 \text{ dBm} = 1138 \text{ mW}.$$

According to the manufacturer's declaration the duty cycle factor for 30min averaging time is 0.6 hence, the equivalent averaged EIRP is:

$$P_T = 1138 \text{ mW} \times 0.6 = 682.8 \text{ mW}.$$

The power density at 20 cm (minimum safe distance, required for mobile devices), calculated as follows:

$$682.8 \text{ mW} / 4\pi (20 \text{ cm})^2 \approx 0.135 \text{ mW/cm}^2 < 0.3 \text{ mW/cm}^2$$

General public cannot be exposed to dangerous RF level.