

FCC TEST REPORT
FOR
Hui Zhou Gaoshengda Technology Co.,LTD
WIFI+BT module
Test Model: WT4XR1210

Prepared for : Hui Zhou Gaoshengda Technology Co.,LTD
Address : NO.75, Zhongkai Development Area, Huizhou, Guangdong,
China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : December 11, 2015
Number of tested samples : 1
Serial number : Prototype
Date of Test : January 04, 2016 - January 20, 2016
Date of Report : January 20, 2016

FCC TEST REPORT

FCC CFR 47 PART 15 C(15.247): 2015

Report Reference No. : LCS1512111003E

Date of Issue : January 20, 2016

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure : Full application of Harmonised standards ☒
Partial application of Harmonised standards ☐
Other standard testing method ☐

Applicant's Name..... : Hui Zhou Gaoshengda Technology Co.,LTD

Address : NO.75, Zhongkai Development Area, Huizhou, Guangdong,
China

Test Specification

Standard : FCC CFR 47 PART 15 C(15.247): 2015 / ANSI C63.10: 2013

Test Report Form No. : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description. : WIFI+BT module


Trade Mark..... : GSD

Test Model : WT4XR1210

Ratings : DC 5V

Result : Positive

Compiled by:




Leo Lee/ File administrators

Supervised by:



Glin Lu/ Technique principal

Approved by:



Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : LCS1512111003EJanuary 20, 2016

Date of issue

Test Model..... : WT4XR1210

EUT..... : WIFI+BT module

Applicant..... : Hui Zhou Gaoshengda Technology Co.,LTDAddress..... : NO.75, Zhongkai Development Area, Huizhou, Guangdong,
China

Telephone..... : /

Fax..... : /

Manufacturer..... : Hui Zhou Gaoshengda Technology Co.,LTDAddress..... : NO.75, Zhongkai Development Area, Huizhou, Guangdong,
China

Telephone..... : /

Fax..... : /

Factory..... : Hui Zhou Gaoshengda Technology Co.,LTDAddress..... : NO.75, Zhongkai Development Area, Huizhou, Guangdong,
China

Telephone..... : /

Fax..... : /

Test Result**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.


TABLE OF CONTENTS

| | |
|---|-----------|
| 1. GENERAL INFORMATION | 5 |
| 1.1 Description of Device (EUT)..... | 5 |
| 1.2 Support Equipment List | 6 |
| 1.3 External I/O | 6 |
| 1.4 Description of Test Facility | 6 |
| 1.5 List Of Measuring Equipments..... | 7 |
| 1.6 Statement of The Measurement Uncertainty | 8 |
| 1.7 Measurement Uncertainty..... | 8 |
| 1.8 Description Of Test Modes..... | 9 |
| 2. TEST METHODOLOGY | 10 |
| 2.1 EUT Configuration | 10 |
| 2.2 EUT Exercise..... | 10 |
| 2.3 General Test Procedures | 10 |
| 3. SYSTEM TEST CONFIGURATION..... | 11 |
| 3.1 Justification..... | 11 |
| 3.2 EUT Exercise Software | 11 |
| 3.3 Special Accessories | 11 |
| 3.4 Block Diagram/Schematics..... | 11 |
| 3.5 Equipment Modifications | 11 |
| 3.6 Test Setup | 11 |
| 4. SUMMARY OF TEST RESULTS | 12 |
| 5. ANTENNA PORT MEASUREMENT..... | 13 |
| 5.1 Conducted Peak Output Power | 13 |
| 5.2 Frequency Separation And 20 dB Bandwidth | 14 |
| 5.3 Number Of Hopping Frequency | 23 |
| 5.4 Time Of Occupancy (Dwell Time)..... | 25 |
| 5.5 Conducted Spurious Emissions and Band Edges Test..... | 28 |
| 6. RADIATED MEASUREMENT | 35 |
| 6.1 Block Diagram of Test Setup..... | 35 |
| 6.2 Radiated Emission Limit | 36 |
| 6.3 Instruments Setting | 37 |
| 6.4 Test Procedures..... | 38 |
| 6.5 Results for Radiated Emissions | 41 |
| 6.6 Results for Band edge Testing (Radiated) | 44 |
| 7. LINE CONDUCTED EMISSIONS..... | 45 |
| 7.1 Standard Applicable..... | 45 |
| 7.2 Block Diagram of Test Setup..... | 45 |
| 7.3 Test Results..... | 45 |
| 8. ANTENNA REQUIREMENT | 47 |
| 8.1 Standard Applicable..... | 47 |
| 8.2 Antenna Connected Construction | 47 |

1. GENERAL INFORMATION

1.1 Description of Device (EUT)

| | |
|----------------------|--|
| EUT | : WIFI+BT module |
| Test Model | : WT4XR1210 |
| Hardware Version | : / |
| Software Version | : / |
| Power Supply | : DC 5V |
| Bluetooth Technology | : |
| Frequency Range | : 2402.00-2480.00MHz |
| Channel Spacing | : 1MHz for Bluetooth V3.0 (DSS) 2MHz for Bluetooth V4.0 (DTS) |
| Channel Number | : 79 channels for Bluetooth V3.0 (DSS) 40 channels for Bluetooth V4.0 (DTS) |
| Modulation Type | : GFSK, Pi/4-DQPSK, 8-DPSK for Bluetooth V3.0 (DSS) GFSK for Bluetooth V4.0 (DTS) |
| Bluetooth Version | : V4.0 |
| Antenna Description | : PCB Antenna (AUX Port), Antenna Gain:2dBi |
| WIFI Technology | : |
| Operating Frequency | : 2412.00-2462.00MHz |
| Channel Spacing | : 5MHz |
| Channel Number | : 11 Channels for 20MHz Bandwidth 7 Channels for 40MHz Bandwidth |
| Modulation Type | : 802.11b: DSSS; 802.11g/n: OFDM |
| Antenna Description | : PCB Antenna (MAIN Port). Antenna Gain:2dBi |



1.2 Support Equipment List

| Manufacturer | Description | Model | Serial Number | Certificate |
|--------------|---------------|------------|---------------|-------------|
| Lenovo | Notebook | B470 | WB05067151 | DOC |
| Lenovo | AC/DC ADAPTER | ADP-90DD B | 36001941 | VOC |

1.3 External I/O

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-------|
| -- | -- | -- |

1.4 Description of Test Facility

CNAS Registration Number. is L4595.

FCC Registration Number. is 899208.

Industry Canada Registration Number. is 9642A-1.

VCCI Registration Number. is C-4260 and R-3804.

ESMD Registration Number. is ARCB0108.

UL Registration Number. is 100571-492.

TUV SUD Registration Number. is SCN1081.

TUV RH Registration Number. is UA 50296516-001

1.5 List Of Measuring Equipments

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Cal Date | Due Date |
|--------------------------|----------------|----------------------------------|-------------|-----------------|---------------|---------------|
| EMC Receiver | R&S | ESCS 30 | 100174 | 9kHz – 2.75GHz | June 18,2015 | June 17,2016 |
| Signal analyzer | Agilent | E4448A(External mixers to 40GHz) | US44300469 | 9kHz~40GHz | July 16,2015 | July 15,2016 |
| LISN | MESS Tec | NNB-2/16Z | 99079 | 9KHz-30MHz | June 18,2015 | June 17,2016 |
| LISN (Support Unit) | EMCO | 3819/2NM | 9703-1839 | 9KHz-30MHz | June 18,2015 | June 17,2016 |
| RF Cable-CON | UTIFLEX | 3102-26886-4 | CB049 | 9KHz-30MHz | June 18,2015 | June 17,2016 |
| ISN | SCHAFFNER | ISN ST08 | 21653 | 9KHz-30MHz | June 18,2015 | June 17,2016 |
| 3m Semi Anechoic Chamber | SIDT FRANKONIA | SAC-3M | 03CH03-HY | 30M-1GHz 3m | June 18,2015 | June 17,2016 |
| Amplifier | SCHAFFNER | COA9231A | 18667 | 9kHz-2GHz | June 18,2015 | June 17,2016 |
| Amplifier | Agilent | 8449B | 3008A02120 | 1GHz-26.5GHz | July 16,2015 | July 15,2016 |
| Amplifier | MITEQ | AMF-6F-260400 | 9121372 | 26.5GHz-40GHz | July 16,2015 | July 15,2016 |
| Spectrum Analyzer | Agilent | E4407B | MY41440292 | 9k-26.5GHz | July 16,2015 | July 15,2016 |
| MAX Signal Analyzer | Agilent | N9020A | MY50510140 | 20Hz~26.5GHz | Oct. 27, 2015 | Oct. 26, 2016 |
| Loop Antenna | R&S | HFH2-Z2 | 860004/001 | 9k-30MHz | June 18,2015 | June 17,2016 |
| By-log Antenna | SCHWARZBECK | VULB9163 | 9163-470 | 30MHz-1GHz | June 10,2015 | June 09,2016 |
| Horn Antenna | EMCO | 3115 | 6741 | 1GHz-18GHz | June 10,2015 | June 09,2016 |
| Horn Antenna | SCHWARZBECK | BBHA9170 | BBHA9170154 | 15GHz-40GHz | June 10,2015 | June 09,2016 |
| RF Cable-R03m | Jye Bao | RG142 | CB021 | 30MHz-1GHz | June 18,2015 | June 17,2016 |
| RF Cable-HIGH | SUHNER | SUCOFLEX 106 | 03CH03-HY | 1GHz-40GHz | June 18,2015 | June 17,2016 |
| Power Meter | R&S | NRVS | 100444 | DC-40GHz | June 18,2015 | June 17,2016 |
| Power Sensor | R&S | NRV-Z51 | 100458 | DC-30GHz | June 18,2015 | June 17,2016 |
| Power Sensor | R&S | NRV-Z32 | 10057 | 30MHz-6GHz | June 18,2015 | June 17,2016 |
| RF CABLE-1m | JYE Bao | RG142 | CB034-1m | 20MHz-7GHz | June 18,2015 | June 17,2016 |
| RF CABLE-2m | JYE Bao | RG142 | CB035-2m | 20MHz-1GHz | June 18,2015 | June 17,2016 |

Note: All equipment through GRGT EST calibration

1.6 Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.7 Measurement Uncertainty

| Test Item | | Frequency Range | Uncertainty | Note |
|------------------------|---|-----------------|-------------|------|
| Radiation Uncertainty | : | 9KHz~30MHz | 3.10dB | (1) |
| | : | 30MHz~200MHz | 2.96dB | (1) |
| | : | 200MHz~1000MHz | 3.10dB | (1) |
| | : | 1GHz~26.5GHz | 3.80dB | (1) |
| | : | 26.5GHz~40GHz | 3.90dB | (1) |
| Conduction Uncertainty | : | 150kHz~30MHz | 1.63dB | (1) |
| Power disturbance | : | 30MHz~300MHz | 1.60dB | (1) |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.8 Description Of Test Modes

Bluetooth operates in the unlicensed ISM Band at 2.4GHz. With the introduction of the enhanced data rate (EDR) feature, the data rates can be up to 3 Mb/s. An increase in the peak data rate beyond the basic rate of 1 Mb/s is achieved by modulating the RF carrier using GFSK techniques, resulting in an increase of two to three times the number of bits per symbol. The 2 Mb/s EDR packets use a $\pi/4$ -DQPSK modulation and the 3 Mb/s EDR packets use 8DPSK modulation. The following operating modes were applied for the related test items. For radiated measurement, the test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position. All test modes were tested, only the result of the worst case was recorded in the report.

| Mode of Operations | Frequency Range (MHz) | Data Rate (Mbps) |
|------------------------|-----------------------|------------------|
| GFSK | 2402 | 1 |
| | 2441 | 1 |
| | 2480 | 1 |
| $\pi/4$ DQPSK | 2402 | 2 |
| | 2441 | 2 |
| | 2480 | 2 |
| 8-DPSK | 2402 | 3 |
| | 2441 | 3 |
| | 2480 | 3 |
| For Conducted Emission | | |
| Test Mode | TX Mode | |
| For Radiated Emission | | |
| Test Mode | TX Mode | |

For pre-testing, when performed power line conducted emission measurement, the input Voltage/Frequency AC 120V/60Hz and AC 240V/60Hz were used. Only recorded the worst case in this report.

Worst-case mode and channel used for 150kHz-30 MHz power line conducted emissions was determined to be TX Mode(1Mbps-Hopping).

Worst-case mode and channel used for 9kHz-1000 MHz radiated emissions was determined to be TX-Middle Channel Mode(1Mbps).

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2013, FCC CFR PART 15C 15.207, 15.209, 15.247 and DA 00-705.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209, 15.247 under the FCC Rules Part 15 Subpart C.

2.3 General Test Procedures

2.3.1 Conducted Emissions

According to the requirements in Section 6.2 of ANSI C63.10: 2013, AC power-line conducted emissions shall be measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table and the turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10: 2013

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a continuous transmit condition.

3.2 EUT Exercise Software

N/A.

3.3 Special Accessories

N/A.

3.4 Block Diagram/Schematics

Please refer to the related document.

3.5 Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6 Test Setup

Please refer to the test setup photo.


4. SUMMARY OF TEST RESULTS

| Applied Standard: FCC Part 15 Subpart C | | |
|---|---|-----------|
| FCC Rules | Description of Test | Result |
| §15.247(b)(1) | Maximum Conducted Output Power | Compliant |
| §15.247(a)(1) | Frequency Separation And 20 dB Bandwidth | Compliant |
| §15.247(a)(1)(iii) | Number Of Hopping Frequency | Compliant |
| §15.247(a)(1)(iii) | Time Of Occupancy (Dwell Time) | Compliant |
| §15.209, §15.247(d) | Radiated and Conducted Spurious Emissions | Compliant |
| §15.205 | Emissions at Restricted Band | Compliant |
| §15.207(a) | Line Conducted Emissions | Compliant |
| §15.203 | Antenna Requirements | Compliant |
| <i>Note: This is a DSS test report for WIFI+BT module, please refer to other document for the DTS test report (LCS1512111004E).</i> | | |

5. ANTENNA PORT MEASUREMENT

5.1 Conducted Peak Output Power

5.1.1 Block Diagram of Test Setup



5.1.2 Limit

According to § 15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

5.1.3 Test Procedure

The transmitter output is connected to the Power Meter.

5.1.4 Test Results


| Mode | Frequency (MHz) | Output Power (dBm, Average) | Output Power (mW) | Limit (mW) | Result |
|------------|-----------------|-----------------------------|-------------------|------------|--------|
| GFSK | 2402 | 0.95 | 1.24 | 1000 | Pass |
| | 2441 | 2.91 | 1.95 | 1000 | Pass |
| | 2480 | 2.50 | 1.78 | 1000 | Pass |
| Pi/4 DQPSK | 2402 | -0.29 | 0.94 | 125 | Pass |
| | 2441 | 1.30 | 1.35 | 125 | Pass |
| | 2480 | 1.56 | 1.43 | 125 | Pass |
| 8-DPSK | 2402 | -0.28 | 0.94 | 125 | Pass |
| | 2441 | 1.81 | 1.52 | 125 | Pass |
| | 2480 | 2.01 | 1.59 | 125 | Pass |

5.2 Frequency Separation And 20 dB Bandwidth

5.2.1 Limit

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.2.2 Block Diagram of Test Setup



5.2.3 Test Procedure

- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set to the maximum power setting and enable the EUT transmit continuously.
- D. For carrier frequency separation measurement, use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW / VBW=100KHz / 300KHz; Sweep = auto; Detector function = peak;
Trace = max hold.
- E. For 20dB bandwidth measurement, use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW/VBW=30KHz / 100KHz; Sweep = auto; Detector function = peak;
Trace = max hold.

5.2.4 Test Results

| The Measurement Result With 1Mbps For GFSK Modulation | | | |
|---|--------------------------|----------------------|---------------|
| 20dB Bandwidth Measurement | | | |
| Channel | | 20dB Bandwidth (MHz) | Limit |
| Low | | 0.749 | Non-specified |
| Middle | | 0.832 | Non-specified |
| High | | 0.832 | Non-specified |
| Channel Separation Measurement | | | |
| Channel | Channel Separation (MHz) | Limit (MHz) | Result |
| Low | 1.000 | >=25 KHz or 20dB BW | Pass |
| Middle | 1.000 | >=25 KHz or 20dB BW | Pass |
| High | 1.000 | >=25 KHz or 20dB BW | Pass |

| The Measurement Result With 2Mbps For Pi/4 DQPSK Modulation | | | |
|---|--------------------------|-------------------------|---------------|
| 20dB Bandwidth Measurement | | | |
| Channel | | 20dB Bandwidth (MHz) | Limit |
| Low | | 1.124 | Non-specified |
| Middle | | 1.129 | Non-specified |
| High | | 1.127 | Non-specified |
| Channel Separation Measurement | | | |
| Channel | Channel Separation (MHz) | Limit (MHz) | Result |
| Low | 1.000 | >=25 KHz or 2/3 20dB BW | Pass |
| Middle | 1.000 | >=25 KHz or 2/3 20dB BW | Pass |
| High | 1.000 | >=25 KHz or 2/3 20dB BW | Pass |

| The Measurement Result With 3Mbps For 8-DPSK Modulation | | | |
|---|--------------------------|-------------------------|---------------|
| 20dB Bandwidth Measurement | | | |
| Channel | | 20dB Bandwidth (MHz) | Limit |
| Low | | 1.172 | Non-specified |
| Middle | | 1.169 | Non-specified |
| High | | 1.171 | Non-specified |
| Channel Separation Measurement | | | |
| Channel | Channel Separation (MHz) | Limit (MHz) | Result |
| Low | 1.000 | >=25 KHz or 2/3 20dB BW | Pass |
| Middle | 1.000 | >=25 KHz or 2/3 20dB BW | Pass |
| High | 1.000 | >=25 KHz or 2/3 20dB BW | Pass |

The test data refer to the following page.

For Frequency Separation Measurement, the Low, Mid and High channels were performed and only recorded the worst test plots for Low in this report.



The Worst Test Plot Of Frequency Separation (1Mbps)







Test Plot Of Frequency Separation (2Mbps)






Test Plot Of Frequency Separation (3Mbps)

Measurement of 20dB Bandwidth**Test frequency: 2402MHz(1Mbps)****Test frequency: 2441MHz(1Mbps)**

Test frequency: 2480MHz(1Mbps)**Test frequency: 2402MHz(2Mbps)**

Test frequency: 2441MHz(2Mbps)**Test frequency: 2480MHz(2Mbps)**

Test frequency: 2402MHz(3Mbps)**Test frequency: 2441MHz(3Mbps)**


Test frequency: 2480MHz(3Mbps)

5.3 Number Of Hopping Frequency

5.3.1 Limit

According to §15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

5.3.2 Block Diagram of Test Setup





5.3.3 Test Procedure

- Place the EUT on the table and set it in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- Set Spectrum Analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = auto.
- Set the Spectrum Analyzer as RBW, VBW=1MHz.
- Max hold, view and count how many channel in the band.

5.3.4 Test Results

| Test Mode | Measurement Result (No. of Ch) | Limit (No. of Ch) | Result |
|---------------------|-----------------------------------|----------------------|--------|
| Hopping(GFSK) | 79 | ≥ 15 | Pass |
| Hopping(Pi/4-DQPSK) | 79 | ≥ 15 | Pass |
| Hopping(8-DPSK) | 79 | ≥ 15 | Pass |

The worst test data refer to the following page.


Test Plot For Number of Hopping Channel(GFSK)

5.4 Time Of Occupancy (Dwell Time)

5.4.1 Limit

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4seconds multiplied by the number of hopping channels employed.

5.4.2 Block Diagram of Test Setup



5.4.3 Test Procedure

- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set center frequency of Spectrum Analyzer = operating frequency.
- D. Set the Spectrum Analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
- E. Repeat above procedures until all frequency measured were complete.

5.4.4 Test Results

The Measurement Result With The Worst Case of 3Mbps For 8-DPSK Modulation

| Channel | Time of Pulse for 3DH5 (ms) | Period Time (s) | Sweep Time (ms) | Limit (ms) |
|---------|-----------------------------|-----------------|-----------------|------------|
| Low | 2.88 | 31.6 | 307.20 | 400 |
| Middle | 2.88 | 31.6 | 307.20 | 400 |
| High | 2.88 | 31.6 | 307.20 | 400 |

Low Channel

$$2.88 * (1600/6) / 79 * 31.6 = 307.20 \text{ms}$$

Middle Channel


$$2.88 * (1600/6) / 79 * 31.6 = 307.20 \text{ms}$$

High Channel


$$2.88 * (1600/6) / 79 * 31.6 = 307.20 \text{ms}$$

The test data refer to the following:


Low Channel



Middle Channel



High Channel




5.5 Conducted Spurious Emissions and Band Edges Test

5.5.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.5.2 Block Diagram of Test Setup



5.5.3 Test Procedure

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 300 KHz.


Measurements are made over the 9kHz to 26.5GHz range with the transmitter set to the lowest, middle, and highest channels

5.5.4 Test Results of Conducted Spurious Emissions


No non-compliance noted. Only record the worst test result (TX-GFSK) in this report. The test data refer to the following page.

Test Plot


9KHz-26.5GHz Low Channel(GFSK)



9KHz-26.5GHz Middle Channel(GFSK)



9KHz-26.5GHz High Channel(GFSK)







5.5.5 Test Results of Band Edges Test



No non-compliance noted. Only record the worst test result in this report. The test data refer to the following page.



Test Plot

Hopping On - (GFSK)




Hopping Off - (GFSK)

Hopping On - (8-DPSK)


Hopping Off - (8-DPSK)

6. RADIATED MEASUREMENT


6.1 Block Diagram of Test Setup



Below 30MHz



Below 1GHz



Above 1GHz

6.2 Radiated Emission Limit

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| \1\ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (\2\) |
| 13.36-13.41 | | | |

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510MHz.

\2\ Above 38.6

Part 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in

Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector.

Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

Part 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009–0.490 | 2400/F(kHz) | 300 |
| 0.490–1.705 | 24000/F(kHz) | 30 |
| 1.705–30.0 | 30 | 30 |
| 30–88 | 100** | 3 |
| 88–216 | 150** | 3 |
| 216–960 | 200** | 3 |
| Above 960 | 500 | 3 |

6.3 Instruments Setting

The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---|--|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10th carrier harmonic |
| RB / VB (Emission in restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average |

| Receiver Parameter | Setting |
|------------------------|----------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 100kHz for QP |

6.4 Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

Premeasurement:

- The antenna is moved spherical over the EUT in different polarisations of the antenna.

Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


6.5 Results for Radiated Emissions

PASS.

Only record the worst test result in this report.

The radiated emissions from 9kHz to 30MHz are at least 20dB below the official limit and no need to report.


The test data please refer to following page:

Below 1GHz

Env./Ins: 24°C/56%
EUT: WIFI+BT module
M/N: WT4XR1210
Power Rating: DC 5V
Test Mode: TX-Middle Channel (1Mbps)
Operator: Leo
Memo:
pol: HORIZONTAL

| | Freq | Reading | CabLos | Antfac | Measured | Limit | Over | Remark |
|---|--------|---------|--------|--------|----------|--------|--------|--------|
| | MHz | dBuV | dB | dB/m | dBuV/m | dBuV/m | dB | |
| 1 | 63.95 | 19.45 | 0.48 | 11.13 | 31.06 | 40.00 | -8.94 | QP |
| 2 | 114.39 | 15.70 | 0.65 | 11.47 | 27.82 | 43.50 | -15.68 | QP |
| 3 | 218.18 | 21.63 | 0.88 | 11.14 | 33.65 | 46.00 | -12.35 | QP |
| 4 | 240.49 | 26.73 | 1.01 | 12.09 | 39.83 | 46.00 | -6.17 | QP |
| 5 | 478.14 | 19.24 | 1.39 | 16.03 | 36.66 | 46.00 | -9.34 | QP |
| 6 | 712.88 | 13.71 | 1.63 | 18.97 | 34.31 | 46.00 | -11.69 | QP |

Note: 1. All readings are Quasi-peak values.
2. Measured= Reading + Antenna Factor + Cable Loss
3. The emission that ate 20db blow the official limit are not reported



Env./Ins: 24°C/56%
EUT: WIFI+BT module
M/N: WT4XR1210
Power Rating: DC 5V
Test Mode: TX-Middle Channel (1Mbps)
Operator: Leo
Memo:
pol: VERTICAL

| | Freq | Reading | CabLos | Antfac | Measured | Limit | Over | Remark |
|---|--------|---------|--------|--------|----------|--------|--------|--------|
| | MHz | dBuV | dB | dB/m | dBuV/m | dBuV/m | dB | |
| 1 | 102.75 | 7.30 | 0.60 | 12.91 | 20.81 | 43.50 | -22.69 | QP |
| 2 | 183.26 | 16.36 | 0.70 | 9.97 | 27.03 | 43.50 | -16.47 | QP |
| 3 | 241.46 | 22.40 | 1.01 | 12.09 | 35.50 | 46.00 | -10.50 | QP |
| 4 | 381.14 | 15.57 | 1.18 | 14.62 | 31.37 | 46.00 | -14.63 | QP |
| 5 | 480.08 | 15.58 | 1.31 | 16.07 | 32.96 | 46.00 | -13.04 | QP |
| 6 | 960.23 | 10.34 | 1.90 | 21.48 | 33.72 | 54.00 | -20.28 | QP |

Note: 1. All readings are Quasi-peak values.
2. Measured= Reading + Antenna Factor + Cable Loss
3. The emission that ate 20db blow the official limit are not reported

***Note:

Pre-scan all mode and recorded the worst case results in this report (TX-Middle Channel(1Mbps)).

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Above 1GHz

Note: Only recorded the worst test result.

The worst test result for GFSK, TX-Low Channel:

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4804.17 | 45.48 | 33.06 | 35.04 | 3.94 | 47.44 | 74 | -26.56 | Peak | Horizontal |
| 4804.20 | 35.69 | 33.06 | 35.04 | 3.94 | 37.65 | 54 | -16.35 | Average | Horizontal |
| 4804.17 | 47.64 | 33.06 | 35.04 | 3.94 | 49.60 | 74 | -24.40 | Peak | Vertical |
| 4804.20 | 37.88 | 33.06 | 35.04 | 3.94 | 39.84 | 54 | -14.16 | Average | Vertical |

The worst test result for GFSK, TX-Middle Channel:

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4882.31 | 47.12 | 33.16 | 35.15 | 3.96 | 49.09 | 74 | -24.91 | Peak | Horizontal |
| 4882.33 | 37.30 | 33.16 | 35.15 | 3.96 | 39.27 | 54 | -14.73 | Average | Horizontal |
| 4882.31 | 49.65 | 33.16 | 35.15 | 3.96 | 51.62 | 74 | -22.38 | Peak | Vertical |
| 4882.33 | 40.52 | 33.16 | 35.15 | 3.96 | 42.49 | 54 | -11.51 | Average | Vertical |

The worst test result for GFSK, TX-High Channel:

| Freq. MHz | Reading dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4960.44 | 46.67 | 33.26 | 35.14 | 3.98 | 48.77 | 74 | -25.23 | Peak | Horizontal |
| 4960.46 | 36.75 | 33.26 | 35.14 | 3.98 | 38.85 | 54 | -15.15 | Average | Horizontal |
| 4960.44 | 48.96 | 33.26 | 35.14 | 3.98 | 51.06 | 74 | -22.94 | Peak | Vertical |
| 4960.46 | 39.27 | 33.26 | 35.14 | 3.98 | 41.37 | 54 | -12.63 | Average | Vertical |

Notes:

1. Measuring frequencies from 9k~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30MHz.
2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
3. 18~25GHz at least have 20dB margin. No recording in the test report.

6.6 Results for Band edge Testing (Radiated)

Note: Only recorded the worst test result.

TX-Low Channel, GFSK, Non-hopping

| Freq. MHz | Reading Level dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 2378.47 | 43.89 | 32.89 | 35.16 | 3.51 | 45.13 | 74 | -28.87 | Peak | Horizontal |
| 2378.50 | 34.26 | 32.90 | 35.16 | 3.51 | 35.51 | 54 | -18.49 | Average | Horizontal |
| 2390.00 | 44.87 | 32.92 | 35.16 | 3.54 | 46.17 | 74 | -27.83 | Peak | Horizontal |
| 2389.98 | 35.19 | 32.92 | 35.16 | 3.54 | 36.49 | 54 | -17.51 | Average | Horizontal |
| 2400.00 | 52.23 | 32.92 | 35.16 | 3.54 | 53.53 | 74 | -20.47 | Peak | Horizontal |
| 2399.98 | 42.66 | 32.92 | 35.16 | 3.54 | 43.96 | 54 | -10.04 | Average | Horizontal |
| 2378.47 | 44.13 | 32.89 | 35.16 | 3.51 | 45.37 | 74 | -28.63 | Peak | Vertical |
| 2378.50 | 34.40 | 32.90 | 35.16 | 3.51 | 35.65 | 54 | -18.35 | Average | Vertical |
| 2390.00 | 45.39 | 32.92 | 35.16 | 3.54 | 46.69 | 74 | -27.31 | Peak | Vertical |
| 2389.98 | 35.81 | 32.92 | 35.16 | 3.54 | 37.11 | 54 | -16.89 | Average | Vertical |
| 2400.00 | 53.89 | 32.92 | 35.16 | 3.54 | 55.19 | 74 | -18.81 | Peak | Vertical |
| 2399.98 | 43.98 | 32.92 | 35.16 | 3.54 | 45.28 | 54 | -8.72 | Average | Vertical |

TX-High Channel, GFSK, Non-hopping

| Freq. MHz | Reading Level dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 2483.50 | 47.26 | 33.06 | 35.18 | 3.60 | 48.74 | 74 | -25.26 | Peak | Horizontal |
| 2483.53 | 37.46 | 33.08 | 35.18 | 3.60 | 38.96 | 54 | -15.04 | Average | Horizontal |
| 2486.74 | 45.60 | 33.08 | 35.18 | 3.62 | 47.12 | 74 | -26.88 | Peak | Horizontal |
| 2486.77 | 35.74 | 33.08 | 35.18 | 3.62 | 37.26 | 54 | -16.74 | Average | Horizontal |
| 2483.50 | 47.43 | 33.06 | 35.18 | 3.60 | 48.91 | 74 | -25.09 | Peak | Vertical |
| 2483.53 | 37.63 | 33.08 | 35.18 | 3.60 | 39.13 | 54 | -14.87 | Average | Vertical |
| 2486.74 | 45.96 | 33.08 | 35.18 | 3.62 | 47.48 | 74 | -26.52 | Peak | Vertical |
| 2486.77 | 36.30 | 33.08 | 35.18 | 3.62 | 37.82 | 54 | -16.18 | Average | Vertical |


7. LINE CONDUCTED EMISSIONS

7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range(MHz) | Limits (dB μ V) | |
|----------------------|---------------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

7.2 Block Diagram of Test Setup




7.3 Test Results

PASS.

The test data please refer to following page.


Test Result For Line Power Input AC 120V/60Hz (Worst Case)



Env. Ins: 24*/56%
EUT: WIFI+BT module
M/N: WT4XR1210
Power Rating: AC 120V/60Hz
Test Mode: TX
Operator: Leo
Memo:
Pol: LINE

| Freq | Reading | LisnFac | CabLos | Atten_Fac | Measured | Limit | Over | Remark |
|------------|---------|---------|--------|-----------|----------|-------|--------|---------|
| MHz | dBuV | dB | dB | dB | dBuV | dBuV | dB | |
| 1 0.15000 | 18.99 | 9.57 | 0.02 | 10.00 | 38.58 | 66.00 | -27.42 | QP |
| 2 0.15010 | 9.09 | 9.57 | 0.02 | 10.00 | 28.68 | 55.99 | -27.31 | Average |
| 3 0.24165 | 7.23 | 9.63 | 0.03 | 10.00 | 26.89 | 62.04 | -35.15 | QP |
| 4 0.24175 | -6.55 | 9.63 | 0.03 | 10.00 | 13.11 | 52.04 | -38.93 | Average |
| 5 0.48890 | 12.29 | 9.62 | 0.04 | 10.00 | 31.95 | 56.19 | -24.24 | QP |
| 6 0.48900 | 3.40 | 9.62 | 0.04 | 10.00 | 23.06 | 46.18 | -23.12 | Average |
| 7 1.85815 | 7.89 | 9.64 | 0.05 | 10.00 | 27.58 | 56.00 | -28.42 | QP |
| 8 1.85915 | -0.86 | 9.64 | 0.05 | 10.00 | 18.83 | 46.00 | -27.17 | Average |
| 9 9.30237 | 9.03 | 9.69 | 0.08 | 10.00 | 28.80 | 60.00 | -31.20 | QP |
| 10 9.30337 | -1.17 | 9.69 | 0.08 | 10.00 | 18.60 | 50.00 | -31.40 | Average |
| 1126.84106 | 6.51 | 9.71 | 0.13 | 10.00 | 26.35 | 60.00 | -33.65 | QP |
| 1226.84206 | -1.50 | 9.71 | 0.13 | 10.00 | 18.34 | 50.00 | -31.66 | Average |

Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss+Atten_Fac.
2. The emission levels that are 20dB below the official limit are not reported.



Env. Ins: 24*/56%
EUT: WIFI+BT module
M/N: WT4XR1210
Power Rating: AC 120V/60Hz
Test Mode: TX
Operator: Leo
Memo:
Pol: NEUTRAL

| Freq | Reading | LisnFac | CabLos | Atten_Fac | Measured | Limit | Over | Remark |
|------------|---------|---------|--------|-----------|----------|-------|--------|---------|
| MHz | dBuV | dB | dB | dB | dBuV | dBuV | dB | |
| 1 0.15000 | 20.97 | 9.70 | 0.02 | 10.00 | 40.69 | 66.00 | -25.31 | QP |
| 2 0.15010 | 7.81 | 9.70 | 0.02 | 10.00 | 27.53 | 55.99 | -28.46 | Average |
| 3 0.50469 | 11.65 | 9.62 | 0.04 | 10.00 | 31.31 | 56.00 | -24.69 | QP |
| 4 0.50479 | 6.01 | 9.62 | 0.04 | 10.00 | 25.67 | 46.00 | -20.33 | Average |
| 5 1.11143 | 8.16 | 9.63 | 0.05 | 10.00 | 27.84 | 56.00 | -28.16 | QP |
| 6 1.11243 | -1.85 | 9.63 | 0.05 | 10.00 | 17.83 | 46.00 | -28.17 | Average |
| 7 2.29679 | 6.65 | 9.63 | 0.05 | 10.00 | 26.33 | 56.00 | -29.67 | QP |
| 8 2.29779 | -4.42 | 9.63 | 0.05 | 10.00 | 15.26 | 46.00 | -30.74 | Average |
| 9 8.82233 | 4.84 | 9.71 | 0.08 | 10.00 | 24.63 | 60.00 | -35.37 | QP |
| 10 8.82333 | -3.86 | 9.71 | 0.08 | 10.00 | 15.93 | 50.00 | -34.07 | Average |
| 1117.56779 | 6.92 | 9.79 | 0.11 | 10.00 | 26.82 | 60.00 | -33.18 | QP |
| 1217.56879 | -1.94 | 9.79 | 0.11 | 10.00 | 17.96 | 50.00 | -32.04 | Average |

Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss+Atten_Fac.
2. The emission levels that are 20dB below the official limit are not reported.

Note: Pre-scan all modes and recorded the worst case results in this report.

8. ANTENNA REQUIREMENT

8.1 Standard Applicable

According to § 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

8.2 Antenna Connected Construction

8.2.1. Antenna Connector Construction

Please see EUT photo for details about the antenna connector. It fulfills the requirement of § 15.203.

8.2.2. Results: Compliance.