

FCC Test Report

(ENDC: n77+B2/B5/B7/B12/B13/B14/B30/B41/B66)

Report No.: RFBHQC-WTW-P21030610F-1

FCC ID: QIPMV31-W

Test Model: MV31-W

Received Date: Sep. 06, 2021

Test Date: Sep. 29 ~ Oct. 10, 2021

Issued Date: Jun. 24, 2022

Applicant: THALES DIS AIS Deutschland GmbH

Address: Siemensdamm 50, Berlin, 13629, German

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location(1): No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

**FCC Registration /
Designation Number(1):** 788550 / TW0003

Test Location(2): No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

**FCC Registration /
Designation Number(2):** 281270 / TW0032



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	11
2.2 Test Site and Instruments	12
3 General Information	13
3.1 General Description of EUT	13
3.2 Configuration of System under Test	22
3.2.1 Description of Support Units	22
3.3 Test Mode Applicability and Tested Channel Detail	23
3.4 EUT Operating Conditions	49
3.5 General Description of Applied Standards and References	49
4 Test Types and Results	50
4.1 Output Power Measurement	50
4.1.1 Limits of Output Power Measurement	50
4.1.2 Test Procedures	51
4.1.3 Test Setup	52
4.1.4 Test Results	53
4.2 Modulation Characteristics Measurement	162
4.2.1 Limits of Modulation Characteristics	162
4.2.2 Test Procedure	162
4.2.3 Test Setup	162
4.2.4 Test Results	163
4.3 Frequency Stability Measurement	174
4.3.1 Limits of Frequency Stability Measurement	174
4.3.2 Test Procedure	174
4.3.3 Test Instruments	174
4.3.4 Test Setup	174
4.3.5 Test Results	175
4.4 Emission Bandwidth Measurement	223
4.4.1 Test Procedure	223
4.4.2 Test Procedure	223
4.4.3 Test Setup	223
4.4.4 Test Result	224
4.5 Channel Edge / Out-of-Band Emission Measurement	268
4.5.1 Limits of Channel Edge / Out-of-Band Emission Measurement	268
4.5.2 Test Setup	270
4.5.3 Test Procedures	270
4.5.4 Test Results	271
4.6 Peak to Average Ratio	319
4.6.1 Limits of Peak to Average Ratio Measurement	319
4.6.2 Test Setup	319
4.6.3 Test Procedures	319
4.6.4 Test Results	320
4.7 Conducted Spurious Emissions	341
4.7.1 Limits of Conducted Spurious Emissions Measurement	341
4.7.2 Test Setup	342
4.7.3 Test Procedure	342
4.7.4 Test Results	343
4.8 Radiated Emission Measurement	425
4.8.1 Limits of Radiated Emission Measurement	425
4.8.2 Test Procedure	426
4.8.3 Deviation from Test Standard	426

4.8.4 Test Setup.....	427
4.8.5 Test Results	428
5 Pictures of Test Arrangements.....	500
Appendix – Information of the Testing Laboratories	501

Release Control Record

Issue No.	Description	Date Issued
RFBHQC-WTW-P21030610F-1	Original release	Jun. 24, 2022

1 Certificate of Conformity

Product: Cinterion MV31-W

Brand: CINTERION

Test Model: MV31-W

Sample Status: Engineering Sample

Applicant: THALES DIS AIS Deutschland GmbH

Test Date: Sep. 29 ~ Oct. 10, 2021

Standards: FCC Part 22, Subpart H
FCC Part 24, Subpart E
FCC Part 27, Subpart C, D, F, H, L, M, O, Q
FCC Part 90, Subpart R

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen, **Date:** Jun. 24, 2022
Pettie Chen / Senior Specialist

Approved by : Jeremy Lin, **Date:** Jun. 24, 2022
Jeremy Lin / Project Engineer

2 Summary of Test Results

For 5GNR n77, n78(Part 27O):

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50 (j)	Equivalent Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement
2.1055 27.54	Frequency Stability Stay with the authorized bands of operation	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
2.1051 27.53(l)	Band Edge / Out of Band Emissions Measurements	Pass	Meet the requirement of limit.
----	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1051 27.53(l)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(l)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -26.88dB at 7680.00MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For 5GNR n77, n78 (Part 27Q):

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50 (k)	Equivalent Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement
----	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability Stay with the authorized bands of operation	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
2.1051 27.53(n)	Band Edge / Out of Band Emissions Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(n)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(n)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -26.94dB at 7000.02MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For LTE Band 2:

Applied Standard: FCC Part 24 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 24.232	Effective Isotropically Radiated Power	Pass	Meet the requirement of limit.
2.1046 24.232 (d)	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement
2.1055 24.235	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
24.238	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -34.50dB at 3760.00MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For LTE Band 5:

Applied Standard: FCC Part 22 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 22.913 (a)	Effective radiated power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement
22.913 (d)	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
22.917	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 22.917	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -37.23dB at 1688.00MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For LTE Band 7:

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(h)(2)	Equivalent Isotropically radiated power	Pass	Meet the requirement of limit.
2.1047	Modulation characteristics	Pass	Meet the requirement
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Emission Bandwidth	Pass	Meet the requirement of limit.
2.1051 27.53(m)(4)(6)	Out of Band Emission Measurements	Pass	Meet the requirement of limit.
--	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1051 27.53(m)(4)(6)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(m)(4)(6)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -21.82dB at 5070.00MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For LTE Band 12:

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50 (c)	Equivalent Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Emission Bandwidth	Pass	Meet the requirement of limit.
2.1051 27.53 (g)	Out of Band Emission Measurements	Pass	Meet the requirement of limit.
--	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1051 27.53 (g)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53 (g)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -39.05dB at 1399.40MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For LTE Band 13:

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(b)	Equivalent radiated power	Pass	Meet the requirement of limit.
2.1047	Modulation characteristics	Pass	Meet the requirement
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Emission Bandwidth	Pass	Meet the requirement of limit.
2.1051 27.53(c)	Channel Edge Measurements	Pass	Meet the requirement of limit.
--	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1051 27.53(c)(f)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(c)(f))	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -10.97dB at 1564.00MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For LTE Band 14:

Applied Standard: FCC Part 90 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 90.542 (a)(7)	Effective Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement
2.1055 90.539 (e)	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
90.210 (n)	Emission Masks	Pass	Meet the requirement of limit.
2.1053 90.543 (e)(2)(3)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 90.543 (e)(3)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 90.543 (e)(f)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -7.34dB at 1586.00MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For LTE Band 30:

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(a)	Equivalent Isotropically radiated power	Pass	Meet the requirement of limit.
2.1047	Modulation characteristics	Pass	Meet the requirement
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Emission Bandwidth	Pass	Meet the requirement of limit.
2.1051 27.53(a)	Out of Band Emission Measurements	Pass	Meet the requirement of limit.
--	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1051 27.53(a)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(a)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -6.40dB at 4620.00MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For LTE Band 41:

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50 (h)(2)	Equivalent Isotropically Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement
----	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability Stay with the authorized bands of operation	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
2.1051 27.53 (m)(4)(6)	Band Edge / Out of Band Emissions Measurements	Pass	Meet the requirement of limit.
2.1051 27.53 (m)(4)(6)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53 (m)(4)(6)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -20.61dB at 5186.00MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For LTE Band 66:

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)	Equivalent Isotropically radiated power	Pass	Meet the requirement of limit.
2.1047	Modulation characteristics	Pass	Meet the requirement
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Emission Bandwidth	Pass	Meet the requirement of limit.
2.1051 27.53(h)	Channel Edge Measurements	Pass	Meet the requirement of limit.
27.50(d)(5)	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -35.11dB at 3490.00MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.04 dB
	30MHz ~ 200MHz	3.59 dB
	200MHz ~ 1000MHz	3.60 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver Rohde & Schwarz	N9038A	MY55420137	Apr. 09, 2021	Apr. 08, 2022
Spectrum Analyzer KEYSIGHT	N9020B	MY60110440	Dec. 18, 2020	Dec. 17, 2021
BILOG Antenna SCHWARZBECK	VULB9168	1213	Nov. 04, 2020	Nov. 03, 2021
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-563	Nov. 22, 2020	Nov. 21, 2021
HORN Antenna SCHWARZBECK	BBHA 9170	995	Nov. 22, 2020	Nov. 21, 2021
Preamplifier EMCI	EMC330N	980782	Jan. 12, 2021	Jan. 11, 2022
Preamplifier EMCI	EMC118A45SE	980808	Jan. 12, 2021	Jan. 11, 2022
Preamplifier EMCI	EMC184045SE	980788	Jan. 12, 2021	Jan. 11, 2022
RF signal cable EMCI	EMC104-SM-SM-(9 000+2000+1000)	201243+ 201231+ 210102	Jan. 12, 2021	Jan. 11, 2022
RF signal cable EMCI	EMCCFD400-NM-N M-(9000+300+500)	201236+ 201235+ 201233	Jan. 12, 2021	Jan. 11, 2022
RF signal cable EMCI	EMC101G-KM-KM- (5000+3000+2000)	201260+201257+201254	Jan. 12, 2021	Jan. 11, 2022
Software BV ADT	ADT_Radiated_V7. 6.15.9.5	NA	NA	NA
Antenna Tower Max-Full	MFT-151SS-0.5T	NA	NA	NA
Turn Table Max-Full	MF-7802BS	NA	NA	NA
Turn Table Controller Max-Full	MF-7802BS	MF780208674	NA	NA
USB Wideband Power Sensor KEYSIGHT	U2021XA	MY55050005/MY55190004/ MY55190007/MY55210005	Jul. 12, 2021	Jul. 11, 2022
Turn Table BV ADT	TT100	TT93021705	NA	NA
Turn Table Controller BV ADT	SC100	SC93021705	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Standard Temperature And Humidity Chamber GIANT FORCE	GTH-120-40-CP-A R	MAA1306-019	Sep. 10, 2021	Sep. 09, 2022
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
True RMS Clamp Meter Fluke	325	31130711WS	Jun. 02, 2021	Jun. 01, 2022
DC power supply Keysight	U8002A	MY56330015	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in WM Chamber 8.

3 General Information

3.1 General Description of EUT

Product	Cinterion MV31-W
Brand	CINTERION
Test Model	MV31-W
Sample Status	Engineering Sample
Power Supply	5 Vdc (Host equipment)
Rating	3.135Vdc~3.63Vdc (Module)

5GNR n77, n78 (Part 270)

Modulation Type	$\pi/2$ BPSK, QPSK, 16QAM, 64QAM, 256QAM					
Waveform Type	CP-OFDM, DFT-s-OFDM					
Operating Band	n77 (3700-3980MHz) / n78 (3700-3800MHz)					
Operating Frequency	n77 (Channel Bandwidth 20MHz)	3710.01MHz ~ 3969.99MHz				
	n77 (Channel Bandwidth 40MHz)	3720.00MHz ~ 3960.00MHz				
	n77 (Channel Bandwidth 50MHz)	3725.01MHz ~ 3954.99MHz				
	n77 (Channel Bandwidth 60MHz)	3730.02MHz ~ 3949.98MHz				
	n77 (Channel Bandwidth 80MHz)	3740.01MHz ~ 3939.99MHz				
	n77 (Channel Bandwidth 90MHz)	3745.02MHz ~ 3934.98MHz				
	n77 (Channel Bandwidth 100MHz)	3750.00MHz ~ 3930.00MHz				
Max. EIRP Power		$\pi/2$ BPSK	QPSK	16QAM	64QAM	256QAM
	n77 (Channel Bandwidth 20MHz)	912.011mW (29.60dBm)	870.964mW (29.40dBm)	690.240mW (28.39dBm)	539.511mW (27.32dBm)	375.837mW (25.75dBm)
	n77 (Channel Bandwidth 40MHz)	912.011mW (29.60dBm)	870.964mW (29.40dBm)	683.912mW (28.35dBm)	548.277mW (27.39dBm)	374.973mW (25.74dBm)
	n77 (Channel Bandwidth 50MHz)	909.913mW (29.59dBm)	860.994mW (29.35dBm)	691.831mW (28.40dBm)	549.541mW (27.40dBm)	380.189mW (25.80dBm)
	n77 (Channel Bandwidth 60MHz)	899.498mW (29.54dBm)	870.964mW (29.40dBm)	691.831mW (28.40dBm)	545.758mW (27.37dBm)	370.681mW (25.69dBm)
	n77 (Channel Bandwidth 80MHz)	907.821mW (29.58dBm)	862.979mW (29.36dBm)	690.240mW (28.39dBm)	544.503mW (27.36dBm)	380.189mW (25.80dBm)
	n77 (Channel Bandwidth 90MHz)	897.429mW (29.53dBm)	870.964mW (29.40dBm)	691.831mW (28.40dBm)	549.541mW (27.40dBm)	380.189mW (25.80dBm)
	n77 (Channel Bandwidth 100MHz)	905.733mW (29.57dBm)	870.964mW (29.40dBm)	690.240mW (28.39dBm)	542.001mW (27.34dBm)	380.189mW (25.80dBm)
Emission Designator		$\pi/2$ BPSK	QPSK	16QAM	64QAM	256QAM
	n77 (Channel Bandwidth 20MHz)	18M1G7D	18M3G7D	18M2D7W	18M2D7W	18M3D7W
	n77 (Channel Bandwidth 40MHz)	37M5G7D	37M8G7D	37M8D7W	37M8D7W	37M8D7W
	n77 (Channel Bandwidth 50MHz)	47M1G7D	47M5G7D	47M5D7W	47M5D7W	47M5D7W
	n77 (Channel Bandwidth 60MHz)	57M9G7D	57M9G7D	57M9D7W	57M9D7W	57M9D7W
	n77 (Channel Bandwidth 80MHz)	77M2G7D	77M5G7D	77M5D7W	77M5D7W	77M5D7W
	n77 (Channel Bandwidth 90MHz)	86M9G7D	87M5G7D	87M5D7W	87M5D7W	87M5D7W
	n77 (Channel Bandwidth 100MHz)	96M8G7D	97M6G7D	97M7D7W	97M6D7W	97M6D7W

*n78 has the same RF characteristic and power setting as n77, the operating frequency range of n77 is wider than n78, therefore n77 was selected as final mode for test.

5GNR n77, n78 (Part 27Q)

Modulation Type	$\pi/2$ BPSK, QPSK, 16QAM, 64QAM, 256QAM					
Waveform Type	CP-OFDM, DFT-s-OFDM					
Operating Band	n77, n78 (3450-3550MHz)					
Operating Frequency	n77 (Channel Bandwidth 20MHz)	3460.02MHz ~ 3540.00MHz				
	n77 (Channel Bandwidth 40MHz)	3470.01MHz ~ 3529.98MHz				
	n77 (Channel Bandwidth 50MHz)	3475.02MHz ~ 3525.00MHz				
	n77 (Channel Bandwidth 60MHz)	3480.00MHz ~ 3519.99MHz				
	n77 (Channel Bandwidth 80MHz)	3490.02MHz ~ 3510.00MHz				
	n77 (Channel Bandwidth 90MHz)	3495.00MHz ~ 3504.99MHz				
	n77 (Channel Bandwidth 100MHz)	3500.01MHz				
Max. EIRP Power		$\pi/2$ BPSK	QPSK	16QAM	64QAM	256QAM
	n77 (Channel Bandwidth 20MHz)	907.821mW (29.58dBm)	699.842mW (28.45dBm)	543.250mW (27.35dBm)	495.450mW (26.95dBm)	358.922mW (25.55dBm)
	n77 (Channel Bandwidth 40MHz)	881.049mW (29.45dBm)	639.735mW (28.06dBm)	555.904mW (27.45dBm)	495.450mW (26.95dBm)	350.752mW (25.45dBm)
	n77 (Channel Bandwidth 50MHz)	860.994mW (29.35dBm)	653.131mW (28.15dBm)	568.853mW (27.55dBm)	506.991mW (27.05dBm)	358.922mW (25.55dBm)
	n77 (Channel Bandwidth 60MHz)	881.049mW (29.45dBm)	704.693mW (28.48dBm)	555.904mW (27.45dBm)	484.172mW (26.85dBm)	350.752mW (25.45dBm)
	n77 (Channel Bandwidth 80MHz)	883.080mW (29.46dBm)	683.912mW (28.35dBm)	568.853mW (27.55dBm)	506.991mW (27.05dBm)	367.282mW (25.65dBm)
	n77 (Channel Bandwidth 90MHz)	883.080mW (29.46dBm)	699.842mW (28.45dBm)	518.800mW (27.15dBm)	462.381mW (26.65dBm)	334.965mW (25.25dBm)
	n77 (Channel Bandwidth 100MHz)	879.023mW (29.44dBm)	696.627mW (28.43dBm)	526.017mW (27.21dBm)	463.447mW (26.66dBm)	318.420mW (25.03dBm)
Emission Designator		$\pi/2$ BPSK	QPSK	16QAM	64QAM	256QAM
	n77 (Channel Bandwidth 20MHz)	18M0G7D	18M2G7D	18M2D7W	18M3D7W	18M2D7W
	n77 (Channel Bandwidth 40MHz)	37M5G7D	37M8G7D	37M8D7W	37M8D7W	37M8D7W
	n77 (Channel Bandwidth 50MHz)	47M1G7D	47M5G7D	47M5D7W	47M5D7W	47M5D7W
	n77 (Channel Bandwidth 60MHz)	57M9G7D	57M9G7D	57M9D7W	57M9D7W	57M9D7W
	n77 (Channel Bandwidth 80MHz)	77M2G7D	77M5G7D	77M5D7W	77M5D7W	77M5D7W
	n77 (Channel Bandwidth 90MHz)	86M9G7D	87M5G7D	87M5D7W	87M5D7W	87M5D7W
	n77 (Channel Bandwidth 100MHz)	96M5G7D	97M4G7D	97M4D7W	97M4D7W	97M4D7W

*n78 has the same RF characteristic and power setting as n77, the operating frequency range of n77 is wider than n78, therefore n77 was selected as final mode for test.

LTE Band

Modulation Type	QPSK, 16QAM, 64QAM, 256QAM		
Operating Frequency	LTE Band 2	Channel Bandwidth 1.4MHz	1850.7MHz ~ 1909.3MHz
		Channel Bandwidth 3MHz	1851.5MHz ~ 1908.5MHz
		Channel Bandwidth 5MHz	1852.5MHz ~ 1907.5MHz
		Channel Bandwidth 10MHz	1855.0MHz ~ 1905.0MHz
		Channel Bandwidth 15MHz	1857.5MHz ~ 1902.5MHz
		Channel Bandwidth 20MHz	1860.0MHz ~ 1900.0MHz
	LTE Band 5	Channel Bandwidth 1.4MHz	824.7MHz ~ 848.3MHz
		Channel Bandwidth 3MHz	825.5MHz ~ 847.5MHz
		Channel Bandwidth 5MHz	826.5MHz ~ 846.5MHz
		Channel Bandwidth 10MHz	829.0MHz ~ 844.0MHz
	LTE Band 7	Channel Bandwidth 5MHz	2502.5MHz ~ 2567.5MHz
		Channel Bandwidth 10MHz	2505.0MHz ~ 2565.0MHz
		Channel Bandwidth 15MHz	2507.5MHz ~ 2562.5MHz
		Channel Bandwidth 20MHz	2510.0MHz ~ 2560.0MHz
	LTE Band 12	Channel Bandwidth 1.4MHz	699.7MHz ~ 715.3MHz
		Channel Bandwidth 3MHz	700.5MHz ~ 714.5MHz
		Channel Bandwidth 5MHz	701.5MHz ~ 713.5MHz
		Channel Bandwidth 10MHz	704.0MHz ~ 711.0MHz
	LTE Band 13	Channel Bandwidth 5MHz	779.5MHz ~ 784.5MHz
		Channel Bandwidth 10MHz	782.0MHz
	LTE Band 14	Channel Bandwidth 5MHz	790.5MHz ~ 795.5MHz
		Channel Bandwidth 10MHz	793MHz
	LTE Band 30	Channel Bandwidth 5MHz	2307.5MHz ~ 2312.5MHz
		Channel Bandwidth 10MHz	2310.0MHz
	LTE Band 41	Channel Bandwidth 5MHz	2498.5MHz ~ 2687.5MHz
		Channel Bandwidth 10MHz	2501.0MHz ~ 2685.0 MHz
		Channel Bandwidth 15MHz	2503.5MHz ~ 2682.5MHz
		Channel Bandwidth 20MHz	2506.0MHz ~ 2680.0 MHz
	LTE Band 66	Channel Bandwidth 1.4MHz	1710.7MHz ~ 1779.3MHz
		Channel Bandwidth 3MHz	1711.5MHz ~ 1778.5MHz
		Channel Bandwidth 5MHz	1712.5MHz ~ 1777.5MHz
		Channel Bandwidth 10MHz	1715.0MHz ~ 1775.0MHz
		Channel Bandwidth 15MHz	1717.5MHz ~ 1772.5MHz
		Channel Bandwidth 20MHz	1720.0MHz ~ 1770.0MHz

Max. EIRP Power			QPSK	16QAM	64QAM	256QAM
Max. EIRP Power	LTE Band 2	Channel Bandwidth 1.4MHz	801.678mW (29.04dBm)	703.072mW (28.47dBm)	547.016mW (27.38dBm)	358.922mW (25.55dBm)
		Channel Bandwidth 3MHz	810.961mW (29.09dBm)	714.496mW (28.54dBm)	572.796mW (27.58dBm)	381.944mW (25.82dBm)
		Channel Bandwidth 5MHz	812.831mW (29.10dBm)	709.578mW (28.51dBm)	563.638mW (27.51dBm)	350.752mW (25.45dBm)
		Channel Bandwidth 10MHz	816.582mW (29.12dBm)	727.780mW (28.62dBm)	588.844mW (27.70dBm)	374.111mW (25.73dBm)
		Channel Bandwidth 15MHz	803.526mW (29.05dBm)	721.107mW (28.58dBm)	567.545mW (27.54dBm)	360.579mW (25.57dBm)
		Channel Bandwidth 20MHz	818.465mW (29.13dBm)	717.794mW (28.56dBm)	579.429mW (27.63dBm)	378.443mW (25.78dBm)
	LTE Band 7	Channel Bandwidth 5MHz	1109.175mW (30.45dBm)	966.051mW (29.85dBm)	778.037mW (28.91dBm)	498.884mW (26.98dBm)
		Channel Bandwidth 10MHz	1071.519mW (30.30dBm)	972.747mW (29.88dBm)	779.830mW (28.92dBm)	510.505mW (27.08dBm)
		Channel Bandwidth 15MHz	1083.927mW (30.35dBm)	905.733mW (29.57dBm)	743.019mW (28.71dBm)	489.779mW (26.90dBm)
		Channel Bandwidth 20MHz	1071.519mW (30.30dBm)	961.612mW (29.83dBm)	783.430mW (28.94dBm)	527.230mW (27.22dBm)
	LTE Band 30	Channel Bandwidth 5MHz	247.172mW (23.93dBm)	220.800mW (23.44dBm)	170.216mW (22.31dBm)	114.815mW (20.60dBm)
		Channel Bandwidth 10MHz	246.604mW (23.92dBm)	207.014mW (23.16dBm)	158.855mW (22.01dBm)	103.992mW (20.17dBm)
	LTE Band 41	Channel Bandwidth 5MHz	1958.845mW (32.92dBm)	1667.247mW (32.22dBm)	1367.729mW (31.36dBm)	893.305mW (29.51dBm)
		Channel Bandwidth 10MHz	1976.970mW (32.96dBm)	1713.957mW (32.34dBm)	1383.566mW (31.41dBm)	870.964mW (29.40dBm)
		Channel Bandwidth 15MHz	1940.886mW (32.88dBm)	1713.957mW (32.34dBm)	1294.196mW (31.12dBm)	851.138mW (29.30dBm)
		Channel Bandwidth 20MHz	1981.527mW (32.97dBm)	1674.943mW (32.24dBm)	1306.171mW (31.16dBm)	881.049mW (29.45dBm)
	LTE Band 66	Channel Bandwidth 1.4MHz	774.462mW (28.89dBm)	663.743mW (28.22dBm)	526.017mW (27.21dBm)	339.625mW (25.31dBm)
		Channel Bandwidth 3MHz	814.704mW (29.11dBm)	688.652mW (28.38dBm)	526.017mW (27.21dBm)	339.625mW (25.31dBm)
		Channel Bandwidth 5MHz	824.138mW (29.16dBm)	711.214mW (28.52dBm)	554.626mW (27.44dBm)	352.371mW (25.47dBm)
		Channel Bandwidth 10MHz	818.465mW (29.13dBm)	695.024mW (28.42dBm)	542.001mW (27.34dBm)	338.844mW (25.30dBm)
		Channel Bandwidth 15MHz	803.526mW (29.05dBm)	699.842mW (28.45dBm)	553.350mW (27.43dBm)	350.752mW (25.45dBm)
		Channel Bandwidth 20MHz	816.582mW (29.12dBm)	712.853mW (28.53dBm)	555.904mW (27.45dBm)	340.408mW (25.32dBm)
Max. ERP Power	LTE Band 5	Channel Bandwidth 1.4MHz	457.088mW (26.60dBm)	411.150mW (26.14dBm)	316.228mW (25.00dBm)	209.411mW (23.21dBm)
		Channel Bandwidth 3MHz	474.242mW (26.76dBm)	412.098mW (26.15dBm)	330.370mW (25.19dBm)	213.304mW (23.29dBm)
		Channel Bandwidth 5MHz	475.335mW (26.77dBm)	412.098mW (26.15dBm)	331.131mW (25.20dBm)	213.304mW (23.29dBm)
		Channel Bandwidth 10MHz	472.063mW (26.74dBm)	431.519mW (26.35dBm)	343.558mW (25.36dBm)	217.771mW (23.38dBm)
	LTE Band 12	Channel Bandwidth 1.4MHz	524.807mW (27.20dBm)	461.318mW (26.64dBm)	367.282mW (25.65dBm)	237.137mW (23.75dBm)
		Channel Bandwidth 3MHz	532.108mW (27.26dBm)	464.515mW (26.67dBm)	365.595mW (25.63dBm)	242.661mW (23.85dBm)
		Channel Bandwidth 5MHz	537.032mW (27.30dBm)	463.447mW (26.66dBm)	371.535mW (25.70dBm)	231.206mW (23.64dBm)
		Channel Bandwidth 10MHz	524.807mW (27.20dBm)	480.839mW (26.82dBm)	373.250mW (25.72dBm)	230.675mW (23.63dBm)
	LTE Band 13	Channel Bandwidth 5MHz	539.511mW (27.32dBm)	485.289mW (26.86dBm)	403.645mW (26.06dBm)	258.821mW (24.13dBm)
		Channel Bandwidth 10MHz	528.445mW (27.23dBm)	462.381mW (26.65dBm)	368.978mW (25.67dBm)	246.037mW (23.91dBm)
	LTE Band 14	Channel Bandwidth 5MHz	538.270mW (27.31dBm)	479.733mW (26.81dBm)	384.592mW (25.85dBm)	237.684mW (23.76dBm)
		Channel Bandwidth 10MHz	524.807mW (27.20dBm)	484.172mW (26.85dBm)	401.791mW (26.04dBm)	264.850mW (24.23dBm)
Antenna Type	Refer to Note as below					
Antenna Connector	Refer to Note as below					
Accessory Device	Refer to Note as below					
Cable Supplied	Refer to Note as below					

Output Power / Emission Designator	n77(Part 27O)+ LTE Band 2		Maximum EIRP	Sum Bandwidth
		n77(Part 27O)	912.011mW (29.6dBm)	38M4D7W
		LTE Band 2 (EIRP)	818.465mW (29.13dBm)	
			EIRP	MAX Sum Bandwidth
		n77(Part 27O)	595.662mW (27.75dBm)	116MD7W
		LTE Band 2 (EIRP)	818.465mW (29.13dBm)	
	n77(Part 27O)+ LTE Band 5		Maximum EIRP / ERP	Sum Bandwidth
		n77(Part 27O)	912.011mW (29.6dBm)	41M8D7W
		LTE Band 5 (ERP)	475.335mW (26.77dBm)	
			EIRP / ERP	MAX Sum Bandwidth
		n77(Part 27O)	595.662mW (27.75dBm)	107MD7W
		LTE Band 5 (ERP)	374.111mW (25.73dBm)	
	n77(Part 27O)+ LTE Band 7		Maximum EIRP	Sum Bandwidth
		n77(Part 27O)	912.011mW (29.6dBm)	41M8D7W
		LTE Band 7 (EIRP)	1109.175mW (30.45dBm)	
			EIRP	MAX Sum Bandwidth
		n77(Part 27O)	595.662mW (27.75dBm)	116MD7W
		LTE Band 7 (EIRP)	338.065mW (25.29dBm)	
	n77(Part 27O)+ LTE Band 12		Maximum EIRP / ERP	Sum Bandwidth
		n77(Part 27O)	912.011mW (29.6dBm)	41M8D7W
		LTE Band 12 (ERP)	573.032mW (27.3dBm)	
			EIRP / ERP	MAX Sum Bandwidth
		n77(Part 27O)	595.662mW (27.75dBm)	107MD7W
		LTE Band 12 (ERP)	429.536mW (26.33dBm)	
	n77(Part 27O)+ LTE Band 13		Maximum EIRP / ERP	Sum Bandwidth
		n77(Part 27O)	912.011mW (29.6dBm)	41M8D7W
		LTE Band 13 (ERP)	539.511mW (27.32dBm)	
			EIRP / ERP	MAX Sum Bandwidth
		n77(Part 27O)	595.662mW (27.75dBm)	107MD7W
		LTE Band 13 (ERP)	441.570mW (26.45dBm)	
	n77(Part 27O)+ LTE Band 14		Maximum EIRP / ERP	Sum Bandwidth
		n77(Part 27O)	912.011mW (29.6dBm)	41M8D7W
		LTE Band 14 (ERP)	538.270mW (27.31dBm)	
			EIRP / ERP	MAX Sum Bandwidth
		n77(Part 27O)	595.662mW (27.75dBm)	107MD7W
		LTE Band 14 (ERP)	419.759mW (26.23dBm)	
	n77(Part 27O)+ LTE Band 30		Maximum EIRP	Sum Bandwidth
		n77(Part 27O)	912.011mW (29.60dBm)	41M8D7W
		LTE Band 30 (EIRP)	247.172mW (23.93dBm)	
			EIRP	MAX Sum Bandwidth
		n77(Part 27O)	595.662mW (27.75dBm)	107MD7W
		LTE Band 30 (EIRP)	194.536mW (22.89dBm)	

Output Power / Emission Designator	n77(Part 27O)+ LTE Band 41		Maximum EIRP	Sum Bandwidth
		n77(Part 27O)	912.011mW (29.6dBm)	46M3D7W
		LTE Band 41 (EIRP)	1976.970mW (32.96dBm)	
			EIRP	MAX Sum Bandwidth
		n77(Part 27O)	595.662mW (27.75dBm)	116MD7W
		LTE Band 41 (EIRP)	1264.736mW (31.02dBm)	
	n77(Part 27O)+ LTE Band 66		Maximum EIRP	Sum Bandwidth
		n77(Part 27O)	912.011mW (29.6dBm)	41M8D7W
		LTE Band 66 (EIRP)	824.138mW (29.16dBm)	
			EIRP	MAX Sum Bandwidth
		n77(Part 27O)	595.662mW (27.75dBm)	116MD7W
		LTE Band 66 (EIRP)	674.143mW (28.11dBm)	

Output Power / Emission Designator	n77(Part 27Q)+ LTE Band 2		Maximum EIRP	Sum Bandwidth
		n77(Part 27Q)	907.821mW (29.58dBm)	35M9D7W
		LTE Band 2 (EIRP)	818.465mW (29.13dBm)	
			EIRP	MAX Sum Bandwidth
		n77(Part 27Q)	879.023mW (29.44dBm)	115MD7W
		LTE Band 2 (EIRP)	818.465mW (29.13dBm)	
	n77(Part 27Q)+ LTE Band 5		Maximum EIRP / ERP	Sum Bandwidth
		n77(Part 27Q)	907.821mW (29.58dBm)	22M5D7W
		LTE Band 5 (ERP)	475.335mW (26.77dBm)	
			EIRP / ERP	MAX Sum Bandwidth
		n77(Part 27Q)	879.023mW (29.44dBm)	106MD7W
		LTE Band 5 (ERP)	374.111mW (25.73dBm)	
	n77(Part 27Q)+ LTE Band 7		Maximum EIRP	Sum Bandwidth
		n77(Part 27Q)	907.821mW (29.58dBm)	22M5D7W
		LTE Band 7 (EIRP)	1109.175mW (30.45dBm)	
			EIRP	MAX Sum Bandwidth
		n77(Part 27Q)	879.023mW (29.44dBm)	101MD7W
		LTE Band 7 (EIRP)	338.065mW (26.33dBm)	
	n77(Part 27Q)+ LTE Band 12		Maximum EIRP / ERP	Sum Bandwidth
		n77(Part 27Q)	907.821mW (29.58dBm)	22M5D7W
		LTE Band 12 (ERP)	537.032mW (27.3dBm)	
			EIRP / ERP	MAX Sum Bandwidth
		n77(Part 27Q)	879.023mW (29.44dBm)	106MD7W
		LTE Band 12 (ERP)	429.536mW (26.33dBm)	
	n77(Part 27Q)+ LTE Band 13		Maximum EIRP / ERP	Sum Bandwidth
		n77(Part 27Q)	907.821mW (29.58dBm)	22M5D7W
		LTE Band 13 (ERP)	539.511mW (27.32dBm)	
			EIRP / ERP	MAX Sum Bandwidth
		n77(Part 27Q)	879.023mW (29.44dBm)	106MD7W
		LTE Band 13 (ERP)	528.445mW (27.23dBm)	

Output Power / Emission Designator	n77(Part 27Q)+ LTE Band 14		Maximum EIRP / ERP	Sum Bandwidth
		n77(Part 27Q)	907.821mW (29.58dBm)	22M5D7W
		LTE Band 14 (ERP)	538.270mW (27.31dBm)	
			EIRP / ERP	MAX Sum Bandwidth
		n77(Part 27Q)	879.023mW (29.44dBm)	106MD7W
		LTE Band 14 (ERP)	524.807mW (27.20dBm)	
	n77(Part 27Q)+ LTE Band 30		Maximum EIRP	Sum Bandwidth
		n77(Part 27Q)	907.821mW (29.58dBm)	22M5D7W
		LTE Band 30 (EIRP)	247.172mW (23.93dBm)	
			EIRP	MAX Sum Bandwidth
		n77(Part 27Q)	879.023mW (29.44dBm)	106MD7W
		LTE Band 30 (EIRP)	246.604mW (23.92dBm)	
	n77(Part 27Q)+ LTE Band 41		Maximum EIRP	Sum Bandwidth
		n77(Part 27Q)	907.821mW (29.58dBm)	35M9D7W
		LTE Band 41 (EIRP)	1981.527mW (32.97dBm)	
			EIRP	MAX Sum Bandwidth
		n77(Part 27Q)	879.023mW (29.44dBm)	115MD7W
		LTE Band 41 (EIRP)	1981.527mW (32.97dBm)	
	n77(Part 27Q)+ LTE Band 66		Maximum EIRP	Sum Bandwidth
		n77(Part 27Q)	907.821mW (29.58dBm)	22M5D7W
		LTE Band 66 (EIRP)	824.138mW (29.16dBm)	
			EIRP	MAX Sum Bandwidth
		n77(Part 27Q)	879.023mW (29.44dBm)	115MD7W
		LTE Band 66 (EIRP)	816.582mW (29.12dBm)	

Note:

1. This report is prepared for FCC class II permissive change. This report is issued as a duplicate report of BV CPS report no.: RFBHQC-WTW-P21030610B-1 (FCC ID: 2AQ68T99W175). Difference compared with the original report is changing applicant, FCC ID, product name, brand and model. Due to no effect any test item, we didn't re-test.
2. There are four Difference HW of MV31-W.

Brand	Model	HW
CINTERION	MV31-W	1. 3G+LTE+Sub6+eSIM
		2. 3G+LTE+Sub6 only w/o eSIM
		3. 3G+LTE+Sub6+eSIM+GNSS connector
		4. 3G+LTE+Sub6 only+w/o eSIM+GNSS connector

*After pre-testing, "HW: 1. 3G+LTE+Sub6+eSIM" is the worst for the final tests.

3. The following antennas were provided to the EUT.

Antenna No.	RF Chain No.	Brand	Model	Antenna Net Gain(dBi)	Frequency range (MHz)	Antenna Type	Connector Type
1		WHA YU	C107-511720-A	4.41	660~803	PCB	I-PEX
2		WHA YU	C107-511721-A	3.81 4.03	791~960 1447.9~1606	PCB	I-PEX
3		WHA YU	C107-511722-A	4.27 5.31	1710~2170 2500~2690	PCB	I-PEX
4		WHA YU	C107-511723-A	2.99 0.92	2300~2400 3500~3700	PCB	I-PEX
5		WHA YU	C107-511724-A	6.45	5150~5925	PCB	I-PEX
6		WHA YU	C107-511725-A	4.89	3400~3700	PCB	I-PEX
7		AVX	5000106-R1-X01	2.91	699~803	Monopole	I-PEX
8		AVX	5000107-R1-X01	2.59	791~960	Monopole	I-PEX
9		AVX	5000108-R1-X01	2.85	1427~1610	Monopole	I-PEX
10		AVX	5000109-R1-X01	2.23 2.94	1710~2200 5150~5925	Monopole	I-PEX
11		AVX	5000110-R1-X01	0.9	2300~2690	Monopole	I-PEX
12		AVX	5000111-R1-X01	0.87	3300~5000	Monopole	I-PEX
13	Tx1/ Rx1	Ethertronics	5003806	0.4 -1.61 0.39 2.95 1.98 0.38 0.83 2.31	698-821 824-960 1425-1515 1710-2200 2300-2690 3300-4200 4400-5000 5150-5925	PIFA	I-PEX
	Rx2	Ethertronics	5003807	-2.24 -4.52 2.87 2.99 2.93 2.91 2.23 -0.85 -3.04	716-821 824-960 1425-1515 1557-1610 1805-2200 2300-2690 3300-4200 4400-5000 5150-5925	PIFA	I-PEX
	Tx2/ Rx3	Ethertronics	5003806	2.21 2.25 -0.45 2.6	1710-2200 2300-2690 3300-4200 4400-5000	PIFA	I-PEX
	Rx4	Ethertronics	5003700	1.38 2.87 0.6 -2.09	1805-2200 2300-2690 3300-4200 4400-5000	PIFA	I-PEX

Antenna No.	RF Chain No.	Brand	Model	Antenna Net Gain(dBi)	Frequency range (MHz)	Antenna Type	Connector Type
14	Ant. 0 (TX/RX)	Master Wave	NA	2.4	880~960	PCB	I-PEX
				2.2	1020~2170		
				2.9	2545~2595		
				2.9	3565~3600		
				2.9	3900~4000		
				NA	GPS		
	Ant. 2 (TX/RX)	Master Wave	NA	NA	880~960	PCB	I-PEX
				2.2	1020~2170		
				2.8	2545~2595		
				2.9	3565~3600		
				2.8	3900~4000		
				NA	GPS		
	Ant. 1 (RX)	Master Wave	NA	NA	880~960	PCB	I-PEX
				5.3	1020~2170		
				5.1	2545~2595		
				4.3	3565~3600		
				4.5	3900~4000		
				NA	GPS		
	Ant. 3 (RX)	Master Wave	NA	1.3	880~960	PCB	I-PEX
				6.8	1020~2170		
				3.7	2545~2595		
				6.4	3565~3600		
				6.2	3900~4000		
				3.7	GPS		

*The antenna for the final tests as following table.


	Band	Antenna
5GNR	n77 (Part27O) (30kHz) / 20/40/50/60/80/90/100	Antenna 14
5GNR	n77 (Part27Q) (30kHz) / 20/40/50/60/80/90/100	Antenna 6

	Band	Antenna
LTE	2	Antenna 3
	5	Antenna 2
	7	Antenna 3
	12	Antenna 1
	13	Antenna 1
	14	Antenna 3
	30	Antenna 4
	41	Antenna 3
	66	Antenna 3

4. The EUT supports the following ENDC configuration.

5GNR	FCC 5G FR1			ENDC
	Band	SCS	Bandwidth (MHz)	
	n25	15kHz	5/10/15/20	Band 12
	n77	30kHz	20/40/50/60/80/90/100	Band 2/5/7/12/13/14/30/41/66

3.2 Configuration of System under Test



Remote site



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	5G Wireless Test Platforms	Keysight	E7515B	MY60102114	NA	-
B.	Adapter	LITEON	PA-1050-39	NA	NA	-
C.	Fixture	NA	NA	NA	NA	Provided by client.

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	USB cable	1	1.5	Y	0	-

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	Radiated Emission
5GNR n77	Z-plane
LTE Band 2	Z-plane
LTE Band 5	Z-plane
LTE Band 7	Z-plane
LTE Band 12	Z-plane
LTE Band 13	Z-plane
LTE Band 14	Z-plane
LTE Band 30	Z-plane
LTE Band 41	Z-plane
LTE Band 66	Z-plane

5GNR n77 (Part 270)

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	EIRP	647334 to 665666	647334 (3710.01MHz), 656000 (3840.00MHz), 665666 (3969.99MHz)	20MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 26 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 13 RB Offset 25 RB / 26 RB Offset 50 RB / 0 RB Offset
		648000 to 664000	648000 (3720.00MHz), 656000 (3840.00MHz), 664000 (3960.00MHz)	40MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 53 RB Offset 1 RB / 104 RB Offset 50 RB / 0 RB Offset 50 RB / 28 RB Offset 50 RB / 56 RB Offset 100 RB / 0 RB Offset
		648334 to 663666	648334 (3725.01MHz), 656000 (3840.00MHz), 663666 (3954.99MHz)	50MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 67 RB Offset 1 RB / 131 RB Offset 64 RB / 0 RB Offset 64 RB / 35 RB Offset 64 RB / 69 RB Offset 128 RB / 0 RB Offset
		648668 to 663332	648668 (3730.02MHz), 656000 (3840.00MHz), 663332 (3949.98MHz)	60MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 81 RB Offset 1 RB / 160 RB Offset 81 RB / 0 RB Offset 81 RB / 41 RB Offset 81 RB / 81 RB Offset 162 RB / 0 RB Offset
		649334 to 662666	649334 (3740.01MHz), 656000 (3840.00MHz), 662666 (3939.99MHz)	80MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 109 RB Offset 1 RB / 215 RB Offset 108 RB / 0 RB Offset 108 RB / 55 RB Offset 108 RB / 109 RB Offset 216 RB / 0 RB Offset
		649558 to 662332	649558 (3745.02MHz), 656000 (3840.00MHz), 662332 (3934.98MHz)	90MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 123 RB Offset 1 RB / 243 RB Offset 120 RB / 0 RB Offset 120 RB / 63 RB Offset 120 RB / 125 RB Offset 240 RB / 0 RB Offset
		650000 to 662000	650000 (3750.00MHz), 656000 (3840.00MHz), 662000 (3930.00MHz)	100MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 137 RB Offset 1 RB / 271 RB Offset 135 RB / 0 RB Offset 135 RB / 69 RB Offset 135 RB / 138 RB Offset 270 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Modulation Characteristics	650000 to 662000	656000 (3840.00MHz)	100MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	270 RB / 0 RB Offset
-	Frequency Stability	647334 to 665666	647334 (3710.01MHz), 665666 (3969.99MHz)	20MHz	$\pi/2$ BPSK	50 RB / 0 RB Offset
		648000 to 664000	648000 (3720.00MHz), 664000 (3960.00MHz)	40MHz	$\pi/2$ BPSK	100 RB / 0 RB Offset
		648334 to 663666	648334 (3725.01MHz), 663666 (3954.99MHz)	50MHz	$\pi/2$ BPSK	128 RB / 0 RB Offset
		648668 to 663332	648668 (3730.02MHz), 663332 (3949.98MHz)	60MHz	$\pi/2$ BPSK	162 RB / 0 RB Offset
		649334 to 662666	649334 (3740.01MHz), 662666 (3939.99MHz)	80MHz	$\pi/2$ BPSK	216 RB / 0 RB Offset
		649558 to 662332	649558 (3745.02MHz), 662332 (3934.98MHz)	90MHz	$\pi/2$ BPSK	240 RB / 0 RB Offset
		650000 to 662000	650000 (3750.00MHz), 662000 (3930.00MHz)	100MHz	$\pi/2$ BPSK	270 RB / 0 RB Offset
-	Emission Bandwidth	647334 to 665666	647334 (3710.01MHz), 656000 (3840.00MHz), 665666 (3969.99MHz)	20MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
		648000 to 664000	648000 (3720.00MHz), 656000 (3840.00MHz), 664000 (3960.00MHz)	40MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	100 RB / 0 RB Offset
		648334 to 663666	648334 (3725.01MHz), 656000 (3840.00MHz), 663666 (3954.99MHz)	50MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	128 RB / 0 RB Offset
		648668 to 663332	648668 (3730.02MHz), 656000 (3840.00MHz), 663332 (3949.98MHz)	60MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	162 RB / 0 RB Offset
		649334 to 662666	649334 (3740.01MHz), 656000 (3840.00MHz), 662666 (3939.99MHz)	80MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	216 RB / 0 RB Offset
		649558 to 662332	649558 (3745.02MHz), 656000 (3840.00MHz), 662332 (3934.98MHz)	90MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	240 RB / 0 RB Offset
		650000 to 662000	650000 (3750.00MHz), 656000 (3840.00MHz), 662000 (3930.00MHz)	100MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	270 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Band Edge	647334 to 665666	647334 (3710.01MHz), 665666 (3969.99MHz)	20MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
		648000 to 664000	648000 (3720.00MHz), 664000 (3960.00MHz)	40MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 104 RB Offset 100 RB / 0 RB Offset
		648334 to 663666	648334 (3725.01MHz), 663666 (3954.99MHz)	50MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 131 RB Offset 128 RB / 0 RB Offset
		648668 to 663332	648668 (3730.02MHz), 663332 (3949.98MHz)	60MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 160 RB Offset 162 RB / 0 RB Offset
		649334 to 662666	649334 (3740.01MHz), 662666 (3939.99MHz)	80MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 215 RB Offset 216 RB / 0 RB Offset
		649558 to 662332	649558 (3745.02MHz), 662332 (3934.98MHz)	90MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 243 RB Offset 240 RB / 0 RB Offset
		650000 to 662000	650000 (3750.00MHz), 662000 (3930.00MHz)	100MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 271 RB Offset 270 RB / 0 RB Offset
-	Peak to Average Ratio	647334 to 665666	647334 (3710.01MHz), 656000 (3840.00MHz), 665666 (3969.99MHz)	20MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		648000 to 664000	648000 (3720.00MHz), 656000 (3840.00MHz), 664000 (3960.00MHz)	40MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		648334 to 663666	648334 (3725.01MHz), 656000 (3840.00MHz), 663666 (3954.99MHz)	50MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		648668 to 663332	648668 (3730.02MHz), 656000 (3840.00MHz), 663332 (3949.98MHz)	60MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		649334 to 662666	649334 (3740.01MHz), 656000 (3840.00MHz), 662666 (3939.99MHz)	80MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		649558 to 662332	649558 (3745.02MHz), 656000 (3840.00MHz), 662332 (3934.98MHz)	90MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		650000 to 662000	650000 (3750.00MHz), 656000 (3840.00MHz), 662000 (3930.00MHz)	100MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Conducted Emission	647334 to 665666	647334 (3710.01MHz), 656000 (3840.00MHz), 665666 (3969.99MHz)	20MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		648000 to 664000	648000 (3720.00MHz), 656000 (3840.00MHz), 664000 (3960.00MHz)	40MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		648334 to 663666	648334 (3725.01MHz), 656000 (3840.00MHz), 663666 (3954.99MHz)	50MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		648668 to 663332	648668 (3730.02MHz), 656000 (3840.00MHz), 663332 (3949.98MHz)	60MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		649334 to 662666	649334 (3740.01MHz), 656000 (3840.00MHz), 662666 (3939.99MHz)	80MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		649558 to 662332	649558 (3745.02MHz), 656000 (3840.00MHz), 662332 (3934.98MHz)	90MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		650000 to 662000	650000 (3750.00MHz), 656000 (3840.00MHz), 662000 (3930.00MHz)	100MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	648334 to 663666	656000 (3840.00MHz)	50MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	647334 to 665666	647334 (3710.01MHz), 656000 (3840.00MHz), 665666 (3969.99MHz)	20MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		648334 to 663666	648334 (3725.01MHz), 656000 (3840.00MHz), 663666 (3954.99MHz)	50MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		650000 to 662000	650000 (3750.00MHz), 656000 (3840.00MHz), 662000 (3930.00MHz)	100MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset

Note:

1. Only output power, modulation characteristics, occupied bandwidth and Peak to average ratio items had been tested under $\pi/2$ BPSK, QPSK, 16QAM, 64QAM and 256QAM modes, the other test items were performed under worst mode according to the maximum output power.
2. For radiated emission above 1GHz, according to 3GPP 38.521-1 Section 6.5.3.1.4, choose the lowest, mid and highest channel bandwidth for final test.
3. For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.

5GNR n77 (Part 27Q)

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	EIRP	630668 to 636000	630668 (3460.02MHz), 633334 (3500.01MHz), 636000 (3540.00MHz)	20MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 26 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 13 RB Offset 25 RB / 26 RB Offset 50 RB / 0 RB Offset
		631334 to 635332	631334 (3470.01MHz), 633334 (3500.01MHz), 635332 (3529.98MHz)	40MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 53 RB Offset 1 RB / 104 RB Offset 50 RB / 0 RB Offset 50 RB / 28 RB Offset 50 RB / 56 RB Offset 100 RB / 0 RB Offset
		631668 to 635000	631668 (3475.02MHz), 633334 (3500.01MHz), 635000 (3525.00MHz)	50MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 67 RB Offset 1 RB / 131 RB Offset 64 RB / 0 RB Offset 64 RB / 35 RB Offset 64 RB / 69 RB Offset 128 RB / 0 RB Offset
		632000 to 634666	632000 (3480.00MHz), 633334 (3500.01MHz), 634666 (3519.99MHz)	60MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 81 RB Offset 1 RB / 160 RB Offset 81 RB / 0 RB Offset 81 RB / 41 RB Offset 81 RB / 81 RB Offset 162 RB / 0 RB Offset
		632668 to 634000	632668 (3490.02MHz), 633334 (3500.01MHz), 634000 (3510.00MHz)	80MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 109 RB Offset 1 RB / 215 RB Offset 108 RB / 0 RB Offset 108 RB / 55 RB Offset 108 RB / 109 RB Offset 216 RB / 0 RB Offset
		633000 to 633666	633000 (3495.00MHz), 633334 (3500.01MHz), 633666 (3504.99MHz)	90MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 123 RB Offset 1 RB / 243 RB Offset 120 RB / 0 RB Offset 120 RB / 63 RB Offset 120 RB / 125 RB Offset 240 RB / 0 RB Offset
		633334	633334 (3500.01MHz)	100MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 137 RB Offset 1 RB / 271 RB Offset 135 RB / 0 RB Offset 135 RB / 69 RB Offset 135 RB / 138 RB Offset 270 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Modulation Characteristics	633334	633334 (3500.01MHz)	100MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	270 RB / 0 RB Offset
-	Frequency Stability	630668 to 636000	630668 (3460.02MHz), 636000 (3540.00MHz)	20MHz	$\pi/2$ BPSK	50 RB / 0 RB Offset
		631334 to 635332	631334 (3470.01MHz), 635332 (3529.98MHz)	40MHz	$\pi/2$ BPSK	100 RB / 0 RB Offset
		631668 to 635000	631668 (3475.02MHz), 635000 (3525.00MHz)	50MHz	$\pi/2$ BPSK	128 RB / 0 RB Offset
		632000 to 634666	632000 (3480.00MHz), 634666 (3519.99MHz)	60MHz	$\pi/2$ BPSK	162 RB / 0 RB Offset
		632668 to 634000	632668 (3490.02MHz), 634000 (3510.00MHz)	80MHz	$\pi/2$ BPSK	216 RB / 0 RB Offset
		633000 to 633666	633000 (3495.00MHz), 633666 (3504.99MHz)	90MHz	$\pi/2$ BPSK	240 RB / 0 RB Offset
		633334	633334 (3500.01MHz)	100MHz	$\pi/2$ BPSK	270 RB / 0 RB Offset
-	Emission Bandwidth	630668 to 636000	630668 (3460.02MHz), 633334 (3500.01MHz), 636000 (3540.00MHz)	20MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
		631334 to 635332	631334 (3470.01MHz), 633334 (3500.01MHz), 635332 (3529.98MHz)	40MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	100 RB / 0 RB Offset
		631668 to 635000	631668 (3475.02MHz), 633334 (3500.01MHz), 635000 (3525.00MHz)	50MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	128 RB / 0 RB Offset
		632000 to 634666	632000 (3480.00MHz), 633334 (3500.01MHz), 634666 (3519.99MHz)	60MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	162 RB / 0 RB Offset
		632668 to 634000	632668 (3490.02MHz), 633334 (3500.01MHz), 634000 (3510.00MHz)	80MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	216 RB / 0 RB Offset
		633000 to 633666	633000 (3495.00MHz), 633334 (3500.01MHz), 633666 (3504.99MHz)	90MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	240 RB / 0 RB Offset
		633334	633334 (3500.01MHz)	100MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	270 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Band Edge	630668 to 636000	630668 (3460.02MHz), 636000 (3540.00MHz)	20MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
		631334 to 635332	631334 (3470.01MHz), 635332 (3529.98MHz)	40MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 104 RB Offset 100 RB / 0 RB Offset
		631668 to 635000	631668 (3475.02MHz), 635000 (3525.00MHz)	50MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 131 RB Offset 128 RB / 0 RB Offset
		632000 to 634666	632000 (3480.00MHz), 634666 (3519.99MHz)	60MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 160 RB Offset 162 RB / 0 RB Offset
		632668 to 634000	632668 (3490.02MHz), 634000 (3510.00MHz)	80MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 215 RB Offset 216 RB / 0 RB Offset
		633000 to 633666	633000 (3495.00MHz), 633666 (3504.99MHz)	90MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 243 RB Offset 240 RB / 0 RB Offset
		633334	633334 (3500.01MHz)	100MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset 1 RB / 271 RB Offset 270 RB / 0 RB Offset
-	Peak to Average Ratio	630668 to 636000	630668 (3460.02MHz), 633334 (3500.01MHz), 636000 (3540.00MHz)	20MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		631334 to 635332	631334 (3470.01MHz), 633334 (3500.01MHz), 635332 (3529.98MHz)	40MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		631668 to 635000	631668 (3475.02MHz), 633334 (3500.01MHz), 635000 (3525.00MHz)	50MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		632000 to 634666	632000 (3480.00MHz), 633334 (3500.01MHz), 634666 (3519.99MHz)	60MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		632668 to 634000	632668 (3490.02MHz), 633334 (3500.01MHz), 634000 (3510.00MHz)	80MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		633000 to 633666	633000 (3495.00MHz), 633334 (3500.01MHz), 633666 (3504.99MHz)	90MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		633334	633334 (3500.01MHz)	100MHz	$\pi/2$ BPSK / QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Conducted Emission	630668 to 636000	630668 (3460.02MHz), 633334 (3500.01MHz), 636000 (3540.00MHz)	20MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		631334 to 635332	631334 (3470.01MHz), 633334 (3500.01MHz), 635332 (3529.98MHz)	40MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		631668 to 635000	631668 (3475.02MHz), 633334 (3500.01MHz), 635000 (3525.00MHz)	50MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		632000 to 634666	632000 (3480.00MHz), 633334 (3500.01MHz), 634666 (3519.99MHz)	60MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		632668 to 634000	632668 (3490.02MHz), 633334 (3500.01MHz), 634000 (3510.00MHz)	80MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		633000 to 633666	633000 (3495.00MHz), 633334 (3500.01MHz), 633666 (3504.99MHz)	90MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		633334	633334 (3500.01MHz)	100MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	633334	633334 (3500.01MHz)	100MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	630668 to 636000	630668 (3460.02MHz), 633334 (3500.01MHz), 636000 (3540.00MHz)	20MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		631668 to 635000	631668 (3475.02MHz), 633334 (3500.01MHz), 635000 (3525.00MHz)	50MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset
		633334	633334 (3500.01MHz)	100MHz	$\pi/2$ BPSK	1 RB / 0 RB Offset

Note:

1. Only output power, modulation characteristics, occupied bandwidth and Peak to average ratio items had been tested under $\pi/2$ BPSK, QPSK, 16QAM, 64QAM and 256QAM modes, the other test items were performed under worst mode according to the maximum output power.
2. For radiated emission above 1GHz, according to 3GPP 38.521-1 Section 6.5.3.1.4, choose the lowest, mid and highest channel bandwidth for final test.
3. For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.

LTE Band 2

EUT Configure Mode	Test item	Available channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	18607 to 19193	18607 (1850.70MHz), 18900 (1880.00MHz), 19193 (1909.30MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 2 RB Offset 1 RB / 5 RB Offset 3 RB / 0 RB Offset 3 RB / 1 RB Offset 3 RB / 3 RB Offset 6 RB / 0 RB Offset
		18615 to 19185	18615 (1851.50MHz), 18900 (1880.00MHz), 19185 (1908.50MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 7 RB Offset 1 RB / 14 RB Offset 8 RB / 0 RB Offset 8 RB / 3 RB Offset 8 RB / 7 RB Offset 15 RB / 0 RB Offset
		18625 to 19175	18625 (1852.50MHz), 18900 (1880.00MHz), 19175 (1907.50MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		18650 to 19150	18650 (1855.00MHz), 18900 (1880.00MHz), 19150 (1905.00MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
		18675 to 19125	18675 (1857.50MHz), 18900 (1880.00MHz), 19125 (1902.50MHz)	15MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 37 RB Offset 1 RB / 74 RB Offset 36 RB / 0 RB Offset 36 RB / 19 RB Offset 36 RB / 39 RB Offset 75 RB / 0 RB Offset
		18700 to 19100	18700 (1860.00MHz), 18900 (1880.00MHz), 19100 (1900.00MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 50 RB Offset 1 RB / 99 RB Offset 50 RB / 0 RB Offset 50 RB / 25 RB Offset 50 RB / 50 RB Offset 100 RB / 0 RB Offset
-	Modulation Characteristics	18700 to 19100	18900 (1880.00MHz)	20MHz	QPSK	100 RB / 0 RB Offset
-	Frequency Stability	18607 to 19193	18607 (1850.70MHz), 19193 (1909.30MHz)	1.4MHz	QPSK	6 RB / 0 RB Offset
		18615 to 19185	18615 (1851.50MHz), 19185 (1908.50MHz)	3MHz	QPSK	15 RB / 0 RB Offset
		18625 to 19175	18625 (1852.50MHz), 19175 (1907.50MHz)	5MHz	QPSK	25 RB / 0 RB Offset
		18650 to 19150	18650 (1855.00MHz), 19150 (1905.00MHz)	10MHz	QPSK	50 RB / 0 RB Offset
		18675 to 19125	18675 (1857.50MHz), 19125 (1902.50MHz)	15MHz	QPSK	75 RB / 0 RB Offset
		18700 to 19100	18700 (1860.00MHz), 19100 (1900.00MHz)	20MHz	QPSK	100 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Occupied Bandwidth	18607 to 19193	18607 (1850.70MHz), 18900 (1880.00MHz), 19193 (1909.30MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	6 RB / 0 RB Offset
		18615 to 19185	18615 (1851.50MHz), 18900 (1880.00MHz), 19185 (1908.50MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	15 RB / 0 RB Offset
		18625 to 19175	18625 (1852.50MHz), 18900 (1880.00MHz), 19175 (1907.50MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	25 RB / 0 RB Offset
		18650 to 19150	18650 (1855.00MHz), 18900 (1880.00MHz), 19150 (1905.00MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
		18675 to 19125	18675 (1857.50MHz), 18900 (1880.00MHz), 19125 (1902.50MHz)	15MHz	QPSK / 16QAM / 64QAM / 256QAM	75 RB / 0 RB Offset
		18700 to 19100	18700 (1860.00MHz), 18900 (1880.00MHz), 19100 (1900.00MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	100 RB / 0 RB Offset
-	Band Edge	18607 to 19193	18607 (1850.70MHz), 19193 (1909.30MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset 1 RB / 5 RB Offset 6 RB / 0 RB Offset
		18615 to 19185	18615 (1851.50MHz), 19185 (1908.50MHz)	3MHz	QPSK	1 RB / 0 RB Offset 1 RB / 14 RB Offset 15 RB / 0 RB Offset
		18625 to 19175	18625 (1852.50MHz), 19175 (1907.50MHz)	5MHz	QPSK	1 RB / 0 RB Offset 1 RB / 24 RB Offset 25 RB / 0 RB Offset
		18650 to 19150	18650 (1855.00MHz), 19150 (1905.00MHz)	10MHz	QPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
		18675 to 19125	18675 (1857.50MHz), 19125 (1902.50MHz)	15MHz	QPSK	1 RB / 0 RB Offset 1 RB / 74 RB Offset 75 RB / 0 RB Offset
		18700 to 19100	18700 (1860.00MHz), 19100 (1900.00MHz)	20MHz	QPSK	1 RB / 0 RB Offset 1 RB / 99 RB Offset 100 RB / 0 RB Offset
-	Peak to Average Ratio	18607 to 19193	18607 (1850.70MHz), 18900 (1880.00MHz), 19193 (1909.30MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		18615 to 19185	18615 (1851.50MHz), 18900 (1880.00MHz), 19185 (1908.50MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		18625 to 19175	18625 (1852.50MHz), 18900 (1880.00MHz), 19175 (1907.50MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		18650 to 19150	18650 (1855.00MHz), 18900 (1880.00MHz), 19150 (1905.00MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		18675 to 19125	18675 (1857.50MHz), 18900 (1880.00MHz), 19125 (1902.50MHz)	15MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		18700 to 19100	18700 (1860.00MHz), 18900 (1880.00MHz), 19100 (1900.00MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Conducted Emission	18607 to 19193	18607 (1850.70MHz), 18900 (1880.00MHz), 19193 (1909.30MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18615 (1851.50MHz), 18900 (1880.00MHz), 19185 (1908.50MHz)	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625 (1852.50MHz), 18900 (1880.00MHz), 19175 (1907.50MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650 (1855.00MHz), 18900 (1880.00MHz), 19150 (1905.00MHz)	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675 (1857.50MHz), 18900 (1880.00MHz), 19125 (1902.50MHz)	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700 (1860.00MHz), 18900 (1880.00MHz), 19100 (1900.00MHz)	20MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	18700 to 19100	18900 (1880.00MHz)	20MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	18607 to 19193	18607 (1850.70MHz), 18900 (1880.00MHz), 19193 (1909.30MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625 (1852.50MHz), 18900 (1880.00MHz), 19175 (1907.50MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700 (1860.00MHz), 18900 (1880.00MHz), 19100 (1900.00MHz)	20MHz	QPSK	1 RB / 0 RB Offset

Note:

1. For radiated emission below 1GHz, select the worst radiated emission (above 1GHz) channel for final testing.

LTE Band 5

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	ERP	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 2 RB Offset 1 RB / 5 RB Offset 3 RB / 0 RB Offset 3 RB / 1 RB Offset 3 RB / 3 RB Offset 6 RB / 0 RB Offset
		20415 to 20635	20415(825.5MHz), 20525(836.5MHz), 20635(847.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 7 RB Offset 1 RB / 14 RB Offset 8 RB / 0 RB Offset 8 RB / 3 RB Offset 8 RB / 7 RB Offset 15 RB / 0 RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
-	Modulation characteristics	20450 to 20600	20525(836.5MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
-	Frequency Stability	20407 to 20643	20407(824.7MHz), 20643(848.3MHz)	1.4MHz	QPSK	6 RB / 0 RB Offset
		20415 to 20635	20415(825.5MHz), 20635(847.5MHz)	3MHz	QPSK	15 RB / 0 RB Offset
		20425 to 20625	20425(826.5MHz), 20625(846.5MHz)	5MHz	QPSK	25 RB / 0 RB Offset
		20450 to 20600	20450(829.0MHz), 20600(844.0MHz)	10MHz	QPSK	50 RB / 0 RB Offset
-	Occupied Bandwidth	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	6 RB / 0 RB Offset
		20415 to 20635	20415(825.5MHz), 20525(836.5MHz), 20635(847.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	15 RB / 0 RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	25 RB / 0 RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Band Edge	20407 to 20643	20407(824.7MHz), 20643(848.3MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset 1 RB / 5 RB Offset 6 RB / 0 RB Offset
		20415 to 20635	20415(825.5MHz), 20635(847.5MHz)	3MHz	QPSK	1 RB / 0 RB Offset 1 RB / 14 RB Offset 15 RB / 0 RB Offset
		20425 to 20625	20425(826.5MHz), 20625(846.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset 1 RB / 24 RB Offset 25 RB / 0 RB Offset
		20450 to 20600	20450(829.0MHz), 20600(844.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
-	Peak to Average Ratio	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		20415 to 20635	20415(825.5MHz), 20525(836.5MHz), 20635(847.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
-	Conducted Emission	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset
		20415 to 20635	20415(825.5MHz), 20525(836.5MHz), 20635(847.5MHz)	3MHz	QPSK	1 RB / 0 RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	20450 to 20600	20600(844.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset

Note:

1. The measured output power for QPSK mode is higher than the measured output power for 16QAM, 64QAM and 256QAM modes. Therefore the radiated emission test items was performed under QPSK mode only.
2. For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.

LTE Band 7

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	EIRP	20775 to 21425	20775 (2502.5MHz), 21100 (2535.0MHz), 21425 (2567.5MHz)	5 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		20800 to 21400	20800 (2505.0MHz), 21100 (2535.0MHz), 21400 (2565.0MHz)	10 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
		20825 to 21375	20825 (2507.5MHz), 21100 (2535.0MHz), 21375 (2562.5MHz)	15 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 37 RB Offset 1 RB / 74 RB Offset 36 RB / 0 RB Offset 36 RB / 19 RB Offset 36 RB / 39 RB Offset 75 RB / 0 RB Offset
		20850 to 21350	20850 (2510.0MHz), 21100 (2535.0MHz), 21350 (2560.0MHz)	20 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 50 RB Offset 1 RB / 99 RB Offset 50 RB / 0 RB Offset 50 RB / 25 RB Offset 50 RB / 50 RB Offset 100 RB / 0 RB Offset
-	Modulation Characteristics	20850 to 21350	21100 (2535.0MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	100 RB / 0 RB Offset
-	Frequency Stability	20775 to 21425	20775 (2502.5MHz), 21425 (2567.5MHz)	5 MHz	QPSK	25 RB / 0 RB Offset
		20800 to 21400	20800 (2505.0MHz), 21400 (2565.0MHz)	10 MHz	QPSK	50 RB / 0 RB Offset
		20825 to 21375	20825 (2507.5MHz), 21375 (2562.5MHz)	15 MHz	QPSK	75 RB / 0 RB Offset
		20850 to 21350	20850 (2510.0MHz), 21350 (2560.0MHz)	20 MHz	QPSK	100 RB / 0 RB Offset
-	Emission Bandwidth	20775 to 21425	20775 (2502.5MHz), 21100 (2535.0MHz), 21425 (2567.5MHz)	5 MHz	QPSK / 16QAM / 64QAM / 256QAM	25 RB / 0 RB Offset
		20800 to 21400	20800 (2505.0MHz), 21100 (2535.0MHz), 21400 (2565.0MHz)	10 MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
		20825 to 21375	20825 (2507.5MHz), 21100 (2535.0MHz), 21375 (2562.5MHz)	15 MHz	QPSK / 16QAM / 64QAM / 256QAM	75 RB / 0 RB Offset
		20850 to 21350	20850 (2510.0MHz), 21100 (2535.0MHz), 21350 (2560.0MHz)	20 MHz	QPSK / 16QAM / 64QAM / 256QAM	100 RB / 0 RB Offset
-	Emission Mask	20775 to 21425	20775 (2502.5MHz), 21100 (2535.0MHz), 21425 (2567.5MHz)	5 MHz	QPSK	1 RB / 0 RB Offset 1 RB / 24 RB Offset 25 RB / 0 RB Offset
		20800 to 21400	20800 (2505.0MHz), 21100 (2535.0MHz), 21400 (2565.0MHz)	10 MHz	QPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
		20825 to 21375	20825 (2507.5MHz), 21100 (2535.0MHz), 21375 (2562.5MHz)	15 MHz	QPSK	1 RB / 0 RB Offset 1 RB / 74 RB Offset 75 RB / 0 RB Offset
		20850 to 21350	20850 (2510.0MHz), 21100 (2535.0MHz), 21350 (2560.0MHz)	20 MHz	QPSK	1 RB / 0 RB Offset 1 RB / 99 RB Offset 100 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Peak to Average Ratio	20775 to 21425	20775 (2502.5MHz), 21100 (2535.0MHz), 21425 (2567.5MHz)	5 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		20800 to 21400	20800 (2505.0MHz), 21100 (2535.0MHz), 21400 (2565.0MHz)	10 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		20825 to 21375	20825 (2507.5MHz), 21100 (2535.0MHz), 21375 (2562.5MHz)	15 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		20850 to 21350	20850 (2510.0MHz), 21100 (2535.0MHz), 21350 (2560.0MHz)	20 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
-	Conducted Emission	20775 to 21425	20775 (2502.5MHz), 21100 (2535.0MHz), 21425 (2567.5MHz)	5 MHz	QPSK	1 RB / 0 RB Offset
		20800 to 21400	20800 (2505.0MHz), 21100 (2535.0MHz), 21400 (2565.0MHz)	10 MHz	QPSK	1 RB / 0 RB Offset
		20825 to 21375	20825 (2507.5MHz), 21100 (2535.0MHz), 21375 (2562.5MHz)	15 MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	20850 (2510.0MHz), 21100 (2535.0MHz), 21350 (2560.0MHz)	20 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	20850 to 21350	21100 (2535.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	20775 to 21425	20775 (2502.5MHz), 21100 (2535.0MHz), 21425 (2567.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	20850 (2510.0MHz), 21100 (2535.0MHz), 21350 (2560.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset

Note:

1. The measured output power for QPSK mode is higher than the measured output power for 16QAM, 64QAM and 256QAM modes. Therefore the radiated emission test items was performed under QPSK mode only.
2. For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.

LTE Band 12

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	ERP	23017 to 23173	23017(699.7MHz), 23095(707.5MHz), 23173(715.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 2 RB Offset 1 RB / 5 RB Offset 3 RB / 0 RB Offset 3 RB / 1 RB Offset 3 RB / 3 RB Offset 6 RB / 0 RB Offset
		23025 to 23165	23025(700.5MHz), 23095(707.5MHz), 23165(714.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 7 RB Offset 1 RB / 14 RB Offset 8 RB / 0 RB Offset 8 RB / 3 RB Offset 8 RB / 7 RB Offset 15 RB / 0 RB Offset
		23035 to 23155	23035(701.5MHz), 23095(707.5MHz), 23155(713.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		23060 to 23130	23060(704.0MHz), 23095(707.5 MHz), 23130(711.0 MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
-	Modulation Characteristics	23060 to 23130	23095(707.5MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
-	Frequency Stability	23017 to 23173	23017(699.7MHz), 23173(715.3MHz)	1.4MHz	QPSK	6 RB / 0 RB Offset
		23025 to 23165	23025(700.5MHz), 23165(714.5MHz)	3MHz	QPSK	15 RB / 0 RB Offset
		23035 to 23155	23035(701.5MHz), 23155(713.5MHz)	5MHz	QPSK	25 RB / 0 RB Offset
		23060 to 23130	23060(704.0MHz), 23130(711.0MHz)	10MHz	QPSK	50 RB / 0 RB Offset
-	Emission Bandwidth	23017 to 23173	23017(699.7MHz), 23095(707.5MHz), 23173(715.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	6 RB / 0 RB Offset
		23025 to 23165	23025(700.5MHz), 23095(707.5MHz), 23165(714.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	15 RB / 0 RB Offset
		23035 to 23155	23035(701.5MHz), 23095(707.5MHz), 23155(713.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	25 RB / 0 RB Offset
		23060 to 23130	23060(704.0MHz), 23095(707.5MHz), 23130(711.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
-	Band Edge	23017 to 23173	23017(699.7MHz), 23173(715.3MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset 1 RB / 5 RB Offset 6 RB / 0 RB Offset
		23025 to 23165	23025(700.5MHz), 23165(714.5MHz)	3MHz	QPSK	1 RB / 0 RB Offset 1 RB / 14 RB Offset 15 RB / 0 RB Offset
		23035 to 23155	23035(701.5MHz), 23155(713.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset 1 RB / 24 RB Offset 25 RB / 0 RB Offset
		23060 to 23130	23060(704.0MHz), 23130(711.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Peak to Average Ratio	23017 to 23173	23017(699.7MHz), 23095(707.5MHz), 23173(715.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		23025 to 23165	23025(700.5MHz), 23095(707.5MHz), 23165(714.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		23035 to 23155	23035(701.5MHz), 23095(707.5MHz), 23155(713.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		23060 to 23130	23060(704.0MHz), 23095(707.5MHz), 23130(711.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
-	Conducted Emission	23017 to 23173	23017(699.7MHz), 23095(707.5MHz), 23173(715.3MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23025(700.5MHz), 23095(707.5MHz), 23165(714.5MHz)	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23035(701.5MHz), 23095(707.5MHz), 23155(713.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23060(704.0MHz), 23095(707.5MHz), 23130(711.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	23017 to 23173	23017(699.7MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	23017 to 23173	23017(699.7MHz), 23095(707.5MHz), 23173(715.3MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23035(701.5MHz), 23095(707.5MHz), 23155(713.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23060(704.0MHz), 23095(707.5MHz), 23130(711.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset

Note:

1. For radiated emission below 1GHz, select the worst radiated emission (above 1GHz) channel for final testing.
2. For radiated emission above 1GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the 1.4MHz & highest channel bandwidth for final test.
3. The conducted output power for QPSK, 16QAM, 64QAM and 256QAM measured value of QPSK is higher than 16QAM, 64QAM and 256QAM mode. Therefore, only ERP, Modulation characteristics, occupied bandwidth and Peak to average ratio items had been tested under QPSK, 16QAM, 64QAM and 256QAM modes, the other test items were performed under QPSK mode only.

LTE Band 13

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	ERP	23205 to 23255	23205(779.5MHz), 23230(782.0MHz), 23255(784.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		23230	23230(782.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
-	Modulation Characteristics	23230	23230(782.0MHz),	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
-	Frequency Stability	23205 to 23255	23205(779.5MHz), 23255(784.5MHz)	5MHz	QPSK	25 RB / 0 RB Offset
		23230	23230(782.0MHz),	10MHz	QPSK	50 RB / 0 RB Offset
-	Emission Bandwidth	23205 to 23255	23205(779.5MHz), 23230(782.0MHz), 23255(784.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	25 RB / 0 RB Offset
		23230	23230(782.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
-	Band Edge	23205 to 23255	23205(779.5MHz), 23255(784.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset 1 RB / 24 RB Offset 25 RB / 0 RB Offset
		23230	23230(782.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
-	Peak to Average Ratio	23205 to 23255	23205(779.5MHz), 23230(782.0MHz), 23255(784.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		23230	23230(782.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
-	Conducted Emission	23205 to 23255	23205(779.5MHz), 23230(782.0MHz), 23255(784.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		23230	23230(782.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	23230	23230(782.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	23205 to 23255	23205(779.5MHz), 23230(782.0MHz), 23255(784.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		23230	23230(782.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset

Note:

- The measured output power for QPSK mode is higher than the measured output power for 16QAM, 64QAM and 256QAM modes. Therefore the radiated emission test items was performed under QPSK mode only.
- For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.

LTE Band 14

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	ERP	23305 to 23355	23305(790.5MHz), 23330(793.0MHz), 23355(795.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		23330	23330(793.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
-	Modulation Characteristics	23330	23330(793.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
-	Frequency Stability	23305 to 23355	23305(790.5MHz), 23355(795.5MHz)	5MHz	QPSK	25 RB / 0 RB Offset
		23330	23330(793.0MHz)	10MHz	QPSK	50 RB / 0 RB Offset
-	Occupied Bandwidth	23305 to 23355	23305(790.5MHz), 23330(793.0MHz), 23355(795.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	25 RB / 0 RB Offset
		23330	23330(793.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
-	Emission Mask	23305 to 23355	23305(790.5MHz), 23330(793.0MHz), 23355(795.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset 1 RB / 24 RB Offset 25 RB / 0 RB Offset
		23330	23330(793.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
-	Conducted Emission	23305 to 23355	23305(790.5MHz), 23330(793.0MHz), 23355(795.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		23330	23330(793.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission below 1GHz	23305 to 23355	23330(793.0MHz)	5MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission above 1GHz	23305 to 23355	23305(790.5MHz), 23330(793.0MHz), 23355(795.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		23330	23330(793.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset

Note:

1. The conducted output power for QPSK, 16QAM, 64QAM and 256QAM measured value of QPSK is higher than 16QAM, 64QAM and 256QAM mode. Therefore, only ERP, Modulation Characteristics, and Emission Bandwidth items had been tested under QPSK, 16QAM, 64QAM and 256QAM modes, the other test items were performed under QPSK mode only.
2. For radiated emission below 1GHz, select the worst radiated emission (above 1GHz) channel for final testing.

LTE Band 30

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	EIRP	27685 to 27735	27685 (2307.5MHz), 27710 (2310.0MHz), 27735 (2312.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		27710	27710 (2310.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
-	Modulation Characteristics	27710	27710 (2310.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
-	Frequency Stability	27685 to 27735	27685 (2307.5MHz), 27735 (2312.5MHz)	5MHz	QPSK	25 RB / 0 RB Offset
		27710	27710 (2310.0MHz)	10MHz	QPSK	50 RB / 0 RB Offset
-	Emission Bandwidth	27685 to 27735	27685 (2307.5MHz), 27710 (2310.0MHz), 27735 (2312.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	25 RB / 0 RB Offset
		27710	27710 (2310.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
-	Emission Mask	27685 to 27735	27685 (2307.5MHz), 27735 (2312.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset 25 RB / 0 RB Offset
		27710	27710 (2310.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
-	Conducted Emission	27685 to 27735	27685 (2307.5MHz), 27710 (2310.0MHz), 27735 (2312.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		27710	27710 (2310.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	27710	27710 (2310.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	27685 to 27735	27685 (2307.5MHz), 27710 (2310.0MHz), 27735 (2312.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		27710	27710 (2310.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset

Note:

1. The measured output power for QPSK mode is higher than the measured output power for 16QAM, 64QAM and 256QAM modes. Therefore the radiated emission test items was performed under QPSK mode only.
2. For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.

LTE Band 41

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	EIRP	39675 to 41565	39675 (2498.5MHz), 40620 (2593.0MHz), 41565 (2687.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		39700 to 41540	39700 (2501.0MHz), 40620 (2593.0MHz), 41540 (2685.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
		39725 to 41515	39725 (2503.5MHz), 40620 (2593.0MHz), 41515 (2682.5MHz)	15MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 37 RB Offset 1 RB / 74 RB Offset 36 RB / 0 RB Offset 36 RB / 19 RB Offset 36 RB / 39 RB Offset 75 RB / 0 RB Offset
		39750 to 41490	39750 (2506.0MHz), 40620 (2593.0MHz), 41490 (2680.0MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 50 RB Offset 1 RB / 99 RB Offset 50 RB / 0 RB Offset 50 RB / 25 RB Offset 50 RB / 50 RB Offset 100 RB / 0 RB Offset
-	Modulation Characteristics	39700 to 41540	40620 (2593.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
-	Frequency Stability	39675 to 41565	39675 (2498.5MHz), 41565 (2687.5MHz)	5MHz	QPSK	25 RB / 0 RB Offset
		39700 to 41540	39700 (2501.0MHz), 41540 (2685.0MHz)	10MHz	QPSK	50 RB / 0 RB Offset
		39725 to 41515	39725 (2503.5MHz), 41515 (2682.5MHz)	15MHz	QPSK	75 RB / 0 RB Offset
		39750 to 41490	39750 (2506.0MHz), 41490 (2680.0MHz)	20MHz	QPSK	100 RB / 0 RB Offset
-	Emission Bandwidth	39675 to 41565	39675 (2498.5MHz), 40620 (2593.0MHz), 41565 (2687.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	25 RB / 0RB Offset
		39700 to 41540	39700 (2501.0MHz), 40620 (2593.0MHz), 41540 (2685.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0RB Offset
		39725 to 41515	39725 (2503.5MHz), 40620 (2593.0MHz), 41515 (2682.5MHz)	15MHz	QPSK / 16QAM / 64QAM / 256QAM	75 RB / 0 RB Offset
		39750 to 41490	39750 (2506.0MHz), 40620 (2593.0MHz), 41490 (2680.0MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	100 RB / 0 RB Offset
-	Band Edge	39675 to 41565	39675 (2498.5MHz), 40620 (2593.0MHz), 41565 (2687.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset 1 RB / 24 RB Offset 25 RB / 0 RB Offset
		39700 to 41540	39700 (2501.0MHz), 40620 (2593.0MHz), 41540 (2685.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
		39725 to 41515	39725 (2503.5MHz), 40620 (2593.0MHz), 41515 (2682.5MHz)	15MHz	QPSK	1 RB / 0 RB Offset 1 RB / 74 RB Offset 75 RB / 0 RB Offset
		39750 to 41490	39750 (2506.0MHz), 40620 (2593.0MHz), 41490 (2680.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset 1 RB / 99 RB Offset 100 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Peak to Average Ratio	39675 to 41565	39675 (2498.5MHz), 40620 (2593.0MHz), 41565 (2687.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		39700 to 41540	39700 (2501.0MHz), 40620 (2593.0MHz), 41540 (2685.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		39725 to 41515	39725 (2503.5MHz), 40620 (2593.0MHz), 41515 (2682.5MHz)	15MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		39750 to 41490	39750 (2506.0MHz), 40620 (2593.0MHz), 41490 (2680.0MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
-	Conducted Emission	39675 to 41565	39675 (2498.5MHz), 40620 (2593.0MHz), 41565 (2687.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		39700 to 41540	39700 (2501.0MHz), 40620 (2593.0MHz), 41540 (2685.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
		39725 to 41515	39725 (2503.5MHz), 40620 (2593.0MHz), 41515 (2682.5MHz)	15MHz	QPSK	1 RB / 0 RB Offset
		39750 to 41490	39750 (2506.0MHz), 40620 (2593.0MHz), 41490 (2680.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	39750 to 41490	40620 (2593.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	39675 to 41565	39675 (2498.5MHz), 40620 (2593.0MHz), 41565 (2687.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		39750 to 41490	39750 (2506.0MHz), 40620 (2593.0MHz), 41490 (2680.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset

Note:

1. For radiated emission below 1GHz, select the worst radiated emission (above 1GHz) channel for final testing.
2. The conducted output power for QPSK, 16QAM, 64QAM and 256QAM measured value of QPSK is higher than 16QAM, 64QAM and 256QAM mode. Therefore, only EIRP, Modulation characteristics, occupied bandwidth and Peak to average ratio items had been tested under QPSK, 16QAM, 64QAM and 256QAM modes, the other test items were performed under QPSK mode only.

LTE Band 66

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	131979 to 132665	131979 (1710.7MHz), 132322 (1745.0MHz), 132665 (1779.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 2 RB Offset 1 RB / 5 RB Offset 3 RB / 0 RB Offset 3 RB / 1 RB Offset 3 RB / 3 RB Offset 6 RB / 0 RB Offset
		131987 to 132657	131987 (1711.5MHz), 132322 (1745.0MHz), 132657 (1778.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 7 RB Offset 1 RB / 14 RB Offset 8 RB / 0 RB Offset 8 RB / 3 RB Offset 8 RB / 7 RB Offset 15 RB / 0 RB Offset
		131997 to 132647	131997 (1712.5MHz), 132322 (1745.0MHz), 132647 (1777.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 12 RB Offset 1 RB / 24 RB Offset 12 RB / 0 RB Offset 12 RB / 6 RB Offset 12 RB / 13 RB Offset 25 RB / 0 RB Offset
		132022 to 132622	132022 (1715.0MHz), 132322 (1745.0MHz), 132622 (1775.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 24 RB Offset 1 RB / 49 RB Offset 25 RB / 0 RB Offset 25 RB / 12 RB Offset 25 RB / 25 RB Offset 50 RB / 0 RB Offset
		132047 to 132597	132047 (1717.5MHz), 132322 (1745.0MHz), 132597 (1772.5MHz)	15MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 37 RB Offset 1 RB / 74 RB Offset 36 RB / 0 RB Offset 36 RB / 19 RB Offset 36 RB / 39 RB Offset 75 RB / 0 RB Offset
		132072 to 132572	132072 (1720.0MHz), 132322 (1745.0MHz), 132572 (1770.0MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset 1 RB / 50 RB Offset 1 RB / 99 RB Offset 50 RB / 0 RB Offset 50 RB / 25 RB Offset 50 RB / 50 RB Offset 100 RB / 0 RB Offset
-	Modulation Characteristics	132072 to 132572	132322 (1745.0MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	100 RB / 0 RB Offset
-	Frequency Stability	131979 to 132665	131979 (1710.7MHz), 132665 (1779.3MHz)	1.4MHz	QPSK	6 RB / 0 RB Offset
		131987 to 132657	131987 (1711.5MHz), 132657 (1778.5MHz)	3MHz	QPSK	15 RB / 0 RB Offset
		131997 to 132647	131997 (1712.5MHz), 132647 (1777.5MHz)	5MHz	QPSK	25 RB / 0 RB Offset
		132022 to 132622	132022 (1715.0MHz), 132622 (1775.0MHz)	10MHz	QPSK	50 RB / 0 RB Offset
		132047 to 132597	132047 (1717.5MHz), 132597 (1772.5MHz)	15MHz	QPSK	75 RB / 0 RB Offset
		132072 to 132572	132072 (1720.0MHz), 132572 (1770.0MHz)	20MHz	QPSK	100 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Emission Bandwidth	131979 to 132665	131979 (1710.7MHz), 132322 (1745.0MHz), 132665 (1779.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	6 RB / 0 RB Offset
		131987 to 132657	131987 (1711.5MHz), 132322 (1745.0MHz), 132657 (1778.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	15 RB / 0 RB Offset
		131997 to 132647	131997 (1712.5MHz), 132322 (1745.0MHz), 132647 (1777.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	25 RB / 0 RB Offset
		132022 to 132622	132022 (1715.0MHz), 132322 (1745.0MHz), 132622 (1775.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	50 RB / 0 RB Offset
		132047 to 132597	132047 (1717.5MHz), 132322 (1745.0MHz), 132597 (1772.5MHz)	15MHz	QPSK / 16QAM / 64QAM / 256QAM	75 RB / 0 RB Offset
		132072 to 132572	132072 (1720.0MHz), 132322 (1745.0MHz), 132572 (1770.0MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	100 RB / 0 RB Offset
-	Band Edge	131979 to 132665	131979 (1710.7MHz), 132665 (1779.3MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset 1 RB / 5 RB Offset 6 RB / 0 RB Offset
		131987 to 132657	131987 (1711.5MHz), 132657 (1778.5MHz)	3MHz	QPSK	1 RB / 0 RB Offset 1 RB / 14 RB Offset 15 RB / 0 RB Offset
		131997 to 132647	131997 (1712.5MHz), 132647 (1777.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset 1 RB / 24 RB Offset 25 RB / 0 RB Offset
		132022 to 132622	132022 (1715.0MHz), 132622 (1775.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset
		132047 to 132597	132047 (1717.5MHz), 132597 (1772.5MHz)	15MHz	QPSK	1 RB / 0 RB Offset 1 RB / 74 RB Offset 75 RB / 0 RB Offset
		132072 to 132572	132072 (1720.0MHz), 132572 (1770.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset 1 RB / 99 RB Offset 100 RB / 0 RB Offset
-	Peak to Average Ratio	131979 to 132665	131979 (1710.7MHz), 132322 (1745.0MHz), 132665 (1779.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		131987 to 132657	131987 (1711.5MHz), 132322 (1745.0MHz), 132657 (1778.5MHz)	3MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		131997 to 132647	131997 (1712.5MHz), 132322 (1745.0MHz), 132647 (1777.5MHz)	5MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		132022 to 132622	132022 (1715.0MHz), 132322 (1745.0MHz), 132622 (1775.0MHz)	10MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		132047 to 132597	132047 (1717.5MHz), 132322 (1745.0MHz), 132597 (1772.5MHz)	15MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset
		132072 to 132572	132072 (1720.0MHz), 132322 (1745.0MHz), 132572 (1770.0MHz)	20MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Conducted Emission	131979 to 132665	131979 (1710.7MHz), 132322 (1745.0MHz), 132665 (1779.3MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset
		131987 to 132657	131987 (1711.5MHz), 132322 (1745.0MHz), 132657 (1778.5MHz)	3MHz	QPSK	1 RB / 0 RB Offset
		131997 to 132647	131997 (1712.5MHz), 132322 (1745.0MHz), 132647 (1777.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		132022 to 132622	132022 (1715.0MHz), 132322 (1745.0MHz), 132622 (1775.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
		132047 to 132597	132047 (1717.5MHz), 132322 (1745.0MHz), 132597 (1772.5MHz)	15MHz	QPSK	1 RB / 0 RB Offset
		132072 to 132572	132072 (1720.0MHz), 132322 (1745.0MHz), 132572 (1770.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	132072 to 132572	132322 (1745.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Above 1GHz	131979 to 132665	131979 (1710.7MHz), 132322 (1745.0MHz), 132665 (1779.3MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset
		131997 to 132647	131997 (1712.5MHz), 132322 (1745.0MHz), 132647 (1777.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset
		132072 to 132572	132072 (1720.0MHz), 132322 (1745.0MHz), 132572 (1770.0MHz)	20MHz	QPSK	1 RB / 0 RB Offset

Note:

1. The measured output power for QPSK mode is higher than the measured output power for 16QAM, 64QAM and 256QAM modes. Therefore the radiated emission test items was performed under QPSK mode only.
2. For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.

Test Condition:

Test Item	Environmental Conditions	Input Power (system)	Tested By
EIRP/ERP	25deg. C, 60%RH	120Vac, 60Hz	James Yang
Modulation characteristics	25deg. C, 60%RH	120Vac, 60Hz	James Yang
Frequency Stability	25deg. C, 60%RH	3.87Vdc	James Yang
Occupied Bandwidth	25deg. C, 60%RH	120Vac, 60Hz	James Yang
Band Edge	25deg. C, 60%RH	120Vac, 60Hz	James Yang
Peak To Average Ratio	25deg. C, 60%RH	120Vac, 60Hz	James Yang
Conducted Emission	25deg. C, 60%RH	120Vac, 60Hz	James Yang
Radiated Emission	23deg. C, 67%RH	120Vac, 60Hz	Titan Hsu Adair Peng

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and References:

Test Standard:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

FCC 47 CFR Part 24

FCC 47 CFR Part 27

FCC 47 CFR Part 90

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 971168 D01 Power Meas License Digital Systems v03r01

KDB 971168 D02 Misc Rev Approv License Devices v02r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

For 5GNR n77 (Part 27O):

Mobile and portable stations transmitting in the 3700-3980 MHz band are limited to 1 Watt EIRP. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

For 5GNR n77 (Part 27Q):

Mobile devices transmitting in the 3450-3550 MHz band are limited to 1Watt (30 dBm) EIRP. Mobile devices operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

For LTE Band 2:

Mobile / Portable station are limited to 2 watts e.i.r.p.

For LTE Band 5:

Mobile / Portable station are limited to 7 watts e.r.p.

For LTE Band 12:

Control and mobile stations in the 698-746 MHz band are limited to 30 watts ERP.

Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

For LTE Band 13:

Control and mobile stations in the 698-746 MHz, 746-757 MHz, 787-788 MHz and 805-806 MHz band are limited to 30 watts ERP.

Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink, 746-757 MHz, 787-788 MHz and 805-806 MHz band are limited to 3 watts ERP.

For LTE Band 14:

Control stations and mobile stations transmitting in the 758-768 MHz band and the 788-798 MHz band are limited to 30 watts ERP. Portable stations (hand-held devices) transmitting in the 758-768 MHz band and the 788-798 MHz band are limited to 3 watts ERP.

For LTE Band 30:

For mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth.

For LTE Band 7, LTE Band 41:

Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

For LTE Band 66:

Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

4.1.2 Test Procedures

Conducted Power Measurement:

The EUT was set up for the maximum power with 5GNR and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

For all band except 5GNR n77 (Part 27Q):

Maximum EIRP / ERP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

$$\text{EIRP} = P_{\text{Meas}} + G_T$$

$$\text{ERP} = P_{\text{Meas}} + G_T - 2.15$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively
(expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

For 5GNR n77 (Part 27Q):

EIRP Measurement:

- In the semi-anechoic chamber, EUT placed on the 0.8m(below or equal 1GHz) and/or 1.5m(above 1GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- Following C63.26 section 5.2.7 and 5.2.2.4
 - EIRP (dBm) = $E \text{ (dB}\mu\text{V/m)} + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
 - ERP (dBm) = $E \text{ (dB}\mu\text{V/m)} + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.

4.1.3 Test Setup


Conducted Power Measurement:




For 5GNR n77 (Part 27Q):

EIRP Measurement:

For radiated emission 30MHz to 1GHz



For radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 Test Results

Conducted Output Power (dBm)

5GNR n77 (Part 270):

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		650000	656000	662000
		Frequency (MHz)		3750	3840	3930
100M	$\pi/2$ BPSK	1	0	26.67	26.50	26.49
		1	137	26.51	26.59	26.55
		1	271	26.62	26.57	26.58
		135	0	26.15	26.13	26.01
		135	69	26.04	26.13	26.22
		135	138	26.16	26.17	26.06
		270	0	26.02	26.18	26.13
	QPSK	1	0	26.20	26.39	26.36
		1	137	26.40	26.31	26.33
		1	271	26.21	26.46	26.50
		135	0	25.90	25.74	25.95
		135	69	25.75	25.86	25.98
		135	138	25.72	25.91	25.71
		270	0	25.80	25.91	25.82
	16QAM	1	0	25.41	25.49	25.40
		1	137	25.24	25.41	25.32
		1	271	25.28	25.20	25.32
		135	0	24.83	24.73	24.83
		135	69	24.91	24.97	24.94
		135	138	24.90	24.80	24.78
		270	0	24.85	24.87	24.98
	64QAM	1	0	24.39	24.32	24.23
		1	137	24.39	24.20	24.44
		1	271	24.31	24.21	24.25
		135	0	23.87	23.94	23.78
		135	69	23.85	23.98	23.79
		135	138	23.99	23.75	23.73
		270	0	23.84	23.78	23.86
	256QAM	1	0	22.74	22.60	22.69
		1	137	22.69	22.75	22.68
		1	271	22.73	22.90	22.68
		135	0	22.13	22.37	22.31
		135	69	22.18	22.19	22.31
		135	138	22.15	22.26	22.23
		270	0	22.30	22.11	22.35

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		649558	656000	662332
		Frequency (MHz)		3745.02	3840	3934.98
90M	$\pi/2$ BPSK	1	0	26.57	26.52	26.52
		1	123	26.46	26.58	26.49
		1	243	26.52	26.63	26.44
		120	0	26.19	26.30	26.27
		120	63	26.19	26.18	26.13
		120	125	26.26	26.06	26.27
		240	0	26.23	26.18	26.20
	QPSK	1	0	26.42	26.25	26.45
		1	123	26.28	26.24	26.45
		1	243	26.50	26.26	26.46
		120	0	25.98	25.84	25.82
		120	63	25.75	25.77	25.96
		120	125	25.83	25.89	25.85
		240	0	25.89	25.83	25.99
	16QAM	1	0	25.46	25.50	25.24
		1	123	25.40	25.36	25.25
		1	243	25.26	25.24	25.46
		120	0	24.91	24.70	24.87
		120	63	24.95	24.71	24.92
		120	125	24.95	24.82	24.79
		240	0	24.92	24.93	24.78
	64QAM	1	0	24.41	24.50	24.32
		1	123	24.26	24.22	24.28
		1	243	24.49	24.50	24.39
		120	0	23.73	23.75	23.92
		120	63	23.81	23.80	24.00
		120	125	23.72	23.81	23.70
		240	0	23.91	23.94	23.71
	256QAM	1	0	22.90	22.76	22.61
		1	123	22.68	22.88	22.90
		1	243	22.80	22.63	22.63
		120	0	22.26	22.12	22.37
		120	63	22.16	22.38	22.37
		120	125	22.33	22.23	22.11
		240	0	22.21	22.11	22.36

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		649334	656000	662666
		Frequency (MHz)		3740.01	3840	3939.99
80M	$\pi/2$ BPSK	1	0	26.68	26.56	26.44
		1	109	26.68	26.51	26.67
		1	215	26.53	26.61	26.54
		108	0	26.22	26.24	26.15
		108	55	26.28	26.08	26.24
		108	109	26.29	26.02	26.24
		216	0	26.05	26.14	26.01
	QPSK	1	0	26.46	26.26	26.44
		1	109	26.25	26.41	26.27
		1	215	26.44	26.22	26.32
		108	0	25.71	25.78	25.89
		108	55	25.78	25.71	25.76
		108	109	25.86	25.71	25.78
		216	0	25.74	25.72	25.98
	16QAM	1	0	25.22	25.35	25.32
		1	109	25.40	25.41	25.49
		1	215	25.25	25.41	25.45
		108	0	24.74	24.70	24.90
		108	55	24.74	24.95	24.78
		108	109	24.99	24.92	24.99
		216	0	24.78	24.75	24.73
	64QAM	1	0	24.26	24.24	24.32
		1	109	24.45	24.45	24.46
		1	215	24.38	24.37	24.20
		108	0	23.87	23.72	23.79
		108	55	23.77	23.92	23.70
		108	109	23.83	23.91	23.88
		216	0	23.77	23.78	23.79
	256QAM	1	0	22.89	22.78	22.85
		1	109	22.90	22.65	22.83
		1	215	22.73	22.85	22.75
		108	0	22.28	22.28	22.29
		108	55	22.34	22.29	22.33
		108	109	22.33	22.11	22.18
		216	0	22.29	22.22	22.18

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		648668	656000	663332
		Frequency (MHz)		3730.02	3840	3949.98
60M	$\pi/2$ BPSK	1	0	26.50	26.52	26.64
		1	81	26.54	26.53	26.45
		1	160	26.54	26.41	26.44
		81	0	26.13	26.23	26.26
		81	41	26.25	26.14	26.04
		81	81	26.05	26.26	26.10
		162	0	26.03	26.13	26.26
	QPSK	1	0	26.24	26.37	26.47
		1	81	26.42	26.27	26.30
		1	160	26.50	26.34	26.36
		81	0	25.89	25.79	25.92
		81	41	25.72	25.90	25.98
		81	81	25.70	25.90	25.73
		162	0	25.94	25.82	25.76
	16QAM	1	0	25.37	25.33	25.20
		1	81	25.49	25.24	25.46
		1	160	25.40	25.50	25.26
		81	0	24.98	24.89	24.98
		81	41	24.85	24.77	24.93
		81	81	24.94	24.97	24.86
		162	0	24.90	24.89	24.72
	64QAM	1	0	24.44	24.24	24.23
		1	81	24.23	24.40	24.30
		1	160	24.40	24.38	24.47
		81	0	23.82	23.98	23.85
		81	41	23.79	23.83	23.95
		81	81	23.89	23.97	23.95
		162	0	23.81	23.95	23.91
	256QAM	1	0	22.64	22.60	22.79
		1	81	22.72	22.62	22.63
		1	160	22.72	22.62	22.70
		81	0	22.17	22.31	22.39
		81	41	22.16	22.16	22.26
		81	81	22.39	22.26	22.34
		162	0	22.13	22.30	22.22

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		648334	656000	663666
		Frequency (MHz)		3725.01	3840	3954.99
50M	$\pi/2$ BPSK	1	0	26.68	26.61	26.68
		1	67	26.69	26.66	26.48
		1	131	26.50	26.40	26.47
		64	0	26.14	26.04	26.24
		64	35	26.18	26.11	26.11
		64	69	26.25	26.28	26.20
		128	0	26.08	26.10	26.06
	QPSK	1	0	26.21	26.23	26.35
		1	67	26.36	26.26	26.41
		1	131	26.45	26.35	26.43
		64	0	25.73	25.81	25.81
		64	35	25.81	25.89	25.74
		64	69	25.93	25.97	25.88
		128	0	25.96	25.95	25.92
	16QAM	1	0	25.25	25.29	25.24
		1	67	25.24	25.38	25.20
		1	131	25.42	25.25	25.50
		64	0	24.92	24.82	24.83
		64	35	24.73	24.87	24.91
		64	69	24.70	24.72	24.72
		128	0	24.87	24.79	24.98
	64QAM	1	0	24.39	24.20	24.41
		1	67	24.28	24.22	24.42
		1	131	24.50	24.38	24.25
		64	0	23.89	23.87	23.81
		64	35	23.86	23.93	23.72
		64	69	23.95	23.84	23.73
		128	0	23.74	23.82	23.96
	256QAM	1	0	22.76	22.85	22.89
		1	67	22.76	22.69	22.90
		1	131	22.70	22.81	22.76
		64	0	22.20	22.14	22.35
		64	35	22.27	22.16	22.17
		64	69	22.33	22.12	22.35
		128	0	22.16	22.22	22.26

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		648000	656000	664000
		Frequency (MHz)		3720	3840	3960
40M	$\pi/2$ BPSK	1	0	26.52	26.55	26.69
		1	53	26.67	26.63	26.57
		1	104	26.69	26.58	26.70
		50	0	26.20	26.00	26.28
		50	28	26.14	26.00	26.28
		50	56	26.30	26.01	26.09
		100	0	26.17	26.05	26.09
	QPSK	1	0	26.40	26.39	26.44
		1	53	26.35	26.29	26.33
		1	104	26.35	26.49	26.50
		50	0	25.99	25.87	25.71
		50	28	25.73	25.90	25.84
		50	56	25.90	25.70	25.79
		100	0	26.00	25.83	25.83
	16QAM	1	0	25.36	25.41	25.33
		1	53	25.28	25.45	25.32
		1	104	25.36	25.28	25.30
		50	0	24.90	24.77	24.98
		50	28	24.97	24.96	24.85
		50	56	24.73	24.90	24.98
		100	0	24.96	25.00	24.76
	64QAM	1	0	24.37	24.45	24.49
		1	53	24.22	24.38	24.23
		1	104	24.29	24.21	24.22
		50	0	23.96	23.76	23.82
		50	28	23.86	23.82	23.81
		50	56	23.72	23.84	23.98
		100	0	23.90	23.77	23.97
	256QAM	1	0	22.73	22.67	22.68
		1	53	22.65	22.70	22.84
		1	104	22.71	22.74	22.83
		50	0	22.21	22.28	22.23
		50	28	22.35	22.22	22.35
		50	56	22.27	22.22	22.21
		100	0	22.36	22.39	22.29

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		647334	656000	665666
		Frequency (MHz)		3710.01	3840	3969.99
20M	$\pi/2$ BPSK	1	0	26.66	26.52	26.50
		1	26	26.57	26.48	26.52
		1	49	26.54	26.52	26.70
		25	0	26.10	26.25	26.29
		25	13	26.03	26.15	26.00
		25	26	26.02	26.30	26.14
		50	0	26.09	26.22	26.01
	QPSK	1	0	26.27	26.28	26.50
		1	26	26.43	26.27	26.30
		1	49	26.27	26.46	26.34
		25	0	25.92	25.74	25.79
		25	13	25.78	25.97	25.91
		25	26	25.74	25.84	25.83
		50	0	25.77	25.74	25.76
	16QAM	1	0	25.49	25.26	25.23
		1	26	25.38	25.45	25.32
		1	49	25.36	25.49	25.41
		25	0	25.00	24.73	24.74
		25	13	24.70	24.78	24.79
		25	26	24.76	24.98	24.74
		50	0	25.00	24.85	24.90
	64QAM	1	0	24.36	24.39	24.41
		1	26	24.42	24.25	24.30
		1	49	24.25	24.27	24.23
		25	0	24.00	23.77	23.96
		25	13	23.74	23.70	23.98
		25	26	23.99	23.77	23.80
		50	0	23.97	23.78	23.86
	256QAM	1	0	22.75	22.77	22.63
		1	26	22.72	22.67	22.85
		1	49	22.70	22.74	22.76
		25	0	22.35	22.25	22.25
		25	13	22.33	22.34	22.11
		25	26	22.38	22.20	22.33
		50	0	22.17	22.17	22.30

5GNR n77 (Part 27Q):

5GNR n77				
BW	MCS Index	RB Size	RB Offset	Mid
		Channel		633334
		Frequency (MHz)		3500.01
100M	QPSK	1	0	26.69
		1	137	26.49
		1	271	26.48
		135	0	26.16
		135	69	26.02
		135	138	26.15
		270	0	26.12
	16QAM	1	0	26.31
		1	137	26.38
		1	271	26.20
		135	0	25.87
		135	69	25.87
		135	138	25.76
		270	0	25.93
	64QAM	1	0	25.25
		1	137	25.46
		1	271	25.26
		135	0	24.94
		135	69	24.90
		135	138	24.81
		270	0	24.86
	256QAM	1	0	24.41
		1	137	24.22
		1	271	24.40
		135	0	23.99
		135	69	23.78
		135	138	23.86
		270	0	23.79

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		633000	633334	633666
		Frequency (MHz)		3495	3500.01	3504.99
90M	$\pi/2$ BPSK	1	0	26.50	26.69	26.55
		1	123	26.64	26.62	26.68
		1	243	26.69	26.53	26.47
		120	0	26.07	26.27	26.01
		120	63	26.11	26.25	26.25
		120	125	26.10	26.27	26.24
		240	0	26.24	26.30	26.15
	QPSK	1	0	26.37	26.46	26.48
		1	123	26.31	26.30	26.29
		1	243	26.40	26.24	26.45
		120	0	25.78	25.72	25.93
		120	63	25.73	25.94	25.70
		120	125	25.99	25.71	25.92
		240	0	25.92	25.94	25.79
	16QAM	1	0	25.25	25.28	25.35
		1	123	25.37	25.45	25.39
		1	243	25.42	25.43	25.25
		120	0	24.86	24.83	24.98
		120	63	24.90	24.77	24.85
		120	125	24.84	24.76	24.92
		240	0	24.90	25.00	24.93
	64QAM	1	0	24.35	24.36	24.48
		1	123	24.38	24.29	24.41
		1	243	24.40	24.36	24.47
		120	0	23.71	23.72	23.99
		120	63	23.93	24.00	23.88
		120	125	24.00	23.86	24.00
		240	0	23.87	23.73	23.91
	256QAM	1	0	22.74	22.73	22.90
		1	123	22.70	22.74	22.83
		1	243	22.87	22.72	22.78
		120	0	22.39	22.28	22.20
		120	63	22.36	22.25	22.30
		120	125	22.35	22.23	22.27
		240	0	22.19	22.39	22.14

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		632668	633334	634000
		Frequency (MHz)		3490.02	3500.01	3510
80M	$\pi/2$ BPSK	1	0	26.54	26.70	26.70
		1	109	26.60	26.68	26.48
		1	215	26.68	26.57	26.45
		108	0	26.04	26.00	26.23
		108	55	26.03	26.17	26.15
		108	109	26.27	26.20	26.12
		216	0	26.01	26.11	26.10
	QPSK	1	0	26.47	26.26	26.26
		1	109	26.46	26.24	26.26
		1	215	26.28	26.35	26.29
		108	0	25.79	25.89	25.95
		108	55	25.93	25.83	25.71
		108	109	25.87	25.75	25.94
		216	0	25.82	25.89	25.70
	16QAM	1	0	25.37	25.40	25.31
		1	109	25.47	25.47	25.26
		1	215	25.30	25.41	25.43
		108	0	24.70	24.72	24.75
		108	55	24.79	24.72	24.87
		108	109	24.72	24.73	24.88
		216	0	24.85	24.83	24.98
	64QAM	1	0	24.37	24.40	24.31
		1	109	24.21	24.37	24.26
		1	215	24.26	24.24	24.30
		108	0	23.83	23.92	24.00
		108	55	23.94	23.87	23.98
		108	109	23.83	23.92	23.77
		216	0	23.82	23.93	23.75
	256QAM	1	0	22.78	22.86	22.67
		1	109	22.77	22.88	22.64
		1	215	22.60	22.87	22.80
		108	0	22.26	22.34	22.21
		108	55	22.33	22.18	22.20
		108	109	22.17	22.40	22.15
		216	0	22.25	22.13	22.39

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		632000	633334	634666
		Frequency (MHz)		3480	3500.01	3519.99
60M	$\pi/2$ BPSK	1	0	26.51	26.64	26.55
		1	81	26.51	26.66	26.70
		1	160	26.62	26.51	26.45
		81	0	26.04	26.06	26.02
		81	41	26.13	26.00	26.12
		81	81	26.23	26.30	26.15
		162	0	26.19	26.29	26.23
	QPSK	1	0	26.31	26.38	26.29
		1	81	26.35	26.47	26.50
		1	160	26.50	26.49	26.43
		81	0	25.72	25.75	25.94
		81	41	25.86	25.81	25.83
		81	81	25.81	25.92	25.93
		162	0	26.00	25.84	25.78
	16QAM	1	0	25.24	25.37	25.29
		1	81	25.43	25.31	25.46
		1	160	25.31	25.49	25.43
		81	0	24.93	24.83	25.00
		81	41	24.83	24.79	24.80
		81	81	24.71	24.80	24.99
		162	0	24.72	24.70	24.86
	64QAM	1	0	24.26	24.35	24.46
		1	81	24.28	24.45	24.34
		1	160	24.23	24.42	24.23
		81	0	23.92	23.75	23.71
		81	41	23.74	23.93	23.82
		81	81	23.77	23.77	23.72
		162	0	23.75	23.86	23.78
	256QAM	1	0	22.89	22.64	22.62
		1	81	22.89	22.62	22.65
		1	160	22.67	22.70	22.65
		81	0	22.11	22.40	22.19
		81	41	22.26	22.19	22.38
		81	81	22.40	22.30	22.30
		162	0	22.31	22.36	22.38

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		631668	633334	635000
		Frequency (MHz)		3475.02	3500.01	3525
50M	$\pi/2$ BPSK	1	0	26.50	26.50	26.60
		1	67	26.62	26.70	26.66
		1	131	26.40	26.41	26.69
		64	0	26.08	26.13	26.14
		64	35	26.06	26.14	26.30
		64	69	26.30	26.03	26.14
		128	0	26.22	26.19	26.08
	QPSK	1	0	26.47	26.26	26.49
		1	67	26.24	26.24	26.21
		1	131	26.40	26.24	26.48
		64	0	25.96	25.89	25.71
		64	35	25.73	25.92	25.89
		64	69	25.84	25.91	25.74
		128	0	25.76	25.89	25.94
	16QAM	1	0	25.48	25.39	25.47
		1	67	25.28	25.22	25.48
		1	131	25.50	25.20	25.33
		64	0	25.00	24.80	24.81
		64	35	24.75	24.95	24.82
		64	69	24.98	24.78	24.77
		128	0	24.77	24.82	24.98
	64QAM	1	0	24.35	24.47	24.26
		1	67	24.43	24.35	24.35
		1	131	24.30	24.44	24.36
		64	0	23.81	23.83	23.84
		64	35	23.85	23.90	23.73
		64	69	23.87	23.97	23.88
		128	0	23.95	23.82	23.82
	256QAM	1	0	22.68	22.75	22.81
		1	67	22.64	22.66	22.72
		1	131	22.64	22.60	22.89
		64	0	22.32	22.19	22.21
		64	35	22.20	22.22	22.33
		64	69	22.23	22.20	22.18
		128	0	22.30	22.11	22.15

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		631334	633334	635332
		Frequency (MHz)		3470.01	3500.01	3529.98
40M	$\pi/2$ BPSK	1	0	26.44	26.47	26.53
		1	53	26.60	26.45	26.70
		1	104	26.66	26.41	26.62
		50	0	26.25	26.06	26.18
		50	28	26.04	26.11	26.12
		50	56	26.25	26.28	26.07
		100	0	26.11	26.00	26.18
	QPSK	1	0	26.33	26.28	26.21
		1	53	26.44	26.28	26.34
		1	104	26.46	26.24	26.32
		50	0	25.75	25.96	25.71
		50	28	25.90	25.91	25.82
		50	56	25.76	25.72	25.78
		100	0	25.94	25.93	25.95
	16QAM	1	0	25.36	25.20	25.32
		1	53	25.34	25.38	25.24
		1	104	25.50	25.45	25.24
		50	0	24.71	24.81	24.86
		50	28	24.70	24.92	24.97
		50	56	24.70	24.71	24.91
		100	0	24.96	24.72	24.76
	64QAM	1	0	24.49	24.37	24.31
		1	53	24.26	24.20	24.37
		1	104	24.50	24.40	24.42
		50	0	23.86	23.96	23.74
		50	28	23.72	23.80	23.86
		50	56	23.82	23.84	23.91
		100	0	23.99	23.72	23.78
	256QAM	1	0	22.90	22.86	22.68
		1	53	22.75	22.82	22.63
		1	104	22.76	22.85	22.61
		50	0	22.12	22.26	22.24
		50	28	22.27	22.27	22.18
		50	56	22.10	22.20	22.38
		100	0	22.16	22.14	22.33

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		630668	633334	636000
		Frequency (MHz)		3460.02	3500.01	3540
20M	$\pi/2$ BPSK	1	0	26.57	26.53	26.58
		1	26	26.51	26.48	26.46
		1	49	26.57	26.70	26.43
		25	0	26.15	26.25	26.16
		25	13	26.14	26.10	26.28
		25	26	26.19	26.06	26.00
		50	0	26.08	26.07	26.30
	QPSK	1	0	26.28	26.49	26.34
		1	26	26.34	26.31	26.50
		1	49	26.23	26.43	26.47
		25	0	25.71	25.72	25.96
		25	13	25.80	25.73	25.78
		25	26	25.71	25.79	25.98
		50	0	25.87	25.94	25.70
	16QAM	1	0	25.23	25.28	25.42
		1	26	25.48	25.23	25.26
		1	49	25.50	25.26	25.32
		25	0	24.88	24.77	24.87
		25	13	24.78	24.71	24.76
		25	26	24.81	24.88	24.75
		50	0	24.83	24.72	24.86
	64QAM	1	0	24.38	24.38	24.49
		1	26	24.41	24.41	24.40
		1	49	24.46	24.30	24.40
		25	0	23.97	23.75	23.91
		25	13	23.78	23.70	23.92
		25	26	23.74	23.75	23.87
		50	0	23.74	23.78	23.87
	256QAM	1	0	22.89	22.73	22.73
		1	26	22.73	22.73	22.61
		1	49	22.83	22.61	22.86
		25	0	22.40	22.12	22.12
		25	13	22.17	22.13	22.34
		25	26	22.26	22.32	22.38
		50	0	22.31	22.18	22.21

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18700	18900	19100
		Frequency (MHz)		1860	1880	1900
20M	QPSK	1	0	24.86	24.73	24.68
		1	50	24.73	24.70	24.41
		1	99	24.45	24.72	24.57
		50	0	23.77	23.77	23.63
		50	25	23.83	23.76	23.63
		50	50	23.75	23.79	23.62
		100	0	23.81	23.67	23.68
	16QAM	1	0	23.83	24.28	24.13
		1	50	23.92	24.29	23.75
		1	99	23.83	24.29	23.60
		50	0	22.64	22.80	22.62
		50	25	22.78	22.69	22.64
		50	50	22.81	22.87	22.58
		100	0	22.82	22.80	22.63
	64QAM	1	0	22.66	23.20	22.91
		1	50	22.71	23.19	22.62
		1	99	22.70	23.36	22.62
		50	0	21.43	21.74	21.56
		50	25	21.49	21.48	21.37
		50	50	21.55	22.05	21.50
		100	0	22.01	21.98	21.65
	256QAM	1	0	20.84	21.38	20.64
		1	50	20.60	21.42	20.44
		1	99	20.42	21.51	20.83
		50	0	19.55	19.67	19.44
		50	25	19.59	19.73	19.43
		50	50	19.29	19.96	19.42
		100	0	19.86	20.23	19.58

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18675	18900	19125
		Frequency (MHz)		1857.5	1880	1902.5
15M	QPSK	1	0	24.70	24.61	24.50
		1	37	24.58	24.78	24.52
		1	74	24.59	24.66	24.52
		36	0	23.79	23.72	23.59
		36	19	23.85	23.79	23.61
		36	39	23.83	23.77	23.64
		75	0	23.90	23.68	23.69
	16QAM	1	0	24.24	24.31	23.67
		1	37	23.89	24.24	24.02
		1	74	24.07	23.94	24.05
		36	0	22.76	22.82	22.58
		36	19	22.85	22.72	22.65
		36	39	22.82	22.77	22.63
		75	0	22.89	22.72	22.68
	64QAM	1	0	23.25	23.27	22.52
		1	37	22.89	23.03	22.83
		1	74	22.80	22.70	22.83
		36	0	21.66	21.92	21.73
		36	19	21.93	21.88	21.83
		36	39	21.73	21.90	21.77
		75	0	22.03	21.89	21.83
	256QAM	1	0	21.30	21.11	20.36
		1	37	20.91	20.87	20.70
		1	74	20.68	20.92	20.67
		36	0	19.88	19.91	19.56
		36	19	19.87	20.01	19.67
		36	39	20.03	19.97	19.97
		75	0	20.18	19.85	20.11

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18650	18900	19150
		Frequency (MHz)		1855	1880	1905
10M	QPSK	1	0	24.76	24.85	24.43
		1	24	24.60	24.50	24.50
		1	49	24.69	24.59	24.48
		25	0	23.78	23.73	23.63
		25	12	23.84	23.77	23.59
		25	25	23.83	23.81	23.61
		50	0	23.82	23.79	23.67
	16QAM	1	0	24.25	24.15	23.79
		1	24	23.76	24.00	24.08
		1	49	24.35	23.96	24.08
		25	0	22.79	22.68	22.57
		25	12	22.78	22.80	22.56
		25	25	22.78	22.69	22.67
		50	0	22.80	22.72	22.65
	64QAM	1	0	23.43	22.91	22.92
		1	24	22.76	22.73	23.26
		1	49	23.29	22.83	23.04
		25	0	21.75	21.80	21.61
		25	12	21.69	21.61	21.44
		25	25	21.50	21.41	21.41
		50	0	21.54	21.67	21.44
	256QAM	1	0	21.42	20.66	21.18
		1	24	20.50	20.87	21.25
		1	49	21.46	21.02	20.79
		25	0	19.97	19.97	19.61
		25	12	19.57	19.75	19.49
		25	25	19.52	19.52	19.70
		50	0	19.77	19.87	19.33

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18625	18900	19175
		Frequency (MHz)		1852.5	1880	1907.5
5M	QPSK	1	0	24.63	24.53	24.40
		1	12	24.83	24.69	24.60
		1	24	24.62	24.64	24.42
		12	0	23.75	23.70	23.49
		12	6	23.78	23.72	23.56
		12	13	23.77	23.75	23.62
		25	0	23.81	23.74	23.54
	16QAM	1	0	23.91	24.19	23.79
		1	12	24.23	23.98	23.66
		1	24	23.83	24.24	23.84
		12	0	22.74	22.71	22.57
		12	6	22.89	22.76	22.47
		12	13	22.75	22.78	22.67
		25	0	22.88	22.65	22.52
	64QAM	1	0	22.61	22.90	22.87
		1	12	23.10	22.71	22.75
		1	24	22.98	23.24	23.00
		12	0	21.68	21.81	21.35
		12	6	21.84	21.90	21.22
		12	13	21.78	21.71	21.68
		25	0	21.59	21.54	21.63
	256QAM	1	0	20.64	20.97	20.71
		1	12	20.96	20.98	20.82
		1	24	20.70	21.18	21.14
		12	0	19.57	19.78	19.53
		12	6	20.07	20.04	19.50
		12	13	19.66	19.45	19.90
		25	0	19.74	19.76	19.69

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18615	18900	19185
		Frequency (MHz)		1851.5	1880	1908.5
3M	QPSK	1	0	24.48	24.67	24.37
		1	7	24.76	24.73	24.59
		1	14	24.82	24.76	24.44
		8	0	23.79	23.72	23.56
		8	3	23.76	23.75	23.49
		8	7	23.80	23.79	23.54
		15	0	23.74	23.75	23.55
	16QAM	1	0	23.96	24.02	23.46
		1	7	24.21	24.27	23.84
		1	14	23.90	23.78	24.13
		8	0	22.78	22.81	22.61
		8	3	22.87	22.78	22.66
		8	7	22.90	22.89	22.47
		15	0	22.65	22.74	22.66
	64QAM	1	0	23.06	22.89	22.35
		1	7	22.93	23.31	22.57
		1	14	22.87	22.49	22.89
		8	0	21.77	21.99	21.35
		8	3	21.82	21.96	21.53
		8	7	21.65	21.63	21.47
		15	0	21.43	21.75	21.70
	256QAM	1	0	21.26	21.18	20.49
		1	7	20.91	21.55	20.54
		1	14	20.94	20.34	21.08
		8	0	19.97	19.99	19.55
		8	3	19.62	19.87	19.40
		8	7	19.81	19.63	19.59
		15	0	19.43	19.54	19.97

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18607	18900	19193
		Frequency (MHz)		1850.7	1880	1909.3
1.4M	QPSK	1	0	24.64	24.59	24.35
		1	2	24.77	24.71	24.44
		1	5	24.58	24.63	24.31
		3	0	24.57	24.63	24.36
		3	1	24.71	24.72	24.44
		3	3	24.63	24.62	24.37
		6	0	23.74	23.69	23.40
	16QAM	1	0	24.20	23.99	23.33
		1	2	23.63	24.20	23.65
		1	5	23.77	23.82	23.95
		3	0	23.73	23.75	23.46
		3	1	23.79	23.78	23.58
		3	3	23.76	23.74	23.51
		6	0	22.83	22.79	22.45
	64QAM	1	0	23.08	23.06	22.41
		1	2	22.44	22.96	22.74
		1	5	22.55	22.70	23.11
		3	0	22.83	22.78	22.17
		3	1	22.88	22.92	22.41
		3	3	22.80	22.60	22.65
		6	0	21.99	21.81	21.31
	256QAM	1	0	21.28	20.78	20.33
		1	2	20.29	20.78	20.71
		1	5	20.64	20.86	21.27
		3	0	20.72	21.00	19.92
		3	1	21.16	21.01	20.21
		3	3	21.10	20.77	20.71
		6	0	19.70	19.65	19.02

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20450	20525	20600
		Frequency (MHz)		829	836.5	844
10M	QPSK	1	0	24.95	25.08	24.89
		1	24	24.90	25.05	24.65
		1	49	24.74	24.96	24.67
		25	0	24.01	24.03	23.94
		25	12	24.00	23.97	24.01
		25	25	24.04	23.98	23.92
		50	0	24.07	24.06	24.01
	16QAM	1	0	24.22	24.55	24.69
		1	24	24.16	24.36	24.26
		1	49	24.14	24.17	24.15
		25	0	23.01	23.06	22.92
		25	12	23.04	22.92	22.86
		25	25	22.99	22.92	22.98
		50	0	22.97	22.94	22.84
	64QAM	1	0	23.06	23.36	23.70
		1	24	23.31	23.42	23.31
		1	49	23.19	22.87	23.30
		25	0	21.87	21.95	21.65
		25	12	22.09	22.02	21.68
		25	25	22.11	21.87	22.07
		50	0	21.92	21.74	21.85
	256QAM	1	0	21.35	21.61	21.56
		1	24	21.61	21.72	21.12
		1	49	21.41	20.66	21.15
		25	0	19.84	19.74	19.59
		25	12	20.17	20.13	19.66
		25	25	20.21	19.70	19.81
		50	0	19.71	19.86	19.94

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20425	20525	20625
		Frequency (MHz)		826.5	836.5	846.5
5M	QPSK	1	0	25.11	25.04	24.84
		1	12	24.97	25.08	24.91
		1	24	25.01	24.88	24.83
		12	0	24.01	23.95	24.01
		12	6	24.02	24.04	23.90
		12	13	24.00	24.02	23.89
		25	0	24.01	24.00	24.01
	16QAM	1	0	24.38	23.98	24.29
		1	12	24.49	24.42	24.43
		1	24	23.93	24.13	24.11
		12	0	23.11	23.06	23.00
		12	6	23.16	22.96	22.87
		12	13	23.04	23.01	23.00
		25	0	23.02	22.91	22.90
	64QAM	1	0	23.35	23.08	23.08
		1	12	23.33	23.51	23.54
		1	24	22.79	23.26	23.05
		12	0	21.87	22.25	21.96
		12	6	22.18	22.01	22.03
		12	13	22.02	22.21	21.80
		25	0	22.07	22.11	22.06
	256QAM	1	0	21.54	20.99	21.16
		1	12	21.54	21.63	21.46
		1	24	20.89	21.50	20.90
		12	0	19.87	20.17	19.96
		12	6	20.05	19.89	19.94
		12	13	20.17	20.24	19.63
		25	0	20.21	20.09	19.78

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20415	20525	20635
		Frequency (MHz)		825.5	836.5	847.5
3M	QPSK	1	0	24.95	24.92	24.94
		1	7	25.10	24.93	24.98
		1	14	24.96	24.84	24.83
		8	0	24.05	23.96	23.89
		8	3	24.02	23.95	23.93
		8	7	24.01	23.91	23.95
		15	0	24.02	23.96	23.88
	16QAM	1	0	24.13	24.49	24.13
		1	7	24.48	24.09	24.05
		1	14	24.09	24.42	24.17
		8	0	23.11	23.05	22.98
		8	3	23.18	23.06	23.06
		8	7	23.01	22.94	22.94
		15	0	23.10	22.89	22.99
	64QAM	1	0	22.91	23.53	23.20
		1	7	23.32	22.98	22.92
		1	14	23.13	23.32	23.01
		8	0	22.23	21.78	21.84
		8	3	22.28	22.20	21.88
		8	7	21.99	21.67	21.94
		15	0	22.13	21.83	21.89
	256QAM	1	0	20.62	21.63	21.18
		1	7	21.62	21.00	20.82
		1	14	21.37	21.27	20.81
		8	0	20.52	19.72	19.59
		8	3	20.14	20.35	19.94
		8	7	20.18	19.49	20.02
		15	0	20.16	20.02	20.17

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20407	20525	20643
		Frequency (MHz)		824.7	836.5	848.3
1.4M	QPSK	1	0	24.94	24.81	24.81
		1	2	24.91	24.92	24.85
		1	5	24.82	24.78	24.73
		3	0	24.91	24.78	24.83
		3	1	24.91	24.83	24.85
		3	3	24.90	24.89	24.75
		6	0	23.96	23.93	23.85
	16QAM	1	0	24.48	23.84	24.21
		1	2	24.02	24.11	24.37
		1	5	24.11	24.34	23.99
		3	0	24.00	23.77	23.94
		3	1	23.86	23.95	23.93
		3	3	23.91	23.94	23.72
		6	0	22.93	23.05	23.05
	64QAM	1	0	23.32	22.59	23.16
		1	2	23.19	22.82	23.31
		1	5	23.14	23.34	22.74
		3	0	22.92	22.69	22.76
		3	1	22.60	23.15	22.71
		3	3	22.66	22.93	22.90
		6	0	22.03	21.88	21.75
	256QAM	1	0	21.55	20.46	20.98
		1	2	21.30	20.99	21.13
		1	5	21.28	21.20	20.67
		3	0	20.82	20.57	20.60
		3	1	20.66	21.13	20.99
		3	3	20.89	20.91	20.82
		6	0	20.23	19.81	19.48

LTE Band 7						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20850	21100	21350
		Frequency (MHz)		2510	2535	2560
20M	QPSK	1	0	24.98	24.87	24.79
		1	50	24.88	24.75	24.64
		1	99	24.95	24.99	24.75
		50	0	24.12	23.99	23.82
		50	25	24.13	24.00	23.99
		50	50	24.15	24.05	23.88
		100	0	24.18	24.00	24.00
	16QAM	1	0	24.08	24.26	23.95
		1	50	24.19	24.08	24.27
		1	99	24.07	24.52	24.40
		50	0	23.12	22.99	22.83
		50	25	23.14	22.99	22.97
		50	50	23.11	23.02	22.95
		100	0	23.10	23.01	22.90
	64QAM	1	0	23.04	23.45	22.95
		1	50	22.96	23.26	23.18
		1	99	23.15	23.63	23.20
		50	0	22.10	22.06	21.76
		50	25	22.02	21.83	21.97
		50	50	21.93	22.03	21.89
		100	0	21.84	22.21	21.83
	256QAM	1	0	20.91	21.51	21.18
		1	50	21.19	21.56	21.41
		1	99	21.42	21.91	20.95
		50	0	19.82	20.05	19.66
		50	25	20.30	19.97	20.09
		50	50	19.96	20.28	19.77
		100	0	19.80	19.98	19.90

LTE Band 7						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20825	21100	21375
		Frequency (MHz)		2507.5	2535	2562.5
15M	QPSK	1	0	25.02	24.89	24.81
		1	37	24.96	24.91	24.72
		1	74	25.04	24.98	24.85
		36	0	24.01	23.95	23.94
		36	19	24.18	23.91	23.86
		36	39	24.14	24.00	23.93
		75	0	24.07	23.98	23.82
	16QAM	1	0	24.26	23.98	23.90
		1	37	24.00	23.77	23.99
		1	74	24.26	24.15	24.05
		36	0	23.13	22.96	22.85
		36	19	23.14	22.98	22.79
		36	39	23.08	23.03	22.92
		75	0	23.14	22.88	22.82
	64QAM	1	0	23.36	22.77	22.75
		1	37	23.03	22.96	22.93
		1	74	23.40	23.17	22.79
		36	0	22.28	21.84	21.77
		36	19	21.93	21.87	21.93
		36	39	22.01	21.86	22.02
		75	0	22.28	21.72	21.87
	256QAM	1	0	21.57	20.68	20.71
		1	37	20.76	20.93	20.97
		1	74	21.59	21.24	21.01
		36	0	20.36	20.01	19.95
		36	19	20.14	19.90	19.99
		36	39	20.12	19.78	20.01
		75	0	20.26	19.50	19.78

LTE Band 7						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20800	21100	21400
		Frequency (MHz)		2505	2535	2565
10M	QPSK	1	0	24.92	24.74	24.67
		1	24	24.99	24.77	24.68
		1	49	24.95	24.90	24.73
		25	0	24.03	23.92	23.86
		25	12	24.15	24.02	23.99
		25	25	24.16	23.98	23.94
		50	0	24.12	23.84	23.86
	16QAM	1	0	24.48	23.82	23.75
		1	24	24.42	24.08	24.35
		1	49	24.29	24.57	23.94
		25	0	23.18	22.85	22.80
		25	12	23.22	22.99	22.99
		25	25	23.07	23.02	22.97
		50	0	23.18	22.91	22.85
	64QAM	1	0	23.61	23.00	22.93
		1	24	23.27	23.13	23.20
		1	49	23.36	23.41	23.10
		25	0	22.38	21.59	21.95
		25	12	22.23	21.77	21.88
		25	25	22.15	21.97	22.11
		50	0	22.09	21.66	21.68
	256QAM	1	0	21.77	20.71	21.12
		1	24	21.45	20.95	21.35
		1	49	21.48	21.13	20.86
		25	0	20.28	19.84	19.96
		25	12	19.97	19.84	19.68
		25	25	19.87	20.14	19.89
		50	0	20.11	19.50	19.39

LTE Band 7						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20775	21100	21425
		Frequency (MHz)		2502.5	2535	2567.5
5M	QPSK	1	0	24.94	24.82	24.86
		1	12	25.14	24.87	24.84
		1	24	24.98	24.91	24.65
		12	0	24.16	24.03	23.93
		12	6	24.06	24.01	23.86
		12	13	24.03	23.99	23.89
		25	0	24.04	23.96	23.87
	16QAM	1	0	24.03	24.31	23.94
		1	12	24.54	24.03	24.25
		1	24	24.21	24.07	23.87
		12	0	23.10	23.02	22.85
		12	6	23.12	22.96	22.94
		12	13	23.15	22.93	22.88
		25	0	23.16	23.04	22.89
	64QAM	1	0	23.23	23.30	22.83
		1	12	23.60	22.91	23.09
		1	24	22.96	22.97	22.85
		12	0	22.29	22.11	21.93
		12	6	22.24	22.14	22.12
		12	13	21.89	21.94	22.03
		25	0	22.05	22.00	21.77
	256QAM	1	0	21.06	21.08	20.92
		1	12	21.67	20.64	21.06
		1	24	21.10	20.99	21.09
		12	0	20.56	20.01	19.69
		12	6	20.27	20.08	19.99
		12	13	19.97	19.87	19.75
		25	0	19.79	20.28	19.79

LTE Band 12						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23060	23095	23130
		Frequency (MHz)		704	707.5	711
10M	QPSK	1	0	24.89	24.94	24.82
		1	24	24.72	24.84	24.93
		1	49	24.82	24.79	24.65
		25	0	23.93	23.89	23.93
		25	12	23.96	23.88	24.01
		25	25	23.97	24.01	24.04
		50	0	24.07	23.90	23.99
	16QAM	1	0	24.32	24.35	23.94
		1	24	24.56	24.45	24.17
		1	49	24.25	24.00	24.23
		25	0	22.99	22.96	22.97
		25	12	23.02	22.95	23.03
		25	25	22.96	22.94	23.01
		50	0	23.02	22.95	23.03
	64QAM	1	0	23.22	23.33	22.99
		1	24	23.46	23.17	23.15
		1	49	22.96	23.04	23.01
		25	0	22.18	21.92	21.80
		25	12	22.12	21.86	21.74
		25	25	22.01	21.78	21.91
		50	0	21.78	21.67	22.05
	256QAM	1	0	21.02	21.26	20.79
		1	24	21.34	20.89	21.37
		1	49	20.73	21.32	20.87
		25	0	20.19	19.71	19.82
		25	12	20.23	19.86	19.55
		25	25	20.21	19.58	19.62
		50	0	19.94	19.95	19.79

LTE Band 12						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23035	23095	23155
		Frequency (MHz)		701.5	707.5	713.5
5M	QPSK	1	0	24.86	24.84	24.81
		1	12	25.04	24.88	24.70
		1	24	24.91	24.91	24.89
		12	0	24.04	23.94	23.89
		12	6	24.03	23.90	23.96
		12	13	23.98	23.97	23.93
		25	0	23.94	23.86	23.86
	16QAM	1	0	24.21	24.09	23.75
		1	12	24.40	24.04	24.22
		1	24	23.84	24.02	24.38
		12	0	23.10	22.90	22.85
		12	6	22.95	22.93	22.96
		12	13	22.96	23.01	22.89
		25	0	22.91	22.94	22.91
	64QAM	1	0	22.99	23.25	22.92
		1	12	23.44	23.04	23.39
		1	24	22.90	23.12	23.18
		12	0	22.06	21.96	21.64
		12	6	21.77	22.05	21.84
		12	13	21.80	21.76	21.95
		25	0	22.05	22.06	22.09
	256QAM	1	0	20.77	21.32	21.21
		1	12	21.38	21.10	21.12
		1	24	21.14	21.14	20.98
		12	0	20.00	20.17	19.52
		12	6	20.07	19.89	20.08
		12	13	19.60	19.64	19.76
		25	0	20.35	20.14	20.22

LTE Band 12						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23025	23095	23165
		Frequency (MHz)		700.5	707.5	714.5
3M	QPSK	1	0	25.00	24.90	24.82
		1	7	24.83	24.95	24.79
		1	14	24.80	24.79	24.81
		8	0	23.96	23.89	23.85
		8	3	24.01	23.94	23.85
		8	7	23.89	23.88	23.87
		15	0	24.02	23.90	23.83
	16QAM	1	0	24.16	24.32	24.06
		1	7	24.06	24.00	24.21
		1	14	24.09	24.41	23.76
		8	0	22.86	23.00	22.86
		8	3	23.15	22.97	22.88
		8	7	23.04	22.91	22.83
		15	0	23.05	22.88	22.78
	64QAM	1	0	23.31	23.08	22.81
		1	7	22.93	23.02	23.37
		1	14	22.91	23.35	22.84
		8	0	21.96	22.11	21.62
		8	3	21.93	22.15	21.66
		8	7	21.97	21.87	21.79
		15	0	22.01	22.08	21.86
	256QAM	1	0	21.30	21.31	21.08
		1	7	21.11	21.20	21.59
		1	14	20.96	21.38	20.94
		8	0	20.17	20.11	19.78
		8	3	20.11	19.89	19.95
		8	7	20.04	20.15	19.73
		15	0	20.31	20.11	19.96

LTE Band 12						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23017	23095	23173
		Frequency (MHz)		699.7	707.5	715.3
1.4M	QPSK	1	0	24.81	24.83	24.74
		1	2	24.92	24.82	24.77
		1	5	24.77	24.69	24.66
		3	0	24.82	24.75	24.68
		3	1	24.94	24.72	24.74
		3	3	24.82	24.83	24.68
		6	0	23.96	23.87	23.76
	16QAM	1	0	24.38	24.20	23.90
		1	2	24.12	24.07	24.05
		1	5	24.08	24.21	23.71
		3	0	23.91	23.83	23.77
		3	1	24.03	23.95	23.68
		3	3	23.92	23.86	23.84
		6	0	23.11	23.01	22.88
	64QAM	1	0	23.21	23.18	22.66
		1	2	23.14	23.06	23.01
		1	5	23.04	23.39	22.48
		3	0	23.01	22.65	22.70
		3	1	23.14	22.79	22.43
		3	3	22.70	22.70	22.54
		6	0	22.19	22.13	21.76
	256QAM	1	0	21.07	21.17	20.54
		1	2	21.28	21.31	20.77
		1	5	21.18	21.49	20.36
		3	0	20.77	20.57	20.64
		3	1	21.18	20.90	20.68
		3	3	20.83	20.44	20.26
		6	0	20.32	20.18	19.89

LTE Band 13				
BW	MCS Index	RB Size	RB Offset	Mid
		Channel		23230
		Frequency (MHz)		782
10M	QPSK	1	0	24.97
		1	24	24.97
		1	49	24.93
		25	0	24.11
		25	12	24.09
		25	25	24.14
		50	0	24.19
	16QAM	1	0	24.39
		1	24	24.24
		1	49	24.38
		25	0	23.15
		25	12	23.09
		25	25	23.23
		50	0	23.07
	64QAM	1	0	23.33
		1	24	23.39
		1	49	23.41
		25	0	22.31
		25	12	21.84
		25	25	21.99
		50	0	21.87
	256QAM	1	0	21.13
		1	24	21.35
		1	49	21.65
		25	0	20.58
		25	12	20.05
		25	25	19.99
		50	0	19.97

LTE Band 13						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23205	23230	23255
		Frequency (MHz)		779.5	782	784.5
5M	QPSK	1	0	24.85	24.92	24.98
		1	12	24.95	25.06	24.99
		1	24	25.04	24.90	24.85
		12	0	24.05	24.08	23.97
		12	6	24.10	24.02	24.02
		12	13	24.13	24.09	24.06
		25	0	24.13	24.10	23.98
	16QAM	1	0	23.95	24.14	24.47
		1	12	24.60	24.51	24.00
		1	24	24.32	24.21	24.42
		12	0	23.05	23.10	23.25
		12	6	23.08	23.07	23.17
		12	13	23.20	23.09	23.11
		25	0	23.05	23.12	23.10
	64QAM	1	0	23.07	23.29	23.31
		1	12	23.80	23.45	23.11
		1	24	23.09	23.07	23.50
		12	0	22.17	21.86	22.33
		12	6	21.96	22.20	21.98
		12	13	21.97	21.87	22.14
		25	0	21.79	22.08	21.83
	256QAM	1	0	20.96	21.20	21.45
		1	12	21.87	21.34	21.28
		1	24	20.97	20.89	21.59
		12	0	20.21	19.64	20.11
		12	6	20.05	20.32	19.70
		12	13	20.09	19.58	20.00
		25	0	19.67	20.27	19.57

LTE Band 14				
BW	MCS Index	RB Size	RB Offset	Mid
		Channel		23330
		Frequency (MHz)		793
10M	QPSK	1	0	24.88
		1	24	24.87
		1	49	24.94
		25	0	24.04
		25	12	23.95
		25	25	23.97
		50	0	23.97
	16QAM	1	0	24.59
		1	24	24.40
		1	49	23.96
		25	0	22.94
		25	12	23.02
		25	25	22.98
		50	0	23.02
	64QAM	1	0	23.78
		1	24	23.16
		1	49	22.83
		25	0	21.80
		25	12	21.90
		25	25	22.13
		50	0	21.82
	256QAM	1	0	21.97
		1	24	21.12
		1	49	21.12
		25	0	20.02
		25	12	20.16
		25	25	20.32
		50	0	20.03

LTE Band 14						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23305	23330	23355
		Frequency (MHz)		790.5	793	795.5
5M	QPSK	1	0	24.80	24.87	24.88
		1	12	24.96	25.05	24.85
		1	24	24.98	25.03	24.88
		12	0	24.00	23.92	23.99
		12	6	24.04	24.01	23.87
		12	13	23.98	24.00	24.00
		25	0	24.04	23.98	23.95
	16QAM	1	0	24.48	24.45	24.44
		1	12	24.23	23.89	24.20
		1	24	24.55	24.39	24.07
		12	0	22.92	23.02	23.07
		12	6	23.05	22.97	23.03
		12	13	23.05	23.01	22.96
		25	0	23.13	22.94	22.97
	64QAM	1	0	23.20	23.31	23.59
		1	12	22.93	22.80	23.31
		1	24	23.38	23.14	23.17
		12	0	21.94	21.80	22.27
		12	6	21.82	22.05	22.16
		12	13	22.25	21.74	21.99
		25	0	21.99	21.85	22.10
	256QAM	1	0	21.26	21.05	21.50
		1	12	20.72	20.63	21.17
		1	24	21.14	21.07	21.47
		12	0	20.05	19.85	19.98
		12	6	20.00	20.29	19.97
		12	13	20.13	19.93	20.18
		25	0	19.91	20.12	19.90

LTE Band 30				
BW	MCS Index	RB Size	RB Offset	Mid
		Channel		27710
		Frequency (MHz)		2310
10M	QPSK	1	0	20.93
		1	24	20.84
		1	49	20.70
		25	0	19.74
		25	12	19.93
		25	25	19.97
		50	0	19.90
	16QAM	1	0	20.10
		1	24	20.17
		1	49	19.85
		25	0	18.72
		25	12	18.85
		25	25	18.88
		50	0	18.76
	64QAM	1	0	18.83
		1	24	19.02
		1	49	18.58
		25	0	17.89
		25	12	18.01
		25	25	18.04
		50	0	17.90
	256QAM	1	0	16.58
		1	24	17.18
		1	49	16.64
		25	0	15.83
		25	12	16.23
		25	25	16.30
		50	0	15.94

LTE Band 30						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		27685	27710	27735
		Frequency (MHz)		2307.5	2310	2312.5
5M	QPSK	1	0	20.56	20.69	20.71
		1	12	20.87	20.94	20.91
		1	24	20.85	20.85	20.86
		12	0	19.76	19.73	19.80
		12	6	19.92	19.87	19.85
		12	13	19.89	19.89	19.88
		25	0	19.86	19.86	19.77
	16QAM	1	0	19.90	19.87	20.24
		1	12	20.28	20.24	20.26
		1	24	19.77	20.42	20.45
		12	0	18.78	18.78	18.80
		12	6	18.86	18.94	18.93
		12	13	18.93	18.89	18.96
		25	0	18.84	18.87	18.86
	64QAM	1	0	18.62	19.01	19.27
		1	12	19.32	19.20	19.06
		1	24	18.47	19.17	19.16
		12	0	17.60	17.52	17.97
		12	6	17.66	17.65	17.64
		12	13	17.74	17.69	17.74
		25	0	17.99	17.97	17.85
	256QAM	1	0	16.33	17.25	17.31
		1	12	17.61	17.13	16.87
		1	24	16.57	17.17	17.13
		12	0	15.42	15.23	15.90
		12	6	15.79	15.73	15.93
		12	13	15.94	15.46	15.93
		25	0	16.23	15.87	16.12

LTE Band 41						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		39750	40620	41490
		Frequency (MHz)		2506	2593	2680
20M	QPSK	1	0	27.66	27.50	27.36
		1	50	27.53	27.35	26.96
		1	99	27.47	27.48	26.16
		50	0	26.74	26.63	26.51
		50	25	26.77	26.65	26.16
		50	50	26.78	26.70	25.75
		100	0	26.73	26.70	26.16
	16QAM	1	0	26.93	26.85	26.84
		1	50	26.84	26.70	26.29
		1	99	26.88	26.72	25.45
		50	0	25.64	25.69	25.57
		50	25	25.74	25.68	25.24
		50	50	25.82	25.70	24.85
		100	0	25.83	25.71	25.25
	64QAM	1	0	25.69	25.85	25.74
		1	50	25.85	25.62	25.00
		1	99	25.69	25.46	24.25
		50	0	24.52	24.55	24.56
		50	25	24.45	24.83	24.37
		50	50	24.56	24.69	23.70
		100	0	24.75	24.72	24.09
	256QAM	1	0	23.77	24.14	23.68
		1	50	24.02	23.75	22.73
		1	99	23.79	23.70	22.43
		50	0	22.38	22.70	22.43
		50	25	22.58	22.87	22.49
		50	50	22.47	22.52	21.74
		100	0	22.57	23.01	22.38

LTE Band 41						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		39725	40620	41515
		Frequency (MHz)		2503.5	2593	2682.5
15M	QPSK	1	0	27.56	27.44	27.34
		1	37	27.57	27.42	26.72
		1	74	27.51	27.47	26.21
		36	0	26.85	26.50	26.19
		36	19	26.81	26.59	25.95
		36	39	26.74	26.63	25.69
		75	0	26.79	26.69	26.03
	16QAM	1	0	26.95	26.74	26.94
		1	37	26.90	27.03	25.98
		1	74	26.87	26.73	25.50
		36	0	25.82	25.60	25.27
		36	19	25.69	25.65	24.99
		36	39	25.70	25.60	24.69
		75	0	25.81	25.69	25.05
	64QAM	1	0	25.74	25.60	25.81
		1	37	25.62	25.74	24.78
		1	74	25.80	25.58	24.60
		36	0	24.80	24.67	24.42
		36	19	24.59	24.82	23.94
		36	39	24.45	24.63	23.80
		75	0	24.74	24.75	24.21
	256QAM	1	0	23.99	23.33	23.83
		1	37	23.76	23.46	22.69
		1	74	23.60	23.48	22.69
		36	0	23.01	22.79	22.66
		36	19	22.47	23.05	21.91
		36	39	22.54	22.36	21.76
		75	0	22.72	22.68	22.46

LTE Band 41						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		39700	40620	41540
		Frequency (MHz)		2501	2593	2685
10M	QPSK	1	0	27.63	27.40	26.93
		1	24	27.65	27.47	26.56
		1	49	27.62	27.30	26.22
		25	0	26.80	26.64	25.97
		25	12	26.80	26.72	25.82
		25	25	26.76	26.70	25.61
		50	0	26.85	26.67	25.76
	16QAM	1	0	27.03	26.74	26.57
		1	24	26.93	26.82	26.18
		1	49	26.99	26.84	25.51
		25	0	25.81	25.77	25.06
		25	12	25.84	25.81	24.93
		25	25	25.81	25.65	24.68
		50	0	25.87	25.74	24.85
	64QAM	1	0	25.88	25.66	25.56
		1	24	25.83	25.77	25.11
		1	49	26.10	25.77	24.31
		25	0	24.92	24.75	24.14
		25	12	24.55	24.72	24.01
		25	25	24.55	24.81	23.60
		50	0	24.80	24.49	23.95
	256QAM	1	0	23.62	23.58	23.27
		1	24	24.09	23.75	23.14
		1	49	23.94	23.62	22.18
		25	0	22.92	22.50	22.01
		25	12	22.27	22.89	22.06
		25	25	22.48	22.84	21.68
		50	0	22.79	22.75	22.12

LTE Band 41						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		39675	40620	41565
		Frequency (MHz)		2498.5	2593	2687.5
5M	QPSK	1	0	27.58	27.38	26.53
		1	12	27.61	27.44	26.34
		1	24	27.54	27.38	26.21
		12	0	26.81	26.66	25.69
		12	6	26.74	26.61	25.66
		12	13	26.77	26.64	25.55
		25	0	26.74	26.61	25.59
	16QAM	1	0	26.88	26.74	25.88
		1	12	26.86	26.77	25.72
		1	24	26.91	26.73	25.59
		12	0	25.82	25.72	24.79
		12	6	25.80	25.78	24.74
		12	13	25.83	25.67	24.62
		25	0	25.78	25.72	24.69
	64QAM	1	0	26.05	25.63	24.84
		1	12	26.04	25.73	24.59
		1	24	25.68	25.64	24.51
		12	0	24.74	24.46	23.74
		12	6	24.63	24.58	23.66
		12	13	24.98	24.76	23.55
		25	0	24.59	24.91	23.51
	256QAM	1	0	24.20	23.82	22.86
		1	12	23.96	23.73	22.67
		1	24	23.88	23.89	22.56
		12	0	22.45	22.40	21.88
		12	6	22.56	22.48	21.64
		12	13	22.96	22.78	21.73
		25	0	22.49	23.06	21.25

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		132072	132322	132572
		Frequency (MHz)		1720	1745	1770
20M	QPSK	1	0	24.78	24.85	24.78
		1	50	24.84	24.75	24.79
		1	99	24.80	24.69	24.66
		50	0	23.85	23.66	23.74
		50	25	23.70	23.74	23.84
		50	50	23.89	23.69	23.87
		100	0	23.65	23.71	23.84
	16QAM	1	0	23.84	24.11	24.26
		1	50	23.84	24.11	24.00
		1	99	23.98	23.89	23.88
		50	0	23.00	23.03	22.97
		50	25	22.78	22.80	23.00
		50	50	23.00	22.71	22.89
		100	0	23.05	22.76	23.28
	64QAM	1	0	22.68	22.81	23.18
		1	50	22.55	23.03	22.90
		1	99	22.71	22.72	22.82
		50	0	21.87	21.97	21.89
		50	25	21.75	21.68	21.83
		50	50	21.91	21.53	21.81
		100	0	22.01	21.71	22.25
	256QAM	1	0	20.69	20.69	21.05
		1	50	20.63	21.00	20.77
		1	99	20.51	20.81	20.91
		50	0	19.85	19.90	19.75
		50	25	19.64	19.54	19.78
		50	50	19.80	19.63	19.85
		100	0	19.91	19.76	20.16

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		132047	132322	132597
		Frequency (MHz)		1717.5	1745	1772.5
15M	QPSK	1	0	24.73	24.54	24.52
		1	37	24.60	24.63	24.75
		1	74	24.69	24.75	24.78
		36	0	23.84	23.65	23.68
		36	19	23.67	23.70	23.78
		36	39	23.67	23.77	23.82
		75	0	23.60	23.61	23.71
	16QAM	1	0	23.87	23.74	23.64
		1	37	24.10	24.12	24.11
		1	74	23.78	24.18	24.13
		36	0	23.22	22.69	22.94
		36	19	22.86	23.03	23.15
		36	39	22.95	23.13	22.92
		75	0	22.61	22.91	23.06
	64QAM	1	0	22.66	22.46	22.49
		1	37	22.83	23.03	22.81
		1	74	22.69	23.16	22.91
		36	0	22.20	21.63	21.76
		36	19	21.82	21.77	22.05
		36	39	21.76	21.85	21.65
		75	0	21.45	21.64	22.00
	256QAM	1	0	20.69	20.38	20.34
		1	37	20.78	21.05	20.75
		1	74	20.68	21.18	20.98
		36	0	20.17	19.66	19.59
		36	19	19.69	19.64	19.93
		36	39	19.81	19.85	19.46
		75	0	19.25	19.58	20.01

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		132022	132322	132622
		Frequency (MHz)		1715	1745	1775
10M	QPSK	1	0	24.76	24.75	24.86
		1	24	24.51	24.53	24.71
		1	49	24.62	24.61	24.58
		25	0	23.66	23.70	23.63
		25	12	23.84	23.76	23.75
		25	25	23.82	23.81	23.90
		50	0	23.78	23.71	23.91
	16QAM	1	0	24.06	23.82	24.15
		1	24	23.86	24.03	23.93
		1	49	23.72	23.62	24.06
		25	0	22.69	22.91	22.99
		25	12	22.86	23.00	23.14
		25	25	22.94	22.88	22.90
		50	0	23.12	22.87	23.20
	64QAM	1	0	22.77	22.59	23.07
		1	24	22.71	22.76	22.85
		1	49	22.48	22.61	22.77
		25	0	21.43	21.79	21.81
		25	12	21.71	21.70	21.97
		25	25	21.64	21.86	21.70
		50	0	22.03	21.78	21.95
	256QAM	1	0	20.69	20.41	21.03
		1	24	20.58	20.75	20.70
		1	49	20.42	20.49	20.70
		25	0	19.52	19.79	19.62
		25	12	19.57	19.80	19.82
		25	25	19.64	19.88	19.66
		50	0	20.09	19.64	20.04

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		131997	132322	132647
		Frequency (MHz)		1712.5	1745	1777.5
5M	QPSK	1	0	24.63	24.70	24.82
		1	12	24.49	24.69	24.69
		1	24	24.89	24.83	24.61
		12	0	23.86	23.67	23.73
		12	6	23.62	23.61	23.65
		12	13	23.84	23.73	23.82
		25	0	23.76	23.64	23.85
	16QAM	1	0	23.92	23.73	24.15
		1	12	23.60	24.06	23.89
		1	24	24.25	24.20	23.62
		12	0	22.87	22.97	23.16
		12	6	22.78	22.98	22.66
		12	13	23.25	22.82	23.21
		25	0	22.80	22.79	23.00
	64QAM	1	0	22.63	22.69	22.87
		1	12	22.37	22.91	22.78
		1	24	23.04	23.17	22.32
		12	0	21.65	21.86	22.13
		12	6	21.70	21.83	21.44
		12	13	22.06	21.58	22.16
		25	0	21.76	21.55	21.94
	256QAM	1	0	20.57	20.63	20.77
		1	12	20.35	20.95	20.76
		1	24	21.11	21.20	20.39
		12	0	19.61	19.96	20.15
		12	6	19.58	19.89	19.40
		12	13	19.92	19.68	20.04
		25	0	19.58	19.59	19.94

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		131987	132322	132657
		Frequency (MHz)		1711.5	1745	1778.5
3M	QPSK	1	0	24.84	24.65	24.58
		1	7	24.59	24.58	24.59
		1	14	24.74	24.71	24.63
		8	0	23.59	23.69	23.88
		8	3	23.81	23.64	23.64
		8	7	23.74	23.71	23.67
		15	0	23.63	23.66	23.57
	16QAM	1	0	23.88	23.98	23.83
		1	7	23.77	23.81	23.69
		1	14	24.11	23.86	23.68
		8	0	22.95	22.88	23.36
		8	3	23.22	22.68	23.10
		8	7	22.97	23.13	22.72
		15	0	22.79	22.84	22.76
	64QAM	1	0	22.77	22.94	22.62
		1	7	22.77	22.72	22.43
		1	14	22.92	22.65	22.44
		8	0	21.80	21.82	22.08
		8	3	22.20	21.49	21.90
		8	7	21.69	22.04	21.59
		15	0	21.58	21.66	21.54
	256QAM	1	0	20.85	21.04	20.56
		1	7	20.78	20.80	20.46
		1	14	20.86	20.58	20.50
		8	0	19.78	19.89	20.18
		8	3	20.09	19.37	19.73
		8	7	19.72	20.05	19.51
		15	0	19.41	19.61	19.63

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		131979	132322	132665
		Frequency (MHz)		1710.7	1745	1779.3
1.4M	QPSK	1	0	24.44	24.56	24.60
		1	2	24.37	24.53	24.47
		1	5	24.28	24.44	24.51
		3	0	24.42	24.32	24.31
		3	1	24.35	24.46	24.62
		3	3	24.18	24.43	24.22
		6	0	23.29	23.58	23.44
	16QAM	1	0	23.88	23.94	23.89
		1	2	23.54	23.80	23.93
		1	5	23.71	23.83	23.84
		3	0	23.84	23.67	23.58
		3	1	23.47	23.58	23.95
		3	3	23.61	23.54	23.22
		6	0	22.53	22.64	22.86
	64QAM	1	0	22.82	22.94	22.73
		1	2	22.41	22.72	22.74
		1	5	22.58	22.66	22.84
		3	0	22.59	22.50	22.48
		3	1	22.33	22.44	22.87
		3	3	22.33	22.53	22.01
		6	0	21.38	21.44	21.81
	256QAM	1	0	20.92	21.04	20.75
		1	2	20.45	20.70	20.72
		1	5	20.64	20.46	20.74
		3	0	20.41	20.38	20.56
		3	1	20.30	20.46	20.86
		3	3	20.23	20.35	20.09
		6	0	19.37	19.40	19.88

EIRP / ERP Power (dBm)

5GNR n77 (Part 270):

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		650000	656000	662000
		Frequency (MHz)		3750	3840	3930
100M	$\pi/2$ BPSK	1	0	29.57	29.40	29.39
		1	137	29.41	29.49	29.45
		1	271	29.52	29.47	29.48
		135	0	29.05	29.03	28.91
		135	69	28.94	29.03	29.12
		135	138	29.06	29.07	28.96
		270	0	28.92	29.08	29.03
	QPSK	1	0	29.10	29.29	29.26
		1	137	29.30	29.21	29.23
		1	271	29.11	29.36	29.40
		135	0	28.80	28.64	28.85
		135	69	28.65	28.76	28.88
		135	138	28.62	28.81	28.61
		270	0	28.70	28.81	28.72
	16QAM	1	0	28.31	28.39	28.30
		1	137	28.14	28.31	28.22
		1	271	28.18	28.10	28.22
		135	0	27.73	27.63	27.73
		135	69	27.81	27.87	27.84
		135	138	27.80	27.70	27.68
		270	0	27.75	27.77	27.88
	64QAM	1	0	27.29	27.22	27.13
		1	137	27.29	27.10	27.34
		1	271	27.21	27.11	27.15
		135	0	26.77	26.84	26.68
		135	69	26.75	26.88	26.69
		135	138	26.89	26.65	26.63
		270	0	26.74	26.68	26.76
	256QAM	1	0	25.64	25.50	25.59
		1	137	25.59	25.65	25.58
		1	271	25.63	25.80	25.58
		135	0	25.03	25.27	25.21
		135	69	25.08	25.09	25.21
		135	138	25.05	25.16	25.13
		270	0	25.20	25.01	25.25

*EIRP = Conducted + antenna gain (2.9dBi)

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		649558	656000	662332
		Frequency (MHz)		3745.02	3840	3934.98
90M	$\pi/2$ BPSK	1	0	29.47	29.42	29.42
		1	123	29.36	29.48	29.39
		1	243	29.42	29.53	29.34
		120	0	29.09	29.20	29.17
		120	63	29.09	29.08	29.03
		120	125	29.16	28.96	29.17
		240	0	29.13	29.08	29.10
	QPSK	1	0	29.32	29.15	29.35
		1	123	29.18	29.14	29.35
		1	243	29.40	29.16	29.36
		120	0	28.88	28.74	28.72
		120	63	28.65	28.67	28.86
		120	125	28.73	28.79	28.75
		240	0	28.79	28.73	28.89
	16QAM	1	0	28.36	28.40	28.14
		1	123	28.30	28.26	28.15
		1	243	28.16	28.14	28.36
		120	0	27.81	27.60	27.77
		120	63	27.85	27.61	27.82
		120	125	27.85	27.72	27.69
		240	0	27.82	27.83	27.68
	64QAM	1	0	27.31	27.40	27.22
		1	123	27.16	27.12	27.18
		1	243	27.39	27.40	27.29
		120	0	26.63	26.65	26.82
		120	63	26.71	26.70	26.90
		120	125	26.62	26.71	26.60
		240	0	26.81	26.84	26.61
	256QAM	1	0	25.80	25.66	25.51
		1	123	25.58	25.78	25.80
		1	243	25.70	25.53	25.53
		120	0	25.16	25.02	25.27
		120	63	25.06	25.28	25.27
		120	125	25.23	25.13	25.01
		240	0	25.11	25.01	25.26

*EIRP = Conducted + antenna gain (2.9dBi)

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		649334	656000	662666
		Frequency (MHz)		3740.01	3840	3939.99
80M	$\pi/2$ BPSK	1	0	29.58	29.46	29.34
		1	109	29.58	29.41	29.57
		1	215	29.43	29.51	29.44
		108	0	29.12	29.14	29.05
		108	55	29.18	28.98	29.14
		108	109	29.19	28.92	29.14
		216	0	28.95	29.04	28.91
	QPSK	1	0	29.36	29.16	29.34
		1	109	29.15	29.31	29.17
		1	215	29.34	29.12	29.22
		108	0	28.61	28.68	28.79
		108	55	28.68	28.61	28.66
		108	109	28.76	28.61	28.68
		216	0	28.64	28.62	28.88
	16QAM	1	0	28.12	28.25	28.22
		1	109	28.30	28.31	28.39
		1	215	28.15	28.31	28.35
		108	0	27.64	27.60	27.80
		108	55	27.64	27.85	27.68
		108	109	27.89	27.82	27.89
		216	0	27.68	27.65	27.63
	64QAM	1	0	27.16	27.14	27.22
		1	109	27.35	27.35	27.36
		1	215	27.28	27.27	27.10
		108	0	26.77	26.62	26.69
		108	55	26.67	26.82	26.60
		108	109	26.73	26.81	26.78
		216	0	26.67	26.68	26.69
	256QAM	1	0	25.79	25.68	25.75
		1	109	25.80	25.55	25.73
		1	215	25.63	25.75	25.65
		108	0	25.18	25.18	25.19
		108	55	25.24	25.19	25.23
		108	109	25.23	25.01	25.08
		216	0	25.19	25.12	25.08

*EIRP = Conducted + antenna gain (2.9dBi)

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		648668	656000	663332
		Frequency (MHz)		3730.02	3840	3949.98
60M	$\pi/2$ BPSK	1	0	29.40	29.42	29.54
		1	81	29.44	29.43	29.35
		1	160	29.44	29.31	29.34
		81	0	29.03	29.13	29.16
		81	41	29.15	29.04	28.94
		81	81	28.95	29.16	29.00
		162	0	28.93	29.03	29.16
	QPSK	1	0	29.14	29.27	29.37
		1	81	29.32	29.17	29.20
		1	160	29.40	29.24	29.26
		81	0	28.79	28.69	28.82
		81	41	28.62	28.80	28.88
		81	81	28.60	28.80	28.63
		162	0	28.84	28.72	28.66
	16QAM	1	0	28.27	28.23	28.10
		1	81	28.39	28.14	28.36
		1	160	28.30	28.40	28.16
		81	0	27.88	27.79	27.88
		81	41	27.75	27.67	27.83
		81	81	27.84	27.87	27.76
		162	0	27.80	27.79	27.62
	64QAM	1	0	27.34	27.14	27.13
		1	81	27.13	27.30	27.20
		1	160	27.30	27.28	27.37
		81	0	26.72	26.88	26.75
		81	41	26.69	26.73	26.85
		81	81	26.79	26.87	26.85
		162	0	26.71	26.85	26.81
	256QAM	1	0	25.54	25.50	25.69
		1	81	25.62	25.52	25.53
		1	160	25.62	25.52	25.60
		81	0	25.07	25.21	25.29
		81	41	25.06	25.06	25.16
		81	81	25.29	25.16	25.24
		162	0	25.03	25.20	25.12

*EIRP = Conducted + antenna gain (2.9dBi)

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		648334	656000	663666
		Frequency (MHz)		3725.01	3840	3954.99
50M	$\pi/2$ BPSK	1	0	29.58	29.51	29.58
		1	67	29.59	29.56	29.38
		1	131	29.40	29.30	29.37
		64	0	29.04	28.94	29.14
		64	35	29.08	29.01	29.01
		64	69	29.15	29.18	29.10
		128	0	28.98	29.00	28.96
	QPSK	1	0	29.11	29.13	29.25
		1	67	29.26	29.16	29.31
		1	131	29.35	29.25	29.33
		64	0	28.63	28.71	28.71
		64	35	28.71	28.79	28.64
		64	69	28.83	28.87	28.78
		128	0	28.86	28.85	28.82
	16QAM	1	0	28.15	28.19	28.14
		1	67	28.14	28.28	28.10
		1	131	28.32	28.15	28.40
		64	0	27.82	27.72	27.73
		64	35	27.63	27.77	27.81
		64	69	27.60	27.62	27.62
		128	0	27.77	27.69	27.88
	64QAM	1	0	27.29	27.10	27.31
		1	67	27.18	27.12	27.32
		1	131	27.40	27.28	27.15
		64	0	26.79	26.77	26.71
		64	35	26.76	26.83	26.62
		64	69	26.85	26.74	26.63
		128	0	26.64	26.72	26.86
	256QAM	1	0	25.66	25.75	25.79
		1	67	25.66	25.59	25.80
		1	131	25.60	25.71	25.66
		64	0	25.10	25.04	25.25
		64	35	25.17	25.06	25.07
		64	69	25.23	25.02	25.25
		128	0	25.06	25.12	25.16

*EIRP = Conducted + antenna gain (2.9dBi)

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		648000	656000	664000
		Frequency (MHz)		3720	3840	3960
40M	$\pi/2$ BPSK	1	0	29.42	29.45	29.59
		1	53	29.57	29.53	29.47
		1	104	29.59	29.48	29.60
		50	0	29.10	28.90	29.18
		50	28	29.04	28.90	29.18
		50	56	29.20	28.91	28.99
		100	0	29.07	28.95	28.99
	QPSK	1	0	29.30	29.29	29.34
		1	53	29.25	29.19	29.23
		1	104	29.25	29.39	29.40
		50	0	28.89	28.77	28.61
		50	28	28.63	28.80	28.74
		50	56	28.80	28.60	28.69
		100	0	28.90	28.73	28.73
	16QAM	1	0	28.26	28.31	28.23
		1	53	28.18	28.35	28.22
		1	104	28.26	28.18	28.20
		50	0	27.80	27.67	27.88
		50	28	27.87	27.86	27.75
		50	56	27.63	27.80	27.88
		100	0	27.86	27.90	27.66
	64QAM	1	0	27.27	27.35	27.39
		1	53	27.12	27.28	27.13
		1	104	27.19	27.11	27.12
		50	0	26.86	26.66	26.72
		50	28	26.76	26.72	26.71
		50	56	26.62	26.74	26.88
		100	0	26.80	26.67	26.87
	256QAM	1	0	25.63	25.57	25.58
		1	53	25.55	25.60	25.74
		1	104	25.61	25.64	25.73
		50	0	25.11	25.18	25.13
		50	28	25.25	25.12	25.25
		50	56	25.17	25.12	25.11
		100	0	25.26	25.29	25.19

*EIRP = Conducted + antenna gain (2.9dBi)

5GNR n77						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		647334	656000	665666
		Frequency (MHz)		3710.01	3840	3969.99
20M	$\pi/2$ BPSK	1	0	29.56	29.42	29.40
		1	26	29.47	29.38	29.42
		1	49	29.44	29.42	29.60
		25	0	29.00	29.15	29.19
		25	13	28.93	29.05	28.90
		25	26	28.92	29.20	29.04
		50	0	28.99	29.12	28.91
	QPSK	1	0	29.17	29.18	29.40
		1	26	29.33	29.17	29.20
		1	49	29.17	29.36	29.24
		25	0	28.82	28.64	28.69
		25	13	28.68	28.87	28.81
		25	26	28.64	28.74	28.73
		50	0	28.67	28.64	28.66
	16QAM	1	0	28.39	28.16	28.13
		1	26	28.28	28.35	28.22
		1	49	28.26	28.39	28.31
		25	0	27.90	27.63	27.64
		25	13	27.60	27.68	27.69
		25	26	27.66	27.88	27.64
		50	0	27.90	27.75	27.80
	64QAM	1	0	27.26	27.29	27.31
		1	26	27.32	27.15	27.20
		1	49	27.15	27.17	27.13
		25	0	26.90	26.67	26.86
		25	13	26.64	26.60	26.88
		25	26	26.89	26.67	26.70
		50	0	26.87	26.68	26.76
	256QAM	1	0	25.65	25.67	25.53
		1	26	25.62	25.57	25.75
		1	49	25.60	25.64	25.66
		25	0	25.25	25.15	25.15
		25	13	25.23	25.24	25.01
		25	26	25.28	25.10	25.23
		50	0	25.07	25.07	25.20

*EIRP = Conducted + antenna gain (2.9dBi)

5GNR n77 (Part 27Q):

Modulation Type: $\pi/2$ BPSK

5GNR n77 (Part 27Q), Channel Bandwidth 100MHz

Mode		TX channel 633334						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3500.01	29.44	30.00	-0.56	1.77 H	5	89.79	-60.35
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3500.01	24.29	30.00	-5.71	1.53 V	190	84.64	-60.35

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 90MHz

Mode		TX channel 633000, 633334, 633666						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3495.00	29.44	30.00	-0.56	1.72 H	9	89.82	-60.38
2	3500.01	29.46	30.00	-0.54	1.81 H	4	89.81	-60.35
3	3504.99	29.38	30.00	-0.62	1.81 H	6	89.71	-60.33
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3495.00	24.15	30.00	-5.85	1.58 V	188	84.53	-60.38
2	3500.01	24.15	30.00	-5.85	1.50 V	188	84.50	-60.35
3	3504.99	24.45	30.00	-5.55	1.49 V	193	84.78	-60.33

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 80MHz

Mode		TX channel 632668, 633334, 634000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.02	29.41	30.00	-0.59	1.78 H	5	89.80	-60.39
2	3500.01	29.46	30.00	-0.54	1.78 H	6	89.81	-60.35
3	3510.00	29.28	30.00	-0.72	1.81 H	4	89.58	-60.30
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.02	24.25	30.00	-5.75	1.51 V	188	84.64	-60.39
2	3500.01	24.26	30.00	-5.74	1.53 V	191	84.61	-60.35
3	3510.00	24.35	30.00	-5.65	1.57 V	189	84.65	-60.30

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 60MHz

Mode		TX channel 632000, 633334, 634666						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3480.00	29.28	30.00	-0.72	1.80 H	2	89.72	-60.44
2	3500.01	29.45	30.00	-0.55	1.73 H	9	89.80	-60.35
3	3519.99	29.38	30.00	-0.62	1.79 H	5	89.64	-60.26
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3480.00	24.15	30.00	-5.85	1.57 V	188	84.59	-60.44
2	3500.01	24.08	30.00	-5.92	1.58 V	190	84.43	-60.35
3	3519.99	24.15	30.00	-5.85	1.50 V	191	84.41	-60.26

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 50MHz

Mode		TX channel 631668, 633334, 635000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3475.02	29.18	30.00	-0.82	1.79 H	7	89.65	-60.47
2	3500.01	29.35	30.00	-0.65	1.74 H	9	89.70	-60.35
3	3525.00	29.28	30.00	-0.72	1.73 H	3	89.52	-60.24
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3475.02	24.45	30.00	-5.55	1.54 V	194	84.92	-60.47
2	3500.01	24.15	30.00	-5.85	1.49 V	193	84.50	-60.35
3	3525.00	24.36	30.00	-5.64	1.50 V	195	84.60	-60.24

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 40MHz

Mode		TX channel 631334, 633334, 635332						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3470.01	29.38	30.00	-0.62	1.75 H	7	89.86	-60.48
2	3500.01	29.45	30.00	-0.55	1.80 H	8	89.80	-60.35
3	3529.98	29.41	30.00	-0.59	1.79 H	7	89.63	-60.22
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3470.01	24.35	30.00	-5.65	1.49 V	191	84.83	-60.48
2	3500.01	24.05	30.00	-5.95	1.48 V	190	84.40	-60.35
3	3529.98	24.37	30.00	-5.63	1.51 V	191	84.59	-60.22

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 20MHz

Mode		TX channel 630668, 633334, 636000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.02	29.18	30.00	-0.82	1.75 H	2	89.71	-60.53
2	3500.01	29.58	30.00	-0.42	1.76 H	4	89.93	-60.35
3	3540.00	29.28	30.00	-0.72	1.79 H	7	89.45	-60.17
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.02	24.35	30.00	-5.65	1.51 V	192	84.88	-60.53
2	3500.01	24.25	30.00	-5.75	1.53 V	194	84.60	-60.35
3	3540.00	24.26	30.00	-5.74	1.49 V	188	84.43	-60.17

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

Modulation Type: QPSK

5GNR n77 (Part 27Q), Channel Bandwidth 100MHz

Mode		TX channel 633334						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3500.01	28.43	30.00	-1.57	1.81 H	6	88.78	-60.35
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3500.01	23.34	30.00	-6.66	1.53 V	187	83.69	-60.35

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 90MHz

Mode		TX channel 633000, 633334, 633666						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3495.00	28.45	30.00	-1.55	1.81 H	7	88.83	-60.38
2	3500.01	28.45	30.00	-1.55	1.78 H	7	88.80	-60.35
3	3504.99	28.35	30.00	-1.65	1.81 H	5	88.68	-60.33
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3495.00	23.14	30.00	-6.86	1.57 V	195	83.52	-60.38
2	3500.01	23.44	30.00	-6.56	1.50 V	190	83.79	-60.35
3	3504.99	23.34	30.00	-6.66	1.58 V	192	83.67	-60.33

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 80MHz

Mode		TX channel 632668, 633334, 634000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.02	28.35	30.00	-1.65	1.78 H	7	88.74	-60.39
2	3500.01	28.15	30.00	-1.85	1.73 H	6	88.50	-60.35
3	3510.00	28.18	30.00	-1.82	1.73 H	3	88.48	-60.30
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.02	23.04	30.00	-6.96	1.57 V	188	83.43	-60.39
2	3500.01	23.24	30.00	-6.76	1.52 V	192	83.59	-60.35
3	3510.00	23.14	30.00	-6.86	1.48 V	189	83.44	-60.30

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 60MHz

Mode		TX channel 632000, 633334, 634666						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3480.00	28.45	30.00	-1.55	1.82 H	5	88.89	-60.44
2	3500.01	28.48	30.00	-1.52	1.77 H	5	88.83	-60.35
3	3519.99	28.15	30.00	-1.85	1.72 H	6	88.41	-60.26
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3480.00	23.14	30.00	-6.86	1.56 V	191	83.58	-60.44
2	3500.01	23.24	30.00	-6.76	1.57 V	188	83.59	-60.35
3	3519.99	23.14	30.00	-6.86	1.54 V	193	83.40	-60.26

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 50MHz

Mode		TX channel 631668, 633334, 635000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3475.02	28.15	30.00	-1.85	1.72 H	4	88.62	-60.47
2	3500.01	28.07	30.00	-1.93	1.73 H	4	88.42	-60.35
3	3525.00	28.15	30.00	-1.85	1.75 H	4	88.39	-60.24
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3475.02	23.44	30.00	-6.56	1.51 V	190	83.91	-60.47
2	3500.01	23.15	30.00	-6.85	1.54 V	188	83.50	-60.35
3	3525.00	23.24	30.00	-6.76	1.53 V	191	83.48	-60.24

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 40MHz

Mode		TX channel 631334, 633334, 635332						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3470.01	28.05	30.00	-1.95	1.76 H	9	88.53	-60.48
2	3500.01	28.06	30.00	-1.94	1.79 H	2	88.41	-60.35
3	3529.98	28.03	30.00	-1.97	1.74 H	3	88.25	-60.22
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3470.01	23.24	30.00	-6.76	1.50 V	195	83.72	-60.48
2	3500.01	23.14	30.00	-6.86	1.52 V	188	83.49	-60.35
3	3529.98	23.04	30.00	-6.96	1.48 V	193	83.26	-60.22

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 20MHz

Mode		TX channel 630668, 633334, 636000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.02	28.45	30.00	-1.55	1.73 H	6	88.98	-60.53
2	3500.01	28.22	30.00	-1.78	1.79 H	8	88.57	-60.35
3	3540.00	28.35	30.00	-1.65	1.75 H	4	88.52	-60.17
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.02	23.04	30.00	-6.96	1.53 V	193	83.57	-60.53
2	3500.01	23.44	30.00	-6.56	1.49 V	190	83.79	-60.35
3	3540.00	23.04	30.00	-6.96	1.56 V	192	83.21	-60.17

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

Modulation Type: 16QAM

5GNR n77 (Part 27Q), Channel Bandwidth 100MHz

Mode		TX channel 633334						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3500.01	27.21	30.00	-2.79	1.78 H	7	87.56	-60.35
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3500.01	22.21	30.00	-7.79	1.53 V	187	82.56	-60.35

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 90MHz

Mode		TX channel 633000, 633334, 633666						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3495.00	27.15	30.00	-2.85	1.73 H	2	87.53	-60.38
2	3500.01	27.15	30.00	-2.85	1.75 H	8	87.50	-60.35
3	3504.99	27.15	30.00	-2.85	1.77 H	2	87.48	-60.33
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3495.00	22.24	30.00	-7.76	1.57 V	194	82.62	-60.38
2	3500.01	22.34	30.00	-7.66	1.57 V	193	82.69	-60.35
3	3504.99	22.44	30.00	-7.56	1.53 V	191	82.77	-60.33

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 80MHz

Mode		TX channel 632668, 633334, 634000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.02	27.05	30.00	-2.95	1.81 H	3	87.44	-60.39
2	3500.01	27.55	30.00	-2.45	1.76 H	6	87.90	-60.35
3	3510.00	27.06	30.00	-2.94	1.72 H	2	87.36	-60.30
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.02	22.24	30.00	-7.76	1.52 V	194	82.63	-60.39
2	3500.01	22.54	30.00	-7.46	1.51 V	191	82.89	-60.35
3	3510.00	22.14	30.00	-7.86	1.52 V	193	82.44	-60.30

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 60MHz

Mode		TX channel 632000, 633334, 634666						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3480.00	27.45	30.00	-2.55	1.77 H	4	87.89	-60.44
2	3500.01	27.35	30.00	-2.65	1.75 H	2	87.70	-60.35
3	3519.99	27.25	30.00	-2.75	1.72 H	9	87.51	-60.26
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3480.00	22.04	30.00	-7.96	1.52 V	188	82.48	-60.44
2	3500.01	22.34	30.00	-7.66	1.50 V	190	82.69	-60.35
3	3519.99	22.04	30.00	-7.96	1.56 V	188	82.30	-60.26

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 50MHz

Mode		TX channel 631668, 633334, 635000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3475.02	27.45	30.00	-2.55	1.73 H	9	87.92	-60.47
2	3500.01	27.25	30.00	-2.75	1.75 H	9	87.60	-60.35
3	3525.00	27.55	30.00	-2.45	1.73 H	4	87.79	-60.24
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3475.02	21.94	30.00	-8.06	1.58 V	190	82.41	-60.47
2	3500.01	22.54	30.00	-7.46	1.52 V	194	82.89	-60.35
3	3525.00	22.24	30.00	-7.76	1.51 V	194	82.48	-60.24

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 40MHz

Mode		TX channel 631334, 633334, 635332						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3470.01	27.15	30.00	-2.85	1.81 H	2	87.63	-60.48
2	3500.01	27.45	30.00	-2.55	1.80 H	6	87.80	-60.35
3	3529.98	27.35	30.00	-2.65	1.80 H	7	87.57	-60.22
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3470.01	21.94	30.00	-8.06	1.51 V	190	82.42	-60.48
2	3500.01	22.24	30.00	-7.76	1.57 V	188	82.59	-60.35
3	3529.98	22.54	30.00	-7.46	1.57 V	188	82.76	-60.22

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 20MHz

Mode		TX channel 630668, 633334, 636000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.02	27.35	30.00	-2.65	1.80 H	7	87.88	-60.53
2	3500.01	27.06	30.00	-2.94	1.81 H	7	87.41	-60.35
3	3540.00	27.25	30.00	-2.75	1.73 H	4	87.42	-60.17
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.02	22.44	30.00	-7.56	1.54 V	195	82.97	-60.53
2	3500.01	22.54	30.00	-7.46	1.57 V	195	82.89	-60.35
3	3540.00	22.05	30.00	-7.95	1.48 V	188	82.22	-60.17

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

Modulation Type: 64QAM

5GNR n77 (Part 27Q), Channel Bandwidth 100MHz

Mode		TX channel 633334						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3500.01	26.66	30.00	-3.34	1.82 H	5	87.01	-60.35
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3500.01	21.56	30.00	-8.44	1.52 V	189	81.91	-60.35

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 90MHz

Mode		TX channel 633000, 633334, 633666						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3495.00	26.65	30.00	-3.35	1.72 H	4	87.03	-60.38
2	3500.01	26.55	30.00	-3.45	1.74 H	7	86.90	-60.35
3	3504.99	26.55	30.00	-3.45	1.78 H	2	86.88	-60.33
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3495.00	21.64	30.00	-8.36	1.53 V	191	82.02	-60.38
2	3500.01	21.94	30.00	-8.06	1.55 V	193	82.29	-60.35
3	3504.99	22.01	30.00	-7.99	1.56 V	194	82.34	-60.33

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 80MHz

Mode		TX channel 632668, 633334, 634000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.02	26.65	30.00	-3.35	1.82 H	4	87.04	-60.39
2	3500.01	27.05	30.00	-2.95	1.77 H	3	87.40	-60.35
3	3510.00	26.45	30.00	-3.55	1.79 H	5	86.75	-60.30
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.02	21.64	30.00	-8.36	1.51 V	190	82.03	-60.39
2	3500.01	21.94	30.00	-8.06	1.58 V	193	82.29	-60.35
3	3510.00	21.74	30.00	-8.26	1.55 V	193	82.04	-60.30

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 60MHz

Mode		TX channel 632000, 633334, 634666						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3480.00	26.85	30.00	-3.15	1.81 H	5	87.29	-60.44
2	3500.01	26.85	30.00	-3.15	1.76 H	3	87.20	-60.35
3	3519.99	26.65	30.00	-3.35	1.81 H	5	86.91	-60.26
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3480.00	21.44	30.00	-8.56	1.51 V	190	81.88	-60.44
2	3500.01	21.94	30.00	-8.06	1.50 V	195	82.29	-60.35
3	3519.99	21.44	30.00	-8.56	1.55 V	192	81.70	-60.26

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 50MHz

Mode		TX channel 631668, 633334, 635000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3475.02	26.95	30.00	-3.05	1.73 H	7	87.42	-60.47
2	3500.01	26.75	30.00	-3.25	1.82 H	6	87.10	-60.35
3	3525.00	27.05	30.00	-2.95	1.80 H	3	87.29	-60.24
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3475.02	21.54	30.00	-8.46	1.54 V	195	82.01	-60.47
2	3500.01	22.14	30.00	-7.86	1.55 V	194	82.49	-60.35
3	3525.00	21.74	30.00	-8.26	1.54 V	188	81.98	-60.24

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 40MHz

Mode		TX channel 631334, 633334, 635332						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3470.01	26.75	30.00	-3.25	1.78 H	3	87.23	-60.48
2	3500.01	26.95	30.00	-3.05	1.78 H	7	87.30	-60.35
3	3529.98	26.85	30.00	-3.15	1.77 H	7	87.07	-60.22
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3470.01	22.14	30.00	-7.86	1.48 V	190	82.62	-60.48
2	3500.01	21.45	30.00	-8.55	1.53 V	189	81.80	-60.35
3	3529.98	21.94	30.00	-8.06	1.48 V	188	82.16	-60.22

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 20MHz

Mode		TX channel 630668, 633334, 636000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.02	26.95	30.00	-3.05	1.74 H	9	87.48	-60.53
2	3500.01	26.55	30.00	-3.45	1.78 H	7	86.90	-60.35
3	3540.00	26.85	30.00	-3.15	1.82 H	8	87.02	-60.17
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.02	22.04	30.00	-7.96	1.58 V	191	82.57	-60.53
2	3500.01	22.05	30.00	-7.95	1.57 V	188	82.40	-60.35
3	3540.00	21.39	30.00	-8.61	1.58 V	190	81.56	-60.17

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

Modulation Type: 256QAM

5GNR n77 (Part 27Q), Channel Bandwidth 100MHz

Mode		TX channel 633334						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3500.01	25.03	30.00	-4.97	1.81 H	9	85.38	-60.35
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3500.01	20.08	30.00	-9.92	1.57 V	186	80.43	-60.35

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 90MHz

Mode		TX channel 633000, 633334, 633666						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3495.00	25.25	30.00	-4.75	1.81 H	3	85.63	-60.38
2	3500.01	25.05	30.00	-4.95	1.75 H	9	85.40	-60.35
3	3504.99	25.04	30.00	-4.96	1.82 H	2	85.37	-60.33
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3495.00	20.03	30.00	-9.97	1.50 V	188	80.41	-60.38
2	3500.01	20.54	30.00	-9.46	1.53 V	190	80.89	-60.35
3	3504.99	20.54	30.00	-9.46	1.53 V	189	80.87	-60.33

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 80MHz

Mode		TX channel 632668, 633334, 634000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.02	25.15	30.00	-4.85	1.73 H	3	85.54	-60.39
2	3500.01	25.65	30.00	-4.35	1.79 H	4	86.00	-60.35
3	3510.00	24.95	30.00	-5.05	1.78 H	5	85.25	-60.30
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3490.02	20.04	30.00	-9.96	1.49 V	193	80.43	-60.39
2	3500.01	20.54	30.00	-9.46	1.55 V	191	80.89	-60.35
3	3510.00	20.14	30.00	-9.86	1.58 V	192	80.44	-60.30

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 60MHz

Mode		TX channel 632000, 633334, 634666						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3480.00	25.35	30.00	-4.65	1.80 H	9	85.79	-60.44
2	3500.01	25.45	30.00	-4.55	1.73 H	7	85.80	-60.35
3	3519.99	25.15	30.00	-4.85	1.72 H	2	85.41	-60.26
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3480.00	20.04	30.00	-9.96	1.50 V	189	80.48	-60.44
2	3500.01	20.34	30.00	-9.66	1.53 V	191	80.69	-60.35
3	3519.99	20.05	30.00	-9.95	1.49 V	192	80.31	-60.26

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 50MHz

Mode		TX channel 631668, 633334, 635000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3475.02	25.45	30.00	-4.55	1.77 H	2	85.92	-60.47
2	3500.01	25.15	30.00	-4.85	1.75 H	4	85.50	-60.35
3	3525.00	25.55	30.00	-4.45	1.73 H	8	85.79	-60.24
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3475.02	20.14	30.00	-9.86	1.57 V	191	80.61	-60.47
2	3500.01	20.64	30.00	-9.36	1.48 V	193	80.99	-60.35
3	3525.00	20.24	30.00	-9.76	1.73 V	8	80.48	-60.24

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 40MHz

Mode		TX channel 631334, 633334, 635332						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3470.01	25.25	30.00	-4.75	1.77 H	3	85.73	-60.48
2	3500.01	25.35	30.00	-4.65	1.82 H	8	85.70	-60.35
3	3529.98	25.45	30.00	-4.55	1.82 H	4	85.67	-60.22
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3470.01	20.64	30.00	-9.36	1.51 V	195	81.12	-60.48
2	3500.01	20.01	30.00	-9.99	1.57 V	193	80.36	-60.35
3	3529.98	20.34	30.00	-9.66	1.51 V	190	80.56	-60.22

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

5GNR n77 (Part 27Q), Channel Bandwidth 20MHz

Mode		TX channel 630668, 633334, 636000						
Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.02	25.55	30.00	-4.45	1.79 H	5	86.08	-60.53
2	3500.01	25.05	30.00	-4.95	1.80 H	7	85.40	-60.35
3	3540.00	25.45	30.00	-4.55	1.76 H	3	85.62	-60.17
Antenna Polarity & Test Distance: Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3460.02	20.44	30.00	-9.56	1.58 V	191	80.97	-60.53
2	3500.01	20.64	30.00	-9.36	1.56 V	190	80.99	-60.35
3	3540.00	20.45	30.00	-9.55	1.58 V	195	80.62	-60.17

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18700	18900	19100
		Frequency (MHz)		1860	1880	1900
20M	QPSK	1	0	29.13	29.00	28.95
		1	50	29.00	28.97	28.68
		1	99	28.72	28.99	28.84
		50	0	28.04	28.04	27.90
		50	25	28.10	28.03	27.90
		50	50	28.02	28.06	27.89
		100	0	28.08	27.94	27.95
	16QAM	1	0	28.10	28.55	28.40
		1	50	28.19	28.56	28.02
		1	99	28.10	28.56	27.87
		50	0	26.91	27.07	26.89
		50	25	27.05	26.96	26.91
		50	50	27.08	27.14	26.85
		100	0	27.09	27.07	26.90
	64QAM	1	0	26.93	27.47	27.18
		1	50	26.98	27.46	26.89
		1	99	26.97	27.63	26.89
		50	0	25.70	26.01	25.83
		50	25	25.76	25.75	25.64
		50	50	25.82	26.32	25.77
		100	0	26.28	26.25	25.92
	256QAM	1	0	25.11	25.65	24.91
		1	50	24.87	25.69	24.71
		1	99	24.69	25.78	25.10
		50	0	23.82	23.94	23.71
		50	25	23.86	24.00	23.70
		50	50	23.56	24.23	23.69
		100	0	24.13	24.50	23.85

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18675	18900	19125
		Frequency (MHz)		1857.5	1880	1902.5
15M	QPSK	1	0	28.97	28.88	28.77
		1	37	28.85	29.05	28.79
		1	74	28.86	28.93	28.79
		36	0	28.06	27.99	27.86
		36	19	28.12	28.06	27.88
		36	39	28.10	28.04	27.91
		75	0	28.17	27.95	27.96
	16QAM	1	0	28.51	28.58	27.94
		1	37	28.16	28.51	28.29
		1	74	28.34	28.21	28.32
		36	0	27.03	27.09	26.85
		36	19	27.12	26.99	26.92
		36	39	27.09	27.04	26.90
		75	0	27.16	26.99	26.95
	64QAM	1	0	27.52	27.54	26.79
		1	37	27.16	27.30	27.10
		1	74	27.07	26.97	27.10
		36	0	25.93	26.19	26.00
		36	19	26.20	26.15	26.10
		36	39	26.00	26.17	26.04
		75	0	26.30	26.16	26.10
	256QAM	1	0	25.57	25.38	24.63
		1	37	25.18	25.14	24.97
		1	74	24.95	25.19	24.94
		36	0	24.15	24.18	23.83
		36	19	24.14	24.28	23.94
		36	39	24.30	24.24	24.24
		75	0	24.45	24.12	24.38

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18650	18900	19150
		Frequency (MHz)		1855	1880	1905
10M	QPSK	1	0	29.03	29.12	28.70
		1	24	28.87	28.77	28.77
		1	49	28.96	28.86	28.75
		25	0	28.05	28.00	27.90
		25	12	28.11	28.04	27.86
		25	25	28.10	28.08	27.88
		50	0	28.09	28.06	27.94
	16QAM	1	0	28.52	28.42	28.06
		1	24	28.03	28.27	28.35
		1	49	28.62	28.23	28.35
		25	0	27.06	26.95	26.84
		25	12	27.05	27.07	26.83
		25	25	27.05	26.96	26.94
		50	0	27.07	26.99	26.92
	64QAM	1	0	27.70	27.18	27.19
		1	24	27.03	27.00	27.53
		1	49	27.56	27.10	27.31
		25	0	26.02	26.07	25.88
		25	12	25.96	25.88	25.71
		25	25	25.77	25.68	25.68
		50	0	25.81	25.94	25.71
	256QAM	1	0	25.69	24.93	25.45
		1	24	24.77	25.14	25.52
		1	49	25.73	25.29	25.06
		25	0	24.24	24.24	23.88
		25	12	23.84	24.02	23.76
		25	25	23.79	23.79	23.97
		50	0	24.04	24.14	23.60

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18625	18900	19175
		Frequency (MHz)		1852.5	1880	1907.5
5M	QPSK	1	0	28.90	28.80	28.67
		1	12	29.10	28.96	28.87
		1	24	28.89	28.91	28.69
		12	0	28.02	27.97	27.76
		12	6	28.05	27.99	27.83
		12	13	28.04	28.02	27.89
		25	0	28.08	28.01	27.81
	16QAM	1	0	28.18	28.46	28.06
		1	12	28.50	28.25	27.93
		1	24	28.10	28.51	28.11
		12	0	27.01	26.98	26.84
		12	6	27.16	27.03	26.74
		12	13	27.02	27.05	26.94
		25	0	27.15	26.92	26.79
	64QAM	1	0	26.88	27.17	27.14
		1	12	27.37	26.98	27.02
		1	24	27.25	27.51	27.27
		12	0	25.95	26.08	25.62
		12	6	26.11	26.17	25.49
		12	13	26.05	25.98	25.95
		25	0	25.86	25.81	25.90
	256QAM	1	0	24.91	25.24	24.98
		1	12	25.23	25.25	25.09
		1	24	24.97	25.45	25.41
		12	0	23.84	24.05	23.80
		12	6	24.34	24.31	23.77
		12	13	23.93	23.72	24.17
		25	0	24.01	24.03	23.96

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18615	18900	19185
		Frequency (MHz)		1851.5	1880	1908.5
3M	QPSK	1	0	28.75	28.94	28.64
		1	7	29.03	29.00	28.86
		1	14	29.09	29.03	28.71
		8	0	28.06	27.99	27.83
		8	3	28.03	28.02	27.76
		8	7	28.07	28.06	27.81
		15	0	28.01	28.02	27.82
	16QAM	1	0	28.23	28.29	27.73
		1	7	28.48	28.54	28.11
		1	14	28.17	28.05	28.40
		8	0	27.05	27.08	26.88
		8	3	27.14	27.05	26.93
		8	7	27.17	27.16	26.74
		15	0	26.92	27.01	26.93
	64QAM	1	0	27.33	27.16	26.62
		1	7	27.20	27.58	26.84
		1	14	27.14	26.76	27.16
		8	0	26.04	26.26	25.62
		8	3	26.09	26.23	25.80
		8	7	25.92	25.90	25.74
		15	0	25.70	26.02	25.97
	256QAM	1	0	25.53	25.45	24.76
		1	7	25.18	25.82	24.81
		1	14	25.21	24.61	25.35
		8	0	24.24	24.26	23.82
		8	3	23.89	24.14	23.67
		8	7	24.08	23.90	23.86
		15	0	23.70	23.81	24.24

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18607	18900	19193
		Frequency (MHz)		1850.7	1880	1909.3
1.4M	QPSK	1	0	28.91	28.86	28.62
		1	2	29.04	28.98	28.71
		1	5	28.85	28.90	28.58
		3	0	28.84	28.90	28.63
		3	1	28.98	28.99	28.71
		3	3	28.90	28.89	28.64
		6	0	28.01	27.96	27.67
	16QAM	1	0	28.47	28.26	27.60
		1	2	27.90	28.47	27.92
		1	5	28.04	28.09	28.22
		3	0	28.00	28.02	27.73
		3	1	28.06	28.05	27.85
		3	3	28.03	28.01	27.78
		6	0	27.10	27.06	26.72
	64QAM	1	0	27.35	27.33	26.68
		1	2	26.71	27.23	27.01
		1	5	26.82	26.97	27.38
		3	0	27.10	27.05	26.44
		3	1	27.15	27.19	26.68
		3	3	27.07	26.87	26.92
		6	0	26.26	26.08	25.58
	256QAM	1	0	25.55	25.05	24.60
		1	2	24.56	25.05	24.98
		1	5	24.91	25.13	25.54
		3	0	24.99	25.27	24.19
		3	1	25.43	25.28	24.48
		3	3	25.37	25.04	24.98
		6	0	23.97	23.92	23.29

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20450	20525	20600
		Frequency (MHz)		829	836.5	844
10M	QPSK	1	0	26.61	26.74	26.55
		1	24	26.56	26.71	26.31
		1	49	26.40	26.62	26.33
		25	0	25.67	25.69	25.60
		25	12	25.66	25.63	25.67
		25	25	25.70	25.64	25.58
		50	0	25.73	25.72	25.67
	16QAM	1	0	25.88	26.21	26.35
		1	24	25.82	26.02	25.92
		1	49	25.80	25.83	25.81
		25	0	24.67	24.72	24.58
		25	12	24.70	24.58	24.52
		25	25	24.65	24.58	24.64
		50	0	24.63	24.60	24.50
	64QAM	1	0	24.72	25.02	25.36
		1	24	24.97	25.08	24.97
		1	49	24.85	24.53	24.96
		25	0	23.53	23.61	23.31
		25	12	23.75	23.68	23.34
		25	25	23.77	23.53	23.73
		50	0	23.58	23.40	23.51
	256QAM	1	0	23.01	23.27	23.22
		1	24	23.27	23.38	22.78
		1	49	23.07	22.32	22.81
		25	0	21.50	21.40	21.25
		25	12	21.83	21.79	21.32
		25	25	21.87	21.36	21.47
		50	0	21.37	21.52	21.60

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20425	20525	20625
		Frequency (MHz)		826.5	836.5	846.5
5M	QPSK	1	0	26.77	26.70	26.50
		1	12	26.63	26.74	26.57
		1	24	26.67	26.54	26.49
		12	0	25.67	25.61	25.67
		12	6	25.68	25.70	25.56
		12	13	25.66	25.68	25.55
		25	0	25.67	25.66	25.67
	16QAM	1	0	26.04	25.64	25.95
		1	12	26.15	26.08	26.09
		1	24	25.59	25.79	25.77
		12	0	24.77	24.72	24.66
		12	6	24.82	24.62	24.53
		12	13	24.70	24.67	24.66
		25	0	24.68	24.57	24.56
	64QAM	1	0	25.01	24.74	24.74
		1	12	24.99	25.17	25.20
		1	24	24.45	24.92	24.71
		12	0	23.53	23.91	23.62
		12	6	23.84	23.67	23.69
		12	13	23.68	23.87	23.46
		25	0	23.73	23.77	23.72
	256QAM	1	0	23.20	22.65	22.82
		1	12	23.20	23.29	23.12
		1	24	22.55	23.16	22.56
		12	0	21.53	21.83	21.62
		12	6	21.71	21.55	21.60
		12	13	21.83	21.90	21.29
		25	0	21.87	21.75	21.44

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20415	20525	20635
		Frequency (MHz)		825.5	836.5	847.5
3M	QPSK	1	0	26.61	26.58	26.60
		1	7	26.76	26.59	26.64
		1	14	26.62	26.50	26.49
		8	0	25.71	25.62	25.55
		8	3	25.68	25.61	25.59
		8	7	25.67	25.57	25.61
		15	0	25.68	25.62	25.54
	16QAM	1	0	25.79	26.15	25.79
		1	7	26.14	25.75	25.71
		1	14	25.75	26.08	25.83
		8	0	24.77	24.71	24.64
		8	3	24.84	24.72	24.72
		8	7	24.67	24.60	24.60
		15	0	24.76	24.55	24.65
	64QAM	1	0	24.57	25.19	24.86
		1	7	24.98	24.64	24.58
		1	14	24.79	24.98	24.67
		8	0	23.89	23.44	23.50
		8	3	23.94	23.86	23.54
		8	7	23.65	23.33	23.60
		15	0	23.79	23.49	23.55
	256QAM	1	0	22.28	23.29	22.84
		1	7	23.28	22.66	22.48
		1	14	23.03	22.93	22.47
		8	0	22.18	21.38	21.25
		8	3	21.80	22.01	21.60
		8	7	21.84	21.15	21.68
		15	0	21.82	21.68	21.83

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20407	20525	20643
		Frequency (MHz)		824.7	836.5	848.3
1.4M	QPSK	1	0	26.60	22.66	22.66
		1	2	26.57	22.77	22.70
		1	5	26.48	22.63	22.58
		3	0	26.57	22.63	22.68
		3	1	26.57	22.68	22.70
		3	3	26.56	22.74	22.60
		6	0	25.62	21.78	21.70
	16QAM	1	0	26.14	25.50	25.87
		1	2	25.68	25.77	26.03
		1	5	25.77	26.00	25.65
		3	0	25.66	25.43	25.60
		3	1	25.52	25.61	25.59
		3	3	25.57	25.60	25.38
		6	0	24.59	24.71	24.71
	64QAM	1	0	24.98	24.25	24.82
		1	2	24.85	24.48	24.97
		1	5	24.80	25.00	24.40
		3	0	24.58	24.35	24.42
		3	1	24.26	24.81	24.37
		3	3	24.32	24.59	24.56
		6	0	23.69	23.54	23.41
	256QAM	1	0	23.21	22.12	22.64
		1	2	22.96	22.65	22.79
		1	5	22.94	22.86	22.33
		3	0	22.48	22.23	22.26
		3	1	22.32	22.79	22.65
		3	3	22.55	22.57	22.48
		6	0	21.89	21.47	21.14

*ERP = Conducted + antenna gain (3.81dBi)-2.15

LTE Band 7						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20850	21100	21350
		Frequency (MHz)		2510	2535	2560
20M	QPSK	1	0	30.29	30.18	30.10
		1	50	30.19	30.06	29.95
		1	99	30.26	30.30	30.06
		50	0	29.43	29.30	29.13
		50	25	29.44	29.31	29.30
		50	50	29.46	29.36	29.19
		100	0	29.49	29.31	29.31
	16QAM	1	0	29.39	29.57	29.26
		1	50	29.50	29.39	29.58
		1	99	29.38	29.83	29.71
		50	0	28.43	28.30	28.14
		50	25	28.45	28.30	28.28
		50	50	28.42	28.33	28.26
		100	0	28.41	28.32	28.21
	64QAM	1	0	28.35	28.76	28.26
		1	50	28.27	28.57	28.49
		1	99	28.46	28.94	28.51
		50	0	27.41	27.37	27.07
		50	25	27.33	27.14	27.28
		50	50	27.24	27.34	27.20
		100	0	27.15	27.52	27.14
	256QAM	1	0	26.22	26.82	26.49
		1	50	26.50	26.87	26.72
		1	99	26.73	27.22	26.26
		50	0	25.13	25.36	24.97
		50	25	25.61	25.28	25.40
		50	50	25.27	25.59	25.08
		100	0	25.11	25.29	25.21

*EIRP = Conducted + antenna gain (5.31dBi)

LTE Band 7						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20825	21100	21375
		Frequency (MHz)		2507.5	2535	2562.5
15M	QPSK	1	0	30.33	30.20	30.12
		1	37	30.27	30.22	30.03
		1	74	30.35	30.29	30.16
		36	0	29.32	29.26	29.25
		36	19	29.49	29.22	29.17
		36	39	29.45	29.31	29.24
		75	0	29.38	29.29	29.13
	16QAM	1	0	29.57	29.29	29.21
		1	37	29.31	29.08	29.30
		1	74	29.57	29.46	29.36
		36	0	28.44	28.27	28.16
		36	19	28.45	28.29	28.10
		36	39	28.39	28.34	28.23
		75	0	28.45	28.19	28.13
	64QAM	1	0	28.67	28.08	28.06
		1	37	28.34	28.27	28.24
		1	74	28.71	28.48	28.10
		36	0	27.59	27.15	27.08
		36	19	27.24	27.18	27.24
		36	39	27.32	27.17	27.33
		75	0	27.59	27.03	27.18
	256QAM	1	0	26.88	25.99	26.02
		1	37	26.07	26.24	26.28
		1	74	26.90	26.55	26.32
		36	0	25.67	25.32	25.26
		36	19	25.45	25.21	25.30
		36	39	25.43	25.09	25.32
		75	0	25.57	24.81	25.09

*EIRP = Conducted + antenna gain (5.31dBi)

LTE Band 7						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20800	21100	21400
		Frequency (MHz)		2505	2535	2565
10M	QPSK	1	0	30.23	30.05	29.98
		1	24	30.30	30.08	29.99
		1	49	30.26	30.21	30.04
		25	0	29.34	29.23	29.17
		25	12	29.46	29.33	29.30
		25	25	29.47	29.29	29.25
		50	0	29.43	29.15	29.17
	16QAM	1	0	29.79	29.13	29.06
		1	24	29.73	29.39	29.66
		1	49	29.60	29.88	29.25
		25	0	28.49	28.16	28.11
		25	12	28.53	28.30	28.30
		25	25	28.38	28.33	28.28
		50	0	28.49	28.22	28.16
	64QAM	1	0	28.92	28.31	28.24
		1	24	28.58	28.44	28.51
		1	49	28.67	28.72	28.41
		25	0	27.69	26.90	27.26
		25	12	27.54	27.08	27.19
		25	25	27.46	27.28	27.42
		50	0	27.40	26.97	26.99
	256QAM	1	0	27.08	26.02	26.43
		1	24	26.76	26.26	26.66
		1	49	26.79	26.44	26.17
		25	0	25.59	25.15	25.27
		25	12	25.28	25.15	24.99
		25	25	25.18	25.45	25.20
		50	0	25.42	24.81	24.70

*EIRP = Conducted + antenna gain (5.31dBi)

LTE Band 7						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20775	21100	21425
		Frequency (MHz)		2502.5	2535	2567.5
5M	QPSK	1	0	30.25	30.13	30.17
		1	12	30.45	30.18	30.15
		1	24	30.29	30.22	29.96
		12	0	29.47	29.34	29.24
		12	6	29.37	29.32	29.17
		12	13	29.34	29.30	29.20
		25	0	29.35	29.27	29.18
	16QAM	1	0	29.34	29.62	29.25
		1	12	29.85	29.34	29.56
		1	24	29.52	29.38	29.18
		12	0	28.41	28.33	28.16
		12	6	28.43	28.27	28.25
		12	13	28.46	28.24	28.19
		25	0	28.47	28.35	28.20
	64QAM	1	0	28.54	28.61	28.14
		1	12	28.91	28.22	28.40
		1	24	28.27	28.28	28.16
		12	0	27.60	27.42	27.24
		12	6	27.55	27.45	27.43
		12	13	27.20	27.25	27.34
		25	0	27.36	27.31	27.08
	256QAM	1	0	26.37	26.39	26.23
		1	12	26.98	25.95	26.37
		1	24	26.41	26.30	26.40
		12	0	25.87	25.32	25.00
		12	6	25.58	25.39	25.30
		12	13	25.28	25.18	25.06
		25	0	25.10	25.59	25.10

*EIRP = Conducted + antenna gain (5.31dBi)

LTE Band 12						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23060	23095	23130
		Frequency (MHz)		704	707.5	711
10M	QPSK	1	0	27.15	27.20	27.08
		1	24	26.98	27.10	27.19
		1	49	27.08	27.05	26.91
		25	0	26.19	26.15	26.19
		25	12	26.22	26.14	26.27
		25	25	26.23	26.27	26.30
		50	0	26.33	26.16	26.25
	16QAM	1	0	26.58	26.61	26.20
		1	24	26.82	26.71	26.43
		1	49	26.51	26.26	26.49
		25	0	25.25	25.22	25.23
		25	12	25.28	25.21	25.29
		25	25	25.22	25.20	25.27
		50	0	25.28	25.21	25.29
	64QAM	1	0	25.48	25.59	25.25
		1	24	25.72	25.43	25.41
		1	49	25.22	25.30	25.27
		25	0	24.44	24.18	24.06
		25	12	24.38	24.12	24.00
		25	25	24.27	24.04	24.17
		50	0	24.04	23.93	24.31
	256QAM	1	0	23.28	23.52	23.05
		1	24	23.60	23.15	23.63
		1	49	22.99	23.58	23.13
		25	0	22.45	21.97	22.08
		25	12	22.49	22.12	21.81
		25	25	22.47	21.84	21.88
		50	0	22.20	22.21	22.05

*ERP = Conducted + antenna gain (4.41dBi)-2.15

LTE Band 12						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23035	23095	23155
		Frequency (MHz)		701.5	707.5	713.5
5M	QPSK	1	0	27.12	27.10	27.07
		1	12	27.30	27.14	26.96
		1	24	27.17	27.17	27.15
		12	0	26.30	26.20	26.15
		12	6	26.29	26.16	26.22
		12	13	26.24	26.23	26.19
		25	0	26.20	26.12	26.12
	16QAM	1	0	26.47	26.35	26.01
		1	12	26.66	26.30	26.48
		1	24	26.10	26.28	26.64
		12	0	25.36	25.16	25.11
		12	6	25.21	25.19	25.22
		12	13	25.22	25.27	25.15
		25	0	25.17	25.20	25.17
	64QAM	1	0	25.25	25.51	25.18
		1	12	25.70	25.30	25.65
		1	24	25.16	25.38	25.44
		12	0	24.32	24.22	23.90
		12	6	24.03	24.31	24.10
		12	13	24.06	24.02	24.21
		25	0	24.31	24.32	24.35
	256QAM	1	0	23.03	23.58	23.47
		1	12	23.64	23.36	23.38
		1	24	23.40	23.40	23.24
		12	0	22.26	22.43	21.78
		12	6	22.33	22.15	22.34
		12	13	21.86	21.90	22.02
		25	0	22.61	22.40	22.48

*ERP = Conducted + antenna gain (4.41dBi)-2.15

LTE Band 12						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23025	23095	23165
		Frequency (MHz)		700.5	707.5	714.5
3M	QPSK	1	0	27.26	27.16	27.08
		1	7	27.09	27.21	27.05
		1	14	27.06	27.05	27.07
		8	0	26.22	26.15	26.11
		8	3	26.27	26.20	26.11
		8	7	26.15	26.14	26.13
		15	0	26.28	26.16	26.09
	16QAM	1	0	26.42	26.58	26.32
		1	7	26.32	26.26	26.47
		1	14	26.35	26.67	26.02
		8	0	25.12	25.26	25.12
		8	3	25.41	25.23	25.14
		8	7	25.30	25.17	25.09
		15	0	25.31	25.14	25.04
	64QAM	1	0	25.57	25.34	25.07
		1	7	25.19	25.28	25.63
		1	14	25.17	25.61	25.10
		8	0	24.22	24.37	23.88
		8	3	24.19	24.41	23.92
		8	7	24.23	24.13	24.05
		15	0	24.27	24.34	24.12
	256QAM	1	0	23.56	23.57	23.34
		1	7	23.37	23.46	23.85
		1	14	23.22	23.64	23.20
		8	0	22.43	22.37	22.04
		8	3	22.37	22.15	22.21
		8	7	22.30	22.41	21.99
		15	0	22.57	22.37	22.22

*ERP = Conducted + antenna gain (4.41dBi)-2.15

LTE Band 12						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23017	23095	23173
		Frequency (MHz)		699.7	707.5	715.3
1.4M	QPSK	1	0	27.07	27.09	27.00
		1	2	27.18	27.08	27.03
		1	5	27.03	26.95	26.92
		3	0	27.08	27.01	26.94
		3	1	27.20	26.98	27.00
		3	3	27.08	27.09	26.94
		6	0	26.22	26.13	26.02
	16QAM	1	0	26.64	26.46	26.16
		1	2	26.38	26.33	26.31
		1	5	26.34	26.47	25.97
		3	0	26.17	26.09	26.03
		3	1	26.29	26.21	25.94
		3	3	26.18	26.12	26.10
		6	0	25.37	25.27	25.14
	64QAM	1	0	25.47	25.44	24.92
		1	2	25.40	25.32	25.27
		1	5	25.30	25.65	24.74
		3	0	25.27	24.91	24.96
		3	1	25.40	25.05	24.69
		3	3	24.96	24.96	24.80
		6	0	24.45	24.39	24.02
	256QAM	1	0	23.33	23.43	22.80
		1	2	23.54	23.57	23.03
		1	5	23.44	23.75	22.62
		3	0	23.03	22.83	22.90
		3	1	23.44	23.16	22.94
		3	3	23.09	22.70	22.52
		6	0	22.58	22.44	22.15

*ERP = Conducted + antenna gain (4.41dBi)-2.15

LTE Band 13				
BW	MCS Index	RB Size	RB Offset	Mid
		Channel		23230
		Frequency (MHz)		782
10M	QPSK	1	0	27.23
		1	24	27.23
		1	49	27.19
		25	0	26.37
		25	12	26.35
		25	25	26.40
		50	0	26.45
	16QAM	1	0	26.65
		1	24	26.50
		1	49	26.64
		25	0	25.41
		25	12	25.35
		25	25	25.49
		50	0	25.33
	64QAM	1	0	25.59
		1	24	25.65
		1	49	25.67
		25	0	24.57
		25	12	24.10
		25	25	24.25
		50	0	24.13
	256QAM	1	0	23.39
		1	24	23.61
		1	49	23.91
		25	0	22.84
		25	12	22.31
		25	25	22.25
		50	0	22.23

*ERP = Conducted + antenna gain (4.41dBi)-2.15

LTE Band 13						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23205	23230	23255
		Frequency (MHz)		779.5	782	784.5
5M	QPSK	1	0	27.11	27.18	27.24
		1	12	27.21	27.32	27.25
		1	24	27.30	27.16	27.11
		12	0	26.31	26.34	26.23
		12	6	26.36	26.28	26.28
		12	13	26.39	26.35	26.32
		25	0	26.39	26.36	26.24
	16QAM	1	0	26.21	26.40	26.73
		1	12	26.86	26.77	26.26
		1	24	26.58	26.47	26.68
		12	0	25.31	25.36	25.51
		12	6	25.34	25.33	25.43
		12	13	25.46	25.35	25.37
		25	0	25.31	25.38	25.36
	64QAM	1	0	25.33	25.55	25.57
		1	12	26.06	25.71	25.37
		1	24	25.35	25.33	25.76
		12	0	24.43	24.12	24.59
		12	6	24.22	24.46	24.24
		12	13	24.23	24.13	24.40
		25	0	24.05	24.34	24.09
	256QAM	1	0	23.22	23.46	23.71
		1	12	24.13	23.60	23.54
		1	24	23.23	23.15	23.85
		12	0	22.47	21.90	22.37
		12	6	22.31	22.58	21.96
		12	13	22.35	21.84	22.26
		25	0	21.93	22.53	21.83

*ERP = Conducted + antenna gain (4.41dBi)-2.15

LTE Band 14				
BW	MCS Index	RB Size	RB Offset	Mid
		Channel		23330
		Frequency (MHz)		793
10M	QPSK	1	0	27.14
		1	24	27.13
		1	49	27.20
		25	0	26.30
		25	12	26.21
		25	25	26.23
		50	0	26.23
	16QAM	1	0	26.85
		1	24	26.66
		1	49	26.22
		25	0	25.20
		25	12	25.28
		25	25	25.24
		50	0	25.28
	64QAM	1	0	26.04
		1	24	25.42
		1	49	25.09
		25	0	24.06
		25	12	24.16
		25	25	24.39
		50	0	24.08
	256QAM	1	0	24.23
		1	24	23.38
		1	49	23.38
		25	0	22.28
		25	12	22.42
		25	25	22.58
		50	0	22.29

*ERP = Conducted + antenna gain (4.41dBi)-2.15

LTE Band 14						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		23305	23330	23355
		Frequency (MHz)		790.5	793	795.5
5M	QPSK	1	0	27.06	27.13	27.14
		1	12	27.22	27.31	27.11
		1	24	27.24	27.29	27.14
		12	0	26.26	26.18	26.25
		12	6	26.30	26.27	26.13
		12	13	26.24	26.26	26.26
		25	0	26.30	26.24	26.21
	16QAM	1	0	26.74	26.71	26.70
		1	12	26.49	26.15	26.46
		1	24	26.81	26.65	26.33
		12	0	25.18	25.28	25.33
		12	6	25.31	25.23	25.29
		12	13	25.31	25.27	25.22
		25	0	25.39	25.20	25.23
	64QAM	1	0	25.46	25.57	25.85
		1	12	25.19	25.06	25.57
		1	24	25.64	25.40	25.43
		12	0	24.20	24.06	24.53
		12	6	24.08	24.31	24.42
		12	13	24.51	24.00	24.25
		25	0	24.25	24.11	24.36
	256QAM	1	0	23.52	23.31	23.76
		1	12	22.98	22.89	23.43
		1	24	23.40	23.33	23.73
		12	0	22.31	22.11	22.24
		12	6	22.26	22.55	22.23
		12	13	22.39	22.19	22.44
		25	0	22.17	22.38	22.16

*ERP = Conducted + antenna gain (4.41dBi)-2.15

LTE Band 30				
BW	MCS Index	RB Size	RB Offset	Mid
		Channel		27710
		Frequency (MHz)		2310
10M	QPSK	1	0	23.92
		1	24	23.83
		1	49	23.69
		25	0	22.73
		25	12	22.92
		25	25	22.96
		50	0	22.89
	16QAM	1	0	23.09
		1	24	23.16
		1	49	22.84
		25	0	21.71
		25	12	21.84
		25	25	21.87
		50	0	21.75
	64QAM	1	0	21.82
		1	24	22.01
		1	49	21.57
		25	0	20.88
		25	12	21.00
		25	25	21.03
		50	0	20.89
	256QAM	1	0	19.57
		1	24	20.17
		1	49	19.63
		25	0	18.82
		25	12	19.22
		25	25	19.29
		50	0	18.93

*EIRP = Conducted + antenna gain (2.99dBi)

LTE Band 30						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		27685	27710	27735
		Frequency (MHz)		2307.5	2310	2312.5
5M	QPSK	1	0	23.55	23.68	23.70
		1	12	23.86	23.93	23.90
		1	24	23.84	23.84	23.85
		12	0	22.75	22.72	22.79
		12	6	22.91	22.86	22.84
		12	13	22.88	22.88	22.87
		25	0	22.85	22.85	22.76
	16QAM	1	0	22.89	22.86	23.23
		1	12	23.27	23.23	23.25
		1	24	22.76	23.41	23.44
		12	0	21.77	21.77	21.79
		12	6	21.85	21.93	21.92
		12	13	21.92	21.88	21.95
		25	0	21.83	21.86	21.85
	64QAM	1	0	21.61	22.00	22.26
		1	12	22.31	22.19	22.05
		1	24	21.46	22.16	22.15
		12	0	20.59	20.51	20.96
		12	6	20.65	20.64	20.63
		12	13	20.73	20.68	20.73
		25	0	20.98	20.96	20.84
	256QAM	1	0	19.32	20.24	20.30
		1	12	20.60	20.12	19.86
		1	24	19.56	20.16	20.12
		12	0	18.41	18.22	18.89
		12	6	18.78	18.72	18.92
		12	13	18.93	18.45	18.92
		25	0	19.22	18.86	19.11

*EIRP = Conducted + antenna gain (2.99dBi)

LTE Band 41						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		39750	40620	41490
		Frequency (MHz)		2506	2593	2680
20M	QPSK	1	0	32.97	32.81	32.67
		1	50	32.84	32.66	32.27
		1	99	32.78	32.79	31.47
		50	0	32.05	31.94	31.82
		50	25	32.08	31.96	31.47
		50	50	32.09	32.01	31.06
		100	0	32.04	32.01	31.47
	16QAM	1	0	32.24	32.16	32.15
		1	50	32.15	32.01	31.60
		1	99	32.19	32.03	30.76
		50	0	30.95	31.00	30.88
		50	25	31.05	30.99	30.55
		50	50	31.13	31.01	30.16
		100	0	31.14	31.02	30.56
	64QAM	1	0	31.00	31.16	31.05
		1	50	31.16	30.93	30.31
		1	99	31.00	30.77	29.56
		50	0	29.83	29.86	29.87
		50	25	29.76	30.14	29.68
		50	50	29.87	30.00	29.01
		100	0	30.06	30.03	29.40
	256QAM	1	0	29.08	29.45	28.99
		1	50	29.33	29.06	28.04
		1	99	29.10	29.01	27.74
		50	0	27.69	28.01	27.74
		50	25	27.89	28.18	27.80
		50	50	27.78	27.83	27.05
		100	0	27.88	28.32	27.69

*EIRP = Conducted + antenna gain (5.31dBi)

LTE Band 41						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		39725	40620	41515
		Frequency (MHz)		2503.5	2593	2682.5
15M	QPSK	1	0	32.87	32.75	32.65
		1	37	32.88	32.73	32.03
		1	74	32.82	32.78	31.52
		36	0	32.16	31.81	31.50
		36	19	32.12	31.90	31.26
		36	39	32.05	31.94	31.00
		75	0	32.10	32.00	31.34
	16QAM	1	0	32.26	32.05	32.25
		1	37	32.21	32.34	31.29
		1	74	32.18	32.04	30.81
		36	0	31.13	30.91	30.58
		36	19	31.00	30.96	30.30
		36	39	31.01	30.91	30.00
		75	0	31.12	31.00	30.36
	64QAM	1	0	31.05	30.91	31.12
		1	37	30.93	31.05	30.09
		1	74	31.11	30.89	29.91
		36	0	30.11	29.98	29.73
		36	19	29.90	30.13	29.25
		36	39	29.76	29.94	29.11
		75	0	30.05	30.06	29.52
	256QAM	1	0	29.30	28.64	29.14
		1	37	29.07	28.77	28.00
		1	74	28.91	28.79	28.00
		36	0	28.32	28.10	27.97
		36	19	27.78	28.36	27.22
		36	39	27.85	27.67	27.07
		75	0	28.03	27.99	27.77

*EIRP = Conducted + antenna gain (5.31dBi)

LTE Band 41						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		39700	40620	41540
		Frequency (MHz)		2501	2593	2685
10M	QPSK	1	0	32.94	32.71	32.24
		1	24	32.96	32.78	31.87
		1	49	32.93	32.61	31.53
		25	0	32.11	31.95	31.28
		25	12	32.11	32.03	31.13
		25	25	32.07	32.01	30.92
		50	0	32.16	31.98	31.07
	16QAM	1	0	32.34	32.05	31.88
		1	24	32.24	32.13	31.49
		1	49	32.30	32.15	30.82
		25	0	31.12	31.08	30.37
		25	12	31.15	31.12	30.24
		25	25	31.12	30.96	29.99
		50	0	31.18	31.05	30.16
	64QAM	1	0	31.19	30.97	30.87
		1	24	31.14	31.08	30.42
		1	49	31.41	31.08	29.62
		25	0	30.23	30.06	29.45
		25	12	29.86	30.03	29.32
		25	25	29.86	30.12	28.91
		50	0	30.11	29.80	29.26
	256QAM	1	0	28.93	28.89	28.58
		1	24	29.40	29.06	28.45
		1	49	29.25	28.93	27.49
		25	0	28.23	27.81	27.32
		25	12	27.58	28.20	27.37
		25	25	27.79	28.15	26.99
		50	0	28.10	28.06	27.43

*EIRP = Conducted + antenna gain (5.31dBi)

LTE Band 41						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		39675	40620	41565
		Frequency (MHz)		2498.5	2593	2687.5
5M	QPSK	1	0	32.89	32.69	31.84
		1	12	32.92	32.75	31.65
		1	24	32.85	32.69	31.52
		12	0	32.12	31.97	31.00
		12	6	32.05	31.92	30.97
		12	13	32.08	31.95	30.86
		25	0	32.05	31.92	30.90
	16QAM	1	0	32.19	32.05	31.19
		1	12	32.17	32.08	31.03
		1	24	32.22	32.04	30.90
		12	0	31.13	31.03	30.10
		12	6	31.11	31.09	30.05
		12	13	31.14	30.98	29.93
		25	0	31.09	31.03	30.00
	64QAM	1	0	31.36	30.94	30.15
		1	12	31.35	31.04	29.90
		1	24	30.99	30.95	29.82
		12	0	30.05	29.77	29.05
		12	6	29.94	29.89	28.97
		12	13	30.29	30.07	28.86
		25	0	29.90	30.22	28.82
	256QAM	1	0	29.51	29.13	28.17
		1	12	29.27	29.04	27.98
		1	24	29.19	29.20	27.87
		12	0	27.76	27.71	27.19
		12	6	27.87	27.79	26.95
		12	13	28.27	28.09	27.04
		25	0	27.80	28.37	26.56

*EIRP = Conducted + antenna gain (5.31dBi)

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		132072	132322	132572
		Frequency (MHz)		1720	1745	1770
20M	QPSK	1	0	29.05	29.12	29.05
		1	50	29.11	29.02	29.06
		1	99	29.07	28.96	28.93
		50	0	28.12	27.93	28.01
		50	25	27.97	28.01	28.11
		50	50	28.16	27.96	28.14
		100	0	27.92	27.98	28.11
	16QAM	1	0	28.11	28.38	28.53
		1	50	28.11	28.38	28.27
		1	99	28.25	28.16	28.15
		50	0	27.27	27.30	27.24
		50	25	27.05	27.07	27.27
		50	50	27.27	26.98	27.16
		100	0	27.32	27.03	27.55
	64QAM	1	0	26.95	27.08	27.45
		1	50	26.82	27.30	27.17
		1	99	26.98	26.99	27.09
		50	0	26.14	26.24	26.16
		50	25	26.02	25.95	26.10
		50	50	26.18	25.80	26.08
		100	0	26.28	25.98	26.52
	256QAM	1	0	24.96	24.96	25.32
		1	50	24.90	25.27	25.04
		1	99	24.78	25.08	25.18
		50	0	24.12	24.17	24.02
		50	25	23.91	23.81	24.05
		50	50	24.07	23.90	24.12
		100	0	24.18	24.03	24.43

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		132047	132322	132597
		Frequency (MHz)		1717.5	1745	1772.5
15M	QPSK	1	0	29.00	28.81	28.79
		1	37	28.87	28.90	29.02
		1	74	28.96	29.02	29.05
		36	0	28.11	27.92	27.95
		36	19	27.94	27.97	28.05
		36	39	27.94	28.04	28.09
		75	0	27.87	27.88	27.98
	16QAM	1	0	28.14	28.01	27.91
		1	37	28.37	28.39	28.38
		1	74	28.05	28.45	28.40
		36	0	27.49	26.96	27.21
		36	19	27.13	27.30	27.42
		36	39	27.22	27.40	27.19
		75	0	26.88	27.18	27.33
	64QAM	1	0	26.93	26.73	26.76
		1	37	27.10	27.30	27.08
		1	74	26.96	27.43	27.18
		36	0	26.47	25.90	26.03
		36	19	26.09	26.04	26.32
		36	39	26.03	26.12	25.92
		75	0	25.72	25.91	26.27
	256QAM	1	0	24.96	24.65	24.61
		1	37	25.05	25.32	25.02
		1	74	24.95	25.45	25.25
		36	0	24.44	23.93	23.86
		36	19	23.96	23.91	24.20
		36	39	24.08	24.12	23.73
		75	0	23.52	23.85	24.28

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		132022	132322	132622
		Frequency (MHz)		1715	1745	1775
10M	QPSK	1	0	29.03	29.02	29.13
		1	24	28.78	28.80	28.98
		1	49	28.89	28.88	28.85
		25	0	27.93	27.97	27.90
		25	12	28.11	28.03	28.02
		25	25	28.09	28.08	28.17
		50	0	28.05	27.98	28.18
	16QAM	1	0	28.33	28.09	28.42
		1	24	28.13	28.30	28.20
		1	49	27.99	27.89	28.33
		25	0	26.96	27.18	27.26
		25	12	27.13	27.27	27.41
		25	25	27.21	27.15	27.17
		50	0	27.39	27.14	27.47
	64QAM	1	0	27.04	26.86	27.34
		1	24	26.98	27.03	27.12
		1	49	26.75	26.88	27.04
		25	0	25.70	26.06	26.08
		25	12	25.98	25.97	26.24
		25	25	25.91	26.13	25.97
		50	0	26.30	26.05	26.22
	256QAM	1	0	24.96	24.68	25.30
		1	24	24.85	25.02	24.97
		1	49	24.69	24.76	24.97
		25	0	23.79	24.06	23.89
		25	12	23.84	24.07	24.09
		25	25	23.91	24.15	23.93
		50	0	24.36	23.91	24.31

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		131997	132322	132647
		Frequency (MHz)		1712.5	1745	1777.5
5M	QPSK	1	0	28.90	28.97	29.09
		1	12	28.76	28.96	28.96
		1	24	29.16	29.10	28.88
		12	0	28.13	27.94	28.00
		12	6	27.89	27.88	27.92
		12	13	28.11	28.00	28.09
		25	0	28.03	27.91	28.12
	16QAM	1	0	28.19	28.00	28.42
		1	12	27.87	28.33	28.16
		1	24	28.52	28.47	27.89
		12	0	27.14	27.24	27.43
		12	6	27.05	27.25	26.93
		12	13	27.52	27.09	27.48
		25	0	27.07	27.06	27.27
	64QAM	1	0	26.90	26.96	27.14
		1	12	26.64	27.18	27.05
		1	24	27.31	27.44	26.59
		12	0	25.92	26.13	26.40
		12	6	25.97	26.10	25.71
		12	13	26.33	25.85	26.43
		25	0	26.03	25.82	26.21
	256QAM	1	0	24.84	24.90	25.04
		1	12	24.62	25.22	25.03
		1	24	25.38	25.47	24.66
		12	0	23.88	24.23	24.42
		12	6	23.85	24.16	23.67
		12	13	24.19	23.95	24.31
		25	0	23.85	23.86	24.21

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		131987	132322	132657
		Frequency (MHz)		1711.5	1745	1778.5
3M	QPSK	1	0	29.11	28.92	28.85
		1	7	28.86	28.85	28.86
		1	14	29.01	28.98	28.90
		8	0	27.86	27.96	28.15
		8	3	28.08	27.91	27.91
		8	7	28.01	27.98	27.94
		15	0	27.90	27.93	27.84
	16QAM	1	0	28.15	28.25	28.10
		1	7	28.04	28.08	27.96
		1	14	28.38	28.13	27.95
		8	0	27.22	27.15	27.63
		8	3	27.49	26.95	27.37
		8	7	27.24	27.40	26.99
		15	0	27.06	27.11	27.03
	64QAM	1	0	27.04	27.21	26.89
		1	7	27.04	26.99	26.70
		1	14	27.19	26.92	26.71
		8	0	26.07	26.09	26.35
		8	3	26.47	25.76	26.17
		8	7	25.96	26.31	25.86
		15	0	25.85	25.93	25.81
	256QAM	1	0	25.12	25.31	24.83
		1	7	25.05	25.07	24.73
		1	14	25.13	24.85	24.77
		8	0	24.05	24.16	24.45
		8	3	24.36	23.64	24.00
		8	7	23.99	24.32	23.78
		15	0	23.68	23.88	23.90

*EIRP = Conducted + antenna gain (4.27dBi)

LTE Band 66						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		131979	132322	132665
		Frequency (MHz)		1710.7	1745	1779.3
1.4M	QPSK	1	0	28.71	28.83	28.87
		1	2	28.64	28.80	28.74
		1	5	28.55	28.71	28.78
		3	0	28.69	28.59	28.58
		3	1	28.62	28.73	28.89
		3	3	28.45	28.70	28.49
		6	0	27.56	27.85	27.71
	16QAM	1	0	28.15	28.21	28.16
		1	2	27.81	28.07	28.20
		1	5	27.98	28.10	28.11
		3	0	28.11	27.94	27.85
		3	1	27.74	27.85	28.22
		3	3	27.88	27.81	27.49
		6	0	26.80	26.91	27.13
	64QAM	1	0	27.09	27.21	27.00
		1	2	26.68	26.99	27.01
		1	5	26.85	26.93	27.11
		3	0	26.86	26.77	26.75
		3	1	26.60	26.71	27.14
		3	3	26.60	26.80	26.28
		6	0	25.65	25.71	26.08
	256QAM	1	0	25.19	25.31	25.02
		1	2	24.72	24.97	24.99
		1	5	24.91	24.73	25.01
		3	0	24.68	24.65	24.83
		3	1	24.57	24.73	25.13
		3	3	24.50	24.62	24.36
		6	0	23.64	23.67	24.15

*EIRP = Conducted + antenna gain (4.27dBi)

4.2 Modulation Characteristics Measurement

4.2.1 Limits of Modulation Characteristics

N/A


4.2.2 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector, The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

4.2.3 Test Setup



4.2.4 Test Results




5G NR n77 (Part 27Q)

Spectrum Plot of Measurement Value

Channel: 633334 / Frequency (MHz): 3500.01MHz


$\pi/2$ BPSK




QPSK




16QAM



64QAM



256QAM




LTE Band 2


Spectrum Plot of Measurement Value

Channel: 18900 / Frequency (MHz): 1880.0MHz


QPSK




16QAM



64QAM



256QAM




LTE Band 5


Spectrum Plot of Measurement Value

Channel: 20525 / Frequency (MHz): 836.5MHz


QPSK




16QAM



64QAM



256QAM




LTE Band 7


Spectrum Plot of Measurement Value

Channel: 21100 / Frequency (MHz): 2535.0MHz


QPSK




16QAM



64QAM



256QAM




LTE Band 12


Spectrum Plot of Measurement Value

Channel: 23095 / Frequency (MHz): 707.5 MHz


QPSK



16QAM



64QAM



256QAM

