

FCC ID::	2A2Y8-FORZA60C				
Test Report No::	TCT220421E036		(c)		(, (, ')
Date of issue::	May 09, 2022				
Testing laboratory::	SHENZHEN TONGCE	TESTING	LAB		
Testing location/ address:	TCT Testing Industrial Street, Bao'an District Republic of China				
Applicant's name:	Guangdong Nanguang	Photo & \	/ideo System	s Co., Ltd	
Address::	DONGLI SECTION, HI CITY, GUANGDONG I			IAI, SHAN	TOU
Manufacturer's name:	Guangdong Nanguang	Photo & \	/ideo System	s Co., Ltd	
Address::	DONGLI SECTION, HI CITY, GUANGDONG I			IAI, SHAN	TOU
Standard(s)::	FCC CFR Title 47 Part	1.1307			
Product Name::	LED RGBLAC Spot Lig	ght			
Trade Mark:	N/A				
Model/Type reference:	Forza 60C	(0)			
Rating(s):	Adapter Information: MODEL: FJ-SW2025G INPUT: AC 100-240V, OUTPUT: DC 15.0V, 6 LED module: 88W	50/60Hz,	2.0A Max		
Date of receipt of test item ::	Apr. 21, 2022				
Date (s) of performance of test:	Apr. 21, 2022 ~ May 0	9, 2022			
Tested by (+signature):	Rleo LIU		Pro Chy	TONGCETE	(0)
Check by (+signature):	Beryl ZHAO		Boyl 20	(TCT)	GNIT
Approved by (+signature):	Tomein	(C)	Tomsin	45 84	

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com





Table of Contents

1.1. 1.2. 2. Ge 2.1. 2.2. 3. Fac 3.1. 3.2.	EUT desc. Model(s) neral Info Test envi Descripti Cilities ar Facilities Location	listormation armation of Sup	and mode. port Units	ent Data		
4. Te:	si Kesuii	S ariu ivie	easurenie	eni Dala .	 <i>(c</i> ¹)	 (či)



1. General Product Information

1.1. EUT description

Product Name:	LED RGBLAC Spot Light		
Model/Type reference:	Forza 60C		
Sample Number:	TCT220421E025-0101		
Operation Frequency:	2402MHz~2480MHz	(0)	
Modulation Type:	GFSK		
Antenna Type:	PCB Antenna		
Antenna Gain:	2dBi		
Rating(s):	Adapter Information: MODEL: FJ-SW2025G1506000D INPUT: AC 100-240V, 50/60Hz, 2.0A Max OUTPUT: DC 15.0V, 6.0A, 90.0W LED module: 88W		

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.





2. General Information

2.1. Test environment and mode

Item	Normal condition					
Temperature	+25°C					
Voltage	AC 120V/60Hz					
Humidity	56%					
Atmospheric Pressure:	1008 mbar					
Test Mode:						
Engineering mode:	Keep the EUT in continuous transmitting by select channel					

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name	
/			1	1	

Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.





3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an

District Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339





4. Test Results and Measurement Data

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1)

For BLE(1M): The maximum output power for antenna is 2.80dBm (1.91mW) at 2480MHz, 2dBi antenna gain(with 1.58 numeric antenna gain).

For BLE(2M): The maximum output power for antenna is 2.84dBm (1.92mW) at 2480MHz, 2dBi antenna gain(with 1.58 numeric antenna gain).

2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser

Calculation

Given

$$E = \sqrt{\frac{30 \times P \times G}{d}} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field Strength in Volts / meter

P = Power in Watts

G=Numeric antenna gain

d=Distance in meters

S=Power Density in milliwatts / square centimeter

Substituting the MPE safe distance using d=20cm into above equation.

Yields: S=0.000199*P*G

Maximum Emissions Level							
Mode	Power(mW) numeric Power density antenna gain (mW/cm2) (Limit (mW/cm2)	Result			
BLE(1M)	1.91	1.58	0.000601	1.0	PASS		
BLE(2M)	1.92	1.58	0.000604	1.0	PASS		



