

Qingdao Richmat Intelligence Technology Inc

FCC Class II Permissive Change Report

Report Type:

FCC Part 15.249 RF report

Model:

HJ RF

REPORT NUMBER:

230800726HAN-001

ISSUE DATE:

September 13, 2023

DOCUMENT CONTROL NUMBER:

TTRF15.249_V1 © 2018 Intertek



Applicant: Qingdao Richmat Intelligence Technology Inc
NO.78 Kongquehe 4th Road, Qingdao Clothing Industry park, Jimo,
Qingdao, Shandong Province, China.

Manufacturer: Qingdao Richmat Intelligence Technology Inc
NO.78 Kongquehe 4th Road, Qingdao Clothing Industry park, Jimo,
Qingdao, Shandong Province, China.

Factory: Qingdao Richmat Intelligence Technology Inc
NO.78 Kongquehe 4th Road, Qingdao Clothing Industry park, Jimo,
Qingdao, Shandong Province, China.

FCC ID: 2AJJGHJRF

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2021): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2020): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

PREPARED BY:**REVIEWED BY:**

Offa Zhou
Project Engineer

Wakeyou Wang
Reviewer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY.....	4
MEASUREMENT RESULT SUMMARY	5
1 GENERAL INFORMATION	6
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	6
1.2 TECHNICAL SPECIFICATION	6
1.3 DESCRIPTION OF TEST FACILITY	7
2 TEST SPECIFICATIONS.....	8
2.1 STANDARDS OR SPECIFICATION	8
2.2 MODE OF OPERATION DURING THE TEST.....	8
2.3 TEST SOFTWARE LIST	9
2.4 TEST PERIPHERALS LIST	9
2.5 TEST ENVIRONMENT CONDITION:.....	9
2.6 INSTRUMENT LIST	10
2.7 MEASUREMENT UNCERTAINTY	11
3 RADIATED EMISSION	12
3.1 LIMIT	12
3.2 MEASUREMENT PROCEDURE	12
3.3 TEST CONFIGURATION	14
3.4 TEST RESULTS OF RADIATED EMISSIONS	16

Revision History

Report No.	Version	Description	Issued Date
230800726HAN-001	Rev. 01	Initial issue of report	September 13, 2023

Measurement result summary

TEST ITEM	FCC REFERENCE	RESULT
Radiated emission	15.249 & 15.209	Pass
Power line conducted emission	15.207	NA
Assigned bandwidth (20dB bandwidth)	15.215(c)	NA
Antenna requirement	15.203	NA

Notes: 1: NA =Not Applicable
 2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.
 3: Additions, Deviations and Exclusions from Standards: None.

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Module
Type/Model:	HJ RF
Description of EUT:	The report is C2PC report, the following host models were added. Host models HJSR79B and HJSR79C have the same PCB except for the number of buttons. Therefore, host models HJSR79 and HJSR79B were tested.
Host models:	HJSR79, HJSR79B, HJSR79C
Rating:	DC 3.7V
EUT type:	☒ Table top ☐ Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	August 17, 2023
Date of test:	August 24, 2023 ~ September 1, 2023

1.2 Technical Specification

Frequency Range:	2405MHz ~ 2480MHz
Type of Modulation:	FSK
Channel Number:	151 channels
Channel Separation:	0.5 MHz
Antenna Information:	PCB antenna, 0dBi

TEST REPORT

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-4243, G-845, C-4723, T-2252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2021)

ANSI C63.10 (2020)

2.2 Mode of operation during the test

The host devices are handheld devices, so three axes (X, Y, Z) were observed while the test receiver worked as “max hold” continuously and the highest reading among the whole test procedure was recorded.

The lowest, middle and highest channel were tested as representatives.

Mode	Lowest (MHz)	Middle (MHz)	Highest (MHz)
-	2405	2440	2480

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Band and Model	Description
1			

2.5 Test environment condition:

Test items	Temperature	Humidity
Radiated emission	25°C	46% RH

2.6 Instrument list

Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESIB 26	EC 3045	2024-07-18
☒	Spectrum analyzer	Agilent	E7402A	EC 2254	2024-07-17
☒	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2024-08-23
☒	Pre-amplifier	R&S	AFS42-00101800-25-S-42	EC5262	2024-06-04
☒	Horn antenna	ETS	3117	EC 4792-1	2024-08-28
Tet Site					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Semi-anechoic chamber	Albatross project	-	EC 3048	2024-07-08
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 5198	2024-03-08

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	$\pm 0.74\text{dB}$
Radiated Emissions in restricted frequency bands below 1GHz	$\pm 4.90\text{dB}$
Radiated Emissions in restricted frequency bands above 1GHz	$\pm 5.02\text{dB}$
Emission outside the frequency band	$\pm 2.89\text{dB}$
Power line conducted emission	$\pm 3.19\text{dB}$

3 Radiated emission

Test result: PASS

3.1 Limit

Fundamental Frequency (MHz)	Fundamental limit (dBuV/m)	Harmonic limit (dBuV/m)
☐ 902 - 928	94	54
☒ 2400 - 2483.5	94	54
☐ 5725 - 5875	94	54
☐ 24000 - 24250	108	68

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

3.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

TEST REPORT**For Radiated emission above 30MHz:**


- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or $3 \times \text{RBW}$ (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported

3.3 Test Configuration


For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:



For Radiated emission above 1GHz:



TEST REPORT

3.4 Test Results of Radiated Emissions

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Test data below 1GHz:

HJSR79:

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	512.187	31.2	20.6	46.0	-14.8	PK
H	566.022	33.3	21.4	46.0	-12.7	PK
H	641.876	34.6	23.4	46.0	-11.4	PK
H	708.321	36.1	24.2	46.0	-9.9	PK
H	842.181	37.0	25.3	46.0	-9.0	PK
H	949.172	38.3	26.6	46.0	-7.7	PK
V	30.194	25.0	16.1	40.0	-15.0	PK
V	507.628	30.6	20.4	46.0	-15.4	PK
V	563.694	32.9	21.5	46.0	-13.1	PK
V	667.872	34.7	23.6	46.0	-11.3	PK
V	803.672	36.2	25.0	46.0	-9.8	PK
V	918.326	37.6	26.3	46.0	-8.4	PK

TEST REPORT

HJSR79B:

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	30.194	25.5	16.1	40.0	-14.5	PK
H	421.104	29.4	18.8	46.0	-16.6	PK
H	499.092	31.3	20.1	46.0	-14.7	PK
H	609.672	33.8	22.8	46.0	-12.2	PK
H	730.049	35.8	24.2	46.0	-10.2	PK
H	958.581	37.9	26.5	46.0	-8.1	PK
V	30.776	25.5	15.5	40.0	-14.5	PK
V	474.842	30.6	19.5	46.0	-15.4	PK
V	536.340	33.4	22.0	46.0	-12.6	PK
V	629.072	34.7	23.6	46.0	-11.3	PK
V	725.587	36.5	24.3	46.0	-9.5	PK
V	929.578	37.9	26.7	46.0	-8.1	PK

TEST REPORT

Test result above 1GHz:

HJSR79:

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2405.00	92.53	9.17	114.00	21.47	PK
	V	2405.00	91.88	9.59	114.00	22.12	PK
	H	2390.00	48.14	9.19	74.00	25.86	PK
	V	2390.00	50.10	9.61	74.00	23.90	PK
	H	4810.00	44.50	9.13	74.00	29.50	PK
	V	4810.00	43.37	9.24	74.00	30.63	PK
	H	7215.00	49.04	8.59	74.00	24.96	PK
	H	7215.00	40.38	8.59	54.00	13.62	AV
	V	7215.00	48.13	8.69	74.00	25.87	PK
	V	7215.00	39.74	8.69	54.00	14.26	AV
M	H	2440.00	92.44	9.09	114.00	21.56	PK
	V	2440.00	92.10	9.51	114.00	21.90	PK
	H	4880.00	44.56	9.13	74.00	29.44	PK
	V	4880.00	43.79	9.31	74.00	30.21	PK
	H	7320.00	48.32	8.56	74.00	25.68	PK
	H	7320.00	38.33	8.56	54.00	15.67	AV
	V	7320.00	50.35	8.66	74.00	23.65	PK
	V	7320.00	39.98	8.66	54.00	14.02	AV
H	H	2480.00	91.84	9.00	114.00	22.16	PK
	V	2480.00	91.00	9.40	114.00	23.00	PK
	H	2483.50	60.06	8.98	74.00	13.94	PK
	V	2483.50	60.21	9.39	74.00	13.79	PK
	H	4960.00	43.78	9.12	74.00	30.22	PK
	V	4960.00	44.07	9.38	74.00	29.93	PK
	H	7440.00	49.84	8.52	74.00	24.16	PK
	H	7440.00	40.37	8.52	54.00	13.63	AV
	V	7440.00	49.90	8.62	74.00	24.1	PK
	V	7440.00	40.52	8.62	54.00	13.48	AV

TEST REPORT

HJSR79B:

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2405.00	92.00	9.17	114.00	22.00	PK
	V	2405.00	92.23	9.59	114.00	21.77	PK
	H	2390.00	51.75	9.19	74.00	22.25	PK
	V	2390.00	51.08	9.61	74.00	22.92	PK
	H	4810.00	44.50	9.13	74.00	29.50	PK
	V	4810.00	45.09	9.24	74.00	28.91	PK
	H	7215.00	50.11	8.59	74.00	23.89	PK
	H	7215.00	42.80	8.59	54.00	11.20	AV
	V	7215.00	49.05	8.69	74.00	24.95	PK
	V	7215.00	40.23	8.69	54.00	13.77	AV
M	H	2440.00	91.98	9.09	114.00	22.02	PK
	V	2440.00	92.07	9.51	114.00	21.93	PK
	H	4880.00	45.64	9.13	74.00	28.36	PK
	V	4880.00	44.85	9.31	74.00	29.15	PK
	H	7320.00	44.58	8.56	74.00	29.42	PK
	H	7320.00	36.31	8.56	54.00	17.69	AV
	V	7320.00	49.33	8.66	74.00	24.67	PK
	V	7320.00	41.76	8.66	54.00	12.24	AV
H	H	2480.00	91.95	9.00	114.00	22.05	PK
	V	2480.00	92.06	9.40	114.00	21.94	PK
	H	2483.50	58.11	8.98	74.00	15.89	PK
	V	2483.50	59.37	9.39	74.00	14.63	PK
	H	4960.00	44.94	9.12	74.00	29.06	PK
	V	4960.00	44.24	9.38	74.00	29.76	PK
	H	7440.00	47.42	8.52	74.00	26.58	PK
	H	7440.00	38.80	8.52	54.00	15.20	AV
	V	7440.00	49.31	8.62	74.00	24.69	PK
	V	7440.00	40.30	8.62	54.00	13.70	AV

TEST REPORT

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
 2. Corrected Reading = Original Receiver Reading + Correct Factor
 3. Margin = Limit - Corrected Reading
 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
 Limit = 40.00dBuV/m.
 Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20\text{dB/m}$;
 Corrected Reading = $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$;
 Margin = $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$.

***** END *****