


FCC RF EXPOSURE REPORT

FCC ID: 2ARNB-DTSWL G3

Project No. : 2503C220
Equipment : Data Transfer Stick
Brand Name : Hoymiles
Test Model : DTS-WL-G3
Series Model : N/A
Applicant : Hoymiles Power Electronics Inc.
Address : No. 18 Kangjing Road, Hangzhou, Zhejiang Province, P.R. China
Manufacturer : Hoymiles Power Electronics Inc.
Address : No. 18 Kangjing Road, Hangzhou, Zhejiang Province, P.R. China
Factory : Hoymiles Power Electronics Inc.
Address : No.149 Kangzhong Road, Hangzhou 310015, Zhejiang Province, P.R. China
Date of Receipt : Mar. 19, 2025
Date of Test : Mar. 20, 2025 ~ Apr. 17, 2025
Issued Date : Apr. 24, 2025
Report Version : R00
Test Sample : Engineering Sample No.: DG20250319241
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091 & KDB 447498 D01 v06

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by :


Nick Chen

Approved by :


Chay Cai

Room 108-116, 309-310, Building 2, No.1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong, People's Republic of China.

Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

REVISION HISTORY

| Report No. | Version | Description | Issued Date | Note |
|---------------------|---------|------------------|---------------|-------|
| BTL-FCCP-3-2503C220 | R00 | Original Report. | Apr. 24, 2025 | Valid |

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

2. ANTENNA SPECIFICATION

| Ant. | Brand | P/N | Antenna Type | Connector | Gain (dBi) |
|------|----------------|------------------|--------------|-----------|------------|
| 1 | SLEing® | SLEingA248970045 | FPC | MHF | -1.27 |

Note: The antenna gain is provided by the manufacturer.

3. CALCULATED RESULT

For BT LE:

| Antenna Gain (dBi) | Antenna Gain (numeric) | Max. Output Power (dBm) | Max. Output Power (mW) | Power Density (S) (mW/cm ²) | Limit of Power Density (S) (mW/cm ²) | Test Result |
|--------------------|------------------------|-------------------------|------------------------|---|--|-------------|
| -1.27 | 0.7464 | 18.64 | 73.1139 | 0.01086 | 1 | Complies |

For 2.4GHz:

| Antenna Gain (dBi) | Antenna Gain (numeric) | Max. Output Power (dBm) | Max. Output Power (mW) | Power Density (S) (mW/cm ²) | Limit of Power Density (S) (mW/cm ²) | Test Result |
|--------------------|------------------------|-------------------------|------------------------|---|--|-------------|
| -1.27 | 0.7464 | 20.85 | 121.6186 | 0.01807 | 1 | Complies |

Note:

- (1) The calculated distance is 20 cm.
- (2) Ratio=Power Density (S) (mW/cm²)/Limit of Power Density (S) (mW/cm²)
- (3) BT LE and WLAN 2.4GHz can not simultaneous transmission.

End of Test Report