



# FCC TEST REPORT

**REPORT NO.:** RF920819R01

**MODEL NO.:** WLC3030

**RECEIVED:** Aug. 19, 2003

**TESTED:** Sep. 1~ Sep. 4, 2003

**APPLICANT:** ASKEY COMPUTER CORP.

**ADDRESS:** 10F,NO.119, CHIENKANG RD.,CHUNG-HO,TAIPEI TAIWAN R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** 47 14th Lin, Chiapau Tsun, Linko, Taipei, Taiwan, R.O.C.

This test report consists of 70 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528  
ILAC MRA



Lab Code: 200102-0



## Table of Contents

1	CERTIFICATION .....	4
2	SUMMARY OF TEST RESULTS .....	5
3	GENERAL INFORMATION .....	6
3.1	GENERAL DESCRIPTION OF EUT .....	6
3.2	DESCRIPTION OF TEST MODES .....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	7
3.4	DESCRIPTION OF SUPPORT UNITS .....	8
3.5	CONFIGURATION OF SYSTEM UNDER TEST .....	8
4	TEST TYPES AND RESULTS .....	9
4.1	CONDUCTED EMISSION MEASUREMENT .....	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	9
4.1.2	TEST INSTRUMENTS .....	9
4.1.3	TEST PROCEDURES .....	10
4.1.4	DEVIATION FROM TEST STANDARD .....	10
4.1.5	TEST SETUP .....	11
4.1.6	EUT OPERATING CONDITIONS .....	11
4.1.7	TEST RESULTS .....	12
4.2	RADIATED EMISSION MEASUREMENT .....	18
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	18
4.2.2	TEST INSTRUMENTS .....	19
4.2.3	TEST PROCEDURES .....	20
4.2.4	DEVIATION FROM TEST STANDARD .....	20
4.2.5	TEST SETUP .....	21
4.2.6	EUT OPERATING CONDITIONS .....	21
4.2.7	TEST RESULTS .....	22
4.2.8	TEST RESULTS (A) .....	23
4.2.9	TEST RESULTS (B) .....	26
4.3	6dB BANDWIDTH MEASUREMENT .....	30
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	30
4.3.2	TEST INSTRUMENTS .....	30
4.3.3	TEST PROCEDURE .....	30
4.3.4	DEVIATION FROM TEST STANDARD .....	31
4.3.5	TEST SETUP .....	31
4.3.6	EUT OPERATING CONDITIONS .....	31
4.3.7	TEST RESULTS (A) .....	32




4.3.8	TEST RESULTS (B) .....	36
4.4	MAXIMUM PEAK OUTPUT POWER .....	42
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	42
4.4.2	TEST INSTRUMENTS .....	42
4.4.3	TEST PROCEDURES .....	43
4.4.4	DEVIATION FROM TEST STANDARD .....	43
4.4.5	TEST SETUP .....	43
4.4.6	EUT OPERATING CONDITIONS .....	43
4.4.7	TEST RESULTS (A) .....	44
4.4.8	TEST RESULTS (B) .....	45
4.5	POWER SPECTRAL DENSITY MEASUREMENT .....	46
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	46
4.5.2	TEST INSTRUMENTS .....	46
4.5.3	TEST PROCEDURE .....	46
4.5.4	DEVIATION FROM TEST STANDARD .....	47
4.5.5	TEST SETUP .....	47
4.5.6	EUT OPERATING CONDITIONS .....	47
4.5.7	TEST RESULTS (A) .....	48
4.5.8	TEST RESULTS (B) .....	52
4.5.9	BAND EDGES MEASUREMENT .....	58
4.5.10	LIMITS OF BAND EDGES MEASUREMENT .....	58
4.5.11	TEST INSTRUMENTS .....	58
4.5.12	TEST PROCEDURE .....	58
4.5.13	DEVIATION FROM TEST STANDARD .....	58
4.5.14	EUT OPERATING CONDITION .....	59
4.5.15	TEST RESULTS (A) .....	59
4.5.16	TEST RESULTS (B) .....	62
4.6	ANTENNA REQUIREMENT .....	67
4.6.1	STANDARD APPLICABLE .....	67
4.6.2	ANTENNA CONNECTED CONSTRUCTION .....	67
5	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	68
6	INFORMATION ON THE TESTING LABORATORIES .....	70



## 1 CERTIFICATION

**PRODUCT :** Wireless LAN PCMCIA Card  
**BRAND NAME :** Askey  
**MODEL NO. :** WLC3030  
**TEST ITEM:** ENGINEERING SAMPLE  
**APPLICANT :** ASKEY COMPUTER CORP.  
**STANDARDS :** 47 CFR Part 15, Subpart C (Section 15.247),  
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Sep. 1~ Sep. 4, 2003. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

**PREPARED BY:**  , **DATE:** Sep. 08, 2003

Stephanie Chung

**APPROVED BY:**  **DATE:** Sep. 08, 2003

Dr. Alan Lane, JVP

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -14.76dB at 0.174MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -5.50dB at 7384.80MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Wireless LAN PCMCIA Card
<b>MODEL NO.</b>	WLC3030
<b>POWER SUPPLY</b>	3.3VDC from host equipment
<b>MODULATION TYPE</b>	DBPSK,DQPSK,CCK,16QAM,64QAM
<b>RADIO TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	up to 54Mbps (Turbo mode: up to 108Mbps *see note 1)
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>OUTPUT POWER</b>	18.02dBm
<b>ANTENNA TYPE</b>	Printed antenna
<b>ANTENNA GAIN</b>	0.81dBi
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	PCMCIA
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. This EUT is capable of providing data rates of up to 108Mbps in Turbo Mode depending upon reception quality.
2. This product was provided to Turbo technique at channel 6.
3. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
4. The EUT complies with IEEE 802.11g draft standards, and backwards compatible with IEEE 802.11b products.
5. For a more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

**NOTE:**

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. Data rate 11Mbps with CCK technique and 6Mbps with OFDM technique, the worst case, was chosen for final test.
4. Two test results were presented in the following sections, the test result A is for CCK technique and the test result B is for OFDM technique.

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Wireless LAN PCMCIA Card. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 15, Subpart C. (15.247)**  
**ANSI C63.4 : 1992**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

### 3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	Dell	PP01L	TW-09C748-12800-16M-5064	FCC DoC Approved
2	PRINTER	EPSON	LQ-300+	DCGY017054	FCC DoC Approved
3	600 $\Omega$ Load	NA	NA	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	NA

**NOTE:** All power cords of the above support units are non shielded (1.8m).

### 3.5 CONFIGURATION OF SYSTEM UNDER TEST





## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESHS 30	828765/002	July 15, 2004
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	835239/001	Apr. 28, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	835239/002	Apr. 28, 2004
ROHDE & SCHWARZ 4-wire ISN	ENY41	935154/007	Apr. 30 2004
ROHDE & SCHWARZ 2-wire ISN	ENY22	833823/026	Apr. 30, 2004
Software	Cond-V2M3	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C09.01	May. 23, 2004
SUHNTER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010789	Jun. 04, 2004

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. “\*”: These equipment are used for conducted telecom port test only (if tested).
  3. The test was performed in ADT Shielded Room No. 9.
  4. The VCCI Site Registration No. is C-1312.




#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



- Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.6 EUT OPERATING CONDITIONS


- Plug the EUT a notebook computer system placed on a testing table.
- The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- The computer system sent "H" messages to its screen.
- The computer system sent "H" messages to modem.
- The computer system sent "H" messages to printer, and the printer prints them on paper.

## 4.1.7 TEST RESULTS

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	30deg. C, 60%RH, 991 hPa	<b>TESTED BY:</b> Hardaway Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.174	0.10	49.91	-	50.01	-	64.77	54.77	-14.76	-
2	0.231	0.12	42.34	-	42.46	-	62.41	52.41	-19.96	-
3	0.291	0.15	39.13	-	39.28	-	60.50	50.50	-21.22	-
4	3.367	0.27	29.20	-	29.47	-	56.00	46.00	-26.53	-
5	5.624	0.38	19.86	-	20.24	-	60.00	50.00	-39.76	-
6	20.639	1.13	28.17	-	29.30	-	60.00	50.00	-30.70	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	30deg. C, 60%RH, 991 hPa	<b>TESTED BY:</b> Hardaway Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.10	47.45	-	47.55	-	64.63	54.63	-17.08	-
2	0.231	0.12	40.61	-	40.73	-	62.41	52.41	-21.69	-
3	0.288	0.14	34.53	-	34.67	-	60.58	50.58	-25.91	-
4	4.009	0.20	31.30	-	31.50	-	56.00	46.00	-24.50	-
5	21.167	0.92	26.43	-	27.35	-	60.00	50.00	-32.65	-
6	26.921	1.04	27.76	-	28.80	-	60.00	50.00	-31.20	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	30deg. C, 60%RH, 991 hPa	<b>TESTED BY:</b> Hardaway Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.174	0.10	48.65	-	48.75	-	64.77	54.77	-16.02	-
2	0.234	0.12	41.80	-	41.92	-	62.31	52.31	-20.39	-
3	0.291	0.15	38.65	-	38.80	-	60.50	50.50	-21.70	-
4	3.904	0.30	29.05	-	29.35	-	56.00	46.00	-26.65	-
5	18.527	1.04	26.38	-	27.42	-	60.00	50.00	-32.58	-
6	26.321	1.33	28.42	-	29.75	-	60.00	50.00	-30.25	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	30deg. C, 60%RH, 991 hPa	<b>TESTED BY:</b> Hardaway Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.174	0.10	48.17	-	48.27	-	64.77	54.77	-16.50	-
2	0.234	0.12	40.85	-	40.97	-	62.31	52.31	-21.34	-
3	0.408	0.20	31.55	-	31.75	-	57.69	47.69	-25.94	-
4	4.015	0.20	33.00	-	33.20	-	56.00	46.00	-22.80	-
5	20.843	0.92	27.47	-	28.39	-	60.00	50.00	-31.61	-
6	27.143	1.04	27.17	-	28.21	-	60.00	50.00	-31.79	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	30deg. C, 60%RH, 991 hPa	<b>TESTED BY:</b> Hardaway Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.10	48.25	-	48.35	-	64.63	54.63	-16.28	-
2	0.231	0.12	39.25	-	39.37	-	62.41	52.41	-23.05	-
3	0.294	0.15	38.23	-	38.38	-	60.41	50.41	-22.03	-
4	3.799	0.29	33.97	-	34.26	-	56.00	46.00	-21.74	-
5	19.871	1.09	27.42	-	28.51	-	60.00	50.00	-31.49	-
6	26.648	1.33	27.97	-	29.30	-	60.00	50.00	-30.70	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	30deg. C, 60%RH, 991 hPa	<b>TESTED BY:</b> Hardaway Lee	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.10	46.91	-	47.01	-	64.63	54.63	-17.62	-
2	0.234	0.12	40.59	-	40.71	-	62.31	52.31	-21.60	-
3	0.291	0.15	35.29	-	35.44	-	60.50	50.50	-25.06	-
4	3.913	0.20	35.23	-	35.43	-	56.00	46.00	-20.57	-
5	18.047	0.86	27.83	-	28.69	-	60.00	50.00	-31.31	-
6	26.399	1.03	28.03	-	29.06	-	60.00	50.00	-30.94	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
*HP Spectrum Analyzer	8590L	3520A00667	Aug. 28, 2004
CHASE Preamplifier	CPA9231A/4	3215	Nov. 06, 2003
* HP Preamplifier	8449B	3008A01201	Dec. 01, 2003
* HP Preamplifier	8449B	3008A01292	Aug. 11, 2004
* ROHDE & SCHWARZ TEST RECEIVER	ESVS10	846285/012	Aug. 28, 2004
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Feb. 13, 2004
SCHAFFNER Tunable Dipole Antenna	VHBA 9123	459	Nov. 22, 2003
SCHWARZBECK Tunable Dipole Antenna	UHA 9105	977	
* CHASE BILOG Antenna	CBL6112B	2751	Mar. 21, 2004
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	Jun. 30, 2004
* EMCO Horn Antenna	3115	9312-4192	Mar. 23, 2004
* CHANCE Turn Table & Tower Controller	ACS-I	NA	NA
* Software	ADT_Radiated_V5.14	NA	NA
* ANRITSU RF Switches	MP59B	M51167	Aug. 16, 2004
* TIMES RF cable	LMR-600	CABLE-ST6-01	Aug. 20, 2004

- NOTE:** 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. "\*" = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. 6.
5. The VCCI Site Registration No. is R-728.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

## 4.2.7 TEST RESULTS

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	Below 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 70 % RH, 991 hPa	<b>TESTED BY:</b> Steven Lu	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	179.68	30.3 QP	43.50	-13.20	2.00 H	265	17.80	12.50
2	199.12	33.5 QP	43.50	-10.00	1.25 H	316	22.20	11.20
3	247.72	34.6 QP	46.00	-11.40	1.50 H	250	21.30	13.30
4	335.19	30.4 QP	46.00	-15.60	1.00 H	85	14.30	16.00
5	381.84	32.6 QP	46.00	-13.40	1.00 H	256	15.30	17.20
6	401.28	34.7 QP	46.00	-11.30	1.00 H	343	16.90	17.80
7	420.72	29.4 QP	46.00	-16.60	1.00 H	55	11.00	18.40
8	453.77	29.8 QP	46.00	-16.20	1.75 H	268	10.40	19.40
9	601.50	34.0 QP	46.00	-12.00	1.25 H	241	11.40	22.60
10	650.10	31.2 QP	46.00	-14.80	1.00 H	220	7.90	23.30
11	681.20	31.2 QP	46.00	-14.80	1.00 H	214	7.50	23.70
12	704.53	35.4 QP	46.00	-10.60	1.50 H	295	11.30	24.10
13	735.63	33.0 QP	46.00	-13.00	1.25 H	328	8.00	25.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	136.91	28.9 QP	43.50	-14.60	1.00 V	169	15.40	13.50
2	251.60	31.7 QP	46.00	-14.30	2.00 V	28	18.30	13.40
3	311.86	28.3 QP	46.00	-17.70	1.50 V	4	12.80	15.40
4	379.90	31.3 QP	46.00	-14.70	1.25 V	16	14.10	17.20
5	459.60	30.7 QP	46.00	-15.30	1.75 V	190	11.30	19.40
6	525.69	28.7 QP	46.00	-17.30	1.00 V	160	8.10	20.60
7	601.50	28.4 QP	46.00	-17.60	1.25 V	265	5.80	22.60
8	704.53	32.8 QP	46.00	-13.20	1.00 V	313	8.70	24.10
9	757.01	30.9 QP	46.00	-15.10	1.25 V	142	5.60	25.40
10	922.24	33.1 QP	46.00	-12.90	2.00 V	55	5.70	27.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.

## 4.2.8 TEST RESULTS (A)

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 70 % RH, 991 hPa	<b>TESTED BY:</b> Steven Lu	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	43.3 PK	74.00	-30.70	1.45 H	8	11.80	31.50
1	2390.00	34.6 AV	54.00	-19.40	1.45 H	8	3.10	31.50
2	*2412.00	103.2 PK			1.45 H	8	71.70	31.50
2	*2412.00	94.5 AV			1.45 H	8	63.00	31.50
3	4824.00	55.3 PK	74.00	-18.70	1.04 H	240	17.50	37.90
3	4824.00	40.4 AV	54.00	-13.60	1.04 H	240	2.60	37.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2412.00	102.1 PK			1.23 V	355	70.60	31.50
1	*2412.00	93.7 AV			1.23 V	355	62.20	31.50
2	4824.00	51.9 PK	74.00	-22.10	1.20 V	196	14.10	37.90
2	4824.00	39.4 AV	54.00	-14.60	1.20 V	196	1.50	37.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency
  6. The other emission levels were very low against the limit.

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 70 % RH, 991 hPa	<b>TESTED BY:</b> Steven Lu	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	109.3 PK			1.00 H	169	77.80	31.50
1	*2437.00	100.7 AV			1.00 H	169	69.10	31.50
2	4874.20	52.9 PK	74.00	-21.10	1.25 H	259	15.00	37.90
2	4874.20	38.7 AV	54.00	-15.30	1.25 H	259	0.80	37.90
3	7336.00	57.7 PK	74.00	-16.30	1.40 H	213	15.30	42.40
3	7336.00	44.8 AV	54.00	-9.20	1.40 H	213	2.40	42.40
4	9748.50	57.9 PK	74.00	-16.10	1.40 H	160	13.10	44.80
4	9748.50	44.3 AV	54.00	-9.70	1.40 H	160	-0.50	44.80

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	98.5 PK			1.15 V	231	67.00	31.50
1	*2437.00	93.5 AV			1.15 V	231	62.00	31.50
2	4874.00	51.5 PK	74.00	-22.50	1.08 V	167	13.50	37.90
2	4874.00	37.8 AV	54.00	-16.20	1.08 V	167	-0.10	37.90
3	7311.00	60.7 PK	74.00	-13.30	1.44 V	255	18.40	42.30
3	7311.00	48.3 AV	54.00	-5.70	1.44 V	255	6.00	42.30
4	9748.00	58.7 PK	74.00	-15.30	1.44 V	255	13.90	44.80
4	9748.00	47.9 AV	54.00	-6.10	1.44 V	255	3.00	44.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency
  6. The other emission levels were very low against the limit.



<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 70 % RH, 991 hPa	<b>TESTED BY:</b> Steven Lu	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	106.8 PK			1.00 H	167	75.20	31.60
1	*2462.00	98.8 AV			1.00 H	167	67.20	31.60
2	2483.50	53.6 PK	74.00	-20.40	1.00 H	167	22.00	31.60
2	2483.50	39.7 AV	54.00	-14.30	1.00 H	167	8.10	31.60
3	4924.00	51.6 PK	74.00	-22.40	1.50 H	201	13.60	38.00
3	4924.00	37.7 AV	54.00	-16.30	1.50 H	201	-0.30	38.00
4	7384.60	56.8 PK	74.00	-17.20	1.50 H	270	14.40	42.40
4	7384.60	43.6 AV	54.00	-10.40	1.50 H	270	1.10	42.40

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	100.3 PK			1.06 V	203	68.70	31.60
1	*2462.00	91.3 AV			1.06 V	203	59.70	31.60
2	4924.00	54.2 PK	74.00	-19.80	1.50 V	244	16.20	38.00
2	4924.00	39.1 AV	54.00	-14.90	1.50 V	244	1.00	38.00
3	7384.80	58.5 PK	74.00	-15.50	1.03 V	241	16.00	42.40
3	7384.80	48.5 AV	54.00	-5.50	1.03 V	241	6.10	42.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency
  6. The other emission levels were very low against the limit.

## 4.2.9 TEST RESULTS (B)

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 1, Normal Mode	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 70 % RH, 991 hPa	<b>TESTED BY:</b> Steven Lu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	51.4 PK	74.00	-22.60	1.44 H	123	19.90	31.50
1	2390.00	39.6 AV	54.00	-14.40	1.44 H	123	8.10	31.50
2	*2412.00	101.4 PK			1.44 H	123	69.90	31.50
2	*2412.00	89.6 AV			1.44 H	123	58.10	31.50
3	4826.30	51.5 PK	74.00	-22.50	1.20 H	242	13.70	37.90
3	4826.30	37.8 AV	54.00	-16.20	1.20 H	242	-0.10	37.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2412.00	98.2 PK			1.17 V	162	66.70	31.50
1	*2412.00	86.7 AV			1.17 V	162	55.20	31.50
2	4824.00	51.0 PK	74.00	-23.00	1.07 V	65	13.20	37.90
2	4824.00	36.8 AV	54.00	-17.20	1.07 V	65	-1.00	37.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency
  6. The other emission levels were very low against the limit.

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 6, Normal Mode	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 70 % RH, 991 hPa	<b>TESTED BY:</b> Steven Lu	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	101.3 PK			1.10 H	123	69.80	31.50
1	*2437.00	90.0 AV			1.10 H	123	58.40	31.50
2	4874.00	51.1 PK	74.00	-22.90	1.32 H	256	13.20	37.90
2	4874.00	38.2 AV	54.00	-15.80	1.32 H	256	0.20	37.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	97.4 PK			1.45 V	24	65.90	31.50
1	*2437.00	87.0 AV			1.45 V	24	55.50	31.50
2	4874.00	50.1 PK	74.00	-23.90	1.00 V	132	12.20	37.90
2	4874.00	37.4 AV	54.00	-16.60	1.00 V	132	-0.60	37.90

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ \* “ : Fundamental frequency
6. The other emission levels were very low against the limit.

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 11, <b>Normal Mode</b>	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 70 % RH, 991 hPa	<b>TESTED BY:</b> Steven Lu	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	101.6 PK			1.40 H	123	70.10	31.60
1	*2462.00	89.8 AV			1.40 H	123	58.20	31.60
2	2483.50	53.5 PK	74.00	-20.30	1.40 H	123	21.90	31.60
2	2483.50	41.7 AV	54.00	-12.30	1.40 H	123	10.10	31.60
3	4918.80	49.5 PK	74.00	-24.50	1.69 H	71	11.50	38.00
3	4918.80	36.7 AV	54.00	-17.30	1.69 H	71	-1.30	38.00

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	98.3 PK			1.14 V	159	66.80	31.60
1	*2462.00	87.4 AV			1.14 V	159	55.80	31.60
2	4925.00	52.1 PK	74.00	-21.90	1.57 V	76	14.00	38.00
2	4925.00	37.8 AV	54.00	-16.20	1.57 V	76	-0.30	38.00

**REMARKS:**

- 1.Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
- 2.Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3.The other emission levels were very low against the limit.
- 4.Margin value = Emission level – Limit value.
- 5.“ \* ” : Fundamental frequency
- 6.The other emission levels were very low against the limit.

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>MODE</b>	Channel 6, Turbo Mode	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 70 % RH, 991 hPa	<b>TESTED BY:</b> Steven Lu	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	50.3 PK	74.00	-23.70	1.00 H	166	18.70	31.50
1	2390.00	39.1 AV	54.00	-14.90	1.00 H	166	7.60	31.50
2	*2437.00	101.9 PK			1.00 H	166	70.30	31.50
2	*2437.00	90.7 AV			1.00 H	166	59.20	31.50
3	2483.50	46.8 PK	74.00	-29.50	1.00 H	166	15.20	31.60
3	2483.50	35.6 AV	54.00	-18.40	1.00 H	166	4.00	31.60
4	4874.00	50.6 PK	74.00	-23.40	1.00 H	360	12.60	37.90
4	4874.00	37.3 AV	54.00	-16.70	1.00 H	360	-0.70	37.90

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2435.00	95.5 PK			1.41 V	155	64.00	31.50
1	*2435.00	82.3 AV			1.41 V	155	50.70	31.50
2	4874.00	52.9 PK	74.00	-21.10	1.31 V	110	14.90	37.90
2	4874.00	38.7 AV	54.00	-15.30	1.31 V	110	0.80	37.90

#### REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ \* ” : Fundamental frequency
6. The other emission levels were very low against the limit.

### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP



#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




## 4.3.7 TEST RESULTS (A)

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 65%RH, 991 hPa
<b>TESTED BY:</b> Steven Lu			


<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	10.96	0.5	PASS
6	2437	11.29	0.5	PASS
11	2462	11.68	0.5	PASS




CH1



CH6



CH11





#### 4.3.8 TEST RESULTS (B)

##### For Normal Mode

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 65%RH, 991 hPa
<b>TESTED BY:</b> Steven Lu			


<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	16.60	0.5	PASS
6	2437	16.60	0.5	PASS
11	2462	16.56	0.5	PASS

\*RBW 100 kHz Delta 1 [T1] 0.34 dB  
 \*VBW 100 kHz  
 Ref 10.5 dBm \*Att 30 dB SWT 5 ms 16.600000000 MHz


Marker	1 [T1]	Level [dBm]
D1	2.403720000 GHz	-8.45 dBm
D2	-	-8.7 dBm
F1	-	-
F2	-	-

Center 2.412 GHz Span 20 MHz  
 2 MHz/

CH6



CH11




**For Turbo Mode**

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 65%RH, 991 hPa
<b>TESTED BY:</b> Steven Lu			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
6	2437	32.88	0.5	PASS



CH6



#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004
R&S SIGNAL GENERATOR	SMP04	100011	May 28, 2004
TEKTRONIX OSCILLOSCOPE	TDS 220	B048470	Mar. 05, 2004
NARDA DETECTOR	4503A	FSCM99899	NA

**NOTE:**

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA..

#### 4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

#### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.5 TEST SETUP



#### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.



## 4.4.7 TEST RESULTS (A)

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 65%RH, 991 hPa
<b>TESTED BY:</b> Steven Lu			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	18.00	30	PASS
6	2437	18.02	30	PASS
11	2462	17.50	30	PASS



## 4.4.8 TEST RESULTS (B)

## For Normal Mode

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 65%RH, 991 hPa
<b>TESTED BY:</b> Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	16.60	30	PASS
6	2437	17.20	30	PASS
11	2462	17.00	30	PASS

## For Turbo Mode

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 65%RH, 991 hPa
<b>TESTED BY:</b> Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
6	2437	16.02	30	PASS

## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.5.5 TEST SETUP



#### 4.5.6 EUT OPERATING CONDITIONS

Same as 4.3.6




## 4.5.7 TEST RESULTS (A)

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 65%RH, 991 hPa
<b>TESTED BY:</b> Steven Lu			


<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-5.79	8	PASS
6	2437	-3.82	8	PASS
11	2462	-6.19	8	PASS




CH1



CH6



CH11






## 4.5.8 TEST RESULTS (B)

## For Normal Mode


<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 65%RH, 991 hPa
<b>TESTED BY:</b> Steven Lu			

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-9.91	8	PASS
6	2437	-11.14	8	PASS
11	2462	-8.39	8	PASS


CH1



CH6



CH11




**For Turbo Mode**

<b>EUT</b>	Wireless LAN PCMCIA Card	<b>MODEL</b>	WLC3030
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 65%RH, 991 hPa
<b>TESTED BY:</b> Steven Lu			

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
6	2437	-10.88	8	PASS



CH6



#### 4.5.9 BAND EDGES MEASUREMENT

#### 4.5.10 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

#### 4.5.11 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.5.12 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

#### 4.5.13 DEVIATION FROM TEST STANDARD

No deviation



#### 4.5.14 EUT OPERATING CONDITION

Same as Item 4.3.6


#### 4.5.15 TEST RESULTS (A)


The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

**NOTE:**

The band edge emission plot on the following first pages shows 56.09dB delta between carrier maximum power and local maximum emission in restrict band (2.390GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 94.5dBuV/m, so the maximum field strength in restrict band is  $94.5 - 56.09 = 38.41$ dBuV/m which is under 54 dBuV/m limit.

The band edge emission plot on the following second pages shows 57.72dB delta between carrier maximum power and local maximum emission in restrict band (2.4865Hz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 98.8dBuV/m, so the maximum field strength in restrict band is  $98.8 - 57.72 = 41.08$ dBuV/m which is under 54 dBuV/m limit.







#### 4.5.16 TEST RESULTS (B)

The spectrum plots are attached on the following 4 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

##### **For Normal Mode**

##### **NOTE:**

The band edge emission plot on the following first pages shows 46.38dB delta between carrier maximum power and local maximum emission in restrict band (2.3892GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 89.6dBuV/m, so the maximum field strength in restrict band is  $89.6 - 46.38 = 43.22$  dBuV/m which is under 54 dBuV/m limit.


The band edge emission plot on the following second pages shows 43.66dB delta between carrier maximum power and local maximum emission in restrict band (2.4837GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 89.8dBuV/m, so the maximum field strength in restrict band is  $89.8 - 43.66 = 43.66$  dBuV/m which is under 54 dBuV/m limit.


##### **For Turbo Mode**

##### **NOTE:**

The band edge emission plot on the following 3-4 pages shows 49.02dB/51.66dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz/2.4839GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.9 is 90.7dBuV/m, so the maximum field strength in restrict band is  $90.7 - 49.02 = 41.68$  dBuV/m which is under 54 dBuV/m limit.


## For Normal Mode








## For Turbo Mode







## **4.6 ANTENNA REQUIREMENT**

### **4.6.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **4.6.2 ANTENNA CONNECTED CONSTRUCTION**


The maximum Gain antenna used in this product is Printed antenna without antenna connector. And the maximum Gain of these antennas is 0.81 dBi.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

### CONDUCTED EMISSION TEST



## RADIATED EMISSION TEST





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>New Zealand</b>	MoC
<b>Norway</b>	NEMKO
<b>R.O.C.</b>	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC Lab:**

Tel: 886-35-935343

Fax: 886-35-935342

**Lin Kou Safety Lab:**

Tel: 886-2-26093195

Fax: 886-2-26093184

**Lin Kou RF&Telecom Lab**

Tel: 886-3-3270910

Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.