

FCC Test Report

Report No.: AGC00803230804FR02

FCC ID : 2AKHJ-HD357-3

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Wireless Keyboard

BRAND NAME : N/A

MODEL NAME : HD357-3

APPLICANT: Shenzhen Hangshi Electronic Technology Co., Ltd

DATE OF ISSUE : Aug. 28, 2023

STANDARD(S) : FCC Part 15.247

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 44

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Aug. 28, 2023	Valid	Initial Release






TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION 2.2. TABLE OF CARRIER FREQUENCYS 2.3. RELATED SUBMITTAL(S)/GRANT(S). 2.4. TEST METHODOLOGY 2.5. SPECIAL ACCESSORIES. 2.6. EQUIPMENT MODIFICATIONS. 2.7. ANTENNA REQUIREMENT 2.8. DUTY CYCLE MEASUREMENT	
3. MEASUREMENT UNCERTAINTY	
4. DESCRIPTION OF TEST MODES	9
5. SYSTEM TEST CONFIGURATION	10
5.1. CONFIGURATION OF TESTED SYSTEM	10
6. TEST FACILITY	11
7. PEAK OUTPUT POWER	12
7.1. MEASUREMENT PROCEDURE	12
8. BANDWIDTH	15
8.1. MEASUREMENT PROCEDURE	
9. CONDUCTED SPURIOUS EMISSION	19
9.1. MEASUREMENT PROCEDURE	19 19
10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	26
10.1. MEASUREMENT PROCEDURE	26 26
11. RADIATED EMISSION	28
11.1. MEASUREMENT PROCEDURE	29 30
12. LINE CONDUCTED EMISSION TEST	40
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	40

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Web: http://www.agccert.com/



Report No.: AGC00803230804FR02 Page 4 of 44



Page 5 of 44

1. VERIFICATION OF COMPLIANCE

Applicant	Shenzhen Hangshi Electronic Technology Co., Ltd
Address	2nd Floor, A1 Building, G Area, Democracy West Industry Area, Shajing Town, Bao'an District, Shenzhen, China.
Manufacturer Shenzhen Hangshi Electronic Technology Co., Ltd	
Address	2nd Floor, A1 Building, G Area, Democracy West Industry Area, Shajing Town, Bao'an District, Shenzhen, China.
Factory	Shenzhen Hangshi Electronic Technology Co., Ltd
Address	2nd Floor, A1 Building, G Area, Democracy West Industry Area, Shajing Town, Bao'an District, Shenzhen, China.
Product Designation	Wireless Keyboard
Brand Name	N/A
Test Model	HD357-3
Date of receipt of test item	Aug. 17, 2023
Date of test	Aug. 17, 2023 to Aug. 28, 2023
Deviation	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Report Template	AGCRT-US-BLE/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Prepared By	Alan Duan	
	Alan Duan (Project Engineer)	Aug. 28, 2023
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Aug. 28, 2023
Approved By	Max Zhang	
	Max Zhang (Authorized Officer)	Aug. 28, 2023



Page 6 of 44

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as a "Wireless Keyboard". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz	
RF Output Power	-4.604dBm (Max)	
Bluetooth Version	V5.0	
Modulation	BR □GFSK, EDR □π /4-DQPSK, □8DPSK BLE □GFSK 1Mbps □GFSK 2Mbps	
Number of channels	40 Channel	
Antenna Designation	PCB Antenna (Comply with requirements of the FCC part 15.203)	
Antenna Gain	2.34dBi	
Hardware Version	V1.0	
Software Version	V3.0	
Power Supply	DC 3.7V by battery or DC 5V by adapter	

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency	
	0	2402 MHz	
	1	2404 MHz	
2400~2483.5MHz	:	:	
	38	2478 MHz	
	39	2480 MHz	

Page 7 of 44

2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2AKHJ-HD357-3** filing to comply with the FCC Part 15.247 requirements.

2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

2.5. SPECIAL ACCESSORIES

Refer to section 5.2.

2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX II: PHOTOGRAPHS OF EUT.

2.8. DUTY CYCLE MEASUREMENT


2.4GHz WLAN (DTS) operation is possible in 20MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(us)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)	Average Factor (dB)
BLE_1Mbps	0.283	45	3.47	3.53	-6.94

Remark:

1. Duty Cycle factor = 10 * log (1/ Duty cycle) 2. Average factor = 20 log10 Duty Cycle
The duty cycle of each frequency band mode reflects the determination requirements of the low channel
measurement value

The test plots as follows:






Page 8 of 44

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2.7 \%$
Uncertainty of Occupied Channel Bandwidth	U _c = ±2 %





4. DESCRIPTION OF TEST MODES

Summary Table of Test Cases				
	Data Rate / Modulation			
Test Item	Bluetooth – LE / GFSK			
Radiated&Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps			
AC Conducted Emission	Mode 1: Bluetooth Link + Battery + USB Cable (Charging from AC Adapter)			

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

 Software Setting Diagram



Wireless function cannot function while charging.




Page 10 of 44

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:



Conducted Emission Configure:

EUT	AE

5.2. EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Wireless Keyboard	HD357-3	2AKHJ-HD357-3	EUT
2	Control Box	N/A	USB-TTL	AE
3	Adapter	Huawei	HW-200325CP0	AE

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant



Page 11 of 44

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

	1201 24011 1112111 01 0011200122 21111001011 1201							
Equipment		Manufacturer	Model	S/N	Cal. Date	Cal. Due		
	TEST RECEIVER	R&S	ESPI	101206	Jun. 03, 2023	Jun. 02, 2024		
	LISN	R&S	ESH2-Z5	100086	Jun. 03, 2023	Jun. 02, 2024		
Test software		R&S	ES-K1(Ver.V1.71)	N/A	N/A	N/A		

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Feb. 18, 2023	Feb. 17, 2024
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Jun. 01, 2023	May 31, 2024
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	Jun. 01, 2023	May 31, 2024
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Mar. 23, 2023	Mar. 22, 2024
Broadband Preamplifier	ETS LINDGREN	3117-PA	00246148	Aug. 04, 2022	Aug. 03, 2024
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 05, 2023	Jan. 04, 2025
Test software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A



Page 12 of 44

7. PEAK OUTPUT POWER


7.1. MEASUREMENT PROCEDURE


For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer
- 2. RBW ≥ DTS bandwidth
- 3. VBW≥3*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external cables.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP








7.3. LIMITS AND MEASUREMENT RESULT


	10. 2 7 7 7 7 7 7						
Test Data of Conducted Output Power							
Test Mode	Test Channel (MHz)	Limits (dBm)	Pass or Fail				
	2402	-5.050	≤30	Pass			
GFSK 1M	2440	-4.723	≤30	Pass			
	2480	-4.604	≤30	Pass			

Test Graphs of Conducted Output Power











Page 15 of 44

8. BANDWIDTH

8.1. MEASUREMENT PROCEDURE

6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW ≥ 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel
 The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video
 bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.


Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.


8.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and DTS Bandwidth							
Test Mode Test Channel (MHz)		I Randwidth I		Test Mode Test Channel Bandwidth Bandwidth		-6dB Bandwidth Limits (MHz)	Pass or Fail
	2402	1.258	0.807	≥0.5	Pass		
GFSK 1M	2440	1.239	0.775	≥0.5	Pass		
	2480	1.205	0.724	≥0.5	Pass		























Test_Graph_LE1M_ANT1_2480_1Mbps_DTSBW

x dB

723.6 kHz



Page 19 of 44

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


The same as described in section 7.2.

9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

9.4. LIMITS AND MEASUREMENT RESULT

J.H. EIMITO AND MEAGOREMENT REGOET					
LIMITS AND MEASUREMENT RESULT					
Applicable Limite	Measurement Result				
Applicable Limits	Test Data	Criteria			
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS			






Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands Avg Type: Log-Pwr Avg|Hold: 10/10 Frequency Center Freq 2.402000000 GHz Trig: Free Run #Atten: 30 dB IFGain:Low **Auto Tune** Mkr1 2.402 052 3 GHz -5.320 dBm Ref 20.00 dBm 10 dB/div Center Freq 2.402000000 GHz Start Freq 2.400500000 GHz Stop Freq 2.403500000 GHz CF Step 300.000 kHz Auto Man Frea Offset 0 Hz Center 2.402000 GHz #Res BW 100 kHz Span 3.000 MHz Sweep 2.000 ms (30000 pts) #VBW 300 kHz Test_Graph_LE1M_ANT1_2402_1Mbps_Reference Level Avg Type: Log-Pwr Avg|Hold: 10/10 Center Freq 1.210000000 GHz Frequency Trig: Free Run #Atten: 30 dB PNO: Fast ↔ IFGain:Low Mkr1 2.206 62 GHz -57.889 dBm **Auto Tune** Ref 20.00 dBm 10 dB/div Log Center Frea 1.210000000 GHz Start Freq 30.000000 MHz Stop Freq 2 390000000 GHz CF Step 236.000000 MHz <u>Auto</u> Freq Offset 0 Hz Stop 2.390 GHz Sweep 226.0 ms (30000 pts)

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test_Graph_LE1M_ANT1_2402_1Mbps_Lower Band Emissions

#VBW 300 kHz


Start 30 MHz #Res BW 100 kHz







































Freq Offset 0 Hz



Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands Avg Type: Log-Pwr Avg|Hold: 100/100 Frequency Center Freq 2.398500000 GHz Trig: Free Run #Atten: 30 dB TYPE **Auto Tune** Mkr2 2.400 000 0 GHz -45.305 dBm Ref 20.00 dBm Center Freq 2.398500000 GHz Start Freq 2.390000000 GHz Stop Freq Mount 2.407000000 GHz Stop 2.407000 GHz 2.000 ms (30000 pts) Start 2.390000 GHz #Res BW 100 kHz CF Step 1.700000 MHz **#VBW** 300 kHz Auto Man -5.016 dBm -45.305 dBm Freq Offset 0 Hz Test_Graph_LE1M_ANT1_2402_1Mbps_Lower Band Edge Emissions Avg Type: Log-Pwr Avg|Hold: 100/100 Frequency Center Freq 2.487500000 GHz PNO: Fast ---IFGain:Low Trig: Free Run #Atten: 30 dB **Auto Tune** Mkr2 2.483 500 0 GHz -60.697 dBm Ref 20.00 dBm Center Frea 2.487500000 GHz Start Freq 2.475000000 GHz Stop Freq 2 500000000 GHz Stop 2.50000 GHz Sweep 4.000 ms (30000 pts) Start 2.47500 GHz #Res BW 100 kHz **CF Step #VBW** 300 kHz 2.500000 MHz <u>Auto</u>

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_LE1M_ANT1_2480_1Mbps_Higher Band Edge Emissions

2.480 036 8 GHz 2.483 500 0 GHz

-4.648 dBm -60.697 dBm



Page 26 of 44

10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

10.1. MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer to Section 7.2.


10.3. MEASUREMENT EQUIPMENT USED


Refer to Section 6.

10.4. LIMITS AND MEASUREMENT RESULT


Test Data of Conducted Output Power Spectral Density						
Test Mode	Test Channel (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail		
	2402	-20.547	≤8	Pass		
GFSK 1M	2440	-20.067	≤8	Pass		
	2480	-19.935	≪8	Pass		

Test Graphs of Conducted Output Power Spectral Density











Page 28 of 44

11. RADIATED EMISSION


11.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.




11.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Page 30 of 44

11.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed


Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT

Radiated emission below 30MHz


The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.





Radiated emission from 30MHz to 1000MHz

EUT	Wireless Keyboard	Model Name	HD357-3
Temperature	22.8° C	Relative Humidity	58.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dΒ	Detector
1		42.7496	6.20	13.71	19.91	40.00	-20.09	peak
2		115.3205	6.28	16.35	22.63	40.00	-17.37	peak
3		291.0360	10.96	15.78	26.74	47.00	-20.26	peak
4		447.9822	6.44	24.82	31.26	47.00	-15.74	peak
5		679.9600	6.61	24.70	31.31	47.00	-15.69	peak
6	*	900.1474	8.31	31.78	40.09	47.00	-6.91	peak

RESULT: PASS



Page 32 of 44

EUT	Wireless Keyboard	Model Name	HD357-3
Temperature	22.8° C	Relative Humidity	58.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical



No. N	/lk. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dB/m	d₿	Detector
1	42.7496	7.77	16.93	24.70	40.00	-15.30	peak
2	87.1117	6.86	15.94	22.80	40.00	-17.20	peak
3	147.4036	6.52	18.20	24.72	43.50	-18.78	peak
4	256.5211	9.80	17.61	27.41	46.00	-18.59	peak
5	440.1963	6.41	26.09	32.50	46.00	-13.50	peak
6 *	714.1734	6.49	28.60	35.09	46.00	-10.91	peak

RESULT: PASS Note:

- 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.
- 2. All test modes had been tested. The mode 3 is the worst case and recorded in the report.



Page 33 of 44

Radiated emission above 1GHz

EUT	Wireless Keyboard	Model Name	HD357-3
Temperature	22.8° C	Relative Humidity	58.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	- Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	43.25	0.08	43.33	74	-30.67	peak
4804.000	35.48	0.08	35.56	54	-18.44	AVG
7206.000	38.56	2.21	40.77	74	-33.23	peak
7206.000	31.73	2.21	33.94	54	-20.06	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	Wireless Keyboard	Model Name	HD357-3
Temperature	22.8° C	Relative Humidity	58.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	44.13	0.08	44.21	74	-29.79	peak
4804.000	34.5	0.08	34.58	54	-19.42	AVG
7206.000	38.44	2.21	40.65	74	-33.35	peak
7206.000	30.25	2.21	32.46	54	-21.54	AVG
Remark:						

Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Page 34 of 44

EUT	Wireless Keyboard	Model Name	HD357-3
Temperature	22.8° C	Relative Humidity	58.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	44.76	0.14	44.9	74	-29.1	peak
4880.000	35.82	0.14	35.96	54	-18.04	AVG
7320.000	39.45	2.36	41.81	74	-32.19	peak
7320.000	31.69	2.36	34.05	54	-19.95	AVG
Remark:			•		•	•
actor = Anter	na Factor + Cabl	e Loss – Pre-	amplifier			

EUT	Wireless Keyboard	Model Name	HD357-3
Temperature	22.8° C	Relative Humidity	58.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	45.26	0.14	45.4	74	-28.6	peak
4880.000	38.59	0.14	38.73	54	-15.27	AVG
7320.000	40.48	2.36	42.84	74	-31.16	peak
7320.000	32.22	2.36	34.58	54	-19.42	AVG
Remark:						

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Page 35 of 44

EUT	Wireless Keyboard	Model Name	HD357-3
Temperature	22.8° C	Relative Humidity	58.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	44.43	0.22	44.65	74	-29.35	peak
4960.000	35.67	0.22	35.89	54	-18.11	AVG
7440.000	38.83	2.64	41.47	74	-32.53	peak
7440.000	29.25	2.64	31.89	54	-22.11	AVG
Remark:						
actor - Antor	na Factor + Cabl	alees Drag	amplifior			

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	Wireless Keyboard	Model Name	HD357-3
Temperature	22.8° C	Relative Humidity	58.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	42.84	0.22	43.06	74	-30.94	peak
4960.000	34.15	0.22	34.37	54	-19.63	AVG
7440.000	38.27	2.64	40.91	74	-33.09	peak
7440.000	29.56	2.64	32.2	54	-21.8	AVG
Remark:			•			1
Factor = Anter	nna Factor + Cab	e Loss – Pre-a	mplifier.			


RESULT: PASS

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin= Emission Level-Limit.

The "Factor" value can be calculated automatically by software of measurement system.







Test result for band edge emission at restricted bands


EUT	Wireless Keyboard	Model Name	HD357-3
Temperature	22.8° C	Relative Humidity	58.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Test Graph for Peak Measurement






RESULT: PASS







Wireless Keyboard **EUT Model Name** HD357-3 22.8° C **Temperature Relative Humidity** 58.6% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 1 **Antenna** Vertical

Test Graph for Peak Measurement





RESULT: PASS







EUT Wireless Keyboard **Model Name** HD357-3 22.8° C **Temperature Relative Humidity** 58.6% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 3 **Antenna** Horizontal

Test Graph for Peak Measurement





RESULT: PASS






EUT Model Name HD357-3 Wireless Keyboard 22.8° C **Temperature Relative Humidity** 58.6% 960hPa Normal Voltage **Pressure Test Voltage Test Mode** Mode 3 **Antenna** Vertical

Test Graph for Peak Measurement





RESULT: PASS

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



Page 40 of 44

12. LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

F	Maximum RF Line Voltage				
Frequency	Q.P.(dBuV)	Average(dBuV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Page 41 of 44

12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.



12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



MEASUREMENT RESULT: "agc_fin"

2023/8/22 9:54

2023/8/22 9:54						
Frequency	Level	Transd	Limit	Margin	Detector	Line
MHz	dBuV	dB	dBuV	dB		
	'		'			
0.154000	42.80	6.1	66	23.0	QP	L1
0.302000	33.20	6.1	60	27.0	QP	L1
0.454000	30.50	6.1	57	26.3	QP	L1
0.506000	39.50	6.2	56	16.5	QP	L1
0.878000	29.00	6.2	56	27.0	QP	L1
1.058000	28.40	6.2	56	27.6	QP	L1


MEASUREMENT RESULT: "agc fin2"

2023/8/22 9:54

2023/8/22 9:54						
Frequency	Level	Transd	Limit	Margin	Detector	Line
MHz	dΒμV	dB	dΒμV	dB		
0.454000	27.60	6.1	47	19.2	AV	L1
0.506000	37.10	6.2	46	8.9	AV	L1
0.530000	36.50	6.2	46	9.5	AV	L1
0.554000	27.40	6.2	46	18.6	AV	L1
0.854000	25.60	6.2	46	20.4	AV	L1
1.182000	25.00	6.2	46	21.0	AV	L1



Line Conducted Emission Test Line 2-N



MEASUREMENT RESULT: "agc_fin"

2023/8/22 Frequen	су	Level	Transd	Limit	_	Detector	Line
	Hz	dΒμV	dB	dΒμV	dB		
0.1620		37.60	6.1	65	27.8	QP	N
0.4620 0.5060		33.20	6.1	57	23.5	QP	N
0.5060		41.70 41.10	6.2 6.2	56 56	14.3 14.9	QP OP	N N
0.8060		27.50	6.2	56	28.5	OP	N
1.0340		30.50	6.2	56	25.5	QP	N

MEASUREMENT RESULT: "agc fin2"

2023/8/22 9:57 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.458000	21.50	6.1	47	25.2	AV	N
0.506000	35.10	6.2	46	10.9	AV	N
0.530000	31.30	6.2	46	14.7	AV	N
0.554000	18.80	6.2	46	27.2	AV	N
0.830000	18.70	6.2	46	27.3	AV	N
1.110000	19.80	6.2	46	26.2	AV	N

RESULT: PASS



Page 44 of 44

APPENDIX I: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC00803230804AP02

APPENDIX II: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC00803230804AP03

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.