

**Advanced  
Compliance Laboratory**

*210 Cougar Court  
Hillsborough, NJ 08844  
Tel: (908) 927 9288  
Fax: (908) 927 0728*

---

**FCC CFR47 PART 15 SUBPART C & IC RSS-247**

**TEST REPORT**

**For**

**SOMFY SYSTEMS INC.**

**Soness2 40 R2 Zigbee HP4/36FC  
Soness2 40 R2 Zigbee HP6/24FC  
Soness2 40 R2 Zigbee HP9/14FC**

**Model Number: 5172631A, 5172632A, 5172633A**

**FCC ID: DWN SON40ZB  
IC: 12049A-SON40ZB**

**Report Number: 0048-240110-01**

*Prepared for*

**SOMFY SYSTEMS INC.  
121 Herrod Blvd.  
Dayton, NJ 08810  
USA**

*Prepared by*

**Advanced Compliance Laboratory, Inc.  
210 Cougar Court  
Hillsborough, NJ 08844  
Tel: (908) 927 9288  
Fax: (908) 927 0728**

**Date: 02/05/2024**

## TABLE OF CONTENTS

|                                                      |    |
|------------------------------------------------------|----|
| 1. TEST RESULT CERTIFICATION .....                   | 3  |
| 2. EUT DESCRIPTION .....                             | 5  |
| 3. TEST METHODOLOGY .....                            | 7  |
| 4. FACILITIES AND ACCREDITATION .....                | 7  |
| 5. CALIBRATION AND UNCERTAINTY .....                 | 8  |
| 5.1. MEASURING INSTRUMENT CALIBRATION .....          | 8  |
| 5.2. MEASUREMENT UNCERTAINTY .....                   | 8  |
| 5.3. TEST AND MEASUREMENT EQUIPMENT .....            | 9  |
| 6. SETUP OF EQUIPMENT UNDER TEST .....               | 10 |
| 7. APPLICABLE LIMITS AND TEST RESULTS .....          | 11 |
| 7.1 6dB &99% BANDWIDTH .....                         | 11 |
| 7.2 PEAK OUTPUT POWER.....                           | 17 |
| 7.3 MAXIMUM PERMISSIBLE EXPOSURE .....               | 22 |
| 7.4 AVERAGE OUTPUT POWER.....                        | 26 |
| 7.5 PEAK POWER SPECTRAL DENSITY .....                | 27 |
| 7.6 CONDUCTED SPURIOUS EMISSIONS.....                | 31 |
| 7.7 RADIATED EMISSIONS .....                         | 38 |
| 7.7.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS ..... | 38 |
| 7.7.2. TRANSMITTER RADIATED EMISSIONS DATA .....     | 40 |
| 7.8 CONDUCTED EMISSION .....                         | 47 |
| 7.9 EUT RECEIVING MODE VERIFICATION.....             | 50 |
| 8. SETUP PHOTOS .....                                | 51 |
| 9. APPENDIX .....                                    | 56 |

## 1. TEST RESULT CERTIFICATION

**COMPANY NAME:** SOMFY SYSTEMS INC.

**EUT Name(s)/PMN:** Sonesse2 40 R2 Zigbee HP4/36FC,  
Sonesse2 40 R2 Zigbee HP6/24FC, Sonesse2 40 R2 Zigbee HP9/14

**EUT Model(s)/HVIN:** 5172631A, 5172632A, 5172633A

**DATE TESTED:** 01/10/2024 to 02/05/2024

| APPLICABLE STANDARDS                                  |                         |
|-------------------------------------------------------|-------------------------|
| STANDARD                                              | TEST RESULTS            |
| FCC Part 15.247 & IC RSS-247:Issue 2& RSS-Gen Issue 5 | NO NON-COMPLIANCE NOTED |

### Test Summary

| Testing Items Per FCC Part 2/ Part 15.247 & IC RSS-247 /RSS-Gen Standard Requirements for DTS Modulation | Section                          | Limit                                       | Result   |
|----------------------------------------------------------------------------------------------------------|----------------------------------|---------------------------------------------|----------|
| DTS Bandwidth                                                                                            | 15.247(a) (2)<br>RSS-247, 5.2(a) | $\geq 500\text{KHz}$                        | Complies |
| Peak Power Limit                                                                                         | 15.247(b) (3)<br>RSS-247, 5.4(d) | Conducted: 1W (30dBm)<br>e.i.r.p. 4W(36dBm) | Complies |
| Peak Power Spectral Density                                                                              | 15.247(e)<br>RSS-247, 5.2(b)     | 8dBm/3KHz                                   | Complies |
| Emissions ( Conducted)                                                                                   | 15.247(d)<br>RSS-247, 5.5        | -20dB/-30dB                                 | Complies |
| Spurious ( Radiated)                                                                                     | 15.205(a)<br>RSS-247, 5.5        | 15.209/RSS-Gen                              | Complies |
| RF Safety*                                                                                               | 1.1310/RSS-102                   | 1.0/5.0 mW/cm <sup>2</sup>                  | Complies |

NOTE: \* For mobile or fixed location transmitters, the minimum separation distance is 20 cm, even if calculations indicate that the MPE distance would be less.

Advanced Compliance Laboratory, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note :** This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Advanced Compliance Laboratory, Inc. (ACL) and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by ACL, Advanced Compliance Laboratory, Inc. will constitute fraud and shall nullify the document.

Approved & Released For ACL By:

Tested By:



---

Wei Li

---

David Tu

Manager  
Advanced Compliance Laboratory, Inc.

EMC Engineer

## 2. EUT DESCRIPTION

The EUT for this certification is a low power transmitter, using digital modulation & operating in the 2400 MHz band.

The transmitter has a maximum peak conducted output power as follows:

### ZIGBEE Mode:

| Frequency /Range (MHz) | Rated Power Selection | Tested Peak Power (dBm/W)* | Max. EIRP (W) |
|------------------------|-----------------------|----------------------------|---------------|
| 2405-2480              | 13dBm/0.020W          | 12.67/0.0185               | 0.032         |
|                        |                       |                            |               |

Frequency band: 2.400 to 2.4835 GHz


Channel spacing: 5 MHz

16 channels are available

Modulation: OQPSK

Coding: DSSS

PCB antenna gain: +2dBi



### Bluetooth Low Energy (BLE) Mode:

| Frequency /Range (MHz) | Rated Power Selection | Tested Peak Power (dBm/W)* | Max. EIRP (W) |
|------------------------|-----------------------|----------------------------|---------------|
| 2402-2480              | 3dBm/0.002W           | 2.49 / 0.0177              | 0.003         |
|                        |                       |                            |               |

Frequency band: 2.400 to 2.4835 GHz

Channel spacing: 2 MHz

40 channels are available

Modulation: GFSK

PCB antenna gain: +2dBi

## Channel List:

| Channel number           | Standard frequency & maximum tolerance |
|--------------------------|----------------------------------------|
| 37 (Advertising channel) | 2402 MHz $\pm 150$ kHz                 |
| 0                        | 2404 MHz $\pm 150$ kHz                 |
| 1                        | 2406 MHz $\pm 150$ kHz                 |
| 2                        | 2408 MHz $\pm 150$ kHz                 |
| 3                        | 2410 MHz $\pm 150$ kHz                 |
| 4                        | 2412 MHz $\pm 150$ kHz                 |
| 5                        | 2414 MHz $\pm 150$ kHz                 |
| 6                        | 2416 MHz $\pm 150$ kHz                 |
| 7                        | 2418 MHz $\pm 150$ kHz                 |
| 8                        | 2420 MHz $\pm 150$ kHz                 |
| 9                        | 2422 MHz $\pm 150$ kHz                 |
| 10                       | 2424 MHz $\pm 150$ kHz                 |
| 38 (Advertising channel) | 2426 MHz $\pm 150$ kHz                 |
| 11                       | 2428 MHz $\pm 150$ kHz                 |
| 12                       | 2430 MHz $\pm 150$ kHz                 |
| 13                       | 2432 MHz $\pm 150$ kHz                 |
| 14                       | 2434 MHz $\pm 150$ kHz                 |
| 15                       | 2436 MHz $\pm 150$ kHz                 |
| 16                       | 2438 MHz $\pm 150$ kHz                 |
| 17                       | 2440 MHz $\pm 150$ kHz                 |

| Channel number           | Standard frequency & maximum tolerance |
|--------------------------|----------------------------------------|
| 18                       | 2442 MHz $\pm 150$ kHz                 |
| 19                       | 2444 MHz $\pm 150$ kHz                 |
| 20                       | 2446 MHz $\pm 150$ kHz                 |
| 21                       | 2448 MHz $\pm 150$ kHz                 |
| 22                       | 2450 MHz $\pm 150$ kHz                 |
| 23                       | 2452 MHz $\pm 150$ kHz                 |
| 24                       | 2454 MHz $\pm 150$ kHz                 |
| 25                       | 2456 MHz $\pm 150$ kHz                 |
| 26                       | 2458 MHz $\pm 150$ kHz                 |
| 27                       | 2460 MHz $\pm 150$ kHz                 |
| 28                       | 2462 MHz $\pm 150$ kHz                 |
| 29                       | 2464 MHz $\pm 150$ kHz                 |
| 30                       | 2466 MHz $\pm 150$ kHz                 |
| 31                       | 2468 MHz $\pm 150$ kHz                 |
| 32                       | 2470 MHz $\pm 150$ kHz                 |
| 33                       | 2472 MHz $\pm 150$ kHz                 |
| 34                       | 2474 MHz $\pm 150$ kHz                 |
| 35                       | 2476 MHz $\pm 150$ kHz                 |
| 36                       | 2478 MHz $\pm 150$ kHz                 |
| 39 (Advertising channel) | 2480 MHz $\pm 150$ kHz                 |


### 3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2014/C63.10-2013, FCC CFR 47 Part 2 & 15 & IC RSS-247:Issue 2& RSS-Gen Issue 5. Test procedure described in FCC “KDB 558074 D01 DTS Measurement Guidance ” is used in this report.

### 4. FACILITIES AND ACCREDITATION

The test sites / measurement facilities for Advanced Compliance Laboratory, Inc.(ACL) to collect data are located at 210 Cougar Court, Hillsborough, New Jersey, USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, “Radio Interference Measuring Apparatus and Measurement Methods”.

This site is accepted by FCC to perform measurements under Part 15 or 18 (MRA#US5347) and also designated by IC as “ site IC 3130A”. ACL is recognized by ISED as a wireless testing laboratory ( CAB ID: US0100) . The NVLAP Lab code for accreditation of FCC EMC Test Method is: 200101-0. is accredited by NVLAP, Laboratory Code 200101-0. The full accreditation can be viewed at <http://www.ac-lab.com>.



No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.

## 5. CALIBRATION AND UNCERTAINTY

### 5.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 5.2. MEASUREMENT UNCERTAINTY

The estimated uncertainty of the test result is given as following. The method of uncertainty calculation is provided in Advanced Compliance Lab. Doc. No. 0048-01-01.

|                                 | Prob. Dist. | Uncertainty(dB) | Uncertainty(dB) | Uncertainty(dB) |
|---------------------------------|-------------|-----------------|-----------------|-----------------|
|                                 |             | 30-1000MHz      | 1-6.5GHz        | Conducted       |
| Combined Std. Uncertainty $u_c$ | norm.       | $\pm 2.36$      | $\pm 2.99$      | $\pm 1.83$      |

### 5.3. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

| Manufacturer     | Model           | Serial No.  | Description                      | Last Cal<br>mm/dd/<br>yy | Cal Due<br>Mm/dd/<br>yy |
|------------------|-----------------|-------------|----------------------------------|--------------------------|-------------------------|
| Agilent          | E4440A          | US40420700  | 3Hz-26.5GHz Spec. Analyzer       | 17/06/23                 | 17/06/24                |
| R & S            | ESPI            | 100018      | 9KHz-7GHz EMI Receiver           | 15/01/23                 | 15/01/25                |
| HP               | HP8546A         | 3448A00290  | 9kHz to 6.5GHz EMI Receiver      | 25/09/23                 | 25/09/24                |
| EMCO             | 3104C           | 9307-4396   | 20-300MHz Biconical Antenna      | 12/11/23                 | 12/11/24                |
| EMCO             | 3146            | 9008-2860   | 200-1000MHz Log-Periodic Antenna | 13/11/23                 | 13/11/24                |
| Electro-Meterics | ALR-25M/30      | 289         | 10KHz-30MHz Active Loop Antenna  | 28/05/23                 | 28/05/24                |
| EMCO             | 3115            | 4945        | Double Ridge Guide Horn Antenna  | 28/11/23                 | 28/11/24                |
| R&S              | SMH             | 8942280/010 | Signal Generator                 | 15/01/23                 | 15/01/25                |
| RES-NET          | RFA500NFF<br>30 | 0108        | 30dB in-line Power Attenuator    | 15/01/23                 | 15/01/25                |

All Test Equipment Used is Calibrated, Traceable to NIST Standards.

## 6. SETUP OF EQUIPMENT UNDER TEST

### SUPPORT EQUIPMENT

None.

### TEST SETUP

Testing Frequency/Channel/Port Selection: **Zigbee Mode**

- Selected Channel Frequency = 2405MHz, 2445 MHz, 2480MHz
- For intentional radiator measurements, 2405/2445/2480 MHz transmitter was configured to transmit continuously.

Testing Frequency/Channel/Port Selection: **BLE Mode**

- Selected Channel Frequency = 2402MHz, 2442 MHz, 2480MHz
- For intentional radiator measurements, 2402/2442/2480 MHz transmitter was configured to transmit continuously. The EUT was powered by 120Vac

### Engineering Justification:

The Sonesse 40 ZigBee are Somfy actuator compatible with Zigbee protocol (for usage) and BLE protocol (only for setting with Tahoma pro App). These 3 actuators share same electronic boards (main board and media board) for the Zigbee radio and same software, but different motor torque.

|                                                         |                                |
|---------------------------------------------------------|--------------------------------|
| 1245920 - Kit reference<br>5172631A - Product reference | SONESSE2 40 R2 Zigbee HP4/36FC |
| 1245921 – Kit reference<br>5172632A – Product reference | SONESSE2 40 R2 Zigbee HP6/24FC |
| 1245922 – Kit reference<br>5172633A – Product reference | SONESSE2 40 R2 Zigbee HP9/14FC |

Therefore, conducted measurements at antenna port were performed on one of actuators, SONESSE2 40 R2 Zigbee HP4/36FC. The radiated measurements were performed on each model. The worst case data was reported in this application.

## 7. APPLICABLE LIMITS AND TEST RESULTS

### 7.1 6dB &99% BANDWIDTH

#### LIMIT

§15.247 (a) (2) & RSS-247 Sec.5.1(1): Min. 6dB DTS bandwidth should be no less than 500KHz.

#### TEST PROCEDURE *per FCC KDB 558074D01v05r02*

| Measurement Procedure for Emission Bandwidth (DTS Bandwidth)       | Applicable to this EUT              |
|--------------------------------------------------------------------|-------------------------------------|
| 8.2 DTS BW Measurement Procedure per Subclause 11.8 of ANSI C63.10 | <input checked="" type="checkbox"/> |

#### RESULTS

No non-compliance noted.


Zigbee Mode:

| Channel | Frequency (MHz) | 6dB Bandwidth (KHz) | 99% Bandwidth (KHz) |
|---------|-----------------|---------------------|---------------------|
| L       | 2405            | 1699                | 2264.2              |
| M       | 2445            | 1709                | 2268.4              |
| H       | 2480            | 1682                | 2276.3              |


Bluetooth Low Energy (BLE) Mode:

| Channel | Frequency (MHz) | 6dB Bandwidth (KHz) | 99% Bandwidth (KHz) |
|---------|-----------------|---------------------|---------------------|
| L       | 2402            | 533.6               | 1024.7              |
| M       | 2442            | 533.8               | 1024.6              |
| H       | 2480            | 532.9               | 1024.7              |


## 6dB & 99% BANDWIDTH\_Zigbee Mode (Res: 100kHz)




## 6dB & 99% BANDWIDTH \_ BLE Mode (ReS: 30kHz)




## 6dB & 99% BANDWIDTH \_ BLE Mode (Res: 100kHz)




## 6dB & 99% BANDWIDTH Zigbee Mode (Res: 100kHz)




## 6dB & 99% BANDWIDTH \_BLE Mode (Res: 30kHz)




## 6dB & 99% BANDWIDTH \_BLE Mode (Res: 100kHz)




## 6dB & 99% BANDWIDTH\_Zigbee Mode (Res: 100kHz)



## 6dB & 99% BANDWIDTH\_BLE Mode (Res: 30kHz)



## 6dB & 99% BANDWIDTH \_BLE Mode (Res: 100kHz)



## 7.2 PEAK OUTPUT POWER

### PEAK POWER LIMIT

§15.247 (b)(3) & RSS-247 Sec. 5.4(4)

The maximum peak conducted output power of the intentional radiator shall not exceed the following:  
For systems using digital modulation in the 900 MHz band: 1 Watt.

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

b(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Therefore, the applicable output power limit shall be calculated as follows:

$$P_{out} = 30 - (G_{tx} - 6) \text{ for antenna gain } \leq 6 \text{ dBi or}$$

$$P_{out} = 30 - \text{Floor}[(G_{tx} - 6)/3]$$

$G_{TX}$  = the maximum transmitting antenna directional gain in dBi.

### TEST PROCEDURE *per FCC KDB 558074D01v05r02*

| Measurement Procedure for Fundamental Emission Output Power*                                                                                                                                               | Applicable to this EUT                        |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| 8.3.1.1 Maximum Peak Conducted Output Power Level Measurement Procedure Option 1 (RBW ≥ DTS BW):<br>Per Subclause 11.9.1.1 of ANSI C63.10                                                                  | <input checked="" type="checkbox"/> preferred |
| 8.3.1.2 Maximum Peak Conducted Output Power Level Measurement Procedure Option 2 (RBW < DTS BW)<br>Integrated band power method: Prefer to use integrated average power measurement, as described in 8.3.2 | <input type="checkbox"/>                      |
| 8.3.1.3 Maximum Peak Conducted Output Power Level Measurement Procedure Option 3:<br>PKPM1 Peak-reading power meter method per Subclause 11.9.1.3 of ANSI C63.10                                           | <input type="checkbox"/>                      |

\* For measuring output power of a device transmitting a wide-band noise-like signal (i.e., digitally-modulated) where the peak power amplitude is a statistical parameter, the preferred methodology is to use integrated average power measurements, as described in 11.9.2 and 11.13.3 of ANSI C63.10.

No non-compliance noted.

### **OUTPUT PEAK POWER**

Summary of Peak Power Testing Data:


#### **Zigbee Mode**

| <b>Channel</b> | <b>Frequency (MHz)</b> | <b>Peak Power (dBm)</b> | <b>Limit (dBm)</b> | <b>Margin (dB)</b> |
|----------------|------------------------|-------------------------|--------------------|--------------------|
| Low            | 2405                   | 3.73                    | 30                 | -22.97             |
| Middle         | 2445                   | 12.67                   | 30                 | -14.39             |
| High           | 2480                   | 1.58                    | 30                 | -25.32             |


#### **BLE Mode**

| <b>Channel</b> | <b>Frequency (MHz)</b> | <b>Peak Power (dBm)</b> | <b>Limit (dBm)</b> | <b>Margin (dB)</b> |
|----------------|------------------------|-------------------------|--------------------|--------------------|
| Low            | 2402                   | 1.92                    | 30                 | -20.59             |
| Middle         | 2442                   | 2.13                    | 30                 | -20.13             |
| High           | 2480                   | 2.49                    | 30                 | -19.89             |

### Zigbee Mode:




### BLE Mode:






### Zigbee Mode:



### BLE Mode:



## 7.3 MAXIMUM PERMISSIBLE EXPOSURE

### LIMITS & RSS-102

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz)                                   | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|---------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                               |                               |                                     |                          |
| 0.3–3.0 .....                                           | 614                           | 1.63                          | *(100)                              | 6                        |
| 3.0–30 .....                                            | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | 6                        |
| 30–300 .....                                            | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300–1500 .....                                          | .....                         | .....                         | f/300                               | 6                        |
| 1500–100,000 .....                                      | .....                         | .....                         | 5                                   | 6                        |
| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 0.3–1.34 .....                                          | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34–30 .....                                           | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|-----------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| 30–300 .....          | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1500 .....        | .....                         | .....                         | f/1500                              | 30                       |
| 1500–100,000 .....    | .....                         | .....                         | 1.0                                 | 30                       |

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

## LIMITS per RSS-102, Table 1 & Section 2.5

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance<sup>4,5</sup>

| Frequency (MHz) | Exemption Limits (mW)           |                                 |                                 |                                 |                                 |
|-----------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
|                 | At separation distance of ≤5 mm | At separation distance of 10 mm | At separation distance of 15 mm | At separation distance of 20 mm | At separation distance of 25 mm |
| ≤300            | 71 mW                           | 101 mW                          | 132 mW                          | 162 mW                          | 193 mW                          |
| 450             | 52 mW                           | 70 mW                           | 88 mW                           | 106 mW                          | 123 mW                          |
| 835             | 17 mW                           | 30 mW                           | 42 mW                           | 55 mW                           | 67 mW                           |
| 1900            | 7 mW                            | 10 mW                           | 18 mW                           | 34 mW                           | 60 mW                           |
| 2450            | 4 mW                            | 7 mW                            | 15 mW                           | 30 mW                           | 52 mW                           |
| 3500            | 2 mW                            | 6 mW                            | 16 mW                           | 32 mW                           | 55 mW                           |
| 5800            | 1 mW                            | 6 mW                            | 15 mW                           | 27 mW                           | 41 mW                           |

| Frequency (MHz) | Exemption Limits (mW)           |                                 |                                 |                                 |                                  |
|-----------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|----------------------------------|
|                 | At separation distance of 30 mm | At separation distance of 35 mm | At separation distance of 40 mm | At separation distance of 45 mm | At separation distance of ≥50 mm |
| ≤300            | 223 mW                          | 254 mW                          | 284 mW                          | 315 mW                          | 345 mW                           |
| 450             | 141 mW                          | 159 mW                          | 177 mW                          | 195 mW                          | 213 mW                           |
| 835             | 80 mW                           | 92 mW                           | 105 mW                          | 117 mW                          | 130 mW                           |
| 1900            | 99 mW                           | 153 mW                          | 225 mW                          | 316 mW                          | 431 mW                           |
| 2450            | 83 mW                           | 123 mW                          | 173 mW                          | 235 mW                          | 309 mW                           |
| 3500            | 86 mW                           | 124 mW                          | 170 mW                          | 225 mW                          | 290 mW                           |
| 5800            | 56 mW                           | 71 mW                           | 85 mW                           | 97 mW                           | 106 mW                           |

### Per 2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- **at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;**
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

## CALCULATIONS

Given

$$E = \sqrt{(30 * P * G) / d}$$

and

$$S = E^2 / 3770$$

where

E = Field Strength in Volts/meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts/square centimeter

Combining equations and rearranging the terms to express the distance as a function of the remaining variables yields:

$$d = \sqrt{((30 * P * G) / (3770 * S))}$$

Changing to units of Power to mW and Distance to cm, using:

$$P(\text{mW}) = P(\text{W}) / 1000 \text{ and}$$

$$d(\text{cm}) = 100 * d(\text{m})$$

yields

$$d = 100 * \sqrt{((30 * (P / 1000) * G) / (3770 * S))}$$

$$d = 0.282 * \sqrt{(P * G / S)}$$

where

d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW/cm<sup>2</sup>

Substituting the logarithmic form of power and gain using: P

$$(\text{mW}) = 10^{(P(\text{dBm}) / 10)} \text{ and}$$

$$G(\text{numeric}) = 10^{(G(\text{dBi}) / 10)}$$

yields

$$d = 0.282 * 10^{((P + G) / 20)} / \sqrt{S}$$

Equation (1)

$$S = 0.0795 * 10^{((P + G) / 10)} / d^2$$

Equation (2)

where

d = MPE distance in cm

P = Power in dBm

G = Antenna Gain in dBi

S = Power Density Limit in mW/cm<sup>2</sup>

Equation (1) and the measured peak power is used to calculate the MPE distance.

Equation (2) and the measured peak power is used to calculate the Power density.

**APPLICABLE LIMITS** for separation  $\geq 20\text{cm}$

FCC: From §1.1310 Table 1 (B), for Public  $S = 1.0 \text{ mW/cm}^2$ ; for Professional,  $S = 5.0 \text{ mW/cm}^2$   
IC: With formula of  $1.31 \times 10^{-2} f^{0.6834} \text{ W}$ , more restricted EIRP limit value are 1.37W at 902MHz,  
2.67W at 2400MHz.

**RESULTS**

No non-compliance noted:

---For FCC, the worst case for this EUT,  $P+G=13+2=15\text{dBm}$ , and  $d=20\text{cm}$

Plug all three items into equation (2), yielding,

| Power Density Limit<br>( $\text{mW/cm}^2$ ) | Output Power<br>(dBm) | Antenna Gain<br>(dBi) | Power Density<br>( $\text{mW/cm}^2$ ) | Meet min. PD Limit |
|---------------------------------------------|-----------------------|-----------------------|---------------------------------------|--------------------|
| 1.0/5.0                                     | 13.0                  | 2.0                   | 0.006                                 | Yes                |

---For ISSED, EUT max. e.r.i.p  $=0.032\text{W} < \text{limit } 2.67\text{W}$

**Therefore, all of results are below the FCC/ISED limit.**

*NOTE: For mobile or fixed location transmitters, the minimum separation distance between the antenna & radiating structures of the device and nearby persons is 20 cm, even if calculations indicate that the MPE distance would be less.*

## 7.4 AVERAGE OUTPUT POWER

### AVERAGE POWER LIMIT

Section 15.247 permits the maximum conducted (average) output power to be measured as an alternative to the maximum peak conducted output power for demonstrating compliance to the limit. When this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth (see ANSI C63.10 for measurement guidance).

### TEST PROCEDURE *per FCC KDB 558074D01v05r02*

| Measurement Procedure for Fundamental Emission Output Power                                                                                                                   | Applicable to this EUT              |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| 8.3.2.2 Maximum Conducted (average) Output Power Level *<br>Measurement Procedure Option 1 (Measurement using a spectrum analyzer (SA): per Subclause 11.9.2.2 of ANSI C63.10 | <input type="checkbox"/>            |
| 8.3.2.3 Maximum Conducted (average) Output Power Level *<br>Measurement Procedure Option 2 (using a power meter(PM): per Subclause 11.9.2.3 of ANSI C63.10                    | <input checked="" type="checkbox"/> |

\* Alternative method. EUT shall be configured to transmit continuously (min. 98% duty cycle at full power). The spectrum analyzer shall be set for bin-to-bin spacing  $\leq$  RBW/2.

The transmitter output is connected to a RF broadband power meter.

### RESULTS

No non-compliance noted:

Zigbee Mode:

| Channel | Frequency (MHz) | Average Power (dBm) |
|---------|-----------------|---------------------|
| Low     | 2405            | 3.50                |
| Middle  | 2445            | 12.34               |
| High    | 2480            | 1.17                |

BLE Mode:

| Channel | Frequency (MHz) | Average Power (dBm) |
|---------|-----------------|---------------------|
| Low     | 2402            | 1.54                |
| Middle  | 2442            | 1.63                |
| High    | 2480            | 1.92                |

## 7.5 PEAK POWER SPECTRAL DENSITY

### LIMIT

§15.247 (e) & RSS-247 Sec. 5.2(2)

For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST PROCEDURE *per FCC KDB 558074D01v05r02*

| Measurement Procedure for Maximum Power Spectral Density in the Fundamental Emission                                                              | Applicable to this EUT                        |
|---------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| 8.4 Measurement Procedure Method PKPSD (peak PSD) per Subclause 11.10.2 of ANSI C63.10                                                            | <input checked="" type="checkbox"/> preferred |
| 8.4 Measurement Procedure for Average PSD** (6 methods: AVGPS-1 & Alt, AVGPS-2 & Alt, AVGPS-3 & Alt) per Subclause 11.10.3~11.10.8 of ANSI C63.10 | <input type="checkbox"/>                      |

### RESULTS

No non-compliance noted:

Summary of PPSD Testing Data:

Zigbee Mode:


| Channel | Frequency (MHz) | PPSD (dBm/3KHz) | Limit (dBm/3KHz) | Margin (dB) |
|---------|-----------------|-----------------|------------------|-------------|
| Low     | 2405            | -11.49          | 8                | -19.49      |
| Middle  | 2445            | -2.75           | 8                | -10.75      |
| High    | 2480            | -13.65          | 8                | -21.65      |

BlueTooth Mode:


| Channel | Frequency (MHz) | PPSD (dBm/3KHz) | Limit (dBm/3KHz) | Margin (dB) |
|---------|-----------------|-----------------|------------------|-------------|
| Low     | 2402            | -14.27          | 8                | -22.27      |
| Middle  | 2442            | -14.10          | 8                | -22.1       |
| High    | 2480            | -13.70          | 8                | -21.7       |

## PEAK POWER SPECTRAL DENSITY


Zigbee Mode:




BLE Mode:




## Zigbee Mode:




## BLE Mode:



## Zigbee Mode:



## BLE Mode:



## 7.6 CONDUCTED SPURIOUS EMISSIONS

### LIMITS

§15.247 (d) & RSS-247 Sec. 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) & RSS-Gen is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205 (a), must also comply with the radiated emission limits specified in §15.209(a) & RSS-Gen (see §15.205(c)).

### TEST PROCEDURE *per FCC KDB 558074D01v05r02,*

#### A. Section 8.5 DTS emissions in non-restricted frequency bands following the methods in Subclause 11.11 of ANSI C63.10

| Conducted Measurement Procedure for Maximum Unwanted Emissions into Non-Restricted Frequency Bands | Applicable to this EUT                        |                              |
|----------------------------------------------------------------------------------------------------|-----------------------------------------------|------------------------------|
|                                                                                                    | Peak Power limit: (-20dB)                     | Average Power Limit: (-30dB) |
| ANSI C63.10, Sec.11.11.1-11.11.2 Measurement Procedure-Reference Level (RBW=100KHz, VBW=300KHz)    | <input checked="" type="checkbox"/>           | <input type="checkbox"/>     |
| ANSI C63.10, Sec. 11.11.3 Measurement Procedure- Emission level*                                   | <input checked="" type="checkbox"/> preferred | <input type="checkbox"/>     |

\* Different attenuation limit shall be used based on the measurement method of fundamental emission power and PSD.

#### B. Section 8.6 DTS emissions in restricted frequency bands following the methods in Subclause 11.12 of ANSI C63.10

| Antenna-Port Conducted Measurement Procedure for Maximum Unwanted Emissions into Restricted Frequency Bands** | Applicable to this EUT   |
|---------------------------------------------------------------------------------------------------------------|--------------------------|
| ANSI C63.10, Sec.11.12.2.3 CISPR Quasi-Peak Measurement (CISPR 16)                                            | <input type="checkbox"/> |
| ANSI C63.10, Sec.11.12.2.4 Peak Power Measurement                                                             | <input type="checkbox"/> |
| ANSI C63.10, Sec.11.12.2.5 Average Power Measurement (three options)***                                       | <input type="checkbox"/> |

\*\* To use this conducted testing method, per 12.2.2-12.2.6, the followings shall be taken as consideration:

1. Proper RBW and detector, per 15.35 a/b, shall be chosen in different frequency ranges;
2. Maximum transmitter antenna gain ( no less than 2dBi), G, shall be added to the measured power level to determine the EIRP;
3. Appropriate factor, A, shall be added to model worst case ground reflections: 6.0dB ( f≤30MHz ) and 4.7dB ( f≤30 to 100MHz )
4. Electric field strength can be obtained from the equation:  $E = \text{EIRP} - 20\log(d) + 104.8 + G \text{ (or } 2.0) + A$ ; Then compare to applicable limit;
5. Unwanted emissions from EUT cabinet or casing shall be measured via radiated emission test method per C63.10 ( in this case, the antenna port may be terminated properly).
6. Absolute peak power limit of -21.2dBm within the unwanted emission bandwidth shall be used for meeting 15.35(b) requirement;
7. Per 15.35(c), for pulse operation, Duty Cycle factor reduction can be applied for unwanted emissions that have the same pulse characteristics as does the fundamental emissions ( such as harmonics) pulse operation

EUT: Sonesse2 40 R2 Zigbee HP4/36FC, Sonesse2 40 R2 Zigbee HP6/24FC, Sonesse2 40 R2 Zigbee HP9/14  
Model: 5172631A, 5172632A, 5172633A

Report No: 0048-240110-01 FCC ID: DWN SON40ZB IC : 12049A-SON40ZB


~~\*\*\* EUT shall be configured to transmit continuously (min. 98% duty cycle at full power). The spectrum analyzer shall be set for bin-to-bin spacing  $\leq$  RBW/2.~~

**C. Section 8.7 DTS band-edge emission measurements following the methods in Subclause 11.13 of ANSI C63.10**


| Conducted Band-edge measurements                                                                    | Applicable to this EUT              |
|-----------------------------------------------------------------------------------------------------|-------------------------------------|
| ANSI C63.10, Sec.11.13.2 Band-Edge Marker-Delta Method (per ANSI C63.10, Sec. 6.10.6) (within 2MHz) | <input type="checkbox"/>            |
| ANSI C63.10, Sec. 11.13.3.2~5 Band-Edge Integration Method (peak / average)                         | <input checked="" type="checkbox"/> |

## RESULTS:


### Zigbee Mode:




# BLE Mode:




## Zigbee Mode:





## BLE Mode:



## Zigbee Mode:



**BLE Mode:**



## 7.7 RADIATED EMISSIONS

### 7.7.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS

#### LIMITS

§15.205 (a) RSS-102 Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz                      | MHz                 | MHz           | GHz              |
|--------------------------|---------------------|---------------|------------------|
| 0.090-0.110              | 16.42-16.423        | 399.9-410     | 4.5-5.15         |
| <sup>1</sup> 0.495-0.505 | 16.69475-16.69525   | 608-614       | 5.35-5.46        |
| 2.1735-2.1905            | 16.80425-16.80475   | 960-1240      | 7.25-7.75        |
| 4.125-4.128              | 25.5-25.67          | 1300-1427     | 8.025-8.5        |
| 4.17725-4.17775          | 37.5-38.25          | 1435-1626.5   | 9.0-9.2          |
| 4.20725-4.20775          | 73-74.6             | 1645.5-1646.5 | 9.3-9.5          |
| 6.215-6.218              | 74.8-75.2           | 1660-1710     | 10.6-12.7        |
| 6.26775-6.26825          | 108-121.94          | 1718.8-1722.2 | 13.25-13.4       |
| 6.31175-6.31225          | 123-138             | 2200-2300     | 14.47-14.5       |
| 8.291-8.294              | 149.9-150.05        | 2310-2390     | 15.35-16.2       |
| 8.362-8.366              | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4        |
| 8.37625-8.38675          | 156.7-156.9         | 2690-2900     | 22.01-23.12      |
| 8.41425-8.41475          | 162.0125-167.17     | 3260-3267     | 23.6-24.0        |
| 12.29-12.293             | 167.72-173.2        | 3332-3339     | 31.2-31.8        |
| 12.51975-12.52025        | 240-285             | 3345.8-3358   | 36.43-36.5       |
| 12.57675-12.57725        | 322-335.4           | 3600-4400     | ( <sup>2</sup> ) |
| 13.36-13.41              |                     |               |                  |

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209 & RSS-Gen. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 & RSS-Gen shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 & RSS-Gen shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) & RSS-Gen Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency<br>(MHz) | Field Strength<br>(microvolts /meter | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 30 – 88            | 100                                  | 3                                |
| 88 – 216           | 150                                  | 3                                |
| 216 – 960          | 200                                  | 3                                |
| Above 960          | 500                                  | 3                                |

§15.209 (b) & RSS-Gen In the emission table above, the tighter limit applies at the band edges.

**TEST PROCEDURE *per FCC KDB 558074D01v05r02* Sec. 8.6 DTS emissions in restricted frequency bands following the method in Subclause 11.12.2.7 of ANSI C63.10 ( Radiated method)**

Also see Sec. 8.1 c)3): Additional measurement procedures and the allowance for duty cycle for DTS device out-of-band measurements in a restricted band for protocol-limited devices.

The EUT is set to transmit in a continuous mode. Established procedures in C63.4/C63.10 for performing radiated measurements shall be used. For cabinet emission measurements, the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. For portable devices, the EUT was tested in three orthogonal planes.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The radio spectrum was investigated from the lowest frequency generated within the device (without going below 9 kHz) up to the 10<sup>th</sup> harmonic of the rated transmitted emission. The emissions are investigated with the transmitter set to the lowest, middle, and highest channels.

The emissions are investigated with the transmitter set to the lowest, middle, and highest channels, if applicable. The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

## RESULTS

No non-compliance noted.

## 7.7.2. TRANSMITTER RADIATED EMISSIONS DATA

**(HARMONICS & SPURIOUS falling in restricted bands listed in Sec.15.205 and non-restricted bands \*)**

**HARMONICS AND SPURIOUS EMISSIONS (>1GHz & <=1GHz)**

**Model:** 5172631A, 5172632A, 5172633A

**Zigbee Mode:**

### Low Channel Harmonics/Spurious

| Freq.<br>(MHz) | Positi<br>on<br>(H,V)<br>X | Dist.<br>(m) | D Corr<br>(dB) | Peak@3m<br>(dBuV/m) | Avg@3m<br>(dBuV/m) | PK<br>Lim<br>(dBu<br>V/m) | QP/Avg<br>.Lim<br>(dBuV/<br>m) | PK Mar<br>(dBuV/m) | QP/Avg.M<br>ar.<br>(dBuV/m) |
|----------------|----------------------------|--------------|----------------|---------------------|--------------------|---------------------------|--------------------------------|--------------------|-----------------------------|
| 4810           | H,X                        | 3            |                | 42.5                | 38.3               | 74                        | 54                             | -31.5              | -15.7                       |
| 7215           | H,X                        | 3            |                | 45.8                | 43.0               | 74                        | 54                             | -28.2              | -11                         |
| 4810           | V,X                        | 3            |                | 41.9                | 37.9               | 74                        | 54                             | -32.1              | -16.1                       |
| 7215           | V,X                        | 3            |                | 46.2                | 43.1               | 74                        | 54                             | -27.8              | -10.9                       |

### Middle Channel Harmonics/Spurious

| Freq.<br>(MHz) | Positi<br>on<br>(H,V)<br>X | Dist.<br>(m) | D Corr<br>(dB) | Peak@3m<br>(dBuV/m) | Avg@3m<br>(dBuV/m) | PK<br>Lim<br>(dBu<br>V/m) | QP/Avg<br>.Lim<br>(dBuV/<br>m) | PK Mar<br>(dBuV/m) | QP/Avg.M<br>ar.<br>(dBuV/m) |
|----------------|----------------------------|--------------|----------------|---------------------|--------------------|---------------------------|--------------------------------|--------------------|-----------------------------|
| 4890           | H,X                        | 3            |                | 44.2                | 41.5               | 74                        | 54                             | -29.8              | -12.5                       |
| 7335           | H,X                        | 3            |                | 47.2                | 43.9               | 74                        | 54                             | -26.8              | -10.1                       |
| 4890           | V,X                        | 3            |                | 46.1                | 43.3               | 74                        | 54                             | -27.9              | -10.7                       |
| 7335           | V,X                        | 3            |                | 47.7                | 43.5               | 74                        | 54                             | -26.3              | -10.5                       |

### High Channel Harmonics/Spurious

| Freq.<br>(MHz) | Positi<br>on<br>(H,V)<br>X | Dist.<br>(m) | D Corr<br>(dB) | Peak@3m<br>(dBuV/m) | Avg@3m<br>(dBuV/m) | PK<br>Lim<br>(dBu<br>V/m) | QP/Avg<br>.Lim<br>(dBuV/<br>m) | PK Mar<br>(dBuV/m) | QP/Avg.M<br>ar.<br>(dBuV/m) |
|----------------|----------------------------|--------------|----------------|---------------------|--------------------|---------------------------|--------------------------------|--------------------|-----------------------------|
| 4960           | H,X                        | 3            |                | 42.3                | 39.7               | 74                        | 54                             | -31.7              | -14.3                       |
| 7440           | H,X                        | 3            |                | 46.3                | 43.5               | 74                        | 54                             | -27.7              | -10.5                       |
| 4960           | V,X                        | 3            |                | 43.1                | 39.9               | 74                        | 54                             | -30.9              | -14.1                       |
| 7440           | V,X                        | 3            |                | 47.0                | 43.7               | 74                        | 54                             | -27                | -10.3                       |

\* Data shown above represents the worst case in all applicable EUT orientations. No other significant emissions were found in the rest frequency range. For spurious in restricted band, the limit is per 15.209 & RSS-Gen. For the others, by measuring the field strength of fundamental (peak) with 100KHz RBW, the limit is 20dB below that level (here it is higher than the limit in 15.209 & RSS-Gen). In this case, all non-fundamental emission points are below 15.209 & RSS-Gen limit, so there is NO additional concern for non-restriction band limit compliance.

**Model: 5172631A, 5172632A, 5172633A**

**BLE Mode:**

**Low Channel Harmonics/Spurious**

| Freq. (MHz) | Position (H,V) X | Dist. (m) | D Corr (dB) | Peak@3m (dBuV/m) | Avg@3m (dBuV/m) | PK Lim (dBuV/m) | QP/Avg Lim (dBuV/m) | PK Mar (dBuV/m) | QP/Avg Mar (dBuV/m) |
|-------------|------------------|-----------|-------------|------------------|-----------------|-----------------|---------------------|-----------------|---------------------|
| 4804        | H,X              | 3         |             | 42.8             | 38.8            | 74              | 54                  | -31.2           | -15.2               |
| 7206        | H,X              | 3         |             | 46.9             | 43.4            | 74              | 54                  | -27.1           | -10.6               |
| 4804        | V,X              | 3         |             | 42.5             | 38.7            | 74              | 54                  | -31.5           | -15.3               |
| 7206        | V,X              | 3         |             | 47.5             | 43.9            | 74              | 54                  | -26.5           | -10.1               |

**Middle Channel Harmonics/Spurious**

| Freq. (MHz) | Position (H,V) X | Dist. (m) | D Corr (dB) | Peak@3m (dBuV/m) | Avg@3m (dBuV/m) | PK Lim (dBuV/m) | QP/Avg Lim (dBuV/m) | PK Mar (dBuV/m) | QP/Avg Mar (dBuV/m) |
|-------------|------------------|-----------|-------------|------------------|-----------------|-----------------|---------------------|-----------------|---------------------|
| 4884        | H,X              | 3         |             | 43.5             | 39.4            | 74              | 54                  | -30.5           | -14.6               |
| 7326        | H,X              | 3         |             | 46.6             | 43.2            | 74              | 54                  | -27.4           | -10.8               |
| 4884        | V,X              | 3         |             | 44.2             | 41.4            | 74              | 54                  | -29.8           | -12.6               |
| 7326        | V,X              | 3         |             | 46.8             | 43.4            | 74              | 54                  | -27.2           | -10.6               |

**High Channel Harmonics/Spurious**

| Freq. (MHz) | Position (H,V) X | Dist. (m) | D Corr (dB) | Peak@3m (dBuV/m) | Avg@3m (dBuV/m) | PK Lim (dBuV/m) | QP/Avg Lim (dBuV/m) | PK Mar (dBuV/m) | QP/Avg Mar (dBuV/m) |
|-------------|------------------|-----------|-------------|------------------|-----------------|-----------------|---------------------|-----------------|---------------------|
| 4960        | H,X              | 3         |             | 43.0             | 38.9            | 74              | 54                  | -31.0           | -15.1               |
| 7440        | H,X              | 3         |             | 46.7             | 43.2            | 74              | 54                  | -27.3           | -10.8               |
| 4960        | V,X              | 3         |             | 43.2             | 39.0            | 74              | 54                  | -30.8           | -15.0               |
| 7440        | V,X              | 3         |             | 46.7             | 43.3            | 74              | 54                  | -27.3           | -10.7               |

\* Data shown above represents the worst case in all applicable EUT orientations. No other significant emissions were found in the rest frequency range. For spurious in restricted band, the limit is per 15.209 & RSS-Gen. For the others, by measuring the field strength of fundamental (peak) with 100KHz RBW, the limit is 20dB below that level (here it is higher than the limit in 15.209 & RSS-Gen). In this case, all non-fundamental emission points are below 15.209 & RSS-Gen limit, so there is NO additional concern for non-restriction band limit compliance.

## Band Edge Data for EUT

In addition, the band-edge requirements are also verified.

*Testing procedure per KDB 558074D01:*

The measurement of unwanted emissions at the edge of the authorized frequency bands can be complicated by the capture of RF energy from the fundamental emission within the RBW passband. The following techniques are permitted for use in performing a measurement of the unwanted emission level at the band edges.

### 10.2.5.1 Marker-Delta Method

The marker-delta method, as described in KDB 913591 and in C63.10, can be used to perform measurements of the unwanted emissions level at the band-edges.

### 10.2.5.2 Integrated Power Measurement

A narrower resolution bandwidth can be used at the band edge to improve the measurement accuracy provided that the measurement is subsequently integrated to the relevant bandwidth specification (e.g., 100 kHz within non-restricted bands and 1 MHz within restricted frequency bands).

## Results:

The testing results for worst case based on pretesting results are shown as following and comply with the band-edge requirements for 2400-2483.5MHz DTS per FCC Part 15.247. EUT antenna with max gain was used for this testing.

- H=Measurement antenna horizontal position
- V= Measurement antenna vertical position
- Using conventional manner for measuring the radiated emissions that are removed by more than two measurement bandwidths from band-edge, such as the emissions in the restricted band 2310-2390MHz & 2483.5-2500MHz, etc.
- Using conventional manner or if needed, using “delta” measurement technique for measuring the radiated emissions that are up to two measurement bandwidths removed from band-edge, such as the restricted band that begins at 2483.5MHz.
- The worst case for different EUT orientations was chosen for final data collection based on pre-scan testing results.



## EUT Duty Cycle Factor:


**The computed worst-case value for an 802.15.4-compliant ZigBee stack, which is 66.** Note that the 66% measurement assumes worst-case values achieved in several randomization functions, so real-world application performance will almost certainly be less than this number. TX duty cycle percentage (P), the correction/relaxation factor (F) applied to your harmonics emissions will be based on the following formula:  $F = 20 * \log(P/100)$ . For example, a 66% TX duty cycle yields a duty cycle correction factor of -3.6 dB =  $20 * \log(0.66)$ .

It may not need to use the Duty Cycling correction factor if the output power from the 2.4GHz radio is low.



The following plots show the band edge spurious with the worst case ( Model# 1241672/1241754 AC mode) based on pre scans. All results are below the limit in FCC 15.247, 15.209 & RSS-247, RSS-Gen.


## Zigbee Mode:





## BLE Mode:





## 7.8 CONDUCTED EMISSION

### 7.8.1 Test Methods and Conditions

The EUT was under normal operational mode during the conducted emission test. EMI Receiver was scanned from 150KHz to 30MHz with maximum hold mode for maximum emission. Recorded data was sent to the plotter to generate output in linear format. At the input of the spectrum analyzer, a HP transient limiter is inserted for protective purpose. This limiter has a 10 dB attenuation in the range of 150KHz to 30MHz. That factor was automatically compensated by the receiver, so the readings are the corrected readings. The reference of the plot is the CISPR 22 Class B limit in following plots.

| Conducted Emission Technical Requirements |                    |                 |                    |                 |
|-------------------------------------------|--------------------|-----------------|--------------------|-----------------|
|                                           | Class A            |                 | Class B            |                 |
| Frequency Range                           | Quasi-Peak<br>dBuV | Average<br>dBuV | Quasi-Peak<br>DBuV | Average<br>dBuV |
| 150kHz-0.5MHz                             | 79 (8912uV)        | 66 (1995uV)     | 66-56              | 56-46           |
| 0.5MHz-30MHz                              | 73 (4467uV)        | 60 (1000uV)     | ---                | ---             |
| 0.5MHz- 5MHz                              | ---                | ---             | 56                 | 46 (250uV)      |
| 5MHz-30MHz                                | ---                | ---             | 60                 | 50              |

Emissions that have peak values close to the specification limit (if any) are also measured in the quasi-peak/average mode to determine compliance.

### 7.8.2 Test Data

The following plots show the neutral and line conducted emissions for the standard operation.

Mode: Zigbee

| Highest Data for AC Line Conducted Emissions |                 |                 |                 |                    |                    |                    |
|----------------------------------------------|-----------------|-----------------|-----------------|--------------------|--------------------|--------------------|
| Frequency (MHz)                              | 0.300<br>(Line) | 0.370<br>(Line) | 0.690<br>(Line) | 0.180<br>(Neutral) | 0.370<br>(Neutral) | 0.460<br>(Neutral) |
| Peak Reading<br>(dBuV)                       | 41.13           | 42.90           | 39.37           | 43.39              | 43.0               | 40.12              |
| Average Reading<br>(dBuV*)                   |                 |                 |                 |                    |                    |                    |

\* no need to show the average reading if the peak value is under average limit.

Mode: BLE

| Highest Data for AC Line Conducted Emissions |                 |                 |                 |                    |                    |                    |
|----------------------------------------------|-----------------|-----------------|-----------------|--------------------|--------------------|--------------------|
| Frequency (MHz)                              | 0.290<br>(Line) | 0.460<br>(Line) | 0.750<br>(Line) | 0.300<br>(Neutral) | 0.450<br>(Neutral) | 0.790<br>(Neutral) |
| Peak Reading<br>(dBuV)                       | 42.64           | 40.63           | 40.74           | 42.88              | 41.43              | 41.38              |
| Average Reading<br>(dBuV*)                   |                 |                 |                 |                    |                    |                    |

\* no need to show the average reading if the peak value is under average limit.

Test Personnel:



Tester Signature: \_\_\_\_\_



David Tu

Typed/Printed Name: \_\_\_\_\_

Date : \_\_\_\_\_ 02/05/2024



## Mode: Zigbee

Model: 5172631A, 5172632A, 5172633A



## Mode: BLE

Model: 5172631A, 5172632A, 5172633A



## 7.9 EUT RECEIVING MODE VERIFICATION

### Radiated Test Data for Receiving/Digital Mode

**Model: 5172631A, 5172632A, 5173633A**

| Frequency<br>(MHz) | Polarity<br>(H,V) | Antenna<br>Height<br>(m) | Azimuth<br>(Degree) | Peak<br>Reading<br>at 3m<br>(2)<br>(dBuV/m) | Peak<br>Reading<br>After<br>Correction<br>(dBuV/m) | FCC/IC<br>3m<br>Limit<br>(1)<br>(dBuV/m) | Difference<br>(dBuV/m) |
|--------------------|-------------------|--------------------------|---------------------|---------------------------------------------|----------------------------------------------------|------------------------------------------|------------------------|
| 113.7              | H                 | 1.8                      | 045                 | 31.1                                        |                                                    | 43.5                                     | -12.4                  |
| 118.4              | H                 | 1.8                      | 000                 | 31.8                                        |                                                    | 43.5                                     | -11.7                  |
| 136.3              | H                 | 1.0                      | 000                 | 31.6                                        |                                                    | 43.5                                     | -11.9                  |
| 157.1              | H                 | 1.0                      | 045                 | 31.2                                        |                                                    | 43.5                                     | -12.3                  |
| 188.5              | H                 | 1.0                      | 000                 | 35.0                                        |                                                    | 43.5                                     | -8.5                   |
| 193.6              | H                 | 1.0                      | 000                 | 35.1                                        |                                                    | 43.5                                     | -8.4                   |
| 392.0              | H                 | 1.0                      | 135                 | 33.8                                        |                                                    | 46.5                                     | -12.7                  |
| 430.3              | H                 | 1.0                      | 045                 | 35.2                                        |                                                    | 46.5                                     | -11.3                  |
| 636.1              | H                 | 1.0                      | 135                 | 37.8                                        |                                                    | 46.5                                     | -8.7                   |
| 700.2              | H                 | 1.0                      | 000                 | 40.8                                        |                                                    | 46.5                                     | -5.7                   |
| 880.0              | H                 | 1.0                      | 045                 | 41.7                                        |                                                    | 46.5                                     | -4.8                   |
| 50.8               | V                 | 1.2                      | 270                 | 28.5                                        |                                                    | 43.5                                     | -15.0                  |
| 114.6              | V                 | 1.1                      | 235                 | 30.6                                        |                                                    | 43.5                                     | -12.9                  |
| 133.3              | V                 | 1.1                      | 235                 | 30.4                                        |                                                    | 43.5                                     | -13.1                  |
| 156.2              | V                 | 1.1                      | 235                 | 32.3                                        |                                                    | 43.5                                     | -11.2                  |
| 163.5              | V                 | 1.1                      | 235                 | 35.0                                        |                                                    | 43.5                                     | -8.5                   |
| 191.1              | V                 | 1.1                      | 330                 | 34.5                                        |                                                    | 43.5                                     | -9.0                   |
| 202.0              | V                 | 1.1                      | 330                 | 30.6                                        |                                                    | 43.5                                     | -12.9                  |
| 264.3              | V                 | 1.1                      | 330                 | 33.2                                        |                                                    | 46.5                                     | -13.3                  |
| 320.1              | V                 | 1.1                      | 235                 | 33.5                                        |                                                    | 46.5                                     | -13.0                  |
| 430.5              | V                 | 1.1                      | 235                 | 36.0                                        |                                                    | 46.5                                     | -10.5                  |
| 448.3              | V                 | 1.1                      | 270                 | 35.9                                        |                                                    | 46.5                                     | -10.6                  |
| 724.1              | V                 | 1.1                      | 270                 | 39.6                                        |                                                    | 46.5                                     | -6.9                   |

- (1) Receiving mode spurious emissions shall be lower than the limit defined in FCC Sec. 15.209 & IC RSS-GEN.  
(2) If the peak reading is less than the FCC/IC quasi-peak or average limit, it'll be not necessary to show the measured/ calculated quasi-peak or average reading.