

## Maximum Permissible Exposure Report

### 1. Product Information

Name of EUT	Battery Operated LTE Cellular GPS Tracker
Model Number	CUT-4LH, SBR-4LH
Model Declaration	PCB board, structure and internal of these model(s) are the same, no additional models were tested.
Test Model	CUT-4LH
Modulation Type	QPSK for UMTS; QPSK, 16QAM for LTE
Antenna Gain	3.37dBi for WCDMA Band II; 0.98dBi for WCDMA Band V; 3.37dBi for LTE Band 2; 0.91dBi for LTE Band 4; 0.70dBi for LTE Band 12; 2.0dBi (max.) For BT
Hardware version	4015R01
Software version	1.0.13
GSM/EDGE/GPRS Operation Frequency Band	Not Supported
UMTS Operation Frequency Band	UMTS FDD Band II/V
LTE Operation Frequency Band	LTE FDD band 2, 4, 12
GSM/EDGE/GPRS	Not Supported
GSM Release Version	Not Supported
GSM/EDGE/GPRS Power Class	Not Supported
GPRS/EDGE Multislot Class	Not Supported
GPRS operation mode	Not Supported
WCDMA Release Version	R8
HSDPA Release Version	Release 8
HSUPA Release Version	Release 6
DC-HSUPA Release Version	Not Supported
LTE Release Version	R9
LTE/UMTS Power Class	Class 3
WLAN FCC Modulation Type	Not Supported
WLAN FCC Operation frequency	Not Supported
Antenna Type	Chip Antenna (for BT)
BT Modulation Type	GFSK (BT V4.0(BT LE Only))
Extreme temp. Tolerance	-20°C to +55°C
GPS function	Support and only RX
FM function	Not Supported
NFC Function	Not Supported
Extreme vol. Limits	10.8VDC to 13.2VDC (nominal: 12.0VDC)
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

## 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

## 3. Limit

### 3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

### 3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

#### 4. MPE Calculation Method

Predication of MPE limit at a given distance  
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

#### 5. Antenna Information

CUT-4LH can only use antennas certificated as follows provided by manufacturer;

Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Internal PILA Antenna	600MHz – 2500MHz	3.37dBi for WCDMA Band II; 0.98dBi for WCDMA Band V; 3.37dBi for LTE Band 2; 0.91dBi for LTE Band 4; 0.70dBi for LTE Band 12
Chip Antenna	600MHz – 2500MHz	2.0dBi(Max.) for Bluetooth

#### 6. Measurement Results

##### 6.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r=20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

##### [Bluetooth]

Modulation Type	Max. Tune up Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE ( $\text{mW}/\text{cm}^2$ )	MPE Limits ( $\text{mW}/\text{cm}^2$ )
	dBm	mW				
GFSK (BT LE)	5.00	3.1623	2.00	1.5849	0.0010	1.0000

##### [WWAN]

Modulation Type	Max. Tune up Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE ( $\text{mW}/\text{cm}^2$ )	MPE Limits ( $\text{mW}/\text{cm}^2$ )
	dBm	mW				
WCDMA Band V	24.00	251.1886	0.98	1.2531	0.0626	0.5493
WCDMA Band II	24.00	251.1886	3.37	2.1727	0.1086	1.0000
LTE FDD Band 2	24.00	251.1886	3.37	2.1727	0.1086	1.0000
LTE FDD Band 4	24.00	251.1886	0.91	1.2331	0.0616	1.0000
LTE FDD Band 12	24.00	251.1886	0.70	1.1749	0.0587	0.4660

Remark:

1. Output power including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.
3. MPE limits for WCDMA Band II refer 1850MHz, WCDMA Band V refer 824MHz, LTE FDD Band 2 refer 1850MHz, LTE FDD Band 4 refer 1710MHz, LTE FDD Band 12 refer 699MHz, as it is lowest frequency.

## 6.2 Simultaneous Transmission MPE

The EUT equipped with one BT module and one WWAN module. Each module has its own antenna and they can transmit at the same time. So need consider simultaneous transmission.

According to KDB447498 D01 General RF Exposure Guidance v06 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\Sigma$  of MPE ratios  $\leq 1.0$

Simultaneous Transmission MPE			
Mode	$\Sigma$ MPE ratios (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Results
BT+WCDMA Band V	0.0636	1.0000	Pass
BT+WCDMA Band II	0.1096	1.0000	Pass
BT+LTE FDD Band 2	0.1096	1.0000	Pass
BT+LTE FDD Band 4	0.0626	1.0000	Pass
BT+LTE FDD Band 12	0.0597	1.0000	Pass

## 7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----