

RF Exposure Report

Report No.: MFBCKS-WTW-P25030760

FCC ID: LXC-V2X-OBU-NAD

Test Model: OBU-5931

Received Date: 2024/7/30

Test Date: 2024/7/30 ~ 2024/12/13

Issued Date: 2025/5/8

Applicant: DENSO International America, Inc.

Address: 2251 Rutherford Road Suite 100, Carlsbad, California, 92008-8815 United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result	7

Release Control Record

Issue No.	Description	Date Issued
MFCKS-WTW-P25030760	Original Release	2025/5/8

1 Certificate of Conformity

Product: On-Board Unit

Brand: MobiQ

Test Model: OBU-5931

Sample Status: Engineering sample

Applicant: DENSO International America, Inc

Test Date: 2024/7/30 ~ 2024/12/13

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

Lena Wang

Date: 2025/5/8

Lena Wang / Specialist

Approved by :

Jeremy Lin

Date: 2025/5/8

Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20 cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

WWAN antenna:

Type	Dipole											
Connector	SMA											
Band	GSM 850 / EDGE 850	GSM 1900 / EDGE 1900	LTE B2	LTE B4	LTE B5	LTE B7	LTE B12	LTE B14	LTE B17	LTE B25	LTE B26	LTE B66
Gain (dBi)	3.4	5.9	5.9	5.9	3.4	4.1	4.1	4.1	4.1	5.9	3.4	5.9
Cable loss	2.06	4.15	4.15	4.35	2.06	3.05	2.1	2.1	2.1	4.15	2.06	4.35
Gain With cable loss (dBi)	1.34	1.75	1.75	1.55	1.34	1.05	2	2	2	1.75	1.34	1.55

*Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2.5 Calculation Result

Operation Mode	Frequency Band (MHz)	Conducted Power (dBm)	Gain (dBi)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
GPRS 850	824-849	30.69	1.34	32.03	20	0.317	0.549
GPRS 1900	1850-1910	28.35	1.75	30.1	20	0.204	1.00
LTE Band 2	1850-1910	22.88	1.75	24.63	20	0.058	1.00
LTE Band 4	1710-1755	22.37	1.55	23.92	20	0.049	1.00
LTE Band 5	824-849	23.09	1.34	24.43	20	0.055	0.549
LTE Band 7	2502-2568	22.73	1.05	23.78	20	0.048	1.00
LTE Band 12	698-716	22.92	2	24.92	20	0.062	0.465
LTE Band 14	788-798	23.02	2	25.02	20	0.063	0.525
LTE Band 17	706-714	22.92	2	24.92	20	0.062	0.469
LTE Band 25	1850-1915	22.55	1.75	24.3	20	0.054	1.00
LTE Band 26	814-824	23.22	1.34	24.56	20	0.057	0.542
LTE Band 26	824-849	23.17	1.34	24.51	20	0.056	0.549
LTE Band 66	1710-1780	22.38	1.55	23.93	20	0.049	1.00

Note:

1. The WWAN module (Brand: WNC, Model: UMC-MT2731CBN, FCC ID: NKRUMC-MT2731CBN) is used in this EUT.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
3. Detail antenna specification please refer to antenna datasheet or an antenna gain measurement report.

---END---