

承 认 书

APPROVAL SHEET

客 户 名 称

CUSTOMER NAME:

产 品 名 称

PRODUCT NAME: 2.4G W86 白色天线 L=125mm+端子

客 户 料 号

CUSTOMER P/N:

优比电子料号

Youbi P/N: UB02C120W2D2338A REV: A

	MANUFACTURER SIGNATURE	CUSTOMER SIGNATURE
CHECKED BY:	Yongqin. Lu 	
APPROVED BY:	Changxing. Liu	
DATE:	2022/04/12	

Modification History

Version	Content Revision	Issued by	Date
A	Original version	Yongxin. Lu	2022-04-12

Content


<i>Item</i>	<i>Description</i>
1.-----	Electrical Specification
2.-----	Test Items and Equipment
3.-----	S Parameter
4.-----	Efficiency and Gain
5.-----	Radiation Pattern
6.-----	Mechanical Specification
7.-----	Packaging

1. Electrical Specification:

Characteristics	Specifications	Unit
Outline Dimensions	12x64.2,L=125	mm
Frequency	2400-2500	MHz
Impedance	50	Ω
VSWR	≤ 2.0	
Polarization	Linear Polarization	
Gain	2 REF	dBi
Efficiency	>60	%
Connector Type	1.13 MHF-1-Plug	
Operating temperature	-20°C~+60°C	
Storage Temp	-20°C~+50°C	

2. Test Items and Equipment


	Test items	Test equipment
S Parameter	1.Return Loss 2.VSWR	Network analyzer (Agilent E5071B)
The whole machine of Passive parameters	1.Frequency 2.Gain 3.Radiation Pattern	1.3D microwave darkroom (5m*5m*5m) 2.Network analyzer (Agilent E5071B)
The whole machine of Active parameters	1.TRP 2.TIS	1.3D microwave darkroom (5m*5m*5m) 2.Comprehensive test instrument (CMW500)



3. S Parameter



Frequency (MHz)	Return Loss (dB)	VSWR
2400	-11.12	1.77
2450	-15.16	1.42
2500	-14.67	1.45

* Voltage Standing Wave Ratio(VSWR)
Return Loss(RL)
 $RL = 20 * \log_{10}[(VSWR + 1) / (VSWR - 1)]$




4. Efficiency and Gain

Frequency (MHz)	2400	2450	2500
Efficiency (%)	74.99	84.53	84.14
Gain (dBi)	1.68	2.23	2.54




5. Radiation Pattern


5-1 Antenna 3D Radiation Pattern



2400MHz




2450MHz




2500MHz


5-2 Antenna 2D Radiation Pattern



Phi 0 2D




Phi 90 2D







Theta 90 2D

6. Mechanical Specification:



7. Packaging

A		B		C		D		E		F		G	
REV: A		DESCRIPTION: First Sample		ECN NO: /		DATE: 2022-4-12		DRAFTER: Yongxin					
1		2		3		4		5		6			
RoHS COMPLIANT 单个产品  内袋包装说明: 1. 50pcs/PE袋. 2. PE袋进行封口. 3. 每袋需贴1pcs内袋标签至PE袋正中间位置.		内袋包装  内袋标签		外箱包装  外箱标签		包装箱封箱标准: 先用胶带封紧, 然后用2条打包带固定. 		1. 纸箱尺寸: 长320mm*宽320mm*高200mm. 2. 每箱装16袋产品, 共计装800pcs产品每箱.		UANT® 东莞市优比电子有限公司 好天线 · 优比造 Dongguan Youbi Electronics Co., Ltd		APPR: Changxing Liu CHECK: Dillon DRAW: Yongxin Lu	
1		2		3		4		5		6			
客户代码 客户料号 优比料号 品名规格 数量 工单号 订单号 生产日期 电话: 0769-81777126 传真: 0769-81777125		客户代码 客户料号 优比料号 品名规格 数量 工单号 订单号 生产日期 电话: 0769-81777126 传真: 0769-81777125											
GENERAL TOLERANCE:		CUST. P/N:		TITLE:		REV:		UNITS		SCALE		1:1	
LINEAR:				2.4G W86白色天线L=125mm+端子		A		mm		1:1			
XXX: ±0.10													
X: ±0.3													
XX: ±0.5													
XXX: ±2.0													
ANGLE: ±0.5													