



Test report No:  
2070388R-RF-US-P06V01

## FCC TEST REPORT & ISED TEST REPORT

|                                             |                                                                                                                       |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Product Name                                | CONTROL ASM-AM/FM STERO RDOC PLYR                                                                                     |
| Trademark                                   | SGMW                                                                                                                  |
| Model and /or type reference                | MP-202SMY-MEXICO                                                                                                      |
| FCC ID                                      | 2AVYXMP-202SMY-MX                                                                                                     |
| Applicant's name / address                  | SAIC GM Wuling Automobile Co., Ltd.<br>No.18 Hexi Road, Liuzhou City, Guangxi Zhuang Autonomous Region, China         |
| Test method requested, standard             | FCC CFR Title 47 Part 15 Subpart C Section 15.247<br>ANSI C63.10: 2013<br>KD558074 D01 15.247 Meas Guidance v05r02    |
| Verdict Summary                             | IN COMPLIANCE                                                                                                         |
| Documented by (name / position & signature) | Kitty Li/Project Assistant<br>     |
| Reviewed by (name / position & signature)   | Frank He/ Technical Supervisor<br> |
| Approved by (name / position & signature)   | Jack Zhang/ Supervisor<br>         |
| Date of issue                               | 2020-08-03                                                                                                            |
| Report template No                          | Template_FCC 15.247-RF-V1.0                                                                                           |

## INDEX

|                                                                    | page |
|--------------------------------------------------------------------|------|
| General conditions .....                                           | 5    |
| Environmental conditions .....                                     | 5    |
| Possible test case verdicts .....                                  | 6    |
| Abbreviations.....                                                 | 6    |
| Document History.....                                              | 7    |
| Remarks and Comments .....                                         | 7    |
| Used Equipment.....                                                | 8    |
| Uncertainty .....                                                  | 10   |
| 1 General Information .....                                        | 11   |
| 1.1 General Description of the Item(s).....                        | 11   |
| 1.2 Antenna Information .....                                      | 12   |
| 1.3 Channel List.....                                              | 13   |
| 2 Description of Test Setup.....                                   | 14   |
| 2.1 Operating mode(s) used for tests .....                         | 14   |
| 2.2 Auxiliary equipment / Test software for the EUT .....          | 14   |
| 2.3 Test Configuration / Block diagram used for tests.....         | 15   |
| 2.4 Testing process .....                                          | 16   |
| 3 Verdict summary section.....                                     | 17   |
| 3.1 Standards .....                                                | 17   |
| 3.2 Deviation(s) from the Standard(s) / Test Specification(s)..... | 17   |
| 3.3 Overview of results .....                                      | 18   |
| 3.4 Test Facility.....                                             | 19   |
| 4 Test Results .....                                               | 20   |
| 4.1 Conducted Emission.....                                        | 20   |
| 4.1.1 Limit .....                                                  | 20   |
| 4.1.2 Test Setup .....                                             | 20   |
| 4.1.3 Test Procedure .....                                         | 20   |
| 4.1.4 Test Data .....                                              | 21   |
| 4.2 Emissions in restricted frequency bands .....                  | 22   |
| 4.2.1 Limit .....                                                  | 22   |
| 4.2.2 Test Setup .....                                             | 24   |
| 4.2.3 Test Procedure .....                                         | 25   |
| 4.2.4 Test Data .....                                              | 26   |
| 4.3 20dB Bandwidth.....                                            | 46   |

|        |                                                  |    |
|--------|--------------------------------------------------|----|
| 4.3.1  | Limit .....                                      | 46 |
| 4.3.2  | Test Setup .....                                 | 46 |
| 4.3.3  | Test Procedure .....                             | 46 |
| 4.3.4  | Test Data .....                                  | 47 |
| 4.4    | Carrier Frequency Separation .....               | 52 |
| 4.4.1  | Limit .....                                      | 52 |
| 4.4.2  | Test Setup .....                                 | 52 |
| 4.4.3  | Test Procedure .....                             | 52 |
| 4.4.4  | Test Data .....                                  | 53 |
| 4.5    | Number of hopping Frequencies .....              | 58 |
| 4.5.1  | Limit .....                                      | 58 |
| 4.5.2  | Test Setup .....                                 | 58 |
| 4.5.3  | Test Procedure .....                             | 58 |
| 4.5.4  | Test Data .....                                  | 59 |
| 4.6    | Time of Occupancy(Dwell Time) .....              | 60 |
| 4.6.1  | Limit .....                                      | 60 |
| 4.6.2  | Test Setup .....                                 | 60 |
| 4.6.3  | Test Procedure .....                             | 60 |
| 4.6.4  | Test Data .....                                  | 61 |
| 4.7    | Peak Output Power.....                           | 64 |
| 4.7.1  | Limit .....                                      | 64 |
| 4.7.2  | Test Setup .....                                 | 64 |
| 4.7.3  | Test Procedure .....                             | 65 |
| 4.7.4  | Test Data .....                                  | 66 |
| 4.8    | Emissions in non-restricted frequency band ..... | 67 |
| 4.8.1  | Limit .....                                      | 67 |
| 4.8.2  | Test Setup .....                                 | 67 |
| 4.8.3  | Test Procedure .....                             | 67 |
| 4.8.4  | Test Data .....                                  | 68 |
| 4.9    | Duty cycle .....                                 | 69 |
| 4.9.1  | Limit .....                                      | 69 |
| 4.9.2  | Test Setup .....                                 | 69 |
| 4.9.3  | Test Procedure .....                             | 69 |
| 4.9.4  | Test Data .....                                  | 70 |
| 4.10   | Radiated Emission Band Edge .....                | 71 |
| 4.10.1 | Limit .....                                      | 71 |
| 4.10.2 | Test Setup .....                                 | 71 |



---

|        |                                       |    |
|--------|---------------------------------------|----|
| 4.10.3 | Test Procedure .....                  | 71 |
| 4.10.4 | Test Data .....                       | 72 |
| 4.11   | Antenna Requirement.....              | 96 |
| 4.11.1 | Limit: .....                          | 96 |
| 4.11.2 | Antenna Connector Construction: ..... | 96 |
| 5      | Test setup photo and EUT Photo .....  | 97 |

## COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

## GENERAL CONDITIONS

|                      |                                                                        |
|----------------------|------------------------------------------------------------------------|
| Test Location        | No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China |
| Date(receive sample) | July. 09, 2020                                                         |
| Date (start test)    | July. 23, 2020                                                         |
| Date (finish test)   | Aug. 01, 2020                                                          |

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

## ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

|                       |               |
|-----------------------|---------------|
| Ambient temperature   | 15 °C – 35 °C |
| Relative Humidity air | 30% - 60%     |

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

## POSSIBLE TEST CASE VERDICTS

|                                         |                 |
|-----------------------------------------|-----------------|
| Test case does not apply to test object | N/A             |
| Test object does meet requirement       | P (Pass) / PASS |
| Test object does not meet requirement   | F (Fail) / FAIL |
| Not measured                            | N/M             |

## ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

|       |                               |
|-------|-------------------------------|
| EUT   | : Equipment Under Test        |
| QP    | : Quasi-Peak                  |
| CAV   | : CISPR Average               |
| AV    | : Average                     |
| CDN   | : Coupling Decoupling Network |
| SAC   | : Semi-Anechoic Chamber       |
| OATS  | : Open Area Test Site         |
| BW    | : Bandwidth                   |
| AM    | : Amplitude Modulation        |
| PM    | : Pulse Modulation            |
| HCP   | : Horizontal Coupling Plane   |
| VCP   | : Vertical Coupling Plane     |
| $U_N$ | : Nominal voltage             |
| $T_x$ | : Transmitter                 |
| $R_x$ | : Receiver                    |
| N/A   | : Not Applicable              |
| N/M   | : Not Measured                |

## DOCUMENT HISTORY

| Report No.            | Version | Description              | Issued Date |
|-----------------------|---------|--------------------------|-------------|
| 2070388R-RF-US-P06V01 | V1.0    | Initial issue of report. | 2020-08-03  |
|                       |         |                          |             |
|                       |         |                          |             |
|                       |         |                          |             |
|                       |         |                          |             |
|                       |         |                          |             |
|                       |         |                          |             |
|                       |         |                          |             |
|                       |         |                          |             |

## REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with Part 15 Subpart C Paragraph 15.247.
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result, unless the specification, standard or customer have special requirements.
4. The test results presented in this report relate only to the object tested.
5. The test results relate only to the samples tested.
6. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
7. This report will not be used for social proof function in China market.

## USED EQUIPMENT

### AC Power Line Conducted Emission / TR1

| Instrument                 | Manufacturer | Model No. | Serial No. | Cal. Date  | Next Cal. Date |
|----------------------------|--------------|-----------|------------|------------|----------------|
| EMI Test Receiver          | R&S          | ESCI      | 100906     | 2020.04.20 | 2021.04.19     |
| Two-Line V-Network         | R&S          | ENV216    | 101190     | 2019.12.28 | 2020.12.27     |
| Two-Line V-Network         | R&S          | ENV216    | 101044     | 2019.12.28 | 2020.12.27     |
| Current Probe              | R&S          | EZ-17     | 100678     | 2020.03.12 | 2021.04.11     |
| 50ohm Termination          | SHX          | TF2       | 07081402   | 2019.09.02 | 2020.09.01     |
| 50ohm Termination          | SHX          | TF2       | 07081403   | 2019.09.02 | 2020.09.01     |
| 50ohm Coaxial Switch       | Anritsu      | MP59B     | 6200464462 | N/A        | N/A            |
| Temperature/Humidity Meter | RTS          | RTS-8S    | TR1-TH     | 2019.08.21 | 2020.08.20     |
| Coaxial Cable              | Suhner       | RG 223    | TR1-C1     | 2019.08.25 | 2020.08.24     |
| Coaxial Cable              | Suhner       | RG 223    | TR1-C2     | 2019.08.25 | 2020.08.24     |
| Dekra test software        | Dekra        | -         | -          | -          | -              |

### Emissions in non-restricted frequency bands/ Occupied Bandwidth/ Fundamental emission output power Power Spectral Density / TR8

| Instrument                | Manufacturer | Model No. | Serial No.     | Cal. Date  | Next Cal. Date |
|---------------------------|--------------|-----------|----------------|------------|----------------|
| Spectrum Analyzer         | Agilent      | N9010A    | MY48030494     | 2019.09.28 | 2020.09.27     |
| EXA Spectrum Analyzer     | Keysight     | N9010A    | MY55370495     | 2020.04.17 | 2021.04.16     |
| MXA Signal Analyzer       | Keysight     | N9020A    | MY56060147     | 2019.08.30 | 2020.08.29     |
| Wideband Peak Power Meter | Anritsu      | ML2495A   | 0905006        | 2019.07.14 | 2020.07.13     |
| Power Sensor              | Anritsu      | MA2411B   | 0846014        | 2019.08.12 | 2020.08.11     |
| Coaxial Cable             | Woken        | SFL402    | F02-150410-044 | 2020.01.01 | 2020.12.31     |
| Dekra test software       | Dekra        | -         | -              | -          | -              |

### Radiated Emission(30MHz-1GHz) / AC3

| Instrument                 | Manufacturer | Model No. | Serial No. | Cal. Date  | Next Cal. Date |
|----------------------------|--------------|-----------|------------|------------|----------------|
| EMI Test Receiver          | R&S          | ESCI      | 100573     | 2020.03.03 | 2021.03.02     |
| Bilog Antenna              | Teseq GmbH   | CBL6112D  | 27611      | 2019.09.23 | 2020.09.22     |
| Temperature/Humidity Meter | RTS          | RTS-8S    | AC2-TH     | 2019.09.02 | 2020.09.01     |
| Coaxial Cable              | Huber+Suhner | RG 214    | AC2-C      | 2020.04.13 | 2021.04.12     |
| Dekra test software        | Dekra        | -         | -          | -          | -              |

## Radiated Emission / AC5(1GHz-40GHz)(Chamber details)

| Instrument                 | Manufacturer | Model No.       | Serial No.  | Cal. Date  | Next Cal. Date |
|----------------------------|--------------|-----------------|-------------|------------|----------------|
| Spectrum Analyzer          | Agilent      | E4446A          | MY45300103  | 2020.05.08 | 2021.05.07     |
| Preamplifier               | Miteq        | NSP1800-25      | 1364185     | 2020.05.06 | 2021.05.05     |
| Preamplifier               | QuieTek      | AP-040G         | CHM-0906001 | 2020.05.06 | 2021.05.05     |
| DRG Horn                   | ETS-Lindgren | 3117            | 00123988    | 2020.01.22 | 2021.01.21     |
| Temperature/Humidity Meter | Zhichen      | ZC1-2           | AC5-TH      | 2019.09.02 | 2020.09.01     |
| Coaxial Cable              | Huber+Suhner | SUCOFLEX<br>106 | AC5-C1      | 2020.04.13 | 2021.04.12     |
| Coaxial Cable              | Huber+Suhner | SUCOFLEX<br>106 | AC5-C2      | 2020.04.13 | 2021.04.12     |
| Coaxial Cable              | Huber+Suhner | SUCOFLEX<br>102 | AC5-C3      | 2020.04.13 | 2021.04.12     |
| Dekra test software        | Dekra        | -               | -           | -          | -              |

## UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%. The Uncertainties comply with standard required as below.

| Test item                                   | Uncertainty                                           |
|---------------------------------------------|-------------------------------------------------------|
| Conducted Emission                          | $\pm 2.02$ dB                                         |
| Emissions in restricted frequency bands     | above 1G : $\pm 3.9$ dB<br>below 1G is : $\pm 3.8$ dB |
| 20dB Bandwidth                              | $\pm 1$ kHz                                           |
| Carrier Frequency Separation                | $\pm 1$ kHz                                           |
| Number of Hopping Frequencies               | $\pm 1$ kHz                                           |
| Time of Occupancy (Dwell Time)              | $\pm 0.1$ us                                          |
| Peak Output Power                           | $\pm 1.0$ dB                                          |
| Emissions in non-restricted frequency bands | $\pm 1.0$ dB                                          |
| Radiated Emission Band Edge                 | above 1G : $\pm 3.9$ dB<br>below 1G : $\pm 3.8$ dB    |

## 1 GENERAL INFORMATION

### 1.1 General Description of the Item(s)

|                           |                                                                                                                          |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Product Name .....        | CONTROL ASM-AM/FM STERO RDOC PLR                                                                                         |
| Model No. ....            | MP-202SMY-MEXICO                                                                                                         |
| Trademark .....           | SGMW                                                                                                                     |
| FCC ID .....              | 2AVYXMP-202SMY-MX                                                                                                        |
| Hardware Version .....    | CN202S MY_HSAE S00                                                                                                       |
| Software Version .....    | CN202S MY_MX_HSAE_MPU_V02.03                                                                                             |
| Manufacturer .....        | Shenzhen Hangsheng Electronics Co.,Ltd                                                                                   |
| Manufacturer Address..... | Hangsheng Industrial Area,Fuyuan 1Rd.,Fuyong Town,Baoan District<br>Shenzhen City, Guangdong                             |
| Factory .....             | Jiangxi Hangsheng Electronics Technology Co.,Ltd                                                                         |
| Factory Address .....     | Shenzhen Road No.268,Jin Gang Mountain Economic and Technological<br>development zone ,Ji An City,Jiangxi Province China |

|                              |                                     |          |                                     |            |                                     |          |
|------------------------------|-------------------------------------|----------|-------------------------------------|------------|-------------------------------------|----------|
| Wireless specification.....  | Bluetooth                           |          |                                     |            |                                     |          |
| Bluetooth Specification..... | V3.0                                |          |                                     |            |                                     |          |
| Operating frequency range(s) | 2400~2483.5MHz                      |          |                                     |            |                                     |          |
| Type of Modulation.....      | GFSK                                |          |                                     |            |                                     |          |
| PHYS                         | <input checked="" type="checkbox"/> | GFSK     | <input checked="" type="checkbox"/> | Pi/4 DQPSK | <input checked="" type="checkbox"/> | 8DPSK    |
| Data Rate .....              | <input checked="" type="checkbox"/> | 1 Mbit/s | <input checked="" type="checkbox"/> | 2 Mbit/s   | <input checked="" type="checkbox"/> | 3 Mbit/s |
| Number of channel.....       | 79                                  |          |                                     |            |                                     |          |
| Operating Temperature Range: | -30°C – 80 °C                       |          |                                     |            |                                     |          |

|                          |                                     |                                |  |  |  |  |
|--------------------------|-------------------------------------|--------------------------------|--|--|--|--|
| Rated power supply ..... | Voltage and Frequency               |                                |  |  |  |  |
|                          | <input type="checkbox"/>            | AC: 220 – 240 V, 50 / 60 Hz    |  |  |  |  |
|                          | <input type="checkbox"/>            | AC: 100 – 240 V, 50 / 60 Hz    |  |  |  |  |
|                          | <input checked="" type="checkbox"/> | DC: 9 -12 V                    |  |  |  |  |
|                          | <input type="checkbox"/>            | Battery: .....                 |  |  |  |  |
| Mounting position .....  | <input type="checkbox"/>            | Table top equipment            |  |  |  |  |
|                          | <input type="checkbox"/>            | Wall/Ceiling mounted equipment |  |  |  |  |
|                          | <input type="checkbox"/>            | Floor standing equipment       |  |  |  |  |
|                          | <input type="checkbox"/>            | Hand-held equipment            |  |  |  |  |
|                          | <input checked="" type="checkbox"/> | Other: Auto parts              |  |  |  |  |

Note: All the information is from the client.

## 1.2 Antenna Information

|                                   |                                     |           |                                     |                        |
|-----------------------------------|-------------------------------------|-----------|-------------------------------------|------------------------|
| Antenna model / type number ..... | PCB Antenna                         |           |                                     |                        |
| Antenna serial number .....       | N/A                                 |           |                                     |                        |
| Antenna Delivery .....            | <input checked="" type="checkbox"/> | 1TX + 1RX |                                     |                        |
|                                   | <input type="checkbox"/>            | 2TX + 2RX |                                     |                        |
| Antenna technology .....          | <input checked="" type="checkbox"/> | SISO      |                                     |                        |
|                                   | <input type="checkbox"/>            | MIMO      | <input type="checkbox"/>            | CDD                    |
|                                   |                                     |           | <input type="checkbox"/>            | Beam-forming           |
| Antenna Type .....                | <input type="checkbox"/>            | External  | <input type="checkbox"/>            | Dipole                 |
|                                   |                                     |           | <input type="checkbox"/>            | Sectorized             |
|                                   | <input checked="" type="checkbox"/> | Internal  | <input type="checkbox"/>            | PIFA                   |
|                                   |                                     |           | <input checked="" type="checkbox"/> | PCB                    |
|                                   |                                     |           | <input type="checkbox"/>            | Metal Monopole Antenna |
|                                   |                                     |           | <input type="checkbox"/>            | Ceramic chip           |
|                                   |                                     |           | <input type="checkbox"/>            | Others.....            |
| Antenna Gain .....                | 3.6 dBi                             |           |                                     |                        |

### 1.3 Channel List

| Bluetooth Working Frequency of Each Channel: (For BDR/EDR) |           |         |           |         |           |         |           |
|------------------------------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                                                    | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 00                                                         | 2402 MHz  | 01      | 2403 MHz  | 02      | 2404 MHz  | 03      | 2405 MHz  |
| 04                                                         | 2406 MHz  | 05      | 2407 MHz  | 06      | 2408 MHz  | 07      | 2409 MHz  |
| 08                                                         | 2410 MHz  | 09      | 2411 MHz  | 10      | 2412 MHz  | 11      | 2413 MHz  |
| 12                                                         | 2414 MHz  | 13      | 2415 MHz  | 14      | 2416 MHz  | 15      | 2417 MHz  |
| 16                                                         | 2418 MHz  | 17      | 2419 MHz  | 18      | 2420 MHz  | 19      | 2421 MHz  |
| 20                                                         | 2422 MHz  | 21      | 2423 MHz  | 22      | 2424 MHz  | 23      | 2425 MHz  |
| 24                                                         | 2426 MHz  | 25      | 2427 MHz  | 26      | 2428 MHz  | 27      | 2429 MHz  |
| 28                                                         | 2430 MHz  | 29      | 2431 MHz  | 30      | 2432 MHz  | 31      | 2433 MHz  |
| 32                                                         | 2434 MHz  | 33      | 2435 MHz  | 34      | 2436 MHz  | 35      | 2437 MHz  |
| 36                                                         | 2438 MHz  | 37      | 2439 MHz  | 38      | 2440 MHz  | 39      | 2441 MHz  |
| 40                                                         | 2442 MHz  | 41      | 2443 MHz  | 42      | 2444 MHz  | 43      | 2445 MHz  |
| 44                                                         | 2446 MHz  | 45      | 2447 MHz  | 46      | 2448 MHz  | 47      | 2449 MHz  |
| 48                                                         | 2450 MHz  | 49      | 2451 MHz  | 50      | 2452 MHz  | 51      | 2453 MHz  |
| 52                                                         | 2454 MHz  | 53      | 2455 MHz  | 54      | 2456 MHz  | 55      | 2457 MHz  |
| 56                                                         | 2458 MHz  | 57      | 2459 MHz  | 58      | 2460 MHz  | 59      | 2461 MHz  |
| 60                                                         | 2462 MHz  | 61      | 2463 MHz  | 62      | 2464 MHz  | 63      | 2465 MHz  |
| 64                                                         | 2466 MHz  | 65      | 2467 MHz  | 66      | 2468 MHz  | 67      | 2469 MHz  |
| 68                                                         | 2470 MHz  | 69      | 2471 MHz  | 70      | 2472 MHz  | 71      | 2473 MHz  |
| 72                                                         | 2474 MHz  | 73      | 2475 MHz  | 74      | 2476 MHz  | 75      | 2477 MHz  |
| 76                                                         | 2478 MHz  | 77      | 2479 MHz  | 78      | 2480 MHz  | N/A     | N/A       |

## 2 DESCRIPTION OF TEST SETUP

### 2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.


|                         |                                                   |
|-------------------------|---------------------------------------------------|
| Test Mode For Bluetooth | Mode 1: Transmitter-1Mbps(GFSK_DH5)               |
|                         | Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)         |
|                         | Mode 3: Transmitter-3Mbps(8DPSK_DH5)              |
|                         | Mode 4: Transmitter-1Mbps(GFSK_DH5)-Hopping       |
|                         | Mode 5: Transmitter-2Mbps(Pi/4 DQPSK_DH5)-Hopping |
|                         | Mode 6: Transmitter-3Mbps(8DPSK_DH5)-Hopping      |

### 2.2 Auxiliary equipment / Test software for the EUT


| Auxiliary equipment | Type / Version | Manufacturer | Supplied by |
|---------------------|----------------|--------------|-------------|
| Notebook            | Think pad x220 | Lenovo       | Adapter     |
| software            | Type / Version | Manufacturer | Supplied by |
| Putty               | 0.71           | N/A          | N/A         |

## 2.3 Test Configuration / Block diagram used for tests

Test setup Diagram- Radiated Test



Test setup Diagram- Conducted test



## 2.4 Testing process

|   |                                                               |
|---|---------------------------------------------------------------|
| 1 | Setup the EUT as shown in Section 2.3.                        |
| 2 | Execute the Putty on the notebook.                            |
| 3 | Configure the test mode, the test channel, and the data rate. |
| 4 | Verify that the EUT works properly.                           |

### 3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

#### 3.1 Standards

| Standard                                          | Year | Description                                                                                                         |
|---------------------------------------------------|------|---------------------------------------------------------------------------------------------------------------------|
| FCC CFR Title 47 Part 15 Subpart C Section 15.247 | 2019 | Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.                                         |
| ANSI C63.10                                       | 2013 | American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices                      |
| KDB 558074 D01 v05r02                             | 2019 | Guidance for performing compliance measurements on Digital Transmission System (DTS) operating under section 15.247 |
|                                                   |      |                                                                                                                     |
|                                                   |      |                                                                                                                     |

#### 3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

*(Please define the deviations from the standard(s) if applicable)*

### 3.3 Overview of results

| Performed Test Item                         | Normative References                                                  | Test Performed | Deviation |
|---------------------------------------------|-----------------------------------------------------------------------|----------------|-----------|
| Conducted Emission                          | FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.207               | Yes            | No        |
| Emissions in restricted frequency bands     | FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.209               | Yes            | No        |
| 20dB Bandwidth                              | FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)         | Yes            | No        |
| Carrier Frequency Separation                | FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)         | Yes            | No        |
| Number of Hopping Frequencies               | FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)(iii)    | Yes            | No        |
| Time of Occupancy (Dwell Time)              | FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)(iii)    | Yes            | No        |
| Peak Output Power                           | FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(b)(1)         | Yes            | No        |
| Emissions in non-restricted frequency bands | FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.215(c), 15.247(d) | Yes            | No        |
| Radiated Emission Band Edge                 | FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(d)            | Yes            | No        |
| Antenna Requirement                         | FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.203               | Yes            | No        |

### 3.4 Test Facility

USA : FCC Designation Number: CN1199

## 4 TEST RESULTS

### 4.1 Conducted Emission

**VERDICT:** N/A

#### 4.1.1 Limit

| Standard              | FCC Part 15 Subpart C Paragraph 15.207 |                                   |
|-----------------------|----------------------------------------|-----------------------------------|
| Frequency range [MHz] | Limit: QP [dB(μV) <sup>1)</sup> ]      | Limit: AV [dB(μV) <sup>1)</sup> ] |
| 0,15 - 0,50           | 66 - 56 <sup>2)</sup>                  | 56 - 46 <sup>2)</sup>             |
| 0,50 - 5,0            | 56                                     | 46                                |
| 5,0 - 30              | 60                                     | 50                                |


<sup>1)</sup> At the transition frequency, the lower limit applies.

<sup>2)</sup> The limit decreases linearly with the logarithm of the frequency.

**NOTE 1:** The exclusion band for transmitters shall be considered for transmitters operating at frequencies below 30 MHz.

**NOTE 2:** Where the AC output port is directly connected (or via a circuit breaker) to the AC power input port of the EUT the AC power output port need not to be tested.

#### 4.1.2 Test Setup



#### 4.1.3 Test Procedure

|                                     | References Rule  | Chapter | Item                                                                                        |
|-------------------------------------|------------------|---------|---------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | ANSI C63.10-2013 | 6.2     | Standard test method for ac power-line conducted emissions from unlicensed wireless devices |

---

|                        |
|------------------------|
| <b>4.1.4 Test Data</b> |
|------------------------|

|                                           |
|-------------------------------------------|
| Not applicable: The device is DC powered. |
|-------------------------------------------|

**4.2 Emissions in restricted frequency bands****VERDICT: PASS****4.2.1 Limit**

| Standard            |                       | FCC Part 15 Subpart C Paragraph 15.207 |                 |
|---------------------|-----------------------|----------------------------------------|-----------------|
| Frequency (MHz)     | Frequency (MHz)       | Frequency (MHz)                        | Frequency (GHz) |
| 0.090 – 0.110       | 16.42 – 16.423        | 399.9 – 410                            | 4.5 – 5.15      |
| 0.495 – 0.505       | 16.69475 – 16.69525   | 608 – 614                              | 5.35 – 5.46     |
| 2.1735 – 2.1905     | 16.80425 – 16.80475   | 960 – 1240                             | 7.25 – 7.75     |
| 4.125 – 4.128       | 25.5 – 25.67          | 1300 – 1427                            | 8.025 – 8.5     |
| 4.17725 – 4.17775   | 37.5 – 38.25          | 1435 – 1626.5                          | 9.0 – 9.2       |
| 4.20725 – 4.20775   | 73 – 74.6             | 1645.5 – 1646.5                        | 9.3 – 9.5       |
| 6.215 – 6.218       | 74.8 – 75.2           | 1660 – 1710                            | 10.6 – 12.7     |
| 6.26775 – 6.26825   | 108 – 121.94          | 1718.8 – 1722.2                        | 13.25 – 13.4    |
| 6.31175 – 6.31225   | 123 – 138             | 2200 – 2300                            | 14.47 – 14.5    |
| 8.291 – 8.294       | 149.9 – 150.05        | 2310 – 2390                            | 15.35 – 16.2    |
| 8.362 – 8.366       | 156.52475 – 156.52525 | 2483.5 – 2500                          | 17.7 – 21.4     |
| 8.37625 – 8.38675   | 156.7 – 156.9         | 2690 – 2900                            | 22.01 – 23.12   |
| 8.81425 – 8.81475   | 162.0125 – 167.17     | 3260 – 3267                            | 23.6 – 24.0     |
| 12.29 – 12.293      | 167.72 – 173.2        | 3332 – 3339                            | 31.2 – 31.8     |
| 12.51975 – 12.52025 | 240 – 285             | 3345.8 – 3358                          | 36.43 – 36.5    |
| 12.57675 – 12.57725 | 322 – 335.4           | 3600 – 4400                            |                 |
| 13.36 – 13.41       |                       |                                        |                 |

**Restricted Band Emissions Limit**

| Frequency (MHz) | Field strength (μV/m) | Field strength (dBμV/m) | Measurement distance (m) |
|-----------------|-----------------------|-------------------------|--------------------------|
| 0.009 - 0.49    | 2400/F(kHz)           | 48.5 – 13.8             | 300 <sup>(Note 1)</sup>  |
| 0.49 - 1.705    | 24000/F(kHz)          | 33.8 - 23               | 30 <sup>(Note 1)</sup>   |
| 1.705 - 30      | 30                    | 29.5                    | 30 <sup>(Note 1)</sup>   |
| 30 - 88         | 100                   | 40                      | 3 <sup>(Note 2)</sup>    |
| 88 - 216        | 150                   | 43.5                    | 3 <sup>(Note 2)</sup>    |
| 216 - 960       | 200                   | 46                      | 3 <sup>(Note 2)</sup>    |
| Above 960       | 500                   | 54                      | 3 <sup>(Note 2)</sup>    |

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).


Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20

---


|                                                                                                                                      |
|--------------------------------------------------------------------------------------------------------------------------------------|
| dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements). |
|--------------------------------------------------------------------------------------------------------------------------------------|

## 4.2.2 Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:




### 4.2.3 Test Procedure

|                                     | References Rule                     |             | Chapter   | Description                                                                                      |
|-------------------------------------|-------------------------------------|-------------|-----------|--------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | ANSI C63.10                         |             | 11.12     | Emissions in restricted frequency bands                                                          |
|                                     | <input checked="" type="checkbox"/> | ANSI C63.10 | 11.12.1   | Radiated emission measurements                                                                   |
|                                     | <input checked="" type="checkbox"/> | ANSI C63.10 | 11.12.2.7 | Radiated spurious emission test                                                                  |
|                                     | <input checked="" type="checkbox"/> | ANSI C63.10 | 6.4       | Radiated emissions from unlicensed wireless devices below 30 MHz                                 |
|                                     | <input checked="" type="checkbox"/> | ANSI C63.10 | 6.5       | Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz |
|                                     | <input checked="" type="checkbox"/> | ANSI C63.10 | 6.6       | Radiated emissions from unlicensed wireless devices above 1 GHz                                  |


#### 4.2.4 Test Data

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 107            |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/08/01 - 15:26 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2402MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4804.000        | 41.666                 | 38.005               | -32.334         | 74.000         | 3.662       | PK   |
| 2  | *    | 7205.000        | 48.276                 | 41.615               | -25.724         | 74.000         | 6.661       | PK   |
| 3  |      | 9608.000        | 44.266                 | 36.130               | -29.734         | 74.000         | 8.137       | PK   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 108            |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/08/01 - 15:26 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2402MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4804.000        | 41.670                 | 38.009               | -32.330         | 74.000         | 3.662       | PK   |
| 2  | *    | 7205.000        | 49.103                 | 42.442               | -24.897         | 74.000         | 6.661       | PK   |
| 3  |      | 9608.000        | 44.471                 | 36.335               | -29.529         | 74.000         | 8.137       | PK   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 109            |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/08/01 - 15:26 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2441MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4882.000        | 41.038                 | 37.420               | -32.962         | 74.000         | 3.619       | PK   |
| 2  | *    | 7323.000        | 45.773                 | 39.070               | -28.227         | 74.000         | 6.702       | PK   |
| 3  |      | 9764.000        | 45.192                 | 36.424               | -28.808         | 74.000         | 8.767       | PK   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 110            |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/08/01 - 15:26 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2441MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4882.000        | 41.512                 | 37.894               | -32.488         | 74.000         | 3.619       | PK   |
| 2  |      | 7323.000        | 45.080                 | 38.377               | -28.920         | 74.000         | 6.702       | PK   |
| 3  | *    | 9764.000        | 45.742                 | 36.974               | -28.258         | 74.000         | 8.767       | PK   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 111            |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/08/01 - 15:26 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2480MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4960.000        | 40.803                 | 37.192               | -33.197         | 74.000         | 3.611       | PK   |
| 2  | *    | 7440.000        | 45.367                 | 38.782               | -28.633         | 74.000         | 6.585       | PK   |
| 3  |      | 9920.000        | 45.065                 | 36.340               | -28.935         | 74.000         | 8.725       | PK   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 112            |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/08/01 - 15:26 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2480MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4960.000        | 41.455                 | 37.844               | -32.545         | 74.000         | 3.611       | PK   |
| 2  | *    | 7440.000        | 45.050                 | 38.465               | -28.950         | 74.000         | 6.585       | PK   |
| 3  |      | 9920.000        | 44.887                 | 36.162               | -29.113         | 74.000         | 8.725       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 113            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:26 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2402MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4804.000        | 42.363                 | 38.702               | -31.637         | 74.000         | 3.662       | PK   |
| 2  | *    | 7205.000        | 47.951                 | 41.290               | -26.049         | 74.000         | 6.661       | PK   |
| 3  |      | 9608.000        | 44.074                 | 35.938               | -29.926         | 74.000         | 8.137       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 114            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:26 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2402MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4804.000        | 42.218                 | 38.557               | -31.782         | 74.000         | 3.662       | PK   |
| 2  | *    | 7205.000        | 49.283                 | 42.622               | -24.717         | 74.000         | 6.661       | PK   |
| 3  |      | 9608.000        | 44.280                 | 36.144               | -29.720         | 74.000         | 8.137       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 115            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:26 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2441MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4882.000        | 40.982                 | 37.364               | -33.018         | 74.000         | 3.619       | PK   |
| 2  | *    | 7324.000        | 46.973                 | 40.264               | -27.027         | 74.000         | 6.709       | PK   |
| 3  |      | 9764.000        | 44.817                 | 36.049               | -29.183         | 74.000         | 8.767       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 116            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:26 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2441MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4882.000        | 40.901                 | 37.283               | -33.099         | 74.000         | 3.619       | PK   |
| 2  | *    | 7324.000        | 45.954                 | 39.245               | -28.046         | 74.000         | 6.709       | PK   |
| 3  |      | 9764.000        | 45.265                 | 36.497               | -28.735         | 74.000         | 8.767       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 117            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:27 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2480MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4960.000        | 40.984                 | 37.373               | -33.016         | 74.000         | 3.611       | PK   |
| 2  | *    | 7440.000        | 45.107                 | 38.522               | -28.893         | 74.000         | 6.585       | PK   |
| 3  |      | 9920.000        | 44.460                 | 35.735               | -29.540         | 74.000         | 8.725       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 118            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:27 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2480MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4960.000        | 41.197                 | 37.586               | -32.803         | 74.000         | 3.611       | PK   |
| 2  | *    | 7440.000        | 45.758                 | 39.173               | -28.242         | 74.000         | 6.585       | PK   |
| 3  |      | 9920.000        | 44.951                 | 36.226               | -29.049         | 74.000         | 8.725       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 119            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:27 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2402MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4804.000        | 41.651                 | 37.990               | -32.349         | 74.000         | 3.662       | PK   |
| 2  | *    | 7205.000        | 49.547                 | 42.886               | -24.453         | 74.000         | 6.661       | PK   |
| 3  |      | 9608.000        | 44.513                 | 36.377               | -29.487         | 74.000         | 8.137       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 120            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:27 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2402MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4804.000        | 41.234                 | 37.573               | -32.766         | 74.000         | 3.662       | PK   |
| 2  | *    | 7205.000        | 46.836                 | 40.175               | -27.164         | 74.000         | 6.661       | PK   |
| 3  |      | 9608.000        | 44.209                 | 36.073               | -29.791         | 74.000         | 8.137       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 121            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:27 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2441MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4882.000        | 40.554                 | 36.936               | -33.446         | 74.000         | 3.619       | PK   |
| 2  |      | 7323.000        | 45.049                 | 38.346               | -28.951         | 74.000         | 6.702       | PK   |
| 3  | *    | 9764.000        | 45.451                 | 36.683               | -28.549         | 74.000         | 8.767       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 122            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:27 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2441MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4882.000        | 41.546                 | 37.928               | -32.454         | 74.000         | 3.619       | PK   |
| 2  | *    | 7323.000        | 45.234                 | 38.531               | -28.766         | 74.000         | 6.702       | PK   |
| 3  |      | 9764.000        | 44.881                 | 36.113               | -29.119         | 74.000         | 8.767       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 123            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:27 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2480MHz by 3DH5 |                          |



| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4960.000        | 41.303                 | 37.692               | -32.697         | 74.000         | 3.611       | PK   |
| 2  |      | 7440.000        | 44.559                 | 37.974               | -29.441         | 74.000         | 6.585       | PK   |
| 3  | *    | 9920.000        | 45.336                 | 36.611               | -28.664         | 74.000         | 8.725       | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 124            |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/08/01 - 15:28 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2480MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 4960.000        | 41.808                 | 38.197               | -32.192         | 74.000         | 3.611       | PK   |
| 2  | *    | 7440.000        | 44.082                 | 37.497               | -29.918         | 74.000         | 6.585       | PK   |
| 3  |      | 9920.000        | 44.046                 | 35.321               | -29.954         | 74.000         | 8.725       | PK   |

Note:

1. " \* ", means this data is the worst emission level.
2. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).


**The worst case of Radiated Emission below 1GHz:**

|                              |                          |
|------------------------------|--------------------------|
| Profile: 2070338R            | Page No.: 19             |
| Engineer: Shuo               |                          |
| Site: AC3                    | Time: 2020/07/20 - 15:57 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0                |
| Probe: SuZ-2141              | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO        | Power: DC 12V            |
| Note: Mode 1:                |                          |



| N o | Mar k | Frequen cy (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Probe (dB/m) | Cable (dB) | Amp (dB) | Ant Pos (cm) | Table Pos (deg) | Typ e |
|-----|-------|------------------|------------------------|----------------------|-----------------|----------------|--------------|------------|----------|--------------|-----------------|-------|
| 1   |       | 55.985           | 26.046                 | 1.100                | -13.954         | 40.000         | 18.458       | 6.488      | 0.000    | 100          | 205             | QP    |
| 2   |       | 65.759           | 23.282                 | 2.500                | -16.718         | 40.000         | 14.233       | 6.549      | 0.000    | 100          | 148             | QP    |
| 3   |       | 525.600          | 37.613                 | 10.400               | -8.387          | 46.000         | 19.043       | 8.170      | 0.000    | 100          | 338             | QP    |
| 4   | *     | 676.000          | 42.887                 | 12.200               | -3.113          | 46.000         | 22.137       | 8.550      | 0.000    | 100          | 320             | QP    |
| 5   |       | 792.905          | 36.048                 | 2.500                | -9.952          | 46.000         | 24.748       | 8.800      | 0.000    | 100          | 70              | QP    |
| 6   |       | 884.257          | 36.679                 | 1.400                | -9.321          | 46.000         | 26.269       | 9.010      | 0.000    | 100          | 360             | QP    |

|                              |                          |
|------------------------------|--------------------------|
| Profile: 2070338R            | Page No.: 20             |
| Engineer: Shuo               |                          |
| Site: AC3                    | Time: 2020/07/20 - 16:03 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0                |
| Probe: SuZ-2141              | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO        | Power: DC 12V            |
| Note: Mode 1                 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Probe (dB/m) | Cable (dB) | Amp (dB) | Ant Pos (cm) | Table Pos (deg) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|--------------|------------|----------|--------------|-----------------|------|
| 1  |      | 131.728         | 25.112                 | 8.600                | -18.388         | 43.500         | 9.622        | 6.890      | 0.000    | 100          | 24              | QP   |
| 2  |      | 187.019         | 27.835                 | 10.200               | -15.665         | 43.500         | 10.507       | 7.129      | 0.000    | 200          | 334             | QP   |
| 3  |      | 364.000         | 37.996                 | 13.500               | -8.004          | 46.000         | 16.776       | 7.720      | 0.000    | 100          | 265             | QP   |
| 4  |      | 525.000         | 39.387                 | 9.900                | -6.613          | 46.000         | 21.317       | 8.170      | 0.000    | 200          | 329             | QP   |
| 5  | *    | 676.000         | 40.416                 | 10.500               | -5.584          | 46.000         | 21.366       | 8.550      | 0.000    | 100          | 360             | QP   |
| 6  |      | 893.254         | 37.217                 | 3.400                | -8.783          | 46.000         | 24.788       | 9.030      | 0.000    | 100          | 160             | QP   |

Note:

1. " \* ", means this data is the worst emission level.
2. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

**4.3 20dB Bandwidth****VERDICT: PASS****4.3.1 Limit**

| Standard                            |                                                                                                                                     | FCC Part 15 Subpart C Paragraph 15.247(a) |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| <input checked="" type="checkbox"/> | For frequency hopping systems operating in 2400-2483.5 MHz band, within frequency range.                                            |                                           |
| <input type="checkbox"/>            | For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz. |                                           |
| <input type="checkbox"/>            | For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.         |                                           |


**4.3.2 Test Setup****4.3.3 Test Procedure**

| References Rule                     |             | Chapter | Description                                       |
|-------------------------------------|-------------|---------|---------------------------------------------------|
| <input checked="" type="checkbox"/> | ANSI C63.10 | 6.9     | Occupied bandwidth tests                          |
| <input checked="" type="checkbox"/> | ANSI C63.10 | 6.9.2   | Occupied bandwidth—relative measurement procedure |


#### 4.3.4 Test Data

| Mode | Channel | Frequency (MHz) | 20dB Bandwidth (kHz) | Limit (kHz) |
|------|---------|-----------------|----------------------|-------------|
| 1    | 00      | 2402            | 923.8                | $\geq 500$  |
|      | 39      | 2441            | 921.1                | $\geq 500$  |
|      | 79      | 2480            | 916.0                | $\geq 500$  |
| 2    | 00      | 2402            | 1446.0               | $\geq 500$  |
|      | 39      | 2441            | 1445.0               | $\geq 500$  |
|      | 79      | 2480            | 1441.0               | $\geq 500$  |
| 3    | 00      | 2402            | 1423.0               | $\geq 500$  |
|      | 39      | 2441            | 1447.0               | $\geq 500$  |
|      | 79      | 2480            | 1423.0               | $\geq 500$  |


Mode 1 CH00(2402MHz)




Mode 1 CH39(2441MHz)




Mode 1 CH78(2480MHz)




## Mode 2 CH00(2402MHz)




## Mode 2 CH39(2441MHz)




## Mode 2 CH78(2480MHz)




## Mode 3 CH00(2402MHz)



## Mode 3 CH39(2441MHz)



## Mode 3 CH78(2480MHz)




#### 4.4 Carrier Frequency Separation

**VERDICT: PASS**

##### 4.4.1 Limit

| Standard                            | FCC Part 15 Subpart C Paragraph 15.247(a)                                                                                                                                                               |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/>            | Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.                          |
| <input checked="" type="checkbox"/> | Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.  |
| <input type="checkbox"/>            | The 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4  |
| <input type="checkbox"/>            | The 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 |
| <input type="checkbox"/>            | Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz.                                   |

##### 4.4.2 Test Setup




##### 4.4.3 Test Procedure

| References Rule                                 | Chapter | Description                                       |
|-------------------------------------------------|---------|---------------------------------------------------|
| <input checked="" type="checkbox"/> ANSI C63.10 | 7.8     | Evaluation of frequency-hopping device parameters |
| <input checked="" type="checkbox"/> ANSI C63.10 | 7.8.2   | Carrier frequency separation                      |


#### 4.4.4 Test Data

| Mode | Channel | Frequency (MHz) | Carrier Frequency Separation (kHz) | Limit (kHz) | Result |
|------|---------|-----------------|------------------------------------|-------------|--------|
| 1    | 00      | 2402            | 1000                               | 615.87      | Pass   |
|      | 39      | 2441            | 1000                               | 614.07      | Pass   |
|      | 78      | 2480            | 1000                               | 610.67      | Pass   |
| 2    | 00      | 2402            | 1000                               | 964.00      | Pass   |
|      | 39      | 2441            | 1000                               | 963.33      | Pass   |
|      | 78      | 2480            | 1000                               | 960.67      | Pass   |
| 3    | 00      | 2402            | 1000                               | 948.67      | Pass   |
|      | 39      | 2441            | 1000                               | 964.67      | Pass   |
|      | 78      | 2480            | 1000                               | 948.67      | Pass   |


Mode 1 CH00(2402MHz)




Mode 1 CH39(2441MHz)




Mode 1 CH78(2480MHz)





Mode 2 CH00(2402MHz)



Mode 2 CH39(2441MHz)






Mode 3 CH39(2441MHz)



Mode 3 CH78(2480MHz)




## 4.5 Number of hopping Frequencies

**VERDICT: PASS**

### 4.5.1 Limit

| Standard                            | FCC Part 15 Subpart C Paragraph 15.247(a)                                                                                                                                     |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.                                                                |
| <input type="checkbox"/>            | For frequency hopping systems operating in 902-928 MHz band, if the 20 dB bandwidth of the hopping channel is less than 250 kHz, shall use at least 50 hopping frequencies.   |
| <input type="checkbox"/>            | For frequency hopping systems operating in 902-928 MHz band, if the 20 dB bandwidth of the hopping channel is higher than 250 kHz, shall use at least 25 hopping frequencies. |
| <input type="checkbox"/>            | For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.                                                                  |

### 4.5.2 Test Setup




### 4.5.3 Test Procedure

| References Rule                                 | Chapter | Description                                       |
|-------------------------------------------------|---------|---------------------------------------------------|
| <input checked="" type="checkbox"/> ANSI C63.10 | 7.8.    | Evaluation of frequency-hopping device parameters |
| <input checked="" type="checkbox"/> ANSI C63.10 | 7.8.3   | Number of Hopping Frequencies                     |


#### 4.5.4 Test Data

| Mode | Number of Hopping Frequencies | Limit | Result |
|------|-------------------------------|-------|--------|
| 4    | 79                            | >15   | Pass   |
| 5    | 79                            | >15   | Pass   |
| 6    | 79                            | >15   | Pass   |


Mode 1



Mode 2




Mode 3



**4.6 Time of Occupancy(Dwell Time)****VERDICT: PASS****4.6.1 Limit**

| Standard                            |                                                                                                                                                                                                                                                                                                 | FCC Part 15 Subpart C Paragraph 15.247(a) |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| <input checked="" type="checkbox"/> | Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.                                  |                                           |
| <input type="checkbox"/>            | For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20  |                                           |
| <input type="checkbox"/>            | For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 |                                           |
| <input type="checkbox"/>            | Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.           |                                           |

**4.6.2 Test Setup****4.6.3 Test Procedure**

| References Rule                     |             | Chapter | Description                                       |
|-------------------------------------|-------------|---------|---------------------------------------------------|
| <input checked="" type="checkbox"/> | ANSI C63.10 | 7.8     | Evaluation of frequency-hopping device parameters |
| <input checked="" type="checkbox"/> | ANSI C63.10 | 7.8.4   | Time of occupancy (dwell time)                    |

#### 4.6.4 Test Data


| Mode | Channel | Frequency (MHz) | Time of Occupancy (ms) | Limit (ms) | Result |
|------|---------|-----------------|------------------------|------------|--------|
| 4    | 39      | 2441            | 121.60                 | < 400      | Pass   |

Note1: Test Time Period:  $0.4 \times 79 = 31.6 \text{ sec}$

Note2: Time of Occupancy =  $0.380 \times 32 \times 31.6 / 3.16 = 121.60 \text{ ms}$

Note3: We have evaluated different packet type, shown in the report is the worst data.

Channel 39 (2441MHz) - (DH1)




| Mode | Channel | Frequency (MHz) | Time of Occupancy (ms) | Limit (ms) | Result |
|------|---------|-----------------|------------------------|------------|--------|
| 1    | 39      | 2441            | 245.25                 | < 400      | Pass   |

Note1: Test Time Period:  $0.4 \times 79 = 31.6 \text{ sec}$

Note2: Time of Occupancy =  $1.635 \times 15 \times 31.6 / 3.16 = 245.25 \text{ ms}$

Note3: We have evaluated different packet type, shown in the report is the worst data.

Channel 39 (2441MHz) - (DH3)




| Mode | Channel | Frequency (MHz) | Time of Occupancy (ms) | Limit (ms) | Result |
|------|---------|-----------------|------------------------|------------|--------|
| 1    | 39      | 2441            | 314.93                 | < 400      | Pass   |

Note1: Test Time Period:  $0.4 \times 79 = 31.6 \text{ sec}$

Note2: Time of Occupancy =  $2.863 \times 11 \times 31.6 / 3.16 = 314.93 \text{ ms}$

Note3: We have evaluated different packet type, shown in the report is the worst data.

Channel 39 (2441MHz) - (DH5)



Note: The packet time of AFH mode is same as normal mode, due to the packet time of AFH mode multiply with lesser factor is dwell time of  $0.4 \times 20 = 8 \text{ S}$ , the dwell time of AFH mode comply with the limit.


## 4.7 Peak Output Power

**VERDICT: PASS**

### 4.7.1 Limit

| Standard                            | FCC Part 15 Subpart C Paragraph 15.247 (a)(1)                                                                                                                                                                                                                                                          |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/>            | Frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.                         |
| <input checked="" type="checkbox"/> | Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. |
| <input type="checkbox"/>            | For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels                                                                      |

### 4.7.2 Test Setup



#### 4.7.3 Test Procedure

|                                     | References Rule                     |             | Chapter | Description                                                                      |
|-------------------------------------|-------------------------------------|-------------|---------|----------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | ANSI C63.10                         |             | 7.8     | Evaluation of frequency-hopping device parameters                                |
|                                     | <input checked="" type="checkbox"/> | ANSI C63.10 | 7.8.5   | Output power test procedure for frequency-hopping spread-spectrum (FHSS) devices |

**4.7.4 Test Data**

| Mode   | Channel | Test Frequency (MHz) | Power Output (dBm) | Limit (dBm) | Result |
|--------|---------|----------------------|--------------------|-------------|--------|
| Mode 1 | 00      | 2402                 | 4.23               | $\leq 21$   | Pass   |
|        | 39      | 2442                 | 4.15               | $\leq 21$   | Pass   |
|        | 78      | 2480                 | 4.17               | $\leq 21$   | Pass   |
| Mode 2 | 00      | 2402                 | 3.56               | $\leq 21$   | Pass   |
|        | 39      | 2442                 | 3.49               | $\leq 21$   | Pass   |
|        | 78      | 2480                 | 3.51               | $\leq 21$   | Pass   |
| Mode 3 | 00      | 2402                 | 3.63               | $\leq 21$   | Pass   |
|        | 39      | 2442                 | 3.56               | $\leq 21$   | Pass   |
|        | 78      | 2480                 | 3.59               | $\leq 21$   | Pass   |

## 4.8 Emissions in non-restricted frequency band

**VERDICT: PASS**


### 4.8.1 Limit

| Standard                            | FCC Part 15 Subpart C Paragraph 15.247(d) |
|-------------------------------------|-------------------------------------------|
| RF Output power (Detection methods) | Limit(dB)                                 |
| RF Output power(Average detector)   | 30dBc(Note1)                              |
| RF Output power(PK detector)        | 20dBc(Note2)                              |

Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

### 4.8.2 Test Setup



### 4.8.3 Test Procedure


| References Rule                                 | Chapter | Description                                       |
|-------------------------------------------------|---------|---------------------------------------------------|
| <input checked="" type="checkbox"/> ANSI C63.10 | 7.8     | Evaluation of frequency-hopping device parameters |
| <input checked="" type="checkbox"/> ANSI C63.10 | 7.8.6   | Band-edge measurements for RF conducted emissions |

#### 4.8.4 Test Data

| Mode | Channel | Test Frequency (MHz) | Maximum In-Band PSD[a] (dBm/100kHz) | Frequency (MHz) | Out-Band PSD[b] (dBm/100kHz) | [a]-[b] (dB) | Limit (dB) | Result |
|------|---------|----------------------|-------------------------------------|-----------------|------------------------------|--------------|------------|--------|
| 1    | 00      | 2402                 | 4.207                               | 2400            | -49.998                      | 54.205       | >20        | Pass   |
|      | 78      | 2480                 | 3.193                               | 2576.149        | -32.456                      | 35.649       | >20        | Pass   |
| 2    | 00      | 2402                 | 4.168                               | 2400            | -23.681                      | 27.849       | >20        | Pass   |
|      | 78      | 2480                 | 2.974                               | 2576.149        | -34.668                      | 37.642       | >20        | Pass   |
| 3    | 00      | 2402                 | 4.131                               | 2400            | -21.870                      | 26.001       | >20        | Pass   |
|      | 78      | 2480                 | 3.174                               | 2575.875        | -34.222                      | 37.396       | >20        | Pass   |


Note: The worst data as shown in below:

Mode 3 CH00(2402MHz)



**4.9 Duty cycle****VERDICT: PASS****4.9.1 Limit**

N/A

**4.9.2 Test Setup****4.9.3 Test Procedure**

| References Rule                     |             | Chapter | Description                                                                |
|-------------------------------------|-------------|---------|----------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | ANSI C63.10 | 11.6    | Duty cycle (D), transmission duration (T), and maximum power control level |

#### 4.9.4 Test Data

| Test Mode | Tx On (ms) | Tx Off (ms) | VBW   | Tx On + Tx Off (ms) | Duty Cycle |
|-----------|------------|-------------|-------|---------------------|------------|
| Mode 1    | 2.875      | 0.875       | 0.350 | 3.750               | 76.67%     |
| Mode 2    | 2.880      | 0.870       | 0.350 | 3.750               | 76.80%     |
| Mode 3    | 2.880      | 0.870       | 0.350 | 3.750               | 76.80%     |


Note 1: T means the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Note 2: According to KDB 558074, when test for Radiated Emission Band Edge and Radiated Emission, for average detector set:  $VBW \geq 1/T$  will be used.


Mode 1 CH39 2441MHz



Mode 2 CH39 2441MHz



Mode 3 CH39 2441MHz




**4.10 Radiated Emission Band Edge****VERDICT: PASS****4.10.1 Limit**

| Standard              |          | FCC Part 15 Subpart C Paragraph 15.247(d) , 15.209 |           |              |
|-----------------------|----------|----------------------------------------------------|-----------|--------------|
| Frequency bands (MHz) | Detector | Limit (dB $\mu$ V/m)                               | RBW (MHz) | Distance (m) |
| 2310-2390             | PK       | 74                                                 | 1         | 3            |
| 2483.5-2500           | AV       | 54                                                 | 1         | 3            |

Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.

**4.10.2 Test Setup**

Above 1GHz Test Setup:


**4.10.3 Test Procedure**

Test Method

|                                     | References Rule | Chapter | Description                                                                                      |
|-------------------------------------|-----------------|---------|--------------------------------------------------------------------------------------------------|
| <input type="checkbox"/>            | DA 00-705       | N/A     | duty cycle correction factor                                                                     |
| <input checked="" type="checkbox"/> | ANSI C63.10     | 6.10    | Band-edge testing                                                                                |
| <input checked="" type="checkbox"/> | ANSI C63.10     | 6.10.5  | Restricted-band band-edge measurements                                                           |
| <input type="checkbox"/>            | ANSI C63.10     | 6.10.6  | Marker-delta method                                                                              |
| <input type="checkbox"/>            | ANSI C63.10     | 6.4     | Radiated emissions from unlicensed wireless devices below 30 MHz                                 |
| <input type="checkbox"/>            | ANSI C63.10     | 6.5     | Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz |
| <input checked="" type="checkbox"/> | ANSI C63.10     | 6.6     | Radiated emissions from unlicensed wireless devices above 1 GHz                                  |


#### 4.10.4 Test Data

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 1              |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/07/31 - 20:54 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2402MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2310.000        | 50.155                 | 14.838               | -23.845         | 74.000         | 35.317      | PK   |
| 2  |      | 2378.875        | 54.275                 | 18.964               | -19.725         | 74.000         | 35.310      | PK   |
| 3  | *    | 2401.960        | 89.601                 | 54.289               | N/A             | N/A            | 35.312      | PK   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 2              |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/07/31 - 20:57 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2402MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2379.160        | 40.689                 | 5.378                | -13.311         | 54.000         | 35.311      | AV   |
| 2  |      | 2390.000        | 37.994                 | 2.679                | -16.006         | 54.000         | 35.315      | AV   |
| 3  | *    | 2402.055        | 89.234                 | 53.922               | N/A             | N/A            | 35.312      | AV   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 3              |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/07/31 - 21:01 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2402MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2379.160        | 54.552                 | 19.241               | -19.448         | 74.000         | 35.311      | PK   |
| 2  |      | 2390.000        | 50.838                 | 15.523               | -23.162         | 74.000         | 35.315      | PK   |
| 3  | *    | 2401.770        | 82.450                 | 47.137               | N/A             | N/A            | 35.312      | PK   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 4              |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/07/31 - 21:21 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2402MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2379.255        | 39.759                 | 4.448                | -14.241         | 54.000         | 35.311      | AV   |
| 2  |      | 2390.000        | 37.970                 | 2.655                | -16.030         | 54.000         | 35.315      | AV   |
| 3  | *    | 2402.055        | 80.187                 | 44.875               | N/A             | N/A            | 35.312      | AV   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 5              |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/07/31 - 21:24 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2480MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2479.950        | 90.432                 | 55.133               | N/A             | N/A            | 35.299      | PK   |
| 2  |      | 2483.500        | 50.577                 | 15.279               | -23.423         | 74.000         | 35.297      | PK   |
| 3  |      | 2484.025        | 52.494                 | 17.197               | -21.506         | 74.000         | 35.297      | PK   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 6              |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/07/31 - 21:27 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2480MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2479.950        | 90.142                 | 54.843               | N/A             | N/A            | 35.299      | AV   |
| 2  |      | 2483.500        | 39.915                 | 4.617                | -14.085         | 54.000         | 35.297      | AV   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 7              |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/07/31 - 21:29 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2480MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2480.025        | 80.953                 | 45.654               | N/A             | N/A            | 35.299      | PK   |
| 2  |      | 2483.500        | 50.874                 | 15.576               | -23.126         | 74.000         | 35.297      | PK   |
| 3  |      | 2486.450        | 53.122                 | 17.825               | -20.878         | 74.000         | 35.296      | PK   |

|                                        |                          |
|----------------------------------------|--------------------------|
| Profile: 2070338R                      | Page No.: 8              |
| Engineer: Pawn                         |                          |
| Site: AC5                              | Time: 2020/07/31 - 21:31 |
| Limit: FCC_Part15.209_RE(3m)           | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)     | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                  | Power: DC 12V            |
| Note: Mode1:Transmit at 2480MHz by DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2479.900        | 80.762                 | 45.463               | N/A             | N/A            | 35.299      | AV   |
| 2  |      | 2483.500        | 38.683                 | 3.385                | -15.317         | 54.000         | 35.297      | AV   |
| 3  |      | 2496.425        | 43.947                 | 8.653                | -10.053         | 54.000         | 35.294      | AV   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 9              |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 21:33 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2402MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2379.255        | 54.794                 | 19.483               | -19.206         | 74.000         | 35.311      | PK   |
| 2  |      | 2390.000        | 50.846                 | 15.531               | -23.154         | 74.000         | 35.315      | PK   |
| 3  | *    | 2402.055        | 92.542                 | 57.230               | N/A             | N/A            | 35.312      | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 10             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 21:42 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2402MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2379.255        | 40.381                 | 5.070                | -13.619         | 54.000         | 35.311      | AV   |
| 2  |      | 2390.000        | 38.031                 | 2.716                | -15.969         | 54.000         | 35.315      | AV   |
| 3  | *    | 2401.960        | 91.330                 | 56.018               | N/A             | N/A            | 35.312      | AV   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 11             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 21:43 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2402MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2378.970        | 54.895                 | 19.584               | -19.105         | 74.000         | 35.311      | PK   |
| 2  |      | 2390.000        | 50.261                 | 14.946               | -23.739         | 74.000         | 35.315      | PK   |
| 3  | *    | 2401.675        | 82.375                 | 47.062               | N/A             | N/A            | 35.312      | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 12             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 21:45 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2402MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2379.160        | 40.505                 | 5.194                | -13.495         | 54.000         | 35.311      | AV   |
| 2  | *    | 2401.960        | 81.153                 | 45.841               | N/A             | N/A            | 35.312      | AV   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 13             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 21:47 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2480MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2480.050        | 90.375                 | 55.076               | N/A             | N/A            | 35.299      | PK   |
| 2  |      | 2483.500        | 67.727                 | 32.429               | -6.273          | 74.000         | 35.297      | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 14             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 21:50 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2480MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2480.025        | 89.137                 | 53.838               | N/A             | N/A            | 35.299      | AV   |
| 2  |      | 2483.500        | 43.065                 | 7.767                | -10.935         | 54.000         | 35.297      | AV   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 15             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 21:52 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2480MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2479.700        | 80.891                 | 45.592               | N/A             | N/A            | 35.299      | PK   |
| 2  |      | 2483.500        | 59.104                 | 23.806               | -14.896         | 74.000         | 35.297      | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 16             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 21:55 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode2:Transmit at 2480MHz by 2DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2479.975        | 79.755                 | 44.456               | N/A             | N/A            | 35.299      | AV   |
| 2  |      | 2483.500        | 40.017                 | 4.719                | -13.983         | 54.000         | 35.297      | AV   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 17             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 21:57 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2402MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2379.255        | 53.910                 | 18.599               | -20.090         | 74.000         | 35.311      | PK   |
| 2  |      | 2390.000        | 55.028                 | 19.713               | -18.972         | 74.000         | 35.315      | PK   |
| 3  | *    | 2401.960        | 92.391                 | 57.079               | N/A             | N/A            | 35.312      | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 18             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 21:59 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2402MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2378.875        | 39.923                 | 4.612                | -14.077         | 54.000         | 35.310      | AV   |
| 2  |      | 2390.000        | 38.457                 | 3.142                | -15.543         | 54.000         | 35.315      | AV   |
| 3  | *    | 2402.055        | 91.156                 | 55.844               | N/A             | N/A            | 35.312      | AV   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 19             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 22:01 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2402MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2378.875        | 54.795                 | 19.484               | -19.205         | 74.000         | 35.310      | PK   |
| 2  | *    | 2402.055        | 82.591                 | 47.279               | N/A             | N/A            | 35.312      | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 20             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 22:03 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2402MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  |      | 2379.350        | 38.804                 | 3.493                | -15.196         | 54.000         | 35.311      | AV   |
| 2  |      | 2390.000        | 37.963                 | 2.648                | -16.037         | 54.000         | 35.315      | AV   |
| 3  | *    | 2401.865        | 77.730                 | 42.417               | N/A             | N/A            | 35.312      | AV   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 21             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 22:04 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2480MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2479.875        | 90.386                 | 55.087               | N/A             | N/A            | 35.299      | PK   |
| 2  |      | 2483.500        | 71.784                 | 36.486               | -2.216          | 74.000         | 35.297      | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 22             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 22:08 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Horizontal     |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2480MHz by 3DH5 |                          |




| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2479.900        | 88.803                 | 53.504               | N/A             | N/A            | 35.299      | AV   |
| 2  |      | 2483.500        | 44.294                 | 8.996                | -9.706          | 54.000         | 35.297      | AV   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 23             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 22:10 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2480MHz by 3DH5 |                          |



| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2479.875        | 81.058                 | 45.759               | N/A             | N/A            | 35.299      | PK   |
| 2  |      | 2483.500        | 61.995                 | 26.697               | -12.005         | 74.000         | 35.297      | PK   |

|                                         |                          |
|-----------------------------------------|--------------------------|
| Profile: 2070338R                       | Page No.: 24             |
| Engineer: Pawn                          |                          |
| Site: AC5                               | Time: 2020/07/31 - 22:12 |
| Limit: FCC_Part15.209_RE(3m)            | Margin: 0                |
| Probe: Horn_3117_00167055(1-18GHz)      | Polarity: Vertical       |
| EUT: MP-202SMY-MEXICO                   | Power: DC 12V            |
| Note: Mode3:Transmit at 2480MHz by 3DH5 |                          |



| No | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor (dB) | Type |
|----|------|-----------------|------------------------|----------------------|-----------------|----------------|-------------|------|
| 1  | *    | 2479.975        | 79.507                 | 44.208               | N/A             | N/A            | 35.299      | AV   |
| 2  |      | 2483.500        | 40.907                 | 5.609                | -13.093         | 54.000         | 35.297      | AV   |

Note:

1. Measured Level = Reading Level + Factor.
2. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.
3. As the radiated emission was performed, so conducted emission was not tested.

**4.11 Antenna Requirement****VERDICT: PASS****4.11.1 Limit:**

| Standard | FCC Part 15 Subpart C Paragraph 15.203 |
|----------|----------------------------------------|
|----------|----------------------------------------|

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

**4.11.2 Antenna Connector Construction:**

- |                                     |                                                                  |
|-------------------------------------|------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | The use of a permanently attached antenna                        |
| <input type="checkbox"/>            | The antenna use of a unique coupling to the intentional radiator |
| <input type="checkbox"/>            | The use of a nonstandard antenna jack or electrical connector    |

Please refer to the attached document "Internal Photograph" to show the antenna connector.

---

## 5 TEST SETUP PHOTO AND EUT PHOTO

Remark: The test setup photo and EUT Photo please see appendix.

\_\_\_\_\_ The End \_\_\_\_\_