



中国认可
国际互认
检测
TESTING
CNAS L6791

TEST REPORT

Applicant: Ugreen Group Limited
Address: URGEEN Building, Longcheng Industrial Park,
Longguanxi Road, Longhua, ShenZhen, China
Equipment Type: Multi-Mode Wireless Vertical Mouse
Model Name: M571 (refer to section 2.3)
Brand Name: **UGREEN**
FCC ID: 2AQI5-65042
Test Standard: 47 CFR Part 15 Subpart C
(refer to section 3.1)
Sample Arrival Date: Dec. 12, 2024
Test Date: Dec. 13, 2024 - Dec. 30, 2024
Date of Issue: Jan. 16, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Julie Zhu**Checked by:** Ye Hongji**Approved by:** Sunny Zou
(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Jan. 16, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	Factory Information	5
2.4	General Description for Equipment under Test (EUT)	5
2.5	Technical Information	6
3	SUMMARY OF TEST RESULTS	7
3.1	Test Standards	7
3.2	Verdict	7
4	GENERAL TEST CONFIGURATIONS	8
4.1	Test Environments	8
4.2	Test Equipment List	8
4.3	Test Software List	8
4.4	Measurement Uncertainty	9
4.5	Description of Test Setup	9
4.6	Measurement Results Explanation Example	12
5	TEST ITEMS	13
5.1	Antenna Requirements	13
5.2	Number of Hopping Frequency	14
5.3	Peak Output Power	15
5.4	Occupied Bandwidth	17

5.5	Carrier Frequency Separation.....	20
5.6	Time of Occupancy (Dwell time)	22
5.7	Conducted Spurious Emission & Authorized-band band-edge.....	23
5.8	Conducted Emission.....	28
5.9	Radiated Spurious Emission	31
5.10	Band Edge (Restricted-band band-edge).....	38
ANNEX A	TEST SETUP PHOTOS	40
1	Radiated Test Photo	40
2	Conducted Test Photo	43
3	Conducted Emission.....	43
ANNEX B	EUT EXTERNAL PHOTOS.....	45
ANNEX C	EUT INTERNAL PHOTOS.....	49

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Ugreen Group Limited
Address	UGREEN Building, Longcheng Industrial Park Longguanxi Road, Longhua, ShenZhen, China

2.2 Manufacturer Information

Manufacturer	Ugreen Group Limited
Address	UGREEN Building, Longcheng Industrial Park Longguanxi Road, Longhua, ShenZhen, China

2.3 Factory Information

Factory	Shenzhen Newidea Technology Co., Ltd
Address	Building31, No5, Cuigang Industria Zone, Fuyong Town, Bao'an Shenzhen, Guangdong, China

2.4 General Description for Equipment under Test (EUT)

EUT Name	Multi-Mode Wireless Vertical Mouse
Model Name Under Test	M571
Series Model Name	M571P
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name. (this information provided by the applicant)
Hardware Version	A0
Software Version	BAB8
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

Remark:

- Product Number (P/N) code in the below table, for marketing purpose, will be marked on the marking plate.

65042	65042A	65042B	65042C	65042U	65042P	65042X	65042JP	65042EU	65042UK	65042US
65666	65666A	65666B	65666C	65666U	65666P	65666X	65666JP	65666EU	65666UK	65666US

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BLE), 2.4G ISM Band
-----------------------------------	--------------------------------

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	1 Mbps
Frequency Range	The frequency range used is 2402 MHz – 2480 MHz; The frequency block is 2400 MHz to 2483.5 MHz.
Number of Channel	40
Tested Channel	Low channel (2402 MHz), Middle channel (2440 MHz), High channel (2480 MHz)
Antenna Type	PCB Antenna
Antenna Gain	2.04 dBi
Adaptive or non-adaptive	Non-Adaptive
The Max RF Output power	0.72 dBm

Channel List

Number	Frequency (MHz)	Number	Frequency (MHz)	Number	Frequency (MHz)
1	2402(Low)	15	2430	29	2458
2	2404	16	2432	30	2460
3	2406	17	2434	31	2462
4	2408	18	2436	32	2464
5	2410	19	2438	33	2466
6	2412	20	2440(Middle)	34	2468
7	2414	21	2442	35	2470
8	2416	22	2444	36	2472
9	2418	23	2446	37	2474
10	2420	24	2448	38	2476
11	2422	25	2450	39	2478
12	2424	26	2452	40	2480(High)
13	2426	27	2454	--	--
14	2428	28	2456	--	--

Note: The modulation is GFSK with FHSS, there are total 40 channels (frequency range is 2402-2480MHz, channel step is 2MHz, totally 40 channels). In this report, the equipment select the lowest, middle and highest channel from 40 channels, Which are 2402 MHz, 2440 MHz and 2480 MHz. The more information please refer to the manufacturer's instructions.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3 ☆	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	--	Pass ^{Note}
2	Number of Hopping Frequency	15.247(a)	5.2.4	Pass
3	Peak Output Power and E.I.R.P	15.247(b)	5.3.4	Pass
4	Occupied Bandwidth	15.247(a)	5.4.4	Pass
5	Hopping Frequency Separation	15.247(a)	5.5.4	Pass
6	Time of Occupancy (Dwell time)	15.247(a)	5.6.4	Pass
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	5.7.4	Pass
8	Conducted Emission	15.207	5.8.4	Pass
9	Radiated Spurious Emission	15.209 15.247(d)	5.9.4	Pass
10	Band Edge (Restricted-band band-edge)	15.209 15.247(d)	5.10.4	Pass

Note: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	42% to 65%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+20.8°C to +24.3°C
Working Voltage of the EUT	NV (Normal Voltage)	1.5 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2024.07.04	2025.07.03
Spectrum Analyzer	KEYSIGHT	N9020A	MY50531259	2024.08.01	2025.07.31
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	02460	2024.05.16	2027.05.15
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Anechoic Chamber	RAINFORD	9m*6m*6m	140	2024.07.28	2027.07.27
Amplifier	COM-MV	LSCX_LNA1-12G-01	7210214	2024.08.01	2025.07.31
Amplifier	COM-MV	XKu_LNA7-18G-01	7210209	2024.08.01	2025.07.31
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2024.08.01	2025.07.31
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2025.01.22
Amplifier	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2024.07.13	2027.07.12
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2024.08.01	2025.07.31
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9163	9163-624	2024.07.06	2027.07.05
Amplifier	COM-MV	ZT30-1000M	B2017119082	2024.11.28	2025.11.27
Anechoic Chamber	RAINFORD	9m*6m*6m	101	2023.03.04	2026.03.03
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2024.08.01	2025.07.31
LISN	SCHWARZBECK	NSLK 8127	8127-687	2024.05.09	2025.05.08
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2022.02.19	2025.02.18

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%

4.5 Description of Test Setup

4.5.1. For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.5.2. For AC Power Supply Port Test




(Diagram 2)

4.5.3. For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4. For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5. For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.6.2 For radiated band edges and spurious emission test:

Per part 15.35(c), the EUT Bluetooth average emission level could be determined by the peak emission level applying duty cycle correction factor, to represent averaging over the whole pulse train.

The average level is derived from the peak level corrected with “Duty cycle correction factor”.

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + Duty cycle correction factor (dB)

Duty cycle correction factor (dB) = $20 * \log (\text{Duty cycle})$.

Duty cycle = on time / 100 milliseconds

On time = dwell time * hopping number in 100 ms

For example: bluetooth with dwell time 2.9 ms and 3 hops in 100 ms, then

Duty cycle correction factor (dB) = $20 * \log ((2.9 * 3) / 100) = -21.21 \text{ dB}$

Following shows an average computation example with duty cycle correction factor = -21.21 dB, and the peak emission level is 45.61 dBuV/m.

Example:

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + duty cycle correction factor (dB)
= $45.61 + (-21.21) = 24.4 \text{ (dBuV/m)}$

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Number of Hopping Frequency

5.2.1 Limit

FCC §15.247(a) (1) (iii)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.2.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.2.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize


5.2.4 Test Result

Test Data


Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	40	15	Pass

Test Plot

GFSK 2.4 GHz ~ 2.4415 GHz



GFSK 2.4415 GHz ~ 2.4835 GHz



5.3 Peak Output Power

5.3.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.3.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.3.4 Test Result

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	0.72	1.18	21	125	Pass
Middle	0.71	1.18			Pass
High	0.34	1.08			Pass

Test Plots

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



5.4 Occupied Bandwidth

5.4.1 Limit

FCC §15.247(a)

Measurement of the 20dB bandwidth of the modulated signal.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.4.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq$ 1% of the 20 dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.4.4 Test Result


Test Data

Test Mode	GFSK	
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low Channel	0.890000	0.778550
Middle Channel	0.992000	0.852940
High Channel	0.986000	0.861240


Test Plots

20 dB Bandwidth


GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL




99% Bandwidth

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



5.5 Carrier Frequency Separation

5.5.1 Limit

FCC §15.247(a)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.


5.5.4 Test Result

Test Data

Mode	Frequency separation (MHz)	2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	2.000	0.661	Pass

Test Plot

GFSK



5.6 Time of Occupancy (Dwell time)

5.6.1 Limit

FCC §15.247(a)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.6.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.6.3 Test Procedure

The average time of occupancy on any channel within the Period can be calculated with formulas:

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * \{\text{Number of Hopping Frequency in Period}\}$$

$$\{\text{Period}\} = 0.4s * \{\text{Number of Hopping Frequency}\}$$

The middle channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.


5.6.4 Test Result

Test Data


GFSK			
Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
10.000	230.000	0.4	Pass

Test Plots

Pulse Width



Total of Dwell



5.7 Conducted Spurious Emission & Authorized-band band-edge

5.7.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.7.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.7.4 Test Result

Test Data

GFSK Mode:


GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-36.57	0.56	-19.44	Pass
Middle	-37.52	0.39	-19.62	Pass
High	-37.77	0.19	-19.81	Pass

Hopping Mode:


GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-37.22	0.84	-19.16	Pass

Test Plots


GFSK LOW CHANNEL, CARRIER LEVEL




GFSK LOW CHANNEL, BAND EDGE




GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK MIDDLE CHANNEL, CARRIER LEVEL




GFSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK HIGH CHANNEL, CARRIER LEVEL




GFSK HIGH CHANNEL, BAND EDGE




GFSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz






GFSK HOPPING, CARRIER LEVEL



GFSK HOPPING BAND EDGE (LOW)



GFSK HOPPING BAND EDGE (HIGH)

GFSK Hopping Mode, SPURIOUS
30 MHz ~ 3 GHzGFSK Hopping Mode, SPURIOUS
3GHz ~ 25 GHz

5.8 Conducted Emission

5.8.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.8.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX A.

5.8.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

5.8.4 Test Result

Note ¹: The EUT was tested in connected the laptop and dongle test mode.


Note ²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note ³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.154	49.56	9.78	65.78	16.22	Peak	L	Pass
1**	0.154	30.65	9.78	55.78	25.13	AV	L	Pass
2	0.188	44.80	9.78	64.12	19.32	Peak	L	Pass
2**	0.188	31.65	9.78	54.12	22.47	AV	L	Pass
3	0.494	37.36	9.99	56.10	18.74	Peak	L	Pass
3**	0.494	27.92	9.99	46.10	18.18	AV	L	Pass
4	0.828	36.51	10.58	56.00	19.49	Peak	L	Pass
4**	0.828	24.83	10.58	46.00	21.17	AV	L	Pass
5	2.348	37.53	9.99	56.00	18.47	Peak	L	Pass
5**	2.348	24.91	9.99	46.00	21.09	AV	L	Pass
6	13.664	39.12	10.71	60.00	20.88	Peak	L	Pass
6**	13.664	27.15	10.71	50.00	22.85	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.152	47.52	9.78	65.89	18.37	Peak	N	Pass
1**	0.152	32.39	9.78	55.89	23.50	AV	N	Pass
2	0.236	39.67	9.77	62.24	22.57	Peak	N	Pass
2**	0.236	26.08	9.77	52.24	26.16	AV	N	Pass
3	0.464	37.92	10.01	56.62	18.70	Peak	N	Pass
3**	0.464	27.19	10.01	46.62	19.43	AV	N	Pass
4	0.924	36.47	10.12	56.00	19.53	Peak	N	Pass
4**	0.924	25.15	10.12	46.00	20.85	AV	N	Pass
5	3.840	36.64	10.29	56.00	19.36	Peak	N	Pass
5**	3.840	25.79	10.29	46.00	20.21	AV	N	Pass
6	11.404	37.98	10.65	60.00	22.02	Peak	N	Pass
6**	11.404	25.51	10.65	50.00	24.49	AV	N	Pass

5.9 Radiated Spurious Emission

5.9.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.9.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.9.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.9.4 Test Result

Note ¹: The symbol of "--" in the table which means not application.

Note ²: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note ³: The EUT was tested in connected the laptop and dongle test mode.

Note ⁴: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Test Data and Plots


30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	46.878	13.16	-24.85	40.0	26.84	Peak	87.50	200	Horizontal	Pass
2	108.958	14.04	-26.75	43.5	29.46	Peak	261.30	200	Horizontal	Pass
3	261.442	21.06	-23.89	46.0	24.94	Peak	281.00	200	Horizontal	Pass
4	439.728	27.74	-19.60	46.0	18.26	Peak	120.20	200	Horizontal	Pass
5	759.101	28.33	-11.66	46.0	17.67	Peak	139.20	200	Horizontal	Pass
6	886.364	30.78	-9.05	46.0	15.22	Peak	114.10	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V

RE Test case_FCC Part 15B_FCC Part 15B Class B 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	53.328	13.23	-24.91	40.0	26.77	Peak	294.90	100	Vertical	Pass
2	108.424	12.67	-26.77	43.5	30.83	Peak	30.00	100	Vertical	Pass
3	199.944	17.00	-25.65	43.5	26.50	Peak	125.40	100	Vertical	Pass
4	298.981	22.90	-23.04	46.0	23.10	Peak	360.00	100	Vertical	Pass
5	432.793	29.98	-20.02	46.0	16.02	Peak	51.00	100	Vertical	Pass
6	739.798	29.59	-12.14	46.0	16.41	Peak	150.70	100	Vertical	Pass

Test Data and Plots

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1378.600	42.87	74.0	31.13	Peak	104.00	100	Horizontal	Pass
1**	1378.600	32.56	54.0	21.44	AV	104.00	100	Horizontal	Pass
2	2402.300	99.99	74.0	-25.99	Peak	319.00	150	Horizontal	N/A
2**	2402.300	99.27	54.0	-45.27	AV	319.00	150	Horizontal	N/A
3	4804.000	48.95	74.0	25.05	Peak	331.00	100	Horizontal	Pass
3**	4804.000	43.49	54.0	10.51	AV	331.00	100	Horizontal	Pass
4	4804.250	49.28	74.0	24.72	Peak	360.00	200	Horizontal	Pass
4**	4804.250	43.36	54.0	10.64	AV	360.00	200	Horizontal	Pass
5	11527.588	53.37	74.0	20.63	Peak	172.00	100	Horizontal	Pass
5**	11527.588	43.74	54.0	10.26	AV	172.00	100	Horizontal	Pass
6	17037.150	56.79	74.0	17.21	Peak	359.00	100	Horizontal	Pass
6**	17037.150	45.79	54.0	8.21	AV	359.00	100	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1333.300	47.59	74.0	26.41	Peak	188.00	400	Vertical	Pass
1**	1333.300	33.57	54.0	20.43	AV	188.00	400	Vertical	Pass
2	2402.300	96.80	74.0	-22.80	Peak	133.00	100	Vertical	N/A
2**	2402.300	96.02	54.0	-42.02	AV	133.00	100	Vertical	N/A
3	4900.250	49.70	74.0	24.30	Peak	331.00	150	Vertical	Pass
3**	4900.250	40.88	54.0	13.12	AV	331.00	150	Vertical	Pass
4	5317.000	57.98	74.0	16.02	Peak	134.00	100	Vertical	Pass
4**	5317.000	48.53	54.0	5.47	AV	134.00	100	Vertical	Pass
5	12496.349	53.54	74.0	20.46	Peak	87.00	300	Vertical	Pass
5**	12496.349	43.89	54.0	10.11	AV	87.00	300	Vertical	Pass
6	17019.301	56.33	74.0	17.67	Peak	324.00	200	Vertical	Pass
6**	17019.301	47.82	54.0	6.18	AV	324.00	200	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1347.900	43.21	74.0	30.79	Peak	66.00	200	Horizontal	Pass
1**	1347.900	32.84	54.0	21.16	AV	66.00	200	Horizontal	Pass
2	2440.700	99.74	74.0	-25.74	Peak	326.00	100	Horizontal	N/A
2**	2440.700	96.13	54.0	-42.13	AV	326.00	100	Horizontal	N/A
3	4982.500	49.68	74.0	24.32	Peak	0.00	100	Horizontal	Pass
3**	4982.500	39.70	54.0	14.30	AV	0.00	100	Horizontal	Pass
4	6895.000	53.52	74.0	20.48	Peak	0.00	400	Horizontal	Pass
4**	6895.000	45.77	54.0	8.23	AV	0.00	400	Horizontal	Pass
5	12503.950	53.68	74.0	20.32	Peak	0.00	300	Horizontal	Pass
5**	12503.950	44.03	54.0	9.97	AV	0.00	300	Horizontal	Pass
6	16985.437	55.79	74.0	18.21	Peak	243.00	300	Horizontal	Pass
6**	16985.437	46.38	54.0	7.62	AV	243.00	300	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1331.500	46.68	74.0	27.32	Peak	175.00	100	Vertical	Pass
1**	1331.500	40.50	54.0	13.50	AV	175.00	100	Vertical	Pass
2	2440.600	95.92	74.0	-21.92	Peak	139.00	200	Vertical	N/A
2**	2440.600	93.65	54.0	-39.65	AV	139.00	200	Vertical	N/A
3	5333.250	52.49	74.0	21.51	Peak	71.00	100	Vertical	Pass
3**	5333.250	42.51	54.0	11.49	AV	71.00	100	Vertical	Pass
4	7310.000	53.28	74.0	20.72	Peak	289.00	100	Vertical	Pass
4**	7310.000	43.87	54.0	10.13	AV	289.00	100	Vertical	Pass
5	12437.213	53.17	74.0	20.83	Peak	161.00	400	Vertical	Pass
5**	12437.213	43.22	54.0	10.78	AV	161.00	400	Vertical	Pass
6	17455.051	55.13	74.0	18.87	Peak	253.00	300	Vertical	Pass
6**	17455.051	46.18	54.0	7.82	AV	253.00	300	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1559.800	41.99	74.0	32.01	Peak	49.00	200	Horizontal	Pass
1**	1559.800	33.49	54.0	20.51	AV	49.00	200	Horizontal	Pass
2	2480.000	98.14	74.0	-24.14	Peak	327.00	150	Horizontal	N/A
2**	2480.000	97.90	54.0	-43.90	AV	327.00	150	Horizontal	N/A
3	4959.750	48.72	74.0	25.28	Peak	12.00	100	Horizontal	Pass
3**	4959.750	44.08	54.0	9.92	AV	12.00	100	Horizontal	Pass
4	4965.750	49.10	74.0	24.90	Peak	360.00	100	Horizontal	Pass
4**	4965.750	39.21	54.0	14.79	AV	360.00	100	Horizontal	Pass
5	12704.638	53.65	74.0	20.35	Peak	207.00	400	Horizontal	Pass
5**	12704.638	43.59	54.0	10.41	AV	207.00	400	Horizontal	Pass
6	17450.850	55.56	74.0	18.44	Peak	281.00	400	Horizontal	Pass
6**	17450.850	46.22	54.0	7.78	AV	281.00	400	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.300	46.22	74.0	27.78	Peak	132.00	200	Vertical	Pass
1**	1332.300	33.79	54.0	20.21	AV	132.00	200	Vertical	Pass
2	2480.000	95.58	74.0	-21.58	Peak	141.00	200	Vertical	N/A
2**	2480.000	95.48	54.0	-41.48	AV	141.00	200	Vertical	N/A
3	4903.250	49.63	74.0	24.37	Peak	244.00	100	Vertical	Pass
3**	4903.250	39.80	54.0	14.20	AV	244.00	100	Vertical	Pass
4	6894.000	52.81	74.0	21.19	Peak	46.00	400	Vertical	Pass
4**	6894.000	44.76	54.0	9.24	AV	46.00	400	Vertical	Pass
5	12997.276	53.20	74.0	20.80	Peak	289.00	100	Vertical	Pass
5**	12997.276	43.96	54.0	10.04	AV	289.00	100	Vertical	Pass
6	17072.850	55.43	74.0	18.57	Peak	239.00	100	Vertical	Pass
6**	17072.850	45.26	54.0	8.74	AV	239.00	100	Vertical	Pass

5.10 Band Edge (Restricted-band band-edge)

5.10.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.10.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ⁴: The Level (dBuV/m) has been corrected by factor.

Test Data

GFSK LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2385.800	55.84	74.0	18.16	Peak	305.00	150	Horizontal	Pass
1**	2385.800	46.44	54.0	7.56	AV	305.00	150	Horizontal	Pass
2	2389.950	53.25	74.0	20.75	Peak	136.00	150	Horizontal	Pass
2**	2389.950	43.16	54.0	10.84	AV	136.00	150	Horizontal	Pass
3	2385.900	54.39	74.0	19.61	Peak	320.00	100	Horizontal	Pass
3**	2385.900	46.99	54.0	7.01	AV	320.00	100	Horizontal	Pass


GFSK HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	54.10	74.0	19.90	Peak	18.00	100	Horizontal	Pass
1**	2483.500	44.02	54.0	9.98	AV	18.00	100	Horizontal	Pass
2	2495.425	56.07	74.0	17.93	Peak	34.00	100	Horizontal	Pass
2**	2495.425	45.44	54.0	8.56	AV	34.00	100	Horizontal	Pass

ANNEX A TEST SETUP PHOTOS

1 Radiated Test Photo

Below 30MHz



Close-up




30MHz-1GHz




Close-up



Above 1GHz



Close-up



2 Conducted Test Photo

Conducted Test




3 Conducted Emission

Photo 1



Photo 2



ANNEX B EUT EXTERNAL PHOTOS


FRONT VIEW OF EUT



REAR VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT




TOP VIEW OF EUT



BOTTOM VIEW OF EUT




Accessory-Dongle




ANNEX C EUT INTERNAL PHOTOS


EUT UNCOVER VIEW 1




EUT UNCOVER VIEW 2




EUT UNCOVER VIEW 3




MAIN BOARD TOP VIEW




MAIN BOARD REAR VIEW




SECONDARY BOARD 1 TOP VIEW




SECONDARY BOARD 1 REAR VIEW



SECONDARY BOARD 2 TOP VIEW



SECONDARY BOARD 2 REAR VIEW



Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--