849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: sid@timcoengr.com



Test Report

Product Name: BATTLE TANK REMOTE CONTROL TRANSMITTER

FCC ID: AEKA50749

Applicant:

TAIYO KOGYO CO., LTD. NO 1-23-17, HIGASHIYOTSUGI KATSUSHIKA-KU TOKYO 124 JAPAN

Date Receipt: 6/1/2005

Date Tested: 6/7/2005

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: sid@timcoengr.com

### TABLE OF CONTENTS LIST

APPLICANT: TAIYO KOGYO CO., LTD.

**FCC ID:** AEKA50749

### TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST PAGE 2.....TEST PROCEDURE PAGE 3-4....RADIATION INTERFERENCE TEST DATA PAGE 5....OCCUPIED BANDWIDTH PAGE 6.....OCCUPIED BANDWIDTH PLOT PAGE 7....TEST SETUP PHOTO

### EXHIBITS INCLUDING:

BLOCK DIAGRAM SCHEMATIC INSTRUCTION MANUAL LABEL SAMPLE LABEL LOCATION EXTERNAL PHOTOGRAPHS INTERNAL PHOTOGRAPHS CIRCUIT DESCRIPTION TEST SET UP PHOTOGRAPH

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: <u>sid@timcoengr.com</u>

### **Equipment List**

Device	Manufacturer	Model	Model Serial Number		Due Date
3/10-Meter OATS	TEI	N/A	N/A	Listed 3/27/04	3/26/07
3-Meter OATS	TEI	N/A	N/A	Listed 1/13/03	1/12/06
Biconnical Antenna	Eaton	94455-1	1057	CAL 3/18/03	3/18/05
Biconnical Antenna	Eaton	94455-1	1096	CAL 10/1/01	10/1/03
Biconnical Antenna	Electro- Metrics	BIA-25	1171	CAL 4/26/01	4/26/03
Blue Tower Quasi-Peak Adapter	HP	85650A	2811A01279	CAL 4/15/03	4/15/05
Blue Tower RF	HP	85685A	2620A00294	CAL 4/27/04	4/27/06
Preselector					
Blue Tower Spectrum Analyzer	HP	8568B	2928A04729 2848A18049	CAL 4/15/03	4/15/05
LISN	Electro- Metrics	ANS-25/2	2604	CAL 10/9/01	10/9/03
LISN	Electro- Metrics	EM-7820	2682	CAL 3/12/03	3/12/05
Log- Periodic Antenna	Eaton	96005	1243	CAL 5/8/03	5/8/05

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: sid@timcoengr.com

### TEST PROCEDURE

**GENERAL:** This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

**RADIATION INTERFERENCE:** The test procedure used was ANSI STANDARD C63.4-2003 using a HEWLETT PACKARD spectrum analyzer with a pre-selector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz. The ambient temperature of the UUT was 80°C with a humidity of 76%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

### Example:

Freq (MHz) METER READING + ACF = FS 33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

**ANSI STANDARD C63.4-2003 10.1.7 MEASUREMENT PROCEDURES:** The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: <u>sid@timcoengr.com</u>

APPLICANT:	TAIYO KOGYO CO., LTD.					
FCC ID:	AEKA50749					
NAME OF TEST:	RADIATION INTERFERENCE					
RULES PART NO.:	15.235					
REQUIREMENTS:	CARRIER FREQUENCY WILL NOT EXCEEDS 80 dBuV/m AT 3M. OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:					
	30 - 88 MHz 40.0 dBuV/M MEASURED AT 3 METERS   88 - 216 MHz 43.5 dBuV/M   216 - 960 MHz 46.0 dBuV/M   ABOVE 960 MHz 54.0 dBuV/M					

### TEST DATA:

Tuned	Emission	Meter	Ant.	Coax	Correction	Field	Margin
Frequency	Frequency	Reading	Polarity	Loss	Factor	Strength	dB
MHz	MHz	dBuV		dB	dB	dBuV/m	
49.9	49.86	63.9	н	0.50	11.20	75.60	4.40
49.9	49.86	66.4	v	0.50	11.07	77.97	2.03
49.9	99.73	18.4	v	0.65	11.55	30.60	12.90
49.9	99.74	9.0	н	0.65	11.39	21.04	22.46
49.9	149.60	6.1	н	0.70	14.33	21.13	22.37
49.9	149.64	7.7	v	0.70	14.12	22.52	20.98
49.9	199.50	6.8	v	0.90	17.22	24.92	18.58
49.9	199.50	6.8	н	0.90	17.32	25.02	18.48
49.9	249.65	7.0	Н	1.00	12.58	20.58	25.42
49.9	249.86	7.0	v	1.00	12.49	20.49	25.51
49.9	299.68	6.8	v	1.10	13.90	21.80	24.20
49.9	299.68	7.2	Н	1.10	14.29	22.59	23.41
49.9	349.54	6.2	Н	1.15	15.20	22.55	23.45
49.9	349.54	8.3	v	1.15	14.60	24.05	21.95
49.9	399.40	7.4	Н	1.20	16.08	24.68	21.32
49.9	399.53	7.2	v	1.20	15.98	24.38	21.62
49.9	449.26	6.9	н	1.25	17.07	25.22	20.78
49.9	449.39	6.5	v	1.25	16.78	24.53	21.47
49.9	499.25	7.7	н	1.30	18.77	27.77	18.23
49.9	499.25	7.9	v	1.30	17.89	27.09	18.91

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: sid@timcoengr.com

APPLICANT: TAIYO KOGYO CO., LTD.

**FCC ID:** AEKA50749

NAME OF TEST: RADIATION INTERFERENCE CONTINUED

**SAMPLE CALCULATION:** FSdBuV/m = MR (dBuV) + ACFdB.

**TEST PROCEDURE:** The procedure used was ANSI STANDARD C63.4-2003. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: MARIO R. de ARANZETA

**DATE:** 6/7/2005

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: sid@timcoengr.com

APPLICANT: TAIYO KOGYO CO., LTD.

**FCC ID:** AEKA50749

**NAME OF TEST:** Occupied Bandwidth

**RULES PART NO.:** 15.235

**REQUIREMENTS:** The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the un-modulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPH ON THE NEXT PAGE REPRESENTS THE EMISSIONS TAKEN FOR THE DEVICE.

**METHOD OF MEASUREMENT:** A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken.

TEST RESULTS: The unit DOES meet the FCC requirements.


PERFORMED BY: JOSEPH SGOGLIO DATE: June 7, 2005

849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: sid@timcoengr.com

- APPLICANT: TAIYO KOGYO CO., LTD.
- **FCC ID:** AEKA50749
- NAME OF TEST: OCCUPIED BANDWIDTH PLOT

### NOTES:

TAIYO KOGYO CO., LTD. - FCC ID: AEKTY-W2326 OCCUPIED BANDWIDTH PLOT



849 NW State Road 45 Newberry, Florida 32669 http://www.timcoengr.com 888.472.2424 F 352.472.2030 email: <u>sid@timcoengr.com</u>

**FCC ID:** AEKA50749

NAME OF TEST: TEST SETUP PHOTO

